
Logtalk APIs

Release v3.80.0

Paulo Moura

Jun 04, 2024

CONTENTS

| | | |
|--------|----------------------------|----|
| 1 | Libraries | 1 |
| 1.1 | arbitrary | 1 |
| 1.1.1 | arbitrary | 1 |
| 1.2 | assertions | 7 |
| 1.2.1 | assertions | 8 |
| 1.2.2 | assertions(Mode) | 9 |
| 1.2.3 | assertions_messages | 11 |
| 1.3 | assignvars | 12 |
| 1.3.1 | assignvars | 12 |
| 1.3.2 | assignvarsp | 13 |
| 1.4 | base64 | 17 |
| 1.4.1 | base64 | 17 |
| 1.4.2 | base64url | 19 |
| 1.5 | cbor | 21 |
| 1.5.1 | cbor | 21 |
| 1.5.2 | cbor(StringRepresentation) | 22 |
| 1.6 | code_metrics | 24 |
| 1.6.1 | cc_metric | 24 |
| 1.6.2 | code_metric | 26 |
| 1.6.3 | code_metrics | 38 |
| 1.6.4 | code_metrics_messages | 40 |
| 1.6.5 | code_metrics_utilities | 41 |
| 1.6.6 | coupling_metric | 46 |
| 1.6.7 | dit_metric | 48 |
| 1.6.8 | doc_metric | 49 |
| 1.6.9 | halstead_metric | 53 |
| 1.6.10 | halstead_metric(Stroud) | 55 |
| 1.6.11 | noc_metric | 56 |
| 1.6.12 | nor_metric | 58 |
| 1.6.13 | size_metric | 59 |
| 1.6.14 | upn_metric | 61 |
| 1.7 | core | 62 |
| 1.7.1 | core_messages | 62 |
| 1.7.2 | expanding | 63 |
| 1.7.3 | forwarding | 65 |
| 1.7.4 | logtalk | 67 |
| 1.7.5 | monitoring | 81 |
| 1.7.6 | user | 83 |
| 1.8 | coroutining | 84 |
| 1.8.1 | coroutining | 84 |

| | | |
|---------|--------------------------------------|-----|
| 1.9 | csv | 87 |
| 1.9.1 | csv | 88 |
| 1.9.2 | csv(Header,Separator,IgnoreQuotes) | 89 |
| 1.9.3 | csv_guess_questions | 90 |
| 1.9.4 | csv_protocol | 92 |
| 1.10 | dates | 102 |
| 1.10.1 | date | 102 |
| 1.10.2 | datep | 103 |
| 1.10.3 | time | 107 |
| 1.10.4 | timep | 108 |
| 1.11 | dead_code_scanner | 110 |
| 1.11.1 | dead_code_scanner | 110 |
| 1.11.2 | dead_code_scanner_messages | 118 |
| 1.12 | debug_messages | 119 |
| 1.12.1 | debug_messages | 119 |
| 1.13 | debugger | 123 |
| 1.13.1 | debugger | 123 |
| 1.13.2 | debugger_messages | 130 |
| 1.13.3 | debuggerp | 131 |
| 1.13.4 | dump_trace | 140 |
| 1.14 | dependents | 142 |
| 1.14.1 | observer | 142 |
| 1.14.2 | subject | 144 |
| 1.15 | diagrams | 147 |
| 1.15.1 | diagram(Format) | 147 |
| 1.15.2 | diagrams | 170 |
| 1.15.3 | diagrams(Format) | 171 |
| 1.15.4 | directory_dependency_diagram | 181 |
| 1.15.5 | directory_dependency_diagram(Format) | 183 |
| 1.15.6 | directory_diagram(Format) | 184 |
| 1.15.7 | directory_load_diagram | 188 |
| 1.15.8 | directory_load_diagram(Format) | 189 |
| 1.15.9 | dot_graph_language | 191 |
| 1.15.10 | entity_diagram | 193 |
| 1.15.11 | entity_diagram(Format) | 194 |
| 1.15.12 | file_dependency_diagram | 198 |
| 1.15.13 | file_dependency_diagram(Format) | 199 |
| 1.15.14 | file_diagram(Format) | 201 |
| 1.15.15 | file_load_diagram | 204 |
| 1.15.16 | file_load_diagram(Format) | 206 |
| 1.15.17 | graph_language_protocol | 208 |
| 1.15.18 | graph_language_registry | 212 |
| 1.15.19 | inheritance_diagram | 213 |
| 1.15.20 | inheritance_diagram(Format) | 215 |
| 1.15.21 | library_dependency_diagram | 216 |
| 1.15.22 | library_dependency_diagram(Format) | 217 |
| 1.15.23 | library_diagram(Format) | 219 |
| 1.15.24 | library_load_diagram | 224 |
| 1.15.25 | library_load_diagram(Format) | 225 |
| 1.15.26 | modules_diagram_support | 227 |
| 1.15.27 | uses_diagram | 229 |
| 1.15.28 | uses_diagram(Format) | 230 |
| 1.15.29 | xref_diagram | 232 |
| 1.15.30 | xref_diagram(Format) | 233 |

| | | |
|--------|--------------------------------------|-----|
| 1.16 | dictionaries | 236 |
| 1.16.1 | avltree | 236 |
| 1.16.2 | bintree | 238 |
| 1.16.3 | dictionaryp | 240 |
| 1.16.4 | rbtree | 252 |
| 1.17 | dif | 254 |
| 1.17.1 | dif | 254 |
| 1.18 | doclet | 256 |
| 1.18.1 | doclet | 256 |
| 1.19 | edcg | 258 |
| 1.19.1 | edcg | 258 |
| 1.20 | events | 262 |
| 1.20.1 | after_event_registry | 262 |
| 1.20.2 | before_event_registry | 263 |
| 1.20.3 | event_registry | 264 |
| 1.20.4 | event_registryp | 265 |
| 1.20.5 | monitor | 269 |
| 1.20.6 | monitorp | 271 |
| 1.21 | expand_library_alias_paths | 274 |
| 1.21.1 | expand_library_alias_paths | 274 |
| 1.22 | expecteds | 276 |
| 1.22.1 | either | 276 |
| 1.22.2 | expected | 278 |
| 1.22.3 | expected(Expected) | 283 |
| 1.23 | fcube | 291 |
| 1.23.1 | fcube | 291 |
| 1.24 | flags | 295 |
| 1.24.1 | flags | 295 |
| 1.24.2 | flags_validator | 302 |
| 1.25 | format | 304 |
| 1.25.1 | format | 304 |
| 1.26 | genint | 306 |
| 1.26.1 | genint | 306 |
| 1.26.2 | genint_core | 308 |
| 1.27 | gensym | 310 |
| 1.27.1 | gensym | 310 |
| 1.27.2 | gensym_core | 311 |
| 1.28 | git | 314 |
| 1.28.1 | git | 314 |
| 1.28.2 | git_protocol | 315 |
| 1.29 | grammars | 319 |
| 1.29.1 | blank_grammars(Format) | 319 |
| 1.29.2 | ip_grammars(Format) | 326 |
| 1.29.3 | number_grammars(Format) | 327 |
| 1.29.4 | sequence_grammars | 333 |
| 1.30 | heaps | 337 |
| 1.30.1 | heap(Order) | 337 |
| 1.30.2 | heapp | 338 |
| 1.30.3 | maxheap | 343 |
| 1.30.4 | minheap | 345 |
| 1.31 | help | 346 |
| 1.31.1 | help | 346 |
| 1.31.2 | help_info_support | 352 |
| 1.32 | hierarchies | 355 |

| | | |
|---------|--|-----|
| 1.32.1 | class_hierarchy | 355 |
| 1.32.2 | class_hierarchyp | 357 |
| 1.32.3 | hierarchyp | 364 |
| 1.32.4 | proto_hierarchy | 367 |
| 1.32.5 | proto_hierarchyp | 368 |
| 1.33 | hook_flows | 371 |
| 1.33.1 | hook_pipeline(Pipeline) | 371 |
| 1.33.2 | hook_set(Set) | 372 |
| 1.34 | hook_objects | 374 |
| 1.34.1 | backend_adapter_hook | 374 |
| 1.34.2 | default_workflow_hook | 375 |
| 1.34.3 | grammar_rules_hook | 376 |
| 1.34.4 | identity_hook | 378 |
| 1.34.5 | object_wrapper_hook | 379 |
| 1.34.6 | object_wrapper_hook(Protocol) | 380 |
| 1.34.7 | object_wrapper_hook(Name,Relations) | 382 |
| 1.34.8 | print_goal_hook | 383 |
| 1.34.9 | prolog_module_hook(Module) | 384 |
| 1.34.10 | suppress_goal_hook | 386 |
| 1.34.11 | write_to_file_hook(File) | 387 |
| 1.34.12 | write_to_file_hook(File,Options) | 388 |
| 1.34.13 | write_to_stream_hook(Stream) | 390 |
| 1.34.14 | write_to_stream_hook(Stream,Options) | 391 |
| 1.35 | html | 392 |
| 1.35.1 | html | 392 |
| 1.35.2 | html5 | 395 |
| 1.35.3 | xhtml11 | 396 |
| 1.36 | ids | 397 |
| 1.36.1 | ids | 397 |
| 1.36.2 | ids(Representation,Bytes) | 398 |
| 1.37 | intervals | 400 |
| 1.37.1 | interval | 400 |
| 1.37.2 | intervalp | 402 |
| 1.38 | iso8601 | 408 |
| 1.38.1 | iso8601 | 408 |
| 1.39 | issue_creator | 420 |
| 1.39.1 | issue_creator | 420 |
| 1.40 | java | 421 |
| 1.40.1 | java | 421 |
| 1.40.2 | java(Reference) | 422 |
| 1.40.3 | java(Reference,ReturnValue) | 424 |
| 1.40.4 | java_access_protocol | 425 |
| 1.40.5 | java_hook | 428 |
| 1.40.6 | java_utils_protocol | 430 |
| 1.41 | json | 439 |
| 1.41.1 | json | 439 |
| 1.41.2 | json(StringRepresentation) | 440 |
| 1.41.3 | json(ObjectRepresentation,PairRepresentation,StringRepresentation) | 441 |
| 1.41.4 | json_protocol | 443 |
| 1.42 | lgtdoc | 445 |
| 1.42.1 | lgtdoc | 445 |
| 1.42.2 | lgtdoc_messages | 448 |
| 1.42.3 | lgtdocp | 449 |
| 1.43 | lgtunit | 461 |

| | | |
|---------|----------------------------|-----|
| 1.43.1 | automation_report | 461 |
| 1.43.2 | coverage_report | 462 |
| 1.43.3 | lgtunit | 464 |
| 1.43.4 | lgtunit_messages | 513 |
| 1.43.5 | minimal_output | 514 |
| 1.43.6 | tap_output | 515 |
| 1.43.7 | tap_report | 517 |
| 1.43.8 | xunit_net_v2_output | 520 |
| 1.43.9 | xunit_net_v2_report | 521 |
| 1.43.10 | xunit_output | 523 |
| 1.43.11 | xunit_report | 525 |
| 1.44 | library | 526 |
| 1.44.1 | cloning | 526 |
| 1.44.2 | counters | 528 |
| 1.44.3 | streamvars | 531 |
| 1.45 | listing | 534 |
| 1.45.1 | listing | 534 |
| 1.46 | logging | 537 |
| 1.46.1 | logger | 537 |
| 1.46.2 | logging | 539 |
| 1.46.3 | loggingp | 541 |
| 1.47 | loops | 545 |
| 1.47.1 | loop | 545 |
| 1.47.2 | loopp | 546 |
| 1.48 | meta | 552 |
| 1.48.1 | meta | 552 |
| 1.48.2 | metap | 553 |
| 1.49 | meta_compiler | 564 |
| 1.49.1 | meta_compiler | 564 |
| 1.50 | metagol | 566 |
| 1.50.1 | metagol | 566 |
| 1.50.2 | metagol_example_protocol | 573 |
| 1.51 | mutations | 575 |
| 1.51.1 | default_atom_mutations | 575 |
| 1.51.2 | default_compound_mutations | 577 |
| 1.51.3 | default_float_mutations | 578 |
| 1.51.4 | default_integer_mutations | 579 |
| 1.51.5 | default_list_mutations | 580 |
| 1.51.6 | mutations | 582 |
| 1.51.7 | mutations_store | 583 |
| 1.52 | nested_dictionaries | 586 |
| 1.52.1 | navltree | 586 |
| 1.52.2 | nbintree | 588 |
| 1.52.3 | nested_dictionary_protocol | 589 |
| 1.52.4 | nrbtree | 594 |
| 1.53 | optionals | 595 |
| 1.53.1 | maybe | 595 |
| 1.53.2 | optional | 597 |
| 1.53.3 | optional(Optional) | 601 |
| 1.54 | options | 608 |
| 1.54.1 | options | 609 |
| 1.54.2 | options_protocol | 610 |
| 1.55 | os | 616 |
| 1.55.1 | os | 616 |

| | | |
|--------|------------------------|-----|
| 1.55.2 | os_types | 618 |
| 1.55.3 | osp | 619 |
| 1.56 | packs | 637 |
| 1.56.1 | pack_protocol | 637 |
| 1.56.2 | packs | 641 |
| 1.56.3 | packs_common | 666 |
| 1.56.4 | packs_messages | 678 |
| 1.56.5 | packs_specs_hook | 679 |
| 1.56.6 | registries | 681 |
| 1.56.7 | registry_loader_hook | 692 |
| 1.56.8 | registry_protocol | 693 |
| 1.57 | pddl_parser | 697 |
| 1.57.1 | pddl | 697 |
| 1.57.2 | read_file | 700 |
| 1.58 | ports_profiler | 701 |
| 1.58.1 | ports_profiler | 701 |
| 1.59 | queues | 708 |
| 1.59.1 | queue | 708 |
| 1.59.2 | queuep | 709 |
| 1.60 | random | 715 |
| 1.60.1 | backend_random | 716 |
| 1.60.2 | fast_random | 717 |
| 1.60.3 | pseudo_random_protocol | 719 |
| 1.60.4 | random | 721 |
| 1.60.5 | random_protocol | 724 |
| 1.61 | reader | 733 |
| 1.61.1 | reader | 733 |
| 1.62 | recorded_database | 742 |
| 1.62.1 | recorded_database | 742 |
| 1.62.2 | recorded_database_core | 743 |
| 1.63 | redis | 749 |
| 1.63.1 | redis | 749 |
| 1.64 | sets | 752 |
| 1.64.1 | set | 752 |
| 1.64.2 | set(Type) | 754 |
| 1.64.3 | setp | 756 |
| 1.65 | statistics | 766 |
| 1.65.1 | population | 766 |
| 1.65.2 | sample | 767 |
| 1.65.3 | statistics | 768 |
| 1.65.4 | statisticsp | 771 |
| 1.66 | term_io | 782 |
| 1.66.1 | term_io | 782 |
| 1.66.2 | term_io_protocol | 784 |
| 1.67 | timeout | 794 |
| 1.67.1 | timeout | 794 |
| 1.68 | toychr | 796 |
| 1.68.1 | toychrdb | 797 |
| 1.69 | tsv | 802 |
| 1.69.1 | tsv | 802 |
| 1.69.2 | tsv(Header) | 803 |
| 1.69.3 | tsv_protocol | 805 |
| 1.70 | tutor | 814 |
| 1.70.1 | tutor | 814 |

| | | |
|---------|------------------------------|-----|
| 1.71 | types | 816 |
| 1.71.1 | atom | 816 |
| 1.71.2 | atomic | 818 |
| 1.71.3 | callable | 819 |
| 1.71.4 | character | 820 |
| 1.71.5 | characterp | 821 |
| 1.71.6 | comparingp | 830 |
| 1.71.7 | compound | 834 |
| 1.71.8 | difflist | 835 |
| 1.71.9 | float | 837 |
| 1.71.10 | integer | 839 |
| 1.71.11 | list | 842 |
| 1.71.12 | list(Type) | 844 |
| 1.71.13 | listp | 845 |
| 1.71.14 | natural | 868 |
| 1.71.15 | number | 869 |
| 1.71.16 | numberlist | 873 |
| 1.71.17 | numberlistp | 874 |
| 1.71.18 | pairs | 884 |
| 1.71.19 | term | 889 |
| 1.71.20 | termp | 891 |
| 1.71.21 | type | 898 |
| 1.71.22 | varlist | 903 |
| 1.71.23 | varlistp | 904 |
| 1.72 | ulid | 914 |
| 1.72.1 | ulid | 914 |
| 1.72.2 | ulid(Representation) | 915 |
| 1.72.3 | ulid_protocol | 917 |
| 1.72.4 | ulid_types | 920 |
| 1.73 | union_find | 921 |
| 1.73.1 | union_find | 921 |
| 1.73.2 | union_find_protocol | 923 |
| 1.74 | uuid | 927 |
| 1.74.1 | uuid | 927 |
| 1.74.2 | uuid(Representation) | 928 |
| 1.74.3 | uuid_protocol | 930 |
| 1.75 | verdi_neruda | 932 |
| 1.75.1 | a_star_interpreter(W) | 933 |
| 1.75.2 | benchmark_generators | 934 |
| 1.75.3 | best_first | 935 |
| 1.75.4 | bfs_interpreter | 937 |
| 1.75.5 | bup_interpreter | 938 |
| 1.75.6 | counter | 939 |
| 1.75.7 | databasep | 943 |
| 1.75.8 | debug_expansion(Mode) | 945 |
| 1.75.9 | demodb | 947 |
| 1.75.10 | dfs_interpreter | 948 |
| 1.75.11 | flatting | 949 |
| 1.75.12 | heuristic_expansion(Mode) | 951 |
| 1.75.13 | iddfs_interpreter(Increment) | 952 |
| 1.75.14 | interpreterp | 953 |
| 1.75.15 | magic | 955 |
| 1.75.16 | magic_expansion(Mode) | 957 |
| 1.75.17 | rule_expansion(Mode) | 958 |

| | | |
|---------|-------------------------------------|-----|
| 1.75.18 | shell | 959 |
| 1.75.19 | shell(Interpreters) | 961 |
| 1.75.20 | shell_expansion(Mode) | 962 |
| 1.76 | wrapper | 963 |
| 1.76.1 | wrapper | 964 |
| 1.77 | xml_parser | 976 |
| 1.77.1 | xml | 976 |
| 1.78 | zippers | 984 |
| 1.78.1 | zipperp | 984 |
| 1.78.2 | zlist | 994 |
| 2 | Directories | 997 |
| 2.1 | contributions/flags/ | 999 |
| 2.2 | contributions/iso8601/ | 999 |
| 2.3 | contributions/pddl_parser/ | 999 |
| 2.4 | contributions/verdi_neruda/ | 999 |
| 2.5 | contributions/xml_parser/ | 999 |
| 2.6 | core/ | 999 |
| 2.7 | library/ | 999 |
| 2.8 | library/arbitrary/ | 999 |
| 2.9 | library/assignvars/ | 999 |
| 2.10 | library/base64/ | 999 |
| 2.11 | library/cbor/ | 999 |
| 2.12 | library/coroutining/ | 999 |
| 2.13 | library/csv/ | 999 |
| 2.14 | library/dates/ | 999 |
| 2.15 | library/dependents/ | 999 |
| 2.16 | library/dictionaries/ | 999 |
| 2.17 | library/dif/ | 999 |
| 2.18 | library/edcg/ | 999 |
| 2.19 | library/events/ | 999 |
| 2.20 | library/expand_library_alias_paths/ | 999 |
| 2.21 | library/expecteds/ | 999 |
| 2.22 | library/format/ | 999 |
| 2.23 | library/genint/ | 999 |
| 2.24 | library/gensym/ | 999 |
| 2.25 | library/git/ | 999 |
| 2.26 | library/grammars/ | 999 |
| 2.27 | library/heaps/ | 999 |
| 2.28 | library/hierarchies/ | 999 |
| 2.29 | library/hook_flows/ | 999 |
| 2.30 | library/hook_objects/ | 999 |
| 2.31 | library/html/ | 999 |
| 2.32 | library/ids/ | 999 |
| 2.33 | library/intervals/ | 999 |
| 2.34 | library/java/ | 999 |
| 2.35 | library/json/ | 999 |
| 2.36 | library/listing/ | 999 |
| 2.37 | library/logging/ | 999 |
| 2.38 | library/loops/ | 999 |
| 2.39 | library/meta/ | 999 |
| 2.40 | library/meta_compiler/ | 999 |
| 2.41 | library/mutations/ | 999 |
| 2.42 | library/nested_dictionaries/ | 999 |

| | | |
|------|----------------------------|------|
| 2.43 | library/optionals/ | 999 |
| 2.44 | library/options/ | 999 |
| 2.45 | library/os/ | 999 |
| 2.46 | library/queues/ | 999 |
| 2.47 | library/random/ | 999 |
| 2.48 | library/reader/ | 999 |
| 2.49 | library/recorded_database/ | 999 |
| 2.50 | library/redis/ | 999 |
| 2.51 | library/sets/ | 999 |
| 2.52 | library/statistics/ | 999 |
| 2.53 | library/term_io/ | 999 |
| 2.54 | library/timeout/ | 999 |
| 2.55 | library/tsv/ | 999 |
| 2.56 | library/types/ | 999 |
| 2.57 | library/ulid/ | 999 |
| 2.58 | library/union_find/ | 999 |
| 2.59 | library/uuid/ | 999 |
| 2.60 | library/zippers/ | 999 |
| 2.61 | ports/fcube/ | 999 |
| 2.62 | ports/metagol/ | 999 |
| 2.63 | ports/toychr/ | 999 |
| 2.64 | tools/assertions/ | 999 |
| 2.65 | tools/code_metrics/ | 999 |
| 2.66 | tools/dead_code_scanner/ | 999 |
| 2.67 | tools/debug_messages/ | 999 |
| 2.68 | tools/debugger/ | 999 |
| 2.69 | tools/diagrams/ | 999 |
| 2.70 | tools/doclet/ | 999 |
| 2.71 | tools/help/ | 999 |
| 2.72 | tools/issue_creator/ | 999 |
| 2.73 | tools/lgtdoc/ | 999 |
| 2.74 | tools/lgtunit/ | 999 |
| 2.75 | tools/packs/ | 999 |
| 2.76 | tools/ports_profiler/ | 999 |
| 2.77 | tools/tutor/ | 999 |
| 2.78 | tools/wrapper/ | 999 |
| 3 | Entities | 1001 |
| 3.1 | Categories | 1001 |
| 3.2 | Objects | 1001 |
| 3.3 | Protocols | 1001 |
| 4 | Predicates | 1003 |
| 4.1 | (/)/2 | 1003 |
| 4.2 | (//)/2 | 1003 |
| 4.3 | (<)/2 | 1003 |
| 4.4 | (<=)/2 | 1003 |
| 4.5 | (=:=)/2 | 1003 |
| 4.6 | (=<)/2 | 1004 |
| 4.7 | (=>)/2 | 1004 |
| 4.8 | (=\=)/2 | 1004 |
| 4.9 | =~/2 | 1004 |
| 4.10 | (>)/2 | 1004 |
| 4.11 | (>=)/2 | 1004 |

| | | |
|------|--------------------------|------|
| 4.12 | absolute_file_name/2 | 1004 |
| 4.13 | activate_debug_handler/1 | 1004 |
| 4.14 | activate_monitor/0 | 1005 |
| 4.15 | active_debug_handler/1 | 1005 |
| 4.16 | add/1 | 1005 |
| 4.17 | add/2 | 1005 |
| 4.18 | add/3 | 1005 |
| 4.19 | addDependent/1 | 1005 |
| 4.20 | after/2 | 1005 |
| 4.21 | after/3 | 1005 |
| 4.22 | all/0 | 1006 |
| 4.23 | all/1 | 1006 |
| 4.24 | all_files/0 | 1006 |
| 4.25 | all_files/1 | 1006 |
| 4.26 | all_libraries/0 | 1006 |
| 4.27 | all_libraries/1 | 1006 |
| 4.28 | all_score/1 | 1007 |
| 4.29 | ancestor/1 | 1007 |
| 4.30 | ancestors/1 | 1007 |
| 4.31 | apis/0 | 1007 |
| 4.32 | apis/1 | 1007 |
| 4.33 | append/2 | 1007 |
| 4.34 | append/3 | 1007 |
| 4.35 | apply/2 | 1007 |
| 4.36 | apply/4 | 1008 |
| 4.37 | approximately_equal/2 | 1008 |
| 4.38 | approximately_equal/3 | 1008 |
| 4.39 | arbitrary/1 | 1008 |
| 4.40 | arbitrary/2 | 1008 |
| 4.41 | archive/1 | 1008 |
| 4.42 | arithmetic_mean/2 | 1008 |
| 4.43 | array_list/2 | 1008 |
| 4.44 | array_to_list/2 | 1009 |
| 4.45 | array_to_terms/2 | 1009 |
| 4.46 | array_to_terms/3 | 1009 |
| 4.47 | as_curly_bracketed/2 | 1009 |
| 4.48 | as_dictionary/2 | 1009 |
| 4.49 | as_difflist/2 | 1009 |
| 4.50 | as_heap/2 | 1009 |
| 4.51 | as_list/2 | 1009 |
| 4.52 | as_nested_dictionary/2 | 1010 |
| 4.53 | as_set/2 | 1010 |
| 4.54 | ask_question/5 | 1010 |
| 4.55 | assertion/1 | 1010 |
| 4.56 | assertion/2 | 1010 |
| 4.57 | assignable/1 | 1010 |
| 4.58 | assignable/2 | 1010 |
| 4.59 | available/0 | 1010 |
| 4.60 | available/1 | 1011 |
| 4.61 | available/2 | 1011 |
| 4.62 | average/2 | 1011 |
| 4.63 | average_deviation/3 | 1011 |
| 4.64 | before/2 | 1011 |
| 4.65 | before/3 | 1011 |

| | | |
|-------|----------------------------|------|
| 4.66 | bench_goal/1 | 1011 |
| 4.67 | benchmark/2 | 1011 |
| 4.68 | benchmark/3 | 1012 |
| 4.69 | benchmark/4 | 1012 |
| 4.70 | benchmark_reified/3 | 1012 |
| 4.71 | between/3 | 1012 |
| 4.72 | bit//1 | 1012 |
| 4.73 | bits//1 | 1012 |
| 4.74 | blank//0 | 1012 |
| 4.75 | blanks//0 | 1012 |
| 4.76 | body_pred/1 | 1013 |
| 4.77 | branch/2 | 1013 |
| 4.78 | built_in_directive/4 | 1013 |
| 4.79 | built_in_flag/2 | 1013 |
| 4.80 | built_in_method/4 | 1013 |
| 4.81 | built_in_non_terminal/4 | 1013 |
| 4.82 | built_in_predicate/4 | 1013 |
| 4.83 | calendar_month/3 | 1013 |
| 4.84 | call_with_timeout/2 | 1014 |
| 4.85 | call_with_timeout/3 | 1014 |
| 4.86 | cat/2 | 1014 |
| 4.87 | change_directory/1 | 1014 |
| 4.88 | changed/0 | 1014 |
| 4.89 | changed/1 | 1014 |
| 4.90 | chebyshev_distance/3 | 1014 |
| 4.91 | chebyshev_norm/2 | 1014 |
| 4.92 | check/1 | 1015 |
| 4.93 | check/2 | 1015 |
| 4.94 | check/3 | 1015 |
| 4.95 | check_option/1 | 1015 |
| 4.96 | check_options/1 | 1015 |
| 4.97 | chr_is/2 | 1015 |
| 4.98 | chr_no_spy/1 | 1015 |
| 4.99 | chr_nospy/0 | 1015 |
| 4.100 | chr_notrace/0 | 1016 |
| 4.101 | chr_option/2 | 1016 |
| 4.102 | chr_spy/1 | 1016 |
| 4.103 | chr_trace/0 | 1016 |
| 4.104 | class/1 | 1016 |
| 4.105 | classes/1 | 1016 |
| 4.106 | clause/5 | 1016 |
| 4.107 | clause_location/6 | 1016 |
| 4.108 | clean/0 | 1017 |
| 4.109 | clean/1 | 1017 |
| 4.110 | clean/2 | 1017 |
| 4.111 | clone/1 | 1017 |
| 4.112 | clone/3 | 1017 |
| 4.113 | clone/4 | 1017 |
| 4.114 | coefficient_of_variation/2 | 1017 |
| 4.115 | command_line_arguments/1 | 1018 |
| 4.116 | commit_author/2 | 1018 |
| 4.117 | commit_date/2 | 1018 |
| 4.118 | commit_hash/2 | 1018 |
| 4.119 | commit_hash_abbreviated/2 | 1018 |

| | | |
|-------|----------------------------------|------|
| 4.120 | commit_log/3 | 1018 |
| 4.121 | commit_message/2 | 1018 |
| 4.122 | compile_aux_clauses/1 | 1018 |
| 4.123 | compile_predicate_heads/4 | 1019 |
| 4.124 | compile_predicate_indicators/3 | 1019 |
| 4.125 | completion/2 | 1019 |
| 4.126 | completions/2 | 1019 |
| 4.127 | connect/1 | 1019 |
| 4.128 | connect/3 | 1019 |
| 4.129 | console/1 | 1019 |
| 4.130 | contains/2 | 1019 |
| 4.131 | control//0 | 1020 |
| 4.132 | control_construct/4 | 1020 |
| 4.133 | controls//0 | 1020 |
| 4.134 | copy_file/2 | 1020 |
| 4.135 | counter/2 | 1020 |
| 4.136 | cover/1 | 1020 |
| 4.137 | cpu_time/1 | 1020 |
| 4.138 | current/2 | 1020 |
| 4.139 | data/0 | 1021 |
| 4.140 | data/1 | 1021 |
| 4.141 | data/2 | 1021 |
| 4.142 | date/4 | 1021 |
| 4.143 | date/5 | 1021 |
| 4.144 | date/6 | 1021 |
| 4.145 | date/7 | 1021 |
| 4.146 | date_string/3 | 1021 |
| 4.147 | date_time/7 | 1022 |
| 4.148 | days_in_month/3 | 1022 |
| 4.149 | deactivate_debug_handler/0 | 1022 |
| 4.150 | debug/0 | 1022 |
| 4.151 | debug_handler/1 | 1022 |
| 4.152 | debug_handler/3 | 1022 |
| 4.153 | debugging/0 | 1022 |
| 4.154 | debugging/1 | 1022 |
| 4.155 | decide/1 | 1023 |
| 4.156 | decide/2 | 1023 |
| 4.157 | decode_exception/2 | 1023 |
| 4.158 | decode_exception/3 | 1023 |
| 4.159 | decompile_predicate_heads/4 | 1023 |
| 4.160 | decompile_predicate_indicators/4 | 1023 |
| 4.161 | decompose_file_name/3 | 1023 |
| 4.162 | decompose_file_name/4 | 1023 |
| 4.163 | decrement_counter/1 | 1024 |
| 4.164 | default_option/1 | 1024 |
| 4.165 | default_options/1 | 1024 |
| 4.166 | define_log_file/2 | 1024 |
| 4.167 | defined/4 | 1024 |
| 4.168 | defined_flag/6 | 1024 |
| 4.169 | del_monitors/0 | 1024 |
| 4.170 | del_monitors/4 | 1024 |
| 4.171 | del_spy_points/4 | 1025 |
| 4.172 | delete/0 | 1025 |
| 4.173 | delete/1 | 1025 |

| | |
|---|------|
| 4.174 delete/2 | 1025 |
| 4.175 delete/3 | 1025 |
| 4.176 delete/4 | 1025 |
| 4.177 delete_all_after/2 | 1025 |
| 4.178 delete_all_after_and_unzip/2 | 1025 |
| 4.179 delete_all_before/2 | 1026 |
| 4.180 delete_all_before_and_unzip/2 | 1026 |
| 4.181 delete_and_next/2 | 1026 |
| 4.182 delete_and_previous/2 | 1026 |
| 4.183 delete_and_unzip/2 | 1026 |
| 4.184 delete_directory/1 | 1026 |
| 4.185 delete_file/1 | 1026 |
| 4.186 delete_in/4 | 1026 |
| 4.187 delete_matches/3 | 1027 |
| 4.188 delete_max/4 | 1027 |
| 4.189 delete_min/4 | 1027 |
| 4.190 dependents/1 | 1027 |
| 4.191 dependents/2 | 1027 |
| 4.192 dependents/3 | 1027 |
| 4.193 depth/2 | 1027 |
| 4.194 descendant/1 | 1027 |
| 4.195 descendant_class/1 | 1028 |
| 4.196 descendant_classes/1 | 1028 |
| 4.197 descendant_instance/1 | 1028 |
| 4.198 descendant_instances/1 | 1028 |
| 4.199 descendants/1 | 1028 |
| 4.200 describe/1 | 1028 |
| 4.201 describe/2 | 1028 |
| 4.202 description/1 | 1028 |
| 4.203 deterministic/1 | 1029 |
| 4.204 deterministic/2 | 1029 |
| 4.205 diagram_description/1 | 1029 |
| 4.206 diagram_name_suffix/1 | 1029 |
| 4.207 dif/1 | 1029 |
| 4.208 dif/2 | 1029 |
| 4.209 digit//1 | 1029 |
| 4.210 digits//1 | 1029 |
| 4.211 directories/1 | 1030 |
| 4.212 directories/2 | 1030 |
| 4.213 directories/3 | 1030 |
| 4.214 directory/1 | 1030 |
| 4.215 directory/2 | 1030 |
| 4.216 directory/3 | 1031 |
| 4.217 directory_exists/1 | 1031 |
| 4.218 directory_files/2 | 1031 |
| 4.219 directory_files/3 | 1031 |
| 4.220 directory_score/2 | 1031 |
| 4.221 disable/1 | 1031 |
| 4.222 disable/2 | 1031 |
| 4.223 disable_logging/1 | 1031 |
| 4.224 disconnect/1 | 1032 |
| 4.225 disjoint/2 | 1032 |
| 4.226 disjoint_sets/2 | 1032 |
| 4.227 doc_goal/1 | 1032 |

| | |
|--|------|
| 4.228 dot//1 | 1032 |
| 4.229 dowhile/2 | 1032 |
| 4.230 drop/3 | 1032 |
| 4.231 during/2 | 1032 |
| 4.232 easter_day/3 | 1033 |
| 4.233 edge/6 | 1033 |
| 4.234 edge_case/2 | 1033 |
| 4.235 either/3 | 1033 |
| 4.236 empty/1 | 1033 |
| 4.237 enable/1 | 1033 |
| 4.238 enable/2 | 1034 |
| 4.239 enable_logging/1 | 1034 |
| 4.240 enabled/1 | 1034 |
| 4.241 enabled/2 | 1034 |
| 4.242 ensure_directory/1 | 1034 |
| 4.243 ensure_file/1 | 1034 |
| 4.244 entity/1 | 1034 |
| 4.245 entity/2 | 1035 |
| 4.246 entity_info_pair_score_hook/3 | 1035 |
| 4.247 entity_info_score_hook/2 | 1035 |
| 4.248 entity_predicates_weights_hook/2 | 1035 |
| 4.249 entity_prefix/2 | 1035 |
| 4.250 entity_score/2 | 1035 |
| 4.251 enumerate/2 | 1035 |
| 4.252 environment_variable/2 | 1035 |
| 4.253 epsilon/1 | 1036 |
| 4.254 equal/2 | 1036 |
| 4.255 erase/1 | 1036 |
| 4.256 essentially_equal/3 | 1036 |
| 4.257 euclidean_distance/3 | 1036 |
| 4.258 euclidean_norm/2 | 1036 |
| 4.259 exclude/3 | 1036 |
| 4.260 execution_context/7 | 1036 |
| 4.261 expand_library_path/2 | 1037 |
| 4.262 expected/1 | 1037 |
| 4.263 expecteds/2 | 1037 |
| 4.264 explain//1 | 1037 |
| 4.265 extension/1 | 1037 |
| 4.266 extensions/1 | 1037 |
| 4.267 false/1 | 1037 |
| 4.268 fcube/0 | 1037 |
| 4.269 file/1 | 1038 |
| 4.270 file/2 | 1038 |
| 4.271 file_exists/1 | 1038 |
| 4.272 file_footer/3 | 1038 |
| 4.273 file_header/3 | 1038 |
| 4.274 file_modification_time/2 | 1038 |
| 4.275 file_permission/2 | 1039 |
| 4.276 file_score/2 | 1039 |
| 4.277 file_size/2 | 1039 |
| 4.278 file_to_bytes/2 | 1039 |
| 4.279 file_to_bytes/3 | 1039 |
| 4.280 file_to_chars/2 | 1039 |
| 4.281 file_to_chars/3 | 1039 |

| | |
|------------------------------|------|
| 4.282 file_to_codes/2 | 1039 |
| 4.283 file_to_codes/3 | 1040 |
| 4.284 file_to_terms/2 | 1040 |
| 4.285 file_to_terms/3 | 1040 |
| 4.286 file_type_extension/2 | 1040 |
| 4.287 files/1 | 1040 |
| 4.288 files/2 | 1040 |
| 4.289 files/3 | 1040 |
| 4.290 filter/2 | 1041 |
| 4.291 find/4 | 1041 |
| 4.292 find/5 | 1041 |
| 4.293 findall_member/4 | 1041 |
| 4.294 findall_member/5 | 1041 |
| 4.295 finished_by/2 | 1041 |
| 4.296 finishes/2 | 1041 |
| 4.297 flag_group_chk/1 | 1041 |
| 4.298 flag_groups/1 | 1042 |
| 4.299 flat_map/2 | 1042 |
| 4.300 flatten/2 | 1042 |
| 4.301 float//1 | 1042 |
| 4.302 fold_left/4 | 1042 |
| 4.303 fold_left_1/3 | 1042 |
| 4.304 fold_right/4 | 1042 |
| 4.305 fold_right_1/3 | 1042 |
| 4.306 fordownto/3 | 1043 |
| 4.307 fordownto/4 | 1043 |
| 4.308 fordownto/5 | 1043 |
| 4.309 foreach/3 | 1043 |
| 4.310 foreach/4 | 1043 |
| 4.311 format/2 | 1043 |
| 4.312 format/3 | 1043 |
| 4.313 format_entity_score//2 | 1043 |
| 4.314 format_object/1 | 1044 |
| 4.315 format_to_atom/3 | 1044 |
| 4.316 format_to_chars/3 | 1044 |
| 4.317 format_to_chars/4 | 1044 |
| 4.318 format_to_codes/3 | 1044 |
| 4.319 format_to_codes/4 | 1044 |
| 4.320 forto/3 | 1044 |
| 4.321 forto/4 | 1044 |
| 4.322 forto/5 | 1045 |
| 4.323 forward/1 | 1045 |
| 4.324 forward/2 | 1045 |
| 4.325 forward/3 | 1045 |
| 4.326 fractile/3 | 1045 |
| 4.327 freeze/2 | 1045 |
| 4.328 from_generator/2 | 1045 |
| 4.329 from_generator/3 | 1045 |
| 4.330 from_generator/4 | 1046 |
| 4.331 from_goal/2 | 1046 |
| 4.332 from_goal/3 | 1046 |
| 4.333 from_goal/4 | 1046 |
| 4.334 frozen/2 | 1046 |
| 4.335 full_device_path/1 | 1046 |

| | | |
|-------|----------------------------|------|
| 4.336 | func_test/3 | 1046 |
| 4.337 | functional/0 | 1046 |
| 4.338 | generate/1 | 1047 |
| 4.339 | generate/2 | 1047 |
| 4.340 | generate/8 | 1047 |
| 4.341 | genint/2 | 1047 |
| 4.342 | gensym/2 | 1047 |
| 4.343 | geometric_mean/2 | 1047 |
| 4.344 | get/1 | 1047 |
| 4.345 | get_field/2 | 1048 |
| 4.346 | get_flag_value/2 | 1048 |
| 4.347 | get_seed/1 | 1048 |
| 4.348 | gnu/0 | 1048 |
| 4.349 | goal_expansion/2 | 1048 |
| 4.350 | graph_footer/5 | 1048 |
| 4.351 | graph_header/5 | 1048 |
| 4.352 | ground/1 | 1048 |
| 4.353 | group_by_key/2 | 1049 |
| 4.354 | group_consecutive_by_key/2 | 1049 |
| 4.355 | group_sorted_by_key/2 | 1049 |
| 4.356 | guess_arity/2 | 1049 |
| 4.357 | guess_separator/2 | 1049 |
| 4.358 | hamming_distance/3 | 1049 |
| 4.359 | handbook/0 | 1049 |
| 4.360 | handbook/1 | 1049 |
| 4.361 | harmonic_mean/2 | 1050 |
| 4.362 | head/2 | 1050 |
| 4.363 | head_pred/1 | 1050 |
| 4.364 | help/0 | 1050 |
| 4.365 | hex_digit//1 | 1050 |
| 4.366 | hex_digits//1 | 1050 |
| 4.367 | home/1 | 1050 |
| 4.368 | ibk/3 | 1050 |
| 4.369 | if_empty/1 | 1051 |
| 4.370 | if_expected/1 | 1051 |
| 4.371 | if_expected_or_else/2 | 1051 |
| 4.372 | if_present/1 | 1051 |
| 4.373 | if_present_or_else/2 | 1051 |
| 4.374 | if_unexpected/1 | 1051 |
| 4.375 | include/3 | 1051 |
| 4.376 | increase/1 | 1051 |
| 4.377 | increment/0 | 1052 |
| 4.378 | increment_counter/1 | 1052 |
| 4.379 | init/0 | 1052 |
| 4.380 | init_log_file/2 | 1052 |
| 4.381 | inorder/2 | 1052 |
| 4.382 | insert/3 | 1052 |
| 4.383 | insert/4 | 1052 |
| 4.384 | insert_after/3 | 1052 |
| 4.385 | insert_all/3 | 1053 |
| 4.386 | insert_before/3 | 1053 |
| 4.387 | insert_in/4 | 1053 |
| 4.388 | install/1 | 1053 |
| 4.389 | install/2 | 1053 |

| | | |
|-------|-------------------------|------|
| 4.390 | install/3 | 1053 |
| 4.391 | install/4 | 1053 |
| 4.392 | installed/0 | 1053 |
| 4.393 | installed/1 | 1054 |
| 4.394 | installed/3 | 1054 |
| 4.395 | installed/4 | 1054 |
| 4.396 | instance/1 | 1054 |
| 4.397 | instance/2 | 1054 |
| 4.398 | instances/1 | 1054 |
| 4.399 | integer//1 | 1054 |
| 4.400 | internal_os_path/2 | 1054 |
| 4.401 | intersect/2 | 1055 |
| 4.402 | intersection/2 | 1055 |
| 4.403 | intersection/3 | 1055 |
| 4.404 | intersection/4 | 1055 |
| 4.405 | invoke/1 | 1055 |
| 4.406 | invoke/2 | 1055 |
| 4.407 | ipv4//1 | 1055 |
| 4.408 | ipv6//1 | 1055 |
| 4.409 | is_absolute_file_name/1 | 1056 |
| 4.410 | is_alpha/1 | 1056 |
| 4.411 | is_alphanumeric/1 | 1056 |
| 4.412 | is_ascii/1 | 1056 |
| 4.413 | is_bin_digit/1 | 1056 |
| 4.414 | is_control/1 | 1056 |
| 4.415 | is_dec_digit/1 | 1056 |
| 4.416 | is_empty/0 | 1056 |
| 4.417 | is_end_of_line/1 | 1057 |
| 4.418 | is_expected/0 | 1057 |
| 4.419 | is_false/1 | 1057 |
| 4.420 | is_hex_digit/1 | 1057 |
| 4.421 | is_layout/1 | 1057 |
| 4.422 | is_letter/1 | 1057 |
| 4.423 | is_lower_case/1 | 1057 |
| 4.424 | is_newline/1 | 1057 |
| 4.425 | is_null/1 | 1058 |
| 4.426 | is_object/1 | 1058 |
| 4.427 | is_octal_digit/1 | 1058 |
| 4.428 | is_period/1 | 1058 |
| 4.429 | is_present/0 | 1058 |
| 4.430 | is_punctuation/1 | 1058 |
| 4.431 | is_quote/1 | 1058 |
| 4.432 | is_true/1 | 1058 |
| 4.433 | is_unexpected/0 | 1059 |
| 4.434 | is_upper_case/1 | 1059 |
| 4.435 | is_void/1 | 1059 |
| 4.436 | is_vowel/1 | 1059 |
| 4.437 | is_white_space/1 | 1059 |
| 4.438 | iterator_element/2 | 1059 |
| 4.439 | join/3 | 1059 |
| 4.440 | join_all/3 | 1059 |
| 4.441 | jump/3 | 1060 |
| 4.442 | jump_all/3 | 1060 |
| 4.443 | jump_all_block/3 | 1060 |

| | | |
|-------|-------------------------|------|
| 4.444 | key/2 | 1060 |
| 4.445 | keys/2 | 1060 |
| 4.446 | keys_values/3 | 1060 |
| 4.447 | keysort/2 | 1060 |
| 4.448 | kurtosis/2 | 1060 |
| 4.449 | language_object/2 | 1061 |
| 4.450 | last/2 | 1061 |
| 4.451 | leaf/1 | 1061 |
| 4.452 | leaf_class/1 | 1061 |
| 4.453 | leaf_classes/1 | 1061 |
| 4.454 | leaf_instance/1 | 1061 |
| 4.455 | leaf_instances/1 | 1061 |
| 4.456 | leap_year/1 | 1061 |
| 4.457 | learn/0 | 1062 |
| 4.458 | learn/1 | 1062 |
| 4.459 | learn/2 | 1062 |
| 4.460 | learn/3 | 1062 |
| 4.461 | learn_seq/2 | 1062 |
| 4.462 | learn_with_timeout/4 | 1062 |
| 4.463 | leash/1 | 1062 |
| 4.464 | leashing/1 | 1062 |
| 4.465 | least_common_multiple/2 | 1063 |
| 4.466 | leaves/1 | 1063 |
| 4.467 | length/2 | 1063 |
| 4.468 | libraries/1 | 1063 |
| 4.469 | libraries/2 | 1063 |
| 4.470 | libraries/3 | 1063 |
| 4.471 | library/0 | 1064 |
| 4.472 | library/1 | 1064 |
| 4.473 | library/2 | 1064 |
| 4.474 | library_score/2 | 1064 |
| 4.475 | license/1 | 1064 |
| 4.476 | line_to_chars/2 | 1064 |
| 4.477 | line_to_chars/3 | 1065 |
| 4.478 | line_to_codes/2 | 1065 |
| 4.479 | line_to_codes/3 | 1065 |
| 4.480 | lint/0 | 1065 |
| 4.481 | lint/1 | 1065 |
| 4.482 | lint/2 | 1065 |
| 4.483 | list/0 | 1065 |
| 4.484 | list_to_array/2 | 1065 |
| 4.485 | listing/0 | 1066 |
| 4.486 | listing/1 | 1066 |
| 4.487 | loaded_file/1 | 1066 |
| 4.488 | loaded_file_property/2 | 1066 |
| 4.489 | log/3 | 1066 |
| 4.490 | log_event/2 | 1066 |
| 4.491 | log_file/2 | 1066 |
| 4.492 | logging/1 | 1066 |
| 4.493 | logging/3 | 1067 |
| 4.494 | logtalk_packs/0 | 1067 |
| 4.495 | logtalk_packs/1 | 1067 |
| 4.496 | lookup/2 | 1067 |
| 4.497 | lookup/3 | 1067 |

| | | |
|-------|-------------------------|------|
| 4.498 | lookup_in/3 | 1067 |
| 4.499 | lower_upper/2 | 1067 |
| 4.500 | magic/2 | 1067 |
| 4.501 | magicise/4 | 1068 |
| 4.502 | make_directory/1 | 1068 |
| 4.503 | make_directory_path/1 | 1068 |
| 4.504 | make_set/3 | 1068 |
| 4.505 | man/1 | 1068 |
| 4.506 | manhattan_distance/3 | 1068 |
| 4.507 | manhattan_norm/2 | 1068 |
| 4.508 | manuals/0 | 1068 |
| 4.509 | map/2 | 1069 |
| 4.510 | map/3 | 1069 |
| 4.511 | map/4 | 1069 |
| 4.512 | map/5 | 1069 |
| 4.513 | map/6 | 1069 |
| 4.514 | map/7 | 1069 |
| 4.515 | map/8 | 1070 |
| 4.516 | map_element/2 | 1070 |
| 4.517 | map_reduce/5 | 1070 |
| 4.518 | max/2 | 1070 |
| 4.519 | max/3 | 1070 |
| 4.520 | max_clauses/1 | 1070 |
| 4.521 | max_inv_preds/1 | 1070 |
| 4.522 | max_size/1 | 1070 |
| 4.523 | maybe/0 | 1071 |
| 4.524 | maybe/1 | 1071 |
| 4.525 | maybe/2 | 1071 |
| 4.526 | maybe_call/1 | 1071 |
| 4.527 | maybe_call/2 | 1071 |
| 4.528 | mean_deviation/2 | 1071 |
| 4.529 | median/2 | 1071 |
| 4.530 | median_deviation/2 | 1071 |
| 4.531 | meets/2 | 1072 |
| 4.532 | member/2 | 1072 |
| 4.533 | memberchk/2 | 1072 |
| 4.534 | merge/3 | 1072 |
| 4.535 | message_hook/4 | 1072 |
| 4.536 | message_prefix_stream/4 | 1072 |
| 4.537 | message_tokens//2 | 1072 |
| 4.538 | met_by/2 | 1073 |
| 4.539 | meta_type/3 | 1073 |
| 4.540 | metarule/6 | 1073 |
| 4.541 | metarule_next_id/1 | 1073 |
| 4.542 | min/2 | 1073 |
| 4.543 | min/3 | 1073 |
| 4.544 | min_clauses/1 | 1073 |
| 4.545 | min_max/3 | 1073 |
| 4.546 | modes/2 | 1074 |
| 4.547 | module_property/2 | 1074 |
| 4.548 | monitor/1 | 1074 |
| 4.549 | monitor/4 | 1074 |
| 4.550 | monitor_activated/0 | 1074 |
| 4.551 | monitored/1 | 1074 |

| | | |
|-------|--------------------|------|
| 4.552 | monitors/1 | 1074 |
| 4.553 | msort/2 | 1074 |
| 4.554 | msort/3 | 1075 |
| 4.555 | mutation/3 | 1075 |
| 4.556 | name/1 | 1075 |
| 4.557 | name_of_day/3 | 1075 |
| 4.558 | name_of_month/3 | 1075 |
| 4.559 | natural//1 | 1075 |
| 4.560 | new/1 | 1075 |
| 4.561 | new/2 | 1076 |
| 4.562 | new/3 | 1076 |
| 4.563 | new_line//0 | 1076 |
| 4.564 | new_lines//0 | 1076 |
| 4.565 | next/2 | 1076 |
| 4.566 | next/3 | 1076 |
| 4.567 | next/4 | 1076 |
| 4.568 | nextto/3 | 1076 |
| 4.569 | node/7 | 1077 |
| 4.570 | nodebug/0 | 1077 |
| 4.571 | nolog/3 | 1077 |
| 4.572 | nologall/0 | 1077 |
| 4.573 | non_blank//1 | 1077 |
| 4.574 | non_blanks//1 | 1077 |
| 4.575 | normal_element/2 | 1077 |
| 4.576 | normalize_range/2 | 1077 |
| 4.577 | normalize_range/4 | 1078 |
| 4.578 | normalize_scalar/2 | 1078 |
| 4.579 | normalize_unit/2 | 1078 |
| 4.580 | nospy/1 | 1078 |
| 4.581 | nospy/4 | 1078 |
| 4.582 | nospyall/0 | 1078 |
| 4.583 | note/2 | 1078 |
| 4.584 | note/3 | 1078 |
| 4.585 | notrace/0 | 1079 |
| 4.586 | now/3 | 1079 |
| 4.587 | nth0/3 | 1079 |
| 4.588 | nth0/4 | 1079 |
| 4.589 | nth1/3 | 1079 |
| 4.590 | nth1/4 | 1079 |
| 4.591 | null/1 | 1079 |
| 4.592 | null_device_path/1 | 1080 |
| 4.593 | number//1 | 1080 |
| 4.594 | number_of_tests/1 | 1080 |
| 4.595 | numbervars/1 | 1080 |
| 4.596 | numbervars/3 | 1080 |
| 4.597 | occurrences/2 | 1080 |
| 4.598 | occurrences/3 | 1080 |
| 4.599 | occurs/2 | 1080 |
| 4.600 | of/2 | 1081 |
| 4.601 | of_expected/2 | 1081 |
| 4.602 | of_unexpected/2 | 1081 |
| 4.603 | one_or_more//0 | 1081 |
| 4.604 | one_or_more//1 | 1081 |
| 4.605 | one_or_more//2 | 1081 |

| | | |
|-------|----------------------------------|------|
| 4.606 | operating_system_machine/1 | 1081 |
| 4.607 | operating_system_name/1 | 1081 |
| 4.608 | operating_system_release/1 | 1082 |
| 4.609 | operating_system_type/1 | 1082 |
| 4.610 | option/2 | 1082 |
| 4.611 | option/3 | 1082 |
| 4.612 | or/2 | 1082 |
| 4.613 | or_else/2 | 1082 |
| 4.614 | or_else_call/2 | 1082 |
| 4.615 | or_else_fail/1 | 1082 |
| 4.616 | or_else_get/2 | 1083 |
| 4.617 | or_else_throw/1 | 1083 |
| 4.618 | or_else_throw/2 | 1083 |
| 4.619 | orphaned/0 | 1083 |
| 4.620 | orphaned/2 | 1083 |
| 4.621 | outdated/0 | 1083 |
| 4.622 | outdated/1 | 1083 |
| 4.623 | outdated/4 | 1083 |
| 4.624 | output_file_name/2 | 1084 |
| 4.625 | overlapped_by/2 | 1084 |
| 4.626 | overlaps/2 | 1084 |
| 4.627 | parent/1 | 1084 |
| 4.628 | parenthesis/2 | 1084 |
| 4.629 | parents/1 | 1084 |
| 4.630 | parse/2 | 1084 |
| 4.631 | parse/3 | 1085 |
| 4.632 | parse_domain/2 | 1085 |
| 4.633 | parse_domain/3 | 1085 |
| 4.634 | parse_problem/2 | 1085 |
| 4.635 | parse_problem/3 | 1085 |
| 4.636 | partial_map/4 | 1085 |
| 4.637 | partition/3 | 1085 |
| 4.638 | partition/4 | 1085 |
| 4.639 | partition/5 | 1086 |
| 4.640 | partition/6 | 1086 |
| 4.641 | path_concat/3 | 1086 |
| 4.642 | permutation/2 | 1086 |
| 4.643 | pid/1 | 1086 |
| 4.644 | pin/0 | 1086 |
| 4.645 | pin/1 | 1086 |
| 4.646 | pinned/1 | 1086 |
| 4.647 | plus/3 | 1087 |
| 4.648 | port/5 | 1087 |
| 4.649 | portray_clause/1 | 1087 |
| 4.650 | postorder/2 | 1087 |
| 4.651 | powerset/2 | 1087 |
| 4.652 | pp/1 | 1087 |
| 4.653 | pprint/1 | 1087 |
| 4.654 | predicate/2 | 1087 |
| 4.655 | predicate_info_pair_score_hook/4 | 1088 |
| 4.656 | predicate_info_score_hook/3 | 1088 |
| 4.657 | predicate_mode_score_hook/3 | 1088 |
| 4.658 | predicate_mode_score_hook/5 | 1088 |
| 4.659 | predicates/2 | 1088 |

| | | |
|-------|--------------------------|------|
| 4.660 | prefix/0 | 1088 |
| 4.661 | prefix/1 | 1088 |
| 4.662 | prefix/2 | 1088 |
| 4.663 | prefix/3 | 1089 |
| 4.664 | preorder/2 | 1089 |
| 4.665 | previous/2 | 1089 |
| 4.666 | previous/3 | 1089 |
| 4.667 | previous/4 | 1089 |
| 4.668 | print_flags/0 | 1089 |
| 4.669 | print_flags/1 | 1089 |
| 4.670 | print_message/3 | 1089 |
| 4.671 | print_message_token/4 | 1090 |
| 4.672 | print_message_tokens/3 | 1090 |
| 4.673 | product/2 | 1090 |
| 4.674 | product/3 | 1090 |
| 4.675 | program_to_clauses/2 | 1090 |
| 4.676 | proper_prefix/2 | 1090 |
| 4.677 | proper_prefix/3 | 1090 |
| 4.678 | proper_suffix/2 | 1090 |
| 4.679 | proper_suffix/3 | 1091 |
| 4.680 | prove/2 | 1091 |
| 4.681 | prove/3 | 1091 |
| 4.682 | provides/2 | 1091 |
| 4.683 | question_hook/6 | 1091 |
| 4.684 | question_prompt_stream/4 | 1091 |
| 4.685 | quick_check/1 | 1091 |
| 4.686 | quick_check/2 | 1091 |
| 4.687 | quick_check/3 | 1092 |
| 4.688 | random/1 | 1092 |
| 4.689 | random/3 | 1092 |
| 4.690 | random_node/1 | 1092 |
| 4.691 | random_tree/1 | 1092 |
| 4.692 | randomize/1 | 1092 |
| 4.693 | randseq/4 | 1092 |
| 4.694 | randset/4 | 1092 |
| 4.695 | range/2 | 1093 |
| 4.696 | rdirectories/1 | 1093 |
| 4.697 | rdirectories/2 | 1093 |
| 4.698 | rdirectory/1 | 1093 |
| 4.699 | rdirectory/2 | 1093 |
| 4.700 | rdirectory/3 | 1093 |
| 4.701 | rdirectory_score/2 | 1094 |
| 4.702 | read_file/2 | 1094 |
| 4.703 | read_file/3 | 1094 |
| 4.704 | read_file_by_line/2 | 1094 |
| 4.705 | read_file_by_line/3 | 1094 |
| 4.706 | read_from_atom/2 | 1094 |
| 4.707 | read_from_chars/2 | 1094 |
| 4.708 | read_from_codes/2 | 1095 |
| 4.709 | read_only_device_path/1 | 1095 |
| 4.710 | read_stream/2 | 1095 |
| 4.711 | read_stream/3 | 1095 |
| 4.712 | read_stream_by_line/2 | 1095 |
| 4.713 | read_stream_by_line/3 | 1095 |

| | |
|-------------------------------------|------|
| 4.714 read_term_from_atom/3 | 1095 |
| 4.715 read_term_from_chars/3 | 1096 |
| 4.716 read_term_from_chars/4 | 1096 |
| 4.717 read_term_from_codes/3 | 1096 |
| 4.718 read_term_from_codes/4 | 1096 |
| 4.719 readme/1 | 1096 |
| 4.720 readme/2 | 1096 |
| 4.721 recorda/2 | 1096 |
| 4.722 recorda/3 | 1096 |
| 4.723 recorded/2 | 1097 |
| 4.724 recorded/3 | 1097 |
| 4.725 recordz/2 | 1097 |
| 4.726 recordz/3 | 1097 |
| 4.727 relative_standard_deviation/2 | 1097 |
| 4.728 removeDependent/1 | 1097 |
| 4.729 remove_duplicates/2 | 1097 |
| 4.730 rename_file/2 | 1097 |
| 4.731 replace/3 | 1098 |
| 4.732 replace_sub_atom/4 | 1098 |
| 4.733 rescale/3 | 1098 |
| 4.734 reset/0 | 1098 |
| 4.735 reset/1 | 1098 |
| 4.736 reset_counter/1 | 1098 |
| 4.737 reset_counters/0 | 1098 |
| 4.738 reset_flags/0 | 1098 |
| 4.739 reset_flags/1 | 1099 |
| 4.740 reset_genint/0 | 1099 |
| 4.741 reset_genint/1 | 1099 |
| 4.742 reset_gensym/0 | 1099 |
| 4.743 reset_gensym/1 | 1099 |
| 4.744 reset_monitor/0 | 1099 |
| 4.745 reset_seed/0 | 1099 |
| 4.746 restore/1 | 1099 |
| 4.747 restore/2 | 1100 |
| 4.748 reverse/2 | 1100 |
| 4.749 rewind/2 | 1100 |
| 4.750 rewind/3 | 1100 |
| 4.751 rlibraries/1 | 1100 |
| 4.752 rlibraries/2 | 1100 |
| 4.753 rlibrary/1 | 1100 |
| 4.754 rlibrary/2 | 1101 |
| 4.755 rlibrary_score/2 | 1101 |
| 4.756 rule/2 | 1101 |
| 4.757 rule/3 | 1101 |
| 4.758 rule/4 | 1101 |
| 4.759 run/0 | 1101 |
| 4.760 run/1 | 1101 |
| 4.761 run/2 | 1102 |
| 4.762 run_test_sets/1 | 1102 |
| 4.763 same_length/2 | 1102 |
| 4.764 same_length/3 | 1102 |
| 4.765 save/0 | 1102 |
| 4.766 save/1 | 1102 |
| 4.767 save/2 | 1102 |

| | |
|--------------------------------|------|
| 4.768 scalar_product/3 | 1102 |
| 4.769 scan_left/4 | 1103 |
| 4.770 scan_left_1/3 | 1103 |
| 4.771 scan_right/4 | 1103 |
| 4.772 scan_right_1/3 | 1103 |
| 4.773 search/1 | 1103 |
| 4.774 select/3 | 1103 |
| 4.775 select/4 | 1103 |
| 4.776 selectchk/3 | 1104 |
| 4.777 selectchk/4 | 1104 |
| 4.778 send/3 | 1104 |
| 4.779 sequence/3 | 1104 |
| 4.780 sequence/4 | 1104 |
| 4.781 sequential_occurrences/2 | 1104 |
| 4.782 sequential_occurrences/3 | 1104 |
| 4.783 serve/3 | 1104 |
| 4.784 set/1 | 1105 |
| 4.785 set/4 | 1105 |
| 4.786 set_element/2 | 1105 |
| 4.787 set_field/2 | 1105 |
| 4.788 set_flag_value/2 | 1105 |
| 4.789 set_flag_value/3 | 1105 |
| 4.790 set_monitor/4 | 1105 |
| 4.791 set_seed/1 | 1105 |
| 4.792 set_spy_point/4 | 1106 |
| 4.793 setup/0 | 1106 |
| 4.794 shell/1 | 1106 |
| 4.795 shell/2 | 1106 |
| 4.796 shell_command/1 | 1106 |
| 4.797 shrink/3 | 1106 |
| 4.798 shrink_sequence/3 | 1106 |
| 4.799 shrinker/1 | 1106 |
| 4.800 sign//1 | 1107 |
| 4.801 singletons/2 | 1107 |
| 4.802 size/2 | 1107 |
| 4.803 skewness/2 | 1107 |
| 4.804 sleep/1 | 1107 |
| 4.805 sort/2 | 1107 |
| 4.806 sort/3 | 1107 |
| 4.807 sort/4 | 1107 |
| 4.808 source_file_extension/1 | 1108 |
| 4.809 space//0 | 1108 |
| 4.810 spaces//0 | 1108 |
| 4.811 split/3 | 1108 |
| 4.812 split/4 | 1108 |
| 4.813 spy/1 | 1108 |
| 4.814 spy/4 | 1108 |
| 4.815 spy_point/4 | 1108 |
| 4.816 spying/1 | 1109 |
| 4.817 spying/4 | 1109 |
| 4.818 standard_deviation/2 | 1109 |
| 4.819 start/0 | 1109 |
| 4.820 start_redirect_to_file/2 | 1109 |
| 4.821 started_by/2 | 1109 |

| | |
|---|------|
| 4.822 starts/2 | 1109 |
| 4.823 stop/0 | 1109 |
| 4.824 stop_redirect_to_file/0 | 1110 |
| 4.825 stream_to_bytes/2 | 1110 |
| 4.826 stream_to_bytes/3 | 1110 |
| 4.827 stream_to_chars/2 | 1110 |
| 4.828 stream_to_chars/3 | 1110 |
| 4.829 stream_to_codes/2 | 1110 |
| 4.830 stream_to_codes/3 | 1110 |
| 4.831 stream_to_terms/2 | 1110 |
| 4.832 stream_to_terms/3 | 1111 |
| 4.833 subclass/1 | 1111 |
| 4.834 subclasses/1 | 1111 |
| 4.835 sublist/2 | 1111 |
| 4.836 subsequence/3 | 1111 |
| 4.837 subsequence/4 | 1111 |
| 4.838 subset/2 | 1111 |
| 4.839 substitute/4 | 1111 |
| 4.840 subsumes/2 | 1112 |
| 4.841 subterm/2 | 1112 |
| 4.842 subtract/3 | 1112 |
| 4.843 succ/2 | 1112 |
| 4.844 suffix/2 | 1112 |
| 4.845 suffix/3 | 1112 |
| 4.846 sum/2 | 1112 |
| 4.847 superclass/1 | 1113 |
| 4.848 superclasses/1 | 1113 |
| 4.849 suspend_monitor/0 | 1113 |
| 4.850 swap/2 | 1113 |
| 4.851 swap_consecutive/2 | 1113 |
| 4.852 symdiff/3 | 1113 |
| 4.853 tab/0 | 1113 |
| 4.854 tabs/0 | 1113 |
| 4.855 take/3 | 1114 |
| 4.856 temporary_directory/1 | 1114 |
| 4.857 term_expansion/2 | 1114 |
| 4.858 terms_to_array/2 | 1114 |
| 4.859 test/1 | 1114 |
| 4.860 time_stamp/1 | 1114 |
| 4.861 timeout/1 | 1114 |
| 4.862 timestamp/2 | 1114 |
| 4.863 timestamp/8 | 1115 |
| 4.864 today/3 | 1115 |
| 4.865 tolerance_equal/4 | 1115 |
| 4.866 top/3 | 1115 |
| 4.867 top_next/5 | 1115 |
| 4.868 trace/0 | 1115 |
| 4.869 trace_event/2 | 1115 |
| 4.870 transpose/2 | 1115 |
| 4.871 true/1 | 1116 |
| 4.872 type/1 | 1116 |
| 4.873 unexpected/1 | 1116 |
| 4.874 unexpecteds/2 | 1116 |
| 4.875 uninstall/0 | 1116 |

| | | |
|-------|--------------------------------|------|
| 4.876 | uninstall/1 | 1116 |
| 4.877 | uninstall/2 | 1116 |
| 4.878 | union/3 | 1116 |
| 4.879 | union/4 | 1117 |
| 4.880 | union_all/3 | 1117 |
| 4.881 | unpin/0 | 1117 |
| 4.882 | unpin/1 | 1117 |
| 4.883 | unzip/2 | 1117 |
| 4.884 | update/0 | 1117 |
| 4.885 | update/1 | 1117 |
| 4.886 | update/2 | 1118 |
| 4.887 | update/3 | 1118 |
| 4.888 | update/4 | 1118 |
| 4.889 | update/5 | 1118 |
| 4.890 | update_in/4 | 1118 |
| 4.891 | update_in/5 | 1118 |
| 4.892 | uuid_null/1 | 1118 |
| 4.893 | uuid_v1/2 | 1118 |
| 4.894 | uuid_v4/1 | 1119 |
| 4.895 | valid/1 | 1119 |
| 4.896 | valid/2 | 1119 |
| 4.897 | valid/3 | 1119 |
| 4.898 | valid_date/3 | 1119 |
| 4.899 | valid_option/1 | 1119 |
| 4.900 | valid_options/1 | 1119 |
| 4.901 | validate/1 | 1120 |
| 4.902 | value/1 | 1120 |
| 4.903 | value/3 | 1120 |
| 4.904 | value_reference/2 | 1120 |
| 4.905 | values/2 | 1120 |
| 4.906 | variables/2 | 1120 |
| 4.907 | variance/2 | 1120 |
| 4.908 | variant/2 | 1120 |
| 4.909 | varnumbers/2 | 1121 |
| 4.910 | varnumbers/3 | 1121 |
| 4.911 | verify_commands_availability/0 | 1121 |
| 4.912 | version/6 | 1121 |
| 4.913 | versions/3 | 1121 |
| 4.914 | void/1 | 1121 |
| 4.915 | void_element/1 | 1121 |
| 4.916 | wall_time/1 | 1121 |
| 4.917 | weighted_mean/3 | 1122 |
| 4.918 | welcome/0 | 1122 |
| 4.919 | when/2 | 1122 |
| 4.920 | whiledo/2 | 1122 |
| 4.921 | white_space//0 | 1122 |
| 4.922 | white_spaces//0 | 1122 |
| 4.923 | with_output_to/2 | 1122 |
| 4.924 | without//2 | 1122 |
| 4.925 | working_directory/1 | 1123 |
| 4.926 | write_file/3 | 1123 |
| 4.927 | write_stream/3 | 1123 |
| 4.928 | write_term_to_atom/3 | 1123 |
| 4.929 | write_term_to_chars/3 | 1123 |

| | | |
|-------|-----------------------|------|
| 4.930 | write_term_to_chars/4 | 1123 |
| 4.931 | write_term_to_codes/3 | 1123 |
| 4.932 | write_term_to_codes/4 | 1123 |
| 4.933 | write_to_atom/2 | 1124 |
| 4.934 | write_to_chars/2 | 1124 |
| 4.935 | write_to_codes/2 | 1124 |
| 4.936 | z_normalization/2 | 1124 |
| 4.937 | zero_or_more/0 | 1124 |
| 4.938 | zero_or_more/1 | 1124 |
| 4.939 | zero_or_more/2 | 1124 |
| 4.940 | zip/2 | 1124 |
| 4.941 | zip/3 | 1125 |
| 4.942 | zip_at_index/4 | 1125 |
| 5 | Indices and tables | 1127 |
| | Index | 1129 |

LIBRARIES

To load any library (including developer tools, ports, and contributions), use the goal `logtalk_load(library_name(loader))`. To run the library tests, use the goal `logtalk_load(library_name(tester))`. To load an entity, always load the loader file of the library that includes it to ensure that all required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

1.1 arbitrary

category

1.1.1 arbitrary

Adds predicates for generating and shrinking random values for selected types to the library type object. User extensible.

Availability:

`logtalk_load(arbitrary(loader))`

Author: Paulo Moura

Version: 2:35:0

Date: 2024-03-07

Compilation flags:

`static`

Complements:

`type`

Uses:

`fast_random`

`integer`

`list`

`type`

Remarks:

- Logtalk specific types: `entity`, `object`, `protocol`, `category`, `entity_identifier`, `object_identifier`, `protocol_identifier`, `category_identifier`, `event`, `predicate`.
- Prolog module related types (when the backend compiler supports modules): `module`, `module_identifier`, `qualified_callable`.
- Prolog base types: `term`, `var`, `nonvar`, `atomic`, `atom`, `number`, `integer`, `float`, `compound`, `callable`, `ground`.
- Atom derived types: `non_quoted_atom`, `non_empty_atom`, `non_empty_atom(CharSet)`, `boolean`, `character`, `in_character`, `char`, `operator_specifier`, `hex_char`.
- Atom derived parametric types: `atom(CharSet)`, `atom(CharSet,Length)`, `non_empty_atom(CharSet)`, `character(CharSet)`, `in_character(CharSet)`, `char(CharSet)`.
- Number derived types: `positive_number`, `negative_number`, `non_positive_number`, `non_negative_number`.
- Float derived types: `positive_float`, `negative_float`, `non_positive_float`, `non_negative_float`, `probability`.
- Integer derived types: `positive_integer`, `negative_integer`, `non_positive_integer`, `non_negative_integer`, `byte`, `in_byte`, `character_code`, `in_character_code`, `code`, `operator_priority`, `hex_code`.
- Integer derived parametric types: `character_code(CharSet)`, `in_character_code(CharSet)`, `code(CharSet)`.
- List types (compound derived types): `list`, `non_empty_list`, `partial_list`, `list_or_partial_list`, `list(Type)`, `list(Type,Length)`, `list(Type,Min,Max)`, `list(Type,Length,Min,Max)`, `non_empty_list(Type)`, `codes`, `chars`.
- Difference list types (compound derived types): `difference_list`, `difference_list(Type)`.
- List and difference list types length: The types that do not take a fixed length generate lists with a length in the `[0,MaxSize]` interval (`[1,MaxSize]` for non-empty list types).
- Predicate and non-terminal indicator types arity: These types generate indicators with an arity in the `[0,MaxSize]` interval.
- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `types_frequency(Pairs)`, `transform(Type,Closure)`, `constrain(Type,Closure)`.
- Type `Object::Closure` notes: Allows calling public object predicates as generators and shrinkers. The `Closure` closure is extended with either a single argument, the generated arbitrary value, or with two arguments, when shrinking a value.
- Type `compound(Name,Types)` notes: Generate a random compound term with the given name with a random argument for each type.
- Type `types_frequency(Pairs)` notes: Generate a random term for one of the types in a list of Type-Frequency pairs. The type is randomly selected taking into account the types frequency.
- Type `transform(Type,Closure)` notes: Generate a random term by transforming the term generated for the given type using the given closure.

- `Type constrain(Type,Closure)` notes: Generate a random term for the given type that satisfy the given closure.
- Registering new types: Add clauses for the arbitrary/1-2 multifile predicates and optionally for the shrinker/1 and shrink/3 multifile predicates. The clauses must have a bound first argument to avoid introducing spurious choice-points.
- Shrinking values: The shrink/3 should either succeed or fail but never throw an exception.
- Character sets: `ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, `unicode_full`.
- Default character sets: The default character set when using a parameterizable type that takes a character set parameter depends on the type.
- Default character sets: Entity, predicate, and non-terminal identifier types plus compound and callable types default to an `ascii_identifier` functor. Character and character code types default to `ascii_full`. Other types default to `ascii_printable`.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code generation is only ensured for LVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

(none)

- Public predicates
 - `arbitrary/1`
 - `arbitrary/2`
 - `shrinker/1`
 - `shrink/3`
 - `shrink_sequence/3`
 - `edge_case/2`
 - `get_seed/1`
 - `set_seed/1`
 - `max_size/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

arbitrary/1

Table of defined types for which an arbitrary value can be generated. A new type can be registered by defining a clause for this predicate and adding a clause for the arbitrary/2 multifile predicate.

Compilation flags:

static, multifile

Template:

arbitrary(Type)

Mode and number of proofs:

arbitrary(?callable) - zero_or_more

arbitrary/2

Generates an arbitrary term of the specified type. Fails if the type is not supported. A new generator can be defined by adding a clause for this predicate and registering it via the arbitrary/1 predicate.

Compilation flags:

static, multifile

Template:

arbitrary(Type,Term)

Meta-predicate template:

arbitrary(:,*)

Mode and number of proofs:

arbitrary(@callable,-term) - zero_or_one

shrinker/1

Table of defined types for which a shrinker is provided. A new shrinker can be registered by defining a clause for this predicate and adding a definition for the shrink/3 multifile predicate.

Compilation flags:

static, multifile

Template:

shrinker(Type)

Mode and number of proofs:

shrinker(?callable) - zero_or_more

`shrink/3`

Shrinks a value to a smaller value if possible. Must generate a finite number of solutions. Fails if the type is not supported. A new shrinker can be defined by adding a clause for this predicate and registering it via the shrinker/1 predicate.

Compilation flags:

static, multifile

Template:

shrink(Type, Large, Small)

Mode and number of proofs:

shrink(@callable, @term, -term) - zero_or_more

`shrink_sequence/3`

Shrinks a value repeatedly until shrinking is no longer possible returning the sequence of values (ordered from larger to smaller value). Fails if the type is not supported.

Compilation flags:

static

Template:

shrink_sequence(Type, Value, Sequence)

Mode and number of proofs:

shrink_sequence(@callable, @term, -list(term)) - zero_or_one

edge_case/2

Table of type edge cases. Fails if the given type have no defined edge cases. New edge cases for existing or new types can be added by defining a clause for this multifile predicate.

Compilation flags:
static, multifile

Template:
edge_case(Type,Term)
Mode and number of proofs:
edge_case(?callable,?term) - zero_or_more

get_seed/1

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:
static

Template:
get_seed(Seed)
Mode and number of proofs:
get_seed(-ground) - one

set_seed/1

Sets the random generator seed to a given value returned by calling the get_seed/1 predicate.

Compilation flags:
static

Template:
set_seed(Seed)
Mode and number of proofs:
set_seed(+ground) - one

`max_size/1`

User defined maximum size for types where its meaningful and implicit. When not defined, defaults to 42. When multiple definitions exist, the first valid one found is used.

Compilation flags:
static, multifile

Template:
max_size(Size)
Mode and number of proofs:
max_size(?positive_integer) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`type`

1.2 assertions

object

1.2.1 assertions

Proxy object for simplifying the use of the assertion meta-predicates.

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-04-03

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public assertions(_)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
assertion/1 assertion/2 goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.2.2 assertions(*Mode*)

A simple assertions framework. Can be used as a hook object for either suppressing assertions (production mode) or expanding them with file context information (debug mode).

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:2:2

Date: 2022-07-04

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
logtalk
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - assertion/1

- assertion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

assertion/1

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure.

Compilation flags:

static

Template:

assertion(Goal)

Meta-predicate template:

assertion(0)

Mode and number of proofs:

assertion(@callable) - one

assertion/2

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure. The context argument can be used to e.g. pass location data.

Compilation flags:

static

Template:

assertion(Context,Goal)

Meta-predicate template:

assertion(*,0)

Mode and number of proofs:

assertion(@term,@callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.2.3 assertions__messages

Assertions framework default message translations.

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:2:0

Date: 2018-02-20

Compilation flags:

```
static
```

Provides:

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.3 assignvars

object

1.3.1 assignvars

Assignable variables (supporting backtracable assignment of non-variable terms).

Availability:

```
logtalk_load(assignvars(loader))
```

Author: Nobukuni Kino and Paulo Moura

Version: 1:7:0

Date: 2018-07-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public assignvarsp
```

Remarks:

(none)

Inherited public predicates:

`(<=)/2` `(=>)/2` `assignable/1` `assignable/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.3.2 assignvarsp

Assignable variables (supporting backtracable assignment of non-variable terms) protocol.

Availability:

`logtalk_load(assignvars(loader))`

Author: Nobukuni Kino and Paulo Moura

Version: 1:0:1

Date: 2019-06-10

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - assignable/1
 - assignable/2
 - (\leq)/2
 - (\geq)/2
- Protected predicates
- Private predicates
- Operators
 - op(100,xfx, \leq)
 - op(100,xfx, \geq)

Public predicates

assignable/1

Makes Variable an assignable variable. Initial state will be empty.

Compilation flags:

static

Template:

assignable(Variable)

Mode and number of proofs:

assignable(--assignvar) - one

Exceptions:

Variable is not a variable:

type__error(variable,Variable)

assignable/2

Makes Variable an assignable variable and sets its initial state to Value.

Compilation flags:

static

Template:

assignable(Variable, Value)

Mode and number of proofs:

assignable(--assignvar, @nonvar) - one

Exceptions:

Variable is not a variable:

type_error(variable, Variable)

Value is not instantiated:

instantiation_error

(<=)/2

Sets the state of the assignable variable Variable to Value (initializing the variable if needed).

Compilation flags:

static

Template:

Variable<=Value

Mode and number of proofs:

(?assignvar)<=(@nonvar) - one

Exceptions:

Value is not instantiated:

instantiation_error

$(=>)/2$

Unifies Value with the current state of the assignable variable Variable.

Compilation flags:

static

Template:

Variable= \Rightarrow Value

Mode and number of proofs:

+assignvar= \Rightarrow ?nonvar - zero_or_one

Exceptions:

Variable is not instantiated:

instantiation_error

Protected predicates

(none)

Private predicates

(none)

Operators

op(100,xfx,<=)

Scope:

public

op(100,xfx,= \Rightarrow)

Scope:

public

See also:

assignvars

1.4 base64

object

1.4.1 base64

Base64 parser and generator.

Availability:

```
logtalk_load(base64(loader))
```

Author: Paulo Moura

Version: 0:10:0

Date: 2021-03-22

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
reader
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse/2`

Parses the Base64 data from the given source (`atom(Atom)`, `chars(List)`, `codes(List)`, `stream(Stream)`, or `file(Path)`) into a list of bytes.

Compilation flags:

`static`

Template:

`parse(Source,Bytes)`

Mode and number of proofs:

`parse(++compound,--list(byte)) - one_or_error`

`generate/2`

Generates Base64 in the representation specified in the first argument (`atom(Atom)`, `chars(List)`, `codes(List)`, `stream(Stream)`, or `file(Path)`) for the list of bytes in the second argument.

Compilation flags:

`static`

Template:

`generate(Sink,Bytes)`

Mode and number of proofs:

`generate(+compound,+list(byte)) - one_or_error`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.4.2 base64url

Base64URL parser and generator.

Availability:

`logtalk__load(base64(loader))`

Author: Paulo Moura

Version: 0:9:0

Date: 2021-03-10

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `parse/2`
 - `generate/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse/2`

Parses the Base64URL data from the given source (`atom(Atom)`, `chars(List)`, or `codes(List)`) into a URL (using the same format as the source).

Compilation flags:

`static`

Template:

`parse(Source,URL)`

Mode and number of proofs:

`parse(++compound,--types([atom,chars,codes])) - one_or_error`

`generate/2`

Generates Base64URL data in the representation specified in the first argument (`atom(Atom)`, `chars(List)`, or `codes(List)`) for the given URL (given in the same format as the sink).

Compilation flags:

`static`

Template:

`generate(Sink,URL)`

Mode and number of proofs:

`generate(+compound,+types([atom,chars,codes])) - one_or_error`

Protected predicates

`(none)`

Private predicates

(none)

Operators

(none)

1.5 cbor

object

1.5.1 cbor

Concise Binary Object Representation (CBOR) format exporter and importer. Uses atoms to represent decoded CBOR strings.

Availability:

```
logtalk_load(cbor(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2021-03-04

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public cbor(atom)
```

Remarks:

(none)

Inherited public predicates:

```
generate/2 parse/2
```

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.5.2 cbor(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding CBOR strings. Possible values are atom (default), chars, and codes.

Concise Binary Object Representation (CBOR) format exporter and importer.

Availability:

`logtalk_load(cbor(loader))`

Author: Paulo Moura

Version: 0:11:1

Date: 2021-12-06

Compilation flags:

`static, context_switching_calls`

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses a list of bytes in the CBOR format returning the corresponding term representation. Throws an error when parsing is not possible (usually due to an invalid byte sequence).

Compilation flags:

static

Template:

parse(Bytes,Term)

Mode and number of proofs:

parse(@list(byte),-ground) - one_or_error

generate/2

Generates a list of bytes in the CBOR format representing the given term. Throws an error when generating is not possible (usually due to a term that have no CBOR corresponding representation).

Compilation flags:

static

Template:

generate(Term,Bytes)

Mode and number of proofs:

generate(@ground,-list(byte)) - one_or_error

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.6 code_metrics

object

1.6.1 cc_metric

Cyclomatic complexity metric. All defined predicates that are not called or updated are counted as graph connected components (the reasoning being that these predicates can be considered entry points). The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:2

Date: 2024-05-15

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list  
logtalk
```

numberlist

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.2 code_metric

Core predicates for computing source code metrics.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:12:1

Date: 2024-05-08

Compilation flags:

```
static
```

Extends:

```
public code_metrics_utilities
```

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3  
valid_option/1 valid_options/1
```

- Public predicates

- entity/1
- file/2
- file/1
- directory/2
- directory/1
- rdirectory/2
- rdirectory/1
- library/2

- library/1
- rlibrary/2
- rlibrary/1
- all/1
- all/0
- entity_score/2
- library_score/2
- rlibrary_score/2
- file_score/2
- directory_score/2
- rdirectory_score/2
- all_score/1
- format_entity_score//2
- Protected predicates
 - process_entity/2
 - process_file/2
 - process_directory/2
 - process_rdirectory/2
 - process_library/2
 - process_rlibrary/2
 - process_all/1
 - sub_directory/2
 - sub_library/2
- Private predicates
- Operators

Public predicates

entity/1

Scans an entity and prints its metric score.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+term) - zero_or_one

file/2

Prints metric scores for all the entities defined in a loaded source file using the given options.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Prints metric scores for all the entities defined in a loaded source file using default options.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans a directory and prints metric scores for all entities defined in its loaded source files using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans a directory and prints metric scores for all entities defined in its loaded source files using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

rdirectory/2

Recursive version of the directory/1 predicate using the given options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list(compound)) - one

`rdirectory/1`

Recursive version of the `directory/1` predicate using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`library/2`

Prints metrics scores for all loaded entities from a given library using the given options.

Compilation flags:

`static`

Template:

`library(Library,Options)`

Mode and number of proofs:

`library(+atom,+list(compound)) - one`

`library/1`

Prints metrics scores for all loaded entities from a given library using default options.

Compilation flags:

`static`

Template:

`library(Library)`

Mode and number of proofs:

`library(+atom) - one`

rlibrary/2

Recursive version of the library/1 predicate using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Recursive version of the library/1 predicate using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all loaded entities and prints their metric scores using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

all/0

Scans all loaded entities and prints their metric scores using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

entity_score/2

Score is a term that represents the metric score associated with a loaded entity. Fails if the metric does not apply.

Compilation flags:

static

Template:

entity_score(Entity,Score)

Mode and number of proofs:

entity_score(@entity_identifier,-ground) - zero_or_one

library_score/2

Score is a term that represents the metric score associated with a loaded library source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

library_score(Library,Score)

Mode and number of proofs:

library_score(@atom,-ground) - zero_or_one

`rlibrary_score/2`

Score is a term that represents the metric score associated with loaded source files from a library and its sub-libraries. Fails if the metric does not apply.

Compilation flags:

`static`

Template:

`rlibrary_score(Library,Score)`

Mode and number of proofs:

`rlibrary_score(@atom,-ground) - zero_or_one`

`file_score/2`

Score is a term that represents the metric score associated with a loaded source file. Fails if the metric does not apply.

Compilation flags:

`static`

Template:

`file_score(File,Score)`

Mode and number of proofs:

`file_score(@atom,-ground) - zero_or_one`

`directory_score/2`

Score is a term that represents the metric score associated with loaded source files from a directory. Fails if the metric does not apply.

Compilation flags:

`static`

Template:

`directory_score(Directory,Score)`

Mode and number of proofs:

directory_score(@atom,-ground) - zero_or_one

rdirectory_score/2

Score is a term that represents the metric score associated with loaded source files from a directory and its sub-directories. Fails if the metric does not apply.

Compilation flags:

static

Template:

rdirectory_score(Directory,Score)

Mode and number of proofs:

rdirectory_score(@atom,-ground) - zero_or_one

all_score/1

Score is a term that represents the metric score associated with all loaded source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

all_score(Score)

Mode and number of proofs:

all_score(-ground) - zero_or_one

`format_entity_score//2`

Formats the entity score for pretty printing.

Compilation flags:

`static`

Template:

`format_entity_score(Entity,Score)`

Mode and number of proofs:

`format_entity_score(@entity_identifier,+ground) - one`

Protected predicates

`process_entity/2`

Processes an entity of the given kind.

Compilation flags:

`static`

Template:

`process_entity(Kind,Entity)`

Mode and number of proofs:

`process_entity(+atom,@entity_identifier) - one`

`process_file/2`

Processes a source file using the given options.

Compilation flags:

`static`

Template:

`process_file(Path,Options)`

Mode and number of proofs:

`process_file(+atom,+list(compound)) - one`

`process_directory/2`

Processes a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_directory(Path,Options)`

Mode and number of proofs:

`process_directory(+atom,+list(compound)) - one`

`process_rdirectory/2`

Recursively process a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_rdirectory(Path,Options)`

Mode and number of proofs:

`process_rdirectory(+atom,+list(compound)) - one`

`process_library/2`

Processes a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_library(Library,Options)`

Mode and number of proofs:

`process_library(+atom,+list(compound)) - one`

`process_rlibrary/2`

Recursively process a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_rlibrary(Library,Options)`

Mode and number of proofs:

`process_rlibrary(+atom,+list(compound)) - one`

`process_all/1`

Processes all loaded source code using the given options.

Compilation flags:

`static`

Template:

`process_all(Options)`

Mode and number of proofs:

`process_all(+list(compound)) - one`

`sub_directory/2`

Enumerates, by backtracking, all directory sub-directories containing loaded files.

Compilation flags:

`static`

Template:

sub_directory(Directory,SubDirectory)

Mode and number of proofs:

sub_directory(+atom,-atom) - one

sub_library/2

Enumerates, by backtracking, all library sub-libraries.

Compilation flags:

static

Template:

sub_library(Library,SubLibrary)

Mode and number of proofs:

sub_library(+atom,-atom) - one

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.3 code_metrics

Helper object to apply all loaded code metrics.

Availability:

logtalk_load(code_metrics(loader))

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:1:0

Date: 2017-12-31

Compilation flags:

static, context_switching_calls

Imports:

public code_metric

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.4 code_metrics_messages

Message translations for the code_metrics tool.

Availability:

logtalk_load(code_metrics(loader))

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:8:0

Date: 2022-05-05

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.5 code_metrics_utilities

Internal predicates for analyzing source code.

Availability:

`logtalk_load(code_metrics(loader))`

Author: Ebrahim Azarisooreh

Version: 0:7:0

Date: 2024-03-28

Compilation flags:

`static`

Uses:

`list`

`logtalk`

Remarks:

- Usage: This is meant to be imported by any metric added to the system.
- Predicate Scope: This is meant for internal use by metrics only. As such, all provided predicates are protected.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
 - ancestor/4
 - current_entity/1
 - declares_predicate/2
 - defines_predicate/2
 - defines_predicate/3
 - entity_calls/3
 - entity_kind/2
 - entity_property/2
 - entity_updates/3
 - not_excluded_file/3
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

ancestor/4

True if Entity descends from Ancestor, and EntityKind and AncestorKind unify with their respective entity types.

Compilation flags:

static

Template:

ancestor(EntityKind,Entity,AncestorKind,Ancestor)

Mode and number of proofs:

ancestor(?entity,?entity_identifier,?entity,?entity_identifier) - zero_or_more

`current_entity/1`

True if Entity is a currently loaded entity.

Compilation flags:

`static`

Template:

`current_entity(Entity)`

Mode and number of proofs:

`current_entity(?entity_identifier) - zero_or_more`

`declares_predicate/2`

True if Entity declares Predicate internally.

Compilation flags:

`static`

Template:

`declares_predicate(Entity,Predicate)`

Mode and number of proofs:

`declares_predicate(?entity_identifier,?predicate_indicator) - zero_or_more`

`defines_predicate/2`

True if Entity defines an implementation of Predicate internally. Auxiliary predicates are excluded from results.

Compilation flags:

`static`

Template:

`defines_predicate(Entity,Predicate)`

Mode and number of proofs:

`defines_predicate(?entity_identifier,?predicate_indicator) - zero_or_more`

`defines__predicate/3`

Same as `defines__predicate/2`, except `Property` is unified with a property of the predicate.

Compilation flags:
 `static`

Template:
 `defines__predicate(Entity,Predicate,Property)`
Mode and number of proofs:
 `defines__predicate(?entity__identifier,?predicate__indicator,?term) - zero_or_more`

`entity__calls/3`

True if a predicate `Caller` within `Entity` makes a `Call`.

Compilation flags:
 `static`

Template:
 `entity__calls(Entity,Caller,Call)`
Mode and number of proofs:
 `entity__calls(?entity__identifier,?predicate__indicator,?predicate__indicator) - zero_or_one`

`entity__kind/2`

True if `Kind` defines `Entity` and is one of category, protocol, or object.

Compilation flags:
 `static`

Template:
 `entity__kind(Entity,Kind)`
Mode and number of proofs:

`entity_kind(+entity_identifier,-entity) - zero_or_one`

`entity_property/2`

True if Property is a valid property of Entity. Entity can be either a category, a protocol, or an object.

Compilation flags:

`static`

Template:

`entity_property(Entity,Property)`

Mode and number of proofs:

`entity_property(+entity_identifier,-term) - zero_or_more`

`entity_updates/3`

True if a predicate Updater within Entity makes a dynamic update to Updated (by using e.g. the `asserta/1` or `retract/1` predicates).

Compilation flags:

`static`

Template:

`entity_updates(Entity,Updater,Updated)`

Mode and number of proofs:

`entity_updates(+entity_identifier,?predicate_indicator,?predicate_indicator) - zero_or_one`

`not_excluded_file/3`

True if the file is not being excluded.

Compilation flags:

`static`

Template:

```
not_excluded_file(ExcludedFiles,Path,Basename)
```

Mode and number of proofs:

```
not_excluded_file(+list(atom),+atom,+atom) - zero_or_one
```

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.6 coupling_metric

Computes entity efferent coupling, afferent coupling, and instability.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:0

Date: 2024-03-27

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Uses:

```
list
```

Remarks:

- Efferent coupling (Ce): Number of entities that an entity depends on.
- Afferent coupling (Ca): Number of entities that depend on an entity.

- Instability (I): Computed as $Ce / (Ce + Ca)$. Measures the entity resilience to change. Ranging from 0 to 1, with 0 indicating a maximally stable entity and 1 indicating a maximally unstable entity. Ideally, an entity is either maximally stable or maximally unstable.
- Abstractness (A): Computed as the ratio between the number of static predicates with scope directives without a local definition and the number of static predicates with scope directives. Measures the rigidity of an entity. Ranging from 0 to 1, with 0 indicating a fully concrete entity and 1 indicating a fully abstract entity.
- Entity score: Represented as the compound term `ce_ca_i_a(Ce,Ca,I,A)`.
- Dependencies count: Includes direct entity relations plus calls or dynamic updates to predicates in external objects or categories.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score/2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.7 dit_metric

Analyzes the depth of inheritance for objects, protocols, and categories.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh

Version: 0:6:1

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Uses:

```
numberlist
```

Remarks:

- Depth: The depth is the maximum length of a node to the root entity. Lower scores are generally better.
- Inheritance: A level of inheritance defined by either one of specialization, instantiation, extension, importation, or implementation.
- Scoring: The maximum path length is determined for each entity in question.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1  
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2  
format_entity_score/2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1  
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1  
valid_options/1
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.8 `doc_metric`

Entity and entity predicates documentation score.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:13:0

Date: 2022-05-05

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code\_metrics\_utilities
public code\_metric
```

Uses:

```
list
```

numberlist

Remarks:

- Score range: Score is a integer percentage where a 100% score means that all expected documentation information is present.
- Score weights: The score is split by default between 20% for the entity documentation and 80% for the entity predicates documentation, Can be customized using the predicate `entity_predicates_weights_hook/2`.
- Score customization: The individual scores of entity info/1 pairs and predicate info/2 pairs can be customized using the `entity_info_pair_score_hook/3` and `predicate_info_pair_score_hook/4` predicates.

Inherited public predicates:

`all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score/2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1`

- Public predicates
 - `entity_predicates_weights_hook/2`
 - `entity_info_score_hook/2`
 - `entity_info_pair_score_hook/3`
 - `predicate_mode_score_hook/3`
 - `predicate_mode_score_hook/5`
 - `predicate_info_score_hook/3`
 - `predicate_info_pair_score_hook/4`
- Protected predicates
- Private predicates
- Operators

Public predicates

`entity_predicates_weights_hook/2`

Relative weight between entity documentation and predicates documentation in percentage. The sum of the two values must be equal to 100.

Compilation flags:

`dynamic, multifile`

Template:

entity_predicates_weights_hook(EntityWeight,PredicatesWeight)

Mode and number of proofs:

entity_predicates_weights_hook(?integer,?integer) - zero_or_one

entity_info_score_hook/2

Maximum score for entity info/1 directives.

Compilation flags:

dynamic, multifile

Template:

entity_info_score_hook(Entity,MaximumScore)

Mode and number of proofs:

entity_info_score_hook(?term,?integer) - zero_or_one

entity_info_pair_score_hook/3

Score for relevant entity info/1 directive pairs. If defined, the entity_info_score_hook/2 predicate should be defined accordingly.

Compilation flags:

dynamic, multifile

Template:

entity_info_pair_score_hook(Pair,Entity,Score)

Mode and number of proofs:

entity_info_pair_score_hook(?callable,?term,?integer) - zero_or_more

`predicate_mode_score_hook/3`

Maximum score for predicate mode/2 directives.

Compilation flags:
dynamic, multifile

Template:
predicate_mode_score_hook(Entity,Predicate,MaximumScore)
Mode and number of proofs:
predicate_mode_score_hook(?term,?term,?integer) - zero_or_more

`predicate_mode_score_hook/5`

Score for a predicate mode/2 directive. If defined, the predicate_mode_score_hook/3 predicate should be defined accordingly.

Compilation flags:
dynamic, multifile

Template:
predicate_mode_score_hook(Template,Solutions,Entity,Predicate,Score)
Mode and number of proofs:
predicate_mode_score_hook(?term,?term,?term,?term,?integer) - zero_or_one

`predicate_info_score_hook/3`

Maximum score for predicate info/2 directives.

Compilation flags:
dynamic, multifile

Template:
predicate_info_score_hook(Entity,Predicate,MaximumScore)
Mode and number of proofs:
predicate_info_score_hook(?term,?term,?integer) - zero_or_one

`predicate_info_pair_score_hook/4`

Score for a predicate info/2 directive pairs. If defined, the `predicate_info_score_hook/3` predicate should be defined accordingly.

Compilation flags:
dynamic, multifile

Template:
 `predicate_info_pair_score_hook(Pair,Entity,Predicate,Score)`
Mode and number of proofs:
 `predicate_info_pair_score_hook(?callable,?term,?term,?integer) - zero_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
object

1.6.9 `halstead_metric`

Computes Halstead complexity numbers for an entity using a Stroud of 18.

Availability:
 `logtalk_load(code_metrics(loader))`

Author: Paulo Moura
Version: 1:0:0
Date: 2018-06-08

Compilation flags:

static, context_switching_calls

Extends:

public halstead_metric(18)

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score/2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.10 `halstead_metric`(Stroud)

- Stroud - Coefficient for computing the time required to program.

Computes Halstead complexity numbers for an entity.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:9:0

Date: 2024-03-27

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
public code_metric
```

Uses:

```
list
numberlist
pairs
```

Remarks:

- Definition of operators: Predicates declared, user-defined, and called are interpreted as operators. Built-in predicates and built-in control constructs are ignored.
- Definition of operands: Predicate arguments are abstracted and interpreted as operands. Note that this definition of operands is a significant deviation from the original definition, which used syntactic literals.
- P_n : Number of distinct predicates (declared, defined, called, or updated).
- PAn : Number of predicate arguments (assumed distinct).
- C_n : Number of predicate calls/updates + number of clauses.
- CAn : Number of predicate call/update arguments + number of clause head arguments.
- EV: Entity vocabulary: $EV = P_n + PAn$.
- EL: Entity length: $EL = C_n + CAn$.
- V: Volume: $V = EL * \log_2(EV)$.
- D: Difficulty: $D = (P_n/2) * (CAn/An)$.
- E: Effort: $E = D * V$.
- T: Time required to program: $T = E/k$ seconds (k is the Stroud number; defaults to 18).

- B: Number of delivered bugs: $B = V/3000$.
- Entity score: Represented as the compound term `pn_pan_cn_can_ev_el_v_d_e_t_b/11`.

Inherited public predicates:

`all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.11 `noc_metric`

Number of entity clauses metric. The score is represented using the compound term `number_of_clauses(Total, User)`.

Availability:

`logtalk_load(code_metrics(loader))`

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:1
Date: 2024-05-08

Compilation flags:
static, context_switching_calls

Imports:
public code_metrics_utilities
public code_metric

Provides:
logtalk::message_tokens//2

Uses:
list
logtalk

Remarks:
(none)

Inherited public predicates:
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.12 `nor_metric`

Number of entity rules metric. The score is represented using the compound term `number_of_rules(Total, User)`.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:1

Date: 2024-05-08

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

```
(none)
```


Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.13 size__metric

Source code size metric. Returned scores are upper bounds and based solely in source file sizes (expressed in bytes).

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:7:1

Date: 2024-05-08

Compilation flags:

static, context_switching_calls

Imports:

public code_metrics_utilities
public code_metric

Provides:

logtalk::message_tokens//2

Uses:

list
logtalk
numberlist
os

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.14 upn_metric

Number of unique predicates nodes metric. The nodes include called and updated predicates independently of where they are defined. The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:6:2

Date: 2024-05-15

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

```
numberlist
```

Remarks:

(none)

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.7 core

category

1.7.1 core_messages

Logtalk core (compiler and runtime) default message tokenization.

Availability:

built_in

Author: Paulo Moura

Version: 1:134:0

Date: 2024-05-18

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4
 logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.7.2 expanding

Term and goal expansion protocol.

Availability:

built_in

Author: Paulo Moura

Version: 1:1:0

Date: 2016-07-12

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - goal_expansion/2
 - term_expansion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

goal_expansion/2

Defines a goal expansion. Called recursively until a fixed point is reached on goals found while compiling a source file (except for goals wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:

static

Template:

goal_expansion(Goal,ExpandedGoal)

Mode and number of proofs:

goal_expansion(+callable,-callable) - zero_or_one

term_expansion/2

Defines a term expansion. Called until it succeeds on all terms read while compiling a source file (except for terms skipped by using the conditional compilation directives or wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:

static

Template:

term_expansion(Term,ExpandedTerms)

Mode and number of proofs:

term_expansion(+term,-term) - zero_or_one

term_expansion(+term,-list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

protocol

1.7.3 forwarding

Message forwarding protocol.

Availability:

built_in

Author: Paulo Moura

Version: 1:0:0

Date: 2013-05-04

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - forward/1
- Protected predicates
- Private predicates
- Operators

Public predicates

forward/1

User-defined message forwarding handler, automatically called (if defined) by the runtime for any message that the receiving object does not understand.

Compilation flags:

static

Template:

forward(Message)

Mode and number of proofs:

forward(@callable) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.7.4 logtalk

Built-in object providing message printing, debugging, library, source file, and hacking methods.

Availability:

built_in

Author: Paulo Moura

Version: 2:0:0

Date: 2024-05-18

Compilation flags:

static, built_in, context_switching_calls, threaded

Dependencies:

(none)

Remarks:

- Default message kinds: silent, silent(Key), banner, help, comment, comment(Key), information, information(Key), warning, warning(Key), error, error(Key), debug, debug(Key), question, and question(Key).
- Printing of silent messages: By default, silent messages are not printed. These messages are only useful when intercepted.
- Printing of banner and comment messages: By default, banner and comment messages are only printed when the report flag is turned on.
- Printing of help, information, and question messages: These messages are always printed by default as they provide requested output.
- Printing of warning messages: By default, warning messages are not printed when the report flag is turned off.

- Printing of error messages: These messages are always printed by default.
- Printing of debug messages: By default, debug messages are only printed when the debug flag is turned on. The compiler suppresses debug message printing goals when compiling in optimized mode.
- Meta messages: A meta message is a message that have another message as argument and is typically used for debugging messages. Meta messages avoid the need of defining tokenizer rules for every message but can be intercepted as any other message.
- Meta message @Message: By default, the message is printed as passed to the write/1 predicate followed by a newline.
- Meta message Key-Value: By default, the message is printed as “Key: Value” followed by a newline. The key is printed as passed to the write/1 predicate while the value is printed as passed to the writeq/1 predicate.
- Meta message Format+Arguments: By default, the message is printed as passed to the format/2 predicate.
- Meta message List: By default, the list items are printed indented one per line. The items are preceded by a dash and can be @Message, Key-Value, or Format+Arguments messages. If that is not the case, the item is printed as passed to the writeq/1 predicate.
- Meta message Title::List: By default, the title is printed followed by a newline and the indented list items, one per line. The items are printed as in the List meta message.
- Meta message [Stream,Prefix]>>Goal: By default, call user-defined Goal in the context of user. The use of a lambda expression allows passing the message stream and prefix. Printing the prefix is delegated to the goal.
- Meta message [Stream]>>Goal: By default, call user-defined Goal in the context of user. The use of a lambda expression allows passing the message stream.
- Message tokens: at_same_line, tab(Expression), nl, flush, Format-Arguments, term(Term,Options), ansi(Attributes,Format,Arguments), begin(Kind,Variable), and end(Variable).

Inherited public predicates:

(none)

- Public predicates
 - print_message/3
 - print_message_tokens/3
 - print_message_token/4
 - message_tokens//2
 - message_prefix_stream/4
 - message_hook/4
 - ask_question/5
 - question_hook/6
 - question_prompt_stream/4
 - trace_event/2

- debug_handler/1
- active_debug_handler/1
- activate_debug_handler/1
- deactivate_debug_handler/0
- debug_handler/3
- expand_library_path/2
- loaded_file/1
- loaded_file_property/2
- file_type_extension/2
- compile_aux_clauses/1
- entity_prefix/2
- compile_predicate_heads/4
- compile_predicate_indicators/3
- decompile_predicate_heads/4
- decompile_predicate_indicators/4
- execution_context/7
- Protected predicates
- Private predicates
 - active_debug_handler_/1
- Operators

Public predicates

print_message/3

Prints a message of the given kind for the specified component.

Compilation flags:

static

Template:

print_message(Kind,Component,Message)

Mode and number of proofs:

print_message(+nonvar,+nonvar,+nonvar) - one

`print_message_tokens/3`

Print the messages tokens to the given stream, prefixing each line with the specified atom.

Compilation flags:

`static`

Template:

`print_message_tokens(Stream,Prefix,Tokens)`

Mode and number of proofs:

`print_message_tokens(@stream_or_alias,+atom,@list(nonvar)) - one`

`print_message_token/4`

User-defined hook predicate for printing a message token (see this object remarks).

Compilation flags:

`dynamic, multifile`

Template:

`print_message_token(Stream,Prefix,Token,Tokens)`

Mode and number of proofs:

`print_message_token(@stream_or_alias,@atom,@nonvar,@list(nonvar)) - zero_or_one`

`message_tokens//2`

User-defined hook grammar rule for converting a message into a list of tokens (see this object remarks).

Compilation flags:

`dynamic, multifile`

Template:

`message_tokens(Message,Component)`

Mode and number of proofs:

`message_tokens(+nonvar,+nonvar) - zero_or_one`

`message_prefix_stream/4`

Message line prefix and output stream to be used when printing a message given its kind and component.

Compilation flags:

dynamic, multifile

Template:

`message_prefix_stream(Kind,Component,Prefix,Stream)`

Mode and number of proofs:

`message_prefix_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more`

`message_hook/4`

User-defined hook predicate for intercepting message printing calls.

Compilation flags:

dynamic, multifile

Template:

`message_hook(Message,Kind,Component,Tokens)`

Mode and number of proofs:

`message_hook(+nonvar,+nonvar,+nonvar,+list(nonvar)) - zero_or_one`

`ask_question/5`

Asks a question and reads the answer until the check predicate is true.

Compilation flags:

static

Template:

`ask_question(Kind,Component,Question,Check,Answer)`

Meta-predicate template:

`ask_question(*,*,*,1,*)`

Mode and number of proofs:

`ask_question(+nonvar,+nonvar,+nonvar,+callable,-term) - one`

`question_hook/6`

User-defined hook predicate for intercepting question asking calls.

Compilation flags:

dynamic, multifile

Template:

```
question_hook(Question,Kind,Component,Tokens,Check,Answer)
```

Meta-predicate template:

```
question_hook(*,*,*,*,1,*)
```

Mode and number of proofs:

```
question_hook(+nonvar,+nonvar,+nonvar,+list(nonvar),+callable,-term) - zero_or_one
```

`question_prompt_stream/4`

Prompt and input stream to be used when asking a question given its kind and component.

Compilation flags:

dynamic, multifile

Template:

```
question_prompt_stream(Kind,Component,Prompt,Stream)
```

Mode and number of proofs:

```
question_prompt_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more
```

`trace_event/2`

Trace event handler. The runtime calls all trace event handlers using a failure-driven loop before calling the debug event handler.

Compilation flags:

dynamic, multifile

Template:

```
trace_event(Event,ExecutionContext)
```

Mode and number of proofs:

```
trace_event(@callable,@execution_context) - zero
```

Remarks:

- Unification events: Generated after a successful unification with a fact - fact(Entity,Fact,Clause,File,Line) - or a rule head - rule(Entity,Head,Clause,File,Line).
- Goal events: Generated when calling a goal: top_goal(Goal,CompiledGoal) or goal(Goal,CompiledGoal).

`debug_handler/1`

Enumerates, by backtracking, all declared debug handler providers. Define a clause for this predicate to declare a new debug handler provider.

Compilation flags:

```
static, multifile
```

Template:

```
debug_handler(Provider)
```

Mode and number of proofs:

```
debug_handler(?object_identifier) - zero_or_more
```

```
debug_handler(?category_identifier) - zero_or_more
```

`active_debug_handler/1`

Current active debug handler provider if any. There is at most one active debug handler provider at any given moment.

Compilation flags:

```
static
```

Template:

```
active_debug_handler(Provider)
```

Mode and number of proofs:

```
active_debug_handler(?category_identifier) - zero_or_one
```

```
active_debug_handler(?category_identifier) - zero_or_one
```

`activate__debug__handler/1`

Activates the given debug handler provider. There is at most one active debug handler provider at any given moment. Fails if the object or category is not declared as a debug handler provider.

Compilation flags:

static

Template:

`activate__debug__handler(Provider)`

Mode and number of proofs:

`activate__debug__handler(@object__identifier) - zero_or_one`

`activate__debug__handler(@category__identifier) - zero_or_one`

`deactivate__debug__handler/0`

Deactivates the current debug handler provider if any.

Compilation flags:

static

Mode and number of proofs:

`deactivate__debug__handler - one`

`debug__handler/3`

Debug event handler. Called by the runtime when the given provider is active.

Compilation flags:

static, multifile

Template:

`debug__handler(Provider,Event,ExecutionContext)`

Mode and number of proofs:

`debug_handler(+object_identifier,+callable,+execution_context) - zero_or_more`
`debug_handler(+category_identifier,+callable,+execution_context) - zero_or_more`

Remarks:

- Unification events: Generated after a successful unification with a fact - `fact(Entity,Fact,Clause,File,Line)` - or a rule head - `rule(Entity,Head,Clause,File,Line)`.
 - Goal events: Generated when calling a goal: `top_goal(Goal,CompiledGoal)` or `goal(Goal,CompiledGoal)`.
-

`expand_library_path/2`

Expands a library alias or a library path into its absolute path. Uses a depth bound to prevent loops.

Compilation flags:

`static`

Template:

`expand_library_path(LibraryPath,AbsolutePath)`

Mode and number of proofs:

`expand_library_path(+atom,?atom) - zero_or_one`

`expand_library_path(+callable,?atom) - zero_or_one`

`loaded_file/1`

Enumerates, by backtracking, all loaded files, returning their full paths.

Compilation flags:

`static`

Template:

`loaded_file(Path)`

Mode and number of proofs:

`loaded_file(?atom) - zero_or_more`

`loaded_file_property/2`

Enumerates, by backtracking, loaded file properties.

Compilation flags:

`static`

Template:

`loaded_file_property(Path,Property)`

Mode and number of proofs:

`loaded_file_property(?atom,?compound) - zero_or_more`

Remarks:

- Property `basename/1`: Basename of the file (includes the file extension, if any).
- Property `directory/1`: Directory of the file (ending with a slash).
- Property `mode/1`: Compilation mode of the file (possible values are `optimal`, `normal`, and `debug`).
- Property `flags/1`: Explicit flags used for compiling the file.
- Property `text_properties/1`: List of the file text properties (`encoding/1` and `bom/1`). Empty if no `encoding/1` directive is present and the stream used for reading the file does not have a `bom/1` (or equivalent) property.
- Property `target/1`: Full path of the generated intermediate Prolog file.
- Property `modified/1`: File modification time stamp (should be regarded as an opaque but otherwise comparable term).
- Property `parent/1`: Full path of the parent file that loaded the file.
- Property `includes/1`: Full path of a file included by the file.
- Property `library/1`: Library alias for the library that includes the file.
- Property `object/1`: Identifier for an object defined in the file.
- Property `protocol/1`: Identifier for a protocol defined in the file.
- Property `category/1`: Identifier for a category defined in the file.

`file_type_extension/2`

Enumerates, by backtracking, all defined file type extensions. The defined types are: `source`, `object`, `logtalk`, `prolog`, and `tmp`. The `source` type returns both `logtalk` and `prolog` type extensions.

Compilation flags:

`static`

Template:

`file_type_extension(Type,Extension)`

Mode and number of proofs:

`file_type_extension(?atom,?atom) - zero_or_more`

`compile_aux_clauses/1`

Compiles a list of auxiliary clauses. Can only be called during source file compilation, usually from `term_expansion/2` or `goal_expansion/2` hook predicate definitions.

Compilation flags:

`static`

Template:

`compile_aux_clauses(Clauses)`

Mode and number of proofs:

`compile_aux_clauses(@list(clause)) - one`

`entity_prefix/2`

Converts between an entity identifier and the entity prefix that is used for its compiled code. When none of the arguments is instantiated, it returns the identifier and the prefix of the entity under compilation, if any.

Compilation flags:

`static`

Template:

`entity_prefix(Entity,Prefix)`

Mode and number of proofs:

`entity_prefix(?entity_identifier,?atom) - zero_or_one`

`compile_predicate_heads/4`

Compiles clause heads. The heads are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

static

Template:

`compile_predicate_heads(Heads,Entity,CompiledHeads,ExecutionContext)`

Mode and number of proofs:

`compile_predicate_heads(@list(callable),?entity_identifier,-list(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@conjunction(callable),?entity_identifier,-conjunction(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@callable,?entity_identifier,-callable,@execution_context) - zero_or_one`

`compile_predicate_indicators/3`

Compiles predicate indicators. The predicate are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

static

Template:

`compile_predicate_indicators(PredicateIndicators,Entity,CompiledPredicateIndicators)`

Mode and number of proofs:

`compile_predicate_indicators(@list(predicate_indicator),?entity_identifier,-list(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@conjunction(predicate_indicator),?entity_identifier,-conjunction(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@predicate_indicator,?entity_identifier,-predicate_indicator) - zero_or_one`

decompile_predicate_heads/4

Decompiles clause heads. All compiled clause heads must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

decompile_predicate_heads(CompiledHeads,Entity,Type,Heads)

Mode and number of proofs:

decompile_predicate_heads(@list(callable),-entity_identifier,-atom,-list(callable)) - zero_or_one

decompile_predicate_heads(@conjunction(callable),-entity_identifier,-atom,-conjunction(callable)) - zero_or_one

decompile_predicate_heads(@callable,-entity_identifier,-atom,-callable) - zero_or_one

decompile_predicate_indicators/4

Decompiles predicate indicators. All compiled predicate indicators must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

decompile_predicate_indicators(CompiledPredicateIndicators,Entity,Type,PredicateIndicators)

Mode and number of proofs:

decompile_predicate_indicators(@list(predicate_indicator),-entity_identifier,-atom,
-list(predicate_indicator)) - zero_or_one

decompile_predicate_indicators(@conjunction(predicate_indicator),-entity_identifier,-atom,
-conjunction(predicate_indicator)) - zero_or_one

decompile_predicate_indicators(@predicate_indicator,-entity_identifier,-atom,-predicate_indicator)
- zero_or_one

`execution_context/7`

Execution context term data. Execution context terms should be considered opaque terms subject to change without notice.

Compilation flags:

`static`

Template:

`execution_context(ExecutionContext,Entity,Sender,This,Self,MetaCallContext,CoinductionStack)`

Mode and number of proofs:

`execution_context(?nonvar,?entity__identifier,?object__identifier,?object__identifier,?object__identifier,
@list(callable),@list(callable)) - zero_or_one`

Protected predicates

(none)

Private predicates

`active_debug_handler_/1`

Current active debug handler provider. There is at most one active debug handler provider at any given moment.

Compilation flags:

`dynamic`

Template:

`active_debug_handler_(Provider)`

Mode and number of proofs:

`active_debug_handler_(?entity__identifier) - zero_or_one`

Operators

(none)

protocol

1.7.5 monitoring

Event handlers protocol. The handlers are automatically called by the runtime for messages sent using the `::/2` control construct from objects or categories compiled with the events flag set to allow.

Availability:

built_in

Author: Paulo Moura

Version: 1:2:0

Date: 2018-11-29

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - before/3
 - after/3
- Protected predicates
- Private predicates
- Operators

Public predicates

before/3

Event handler for before events. A before event handler may prevent a method from being looked up or called by failing.

Compilation flags:

static

Template:

before(Object,Message,Sender)

Mode and number of proofs:

before(?term,?term,?term) - zero_or_more

after/3

Event handler for after events. An after event handler may prevent a method from succeeding by failing.

Compilation flags:

static

Template:

after(Object,Message,Sender)

Mode and number of proofs:

after(?term,?term,?term) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.7.6 user

Pseudo-object representing the plain Prolog database. Can be used as a monitor by defining `before/3` and `after/3` predicates. Can be used as a hook object by defining `term_expansion/2` and `goal_expansion/2` multifile and dynamic predicates.

Availability:

`built_in`

Author: Paulo Moura

Version: 1:5:0

Date: 2022-10-12

Compilation flags:

`static`, `built_in`, `context_switching_calls`, `dynamic_declarations`, `threaded`

Implements:

`public expanding`

`public forwarding`

`public monitoring`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

`after/3` `before/3` `forward/1` `goal_expansion/2` `term_expansion/2`

- `Public predicates`
- `Protected predicates`
- `Private predicates`

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.8 coroutining

object

1.8.1 coroutining

Coroutining predicates.

Availability:

`logtalk_load(coroutining(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2021-12-17

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - dif/2
 - dif/1
 - freeze/2
 - frozen/2
 - when/2
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:

static

Template:

dif(Term1,Term2)

Mode and number of proofs:

dif(+term,+term) - zero_or_one

`dif/1`

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:

`static`

Template:

`dif(Terms)`

Mode and number of proofs:

`dif(+list(term)) - zero_or_one`

`freeze/2`

Delays the execution of a goal until a variable is bound.

Compilation flags:

`static`

Template:

`freeze(Variable,Goal)`

Meta-predicate template:

`freeze(*,0)`

Mode and number of proofs:

`freeze(+term,+callable) - zero_or_more`

`frozen/2`

Unifies Goal with the goal delayed by Variable. When no goals are frozen on Variable, Goal is unified with true.

Compilation flags:

`static`

Template:

`frozen(Variable,Goal)`

Mode and number of proofs:

frozen(@var,--callable) - one

when/2

Calls Goal when Condition becomes true. The portable conditions are: nonvar/1, ground/1, (,)/2, and (;)/2.

Compilation flags:

static

Template:

when(Condition,Goal)

Meta-predicate template:

when(*,0)

Mode and number of proofs:

when(+callable,+callable) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.9 csv

object

1.9.1 csv

CSV files reading and writing predicates using the options Header - keep, Separator - comma, and Ignore-Quotes - false.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-02

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public csv(keep,comma,false)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2  
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2  
read_stream_by_line/3 write_file/3 write_stream/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.9.2 csv(Header,Separator,IgnoreQuotes)

- Header - Header handling option with possible values missing, skip, and keep (default).
- Separator - Separator handling option with possible values comma (default for non .tsv and non .tab files or when no file name extension is available), tab (default for .tsv and .tab files), semicolon, and colon.
- IgnoreQuotes - Double-quotes handling option to ignore (true) or preserve (false; default) double quotes surrounding data.

CSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila and Paulo Moura

Version: 2:1:0

Date: 2023-11-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public csv_protocol
```

Uses:

```
list
logtalk
os
reader
type
```

Remarks:

(none)

Inherited public predicates:

guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2
read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.9.3 csv_guess_questions

Support for asking questions when guessing the separator and the record arity of CSV files.

Availability:

logtalk_load(csv(loader))

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-03

Compilation flags:

static

Provides:

logtalk::message_tokens//2
logtalk::question_prompt_stream/4

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.9.4 csv_protocol

CSV file and stream reading and writing protocol.

Availability:

logtalk_load(csv(loader))

Author: Jacinto Dávila and Paulo Moura

Version: 2:0:0

Date: 2023-03-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

(none)

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
 - guess_separator/2
 - guess_arity/2

- Protected predicates
- Private predicates
- Operators

Public predicates

`read_file/3`

Reads a CSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Object,Predicate)`

Mode and number of proofs:

`read_file(+atom,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_stream/3`

Reads a CSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream, Object, Predicate)`

Mode and number of proofs:

`read_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias, Stream)`

Stream is not an open stream:

`existence_error(stream, Stream)`

Stream is an output stream:

`permission_error(input, stream, Stream)`

Stream is a binary stream:

`permission_error(input, binary_stream, Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier, Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object, Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator, Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate, Predicate)`

`read_file/2`

Reads a CSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Rows)`

Mode and number of proofs:

`read_file(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream/2`

Reads a CSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Rows)`

Mode and number of proofs:

`read_stream(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```
domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)
```

`read_file_by_line/3`

Reads a CSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:
static

Template:

```
read_file_by_line(File,Object,Predicate)
```

Mode and number of proofs:

```
read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be opened for reading:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`read_stream_by_line/3`

Reads a CSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_file_by_line/2`

Reads a CSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file_by_line(File,Rows)`

Mode and number of proofs:

`read_file_by_line(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream_by_line/2`

Reads a CSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:


```
domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)
```

`write_file/3`

Writes a CSV file with the data represented by the clauses of the specified object predicate.

Compilation flags:

```
static
```

Template:

```
write_file(File,Object,Predicate)
```

Mode and number of proofs:

```
write_file(+atom,+object_identifier,+predicate_indicator) - one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but cannot be opened for writing:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`write_stream/3`

Writes a CSV stream with the data represented by the clauses of the specified object predicate.

Compilation flags:

`static`

Template:

`write_stream(Stream, Object, Predicate)`

Mode and number of proofs:

`write_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias, Stream)`

Stream is not an open stream:

`existence_error(stream, Stream)`

Stream is an input stream:

`permission_error(output, stream, Stream)`

Stream is a binary stream:

`permission_error(output, binary_stream, Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier, Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object, Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator, Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate, Predicate)`

`guess_separator/2`

Guesses the separator used in a given file, asking the user to confirm.

Compilation flags:

`static`

Template:

`guess_separator(File,Separator)`

Mode and number of proofs:

`guess_separator(+atom,-atom) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an atom but cannot be opened for writing:

`permission_error(open,source_sink,File)`

`guess_arity/2`

Guesses the arity of records in a given file, asking the user to confirm.

Compilation flags:

`static`

Template:

`guess_arity(File,Arity)`

Mode and number of proofs:

`guess_arity(+atom,-number) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

```
existence_error(file,File)
File is an atom but cannot be opened for writing:
permission_error(open,source_sink,File)
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.10 dates

object

1.10.1 date

Date predicates.

Availability:

```
logtalk_load(dates(loader))
```

Author: Paulo Moura

Version: 1:2:0

Date: 2014-09-27

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public datep
```

Uses:

```
os
```

Remarks:

(none)

Inherited public predicates:

days_in_month/3 leap_year/1 name_of_day/3 name_of_month/3 today/3 valid/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.10.2 datep

Date protocol.

Availability:

logtalk_load(dates(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2005-03-17

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - today/3
 - leap_year/1
 - name_of_day/3
 - name_of_month/3
 - days_in_month/3
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

today/3

Returns current date.

Compilation flags:

static

Template:

today(Year,Month,Day)

Mode and number of proofs:

today(-integer,-integer,-integer) - one

leap_year/1

True if the argument is a leap year.

Compilation flags:

static

Template:

leap_year(Year)

Mode and number of proofs:

leap_year(+integer) - zero_or_one

name_of_day/3

Name and short name of day.

Compilation flags:

static

Template:

name_of_day(Index,Name,Short)

Mode and number of proofs:

name_of_day(?integer,?atom,?atom) - zero_or_more

name_of_month/3

Name and short name of month.

Compilation flags:

static

Template:

name_of_month(Index,Name,Short)

Mode and number of proofs:

name_of_month(?integer,?atom,?atom) - zero_or_more

days_in_month/3

Number of days in a month.

Compilation flags:

static

Template:

days_in_month(Month,Year,Days)

Mode and number of proofs:

days_in_month(?integer,+integer,?integer) - zero_or_more

valid/3

True if the arguments represent a valid date.

Compilation flags:

static

Template:

valid(Year,Month,Day)

Mode and number of proofs:

valid(@integer,@integer,@integer) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[date](#), [timep](#)

[object](#)

1.10.3 [time](#)

Time predicates.

Availability:

`logtalk_load(dates(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2014-09-27

Compilation flags:

`static, context_switching_calls`

Implements:

`public timep`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

`cpu_time/1 now/3 valid/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[datep](#)

[protocol](#)

1.10.4 timep

Time protocol.

Availability:

`logtalk__load(dates(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - now/3
 - cpu_time/1
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

now/3

Returns current time.

Compilation flags:
static

Template:

now(Hours,Mins,Secs)

Mode and number of proofs:

now(-integer,-integer,-integer) - one

cpu_time/1

Returns the current cpu time.

Compilation flags:
static

Template:

cpu_time(Time)

Mode and number of proofs:

cpu_time(-number) - one

`valid/3`

True if the arguments represent a valid time value.

Compilation flags:

`static`

Template:

`valid(Hours,Mins,Secs)`

Mode and number of proofs:

`valid(+integer,+integer,+integer) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`time`, `datep`

1.11 dead_code_scanner

object

1.11.1 dead_code_scanner

A tool for detecting likely dead code in compiled Logtalk entities and Prolog modules compiled as objects.

Availability:

`logtalk_load(dead_code_scanner(loader))`

Author: Barry Evans and Paulo Moura

Version: 0:15:0

Date: 2024-05-07

Compilation flags:

static, context_switching_calls

Imports:

public options

Uses:

list

logtalk

os

type

Remarks:

- Dead code: A predicate or non-terminal that is not called (directly or indirectly) by any scoped predicate or non-terminal. These predicates and non-terminals are not used, cannot be called without breaking encapsulation, and are thus considered dead code.
- Known issues: Use of local meta-calls with goal arguments only known at runtime can result in false positives. Calls from non-standard meta-predicates may be missed if the meta-calls are not optimized.
- Requirements: Source files must be compiled with the source_data flag turned on. To avoid false positives due to meta-calls, compilation of source files with the optimized flag turned on is also advised.

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
valid_option/1 valid_options/1

- Public predicates
 - entity/1
 - file/2
 - file/1
 - directory/2
 - directory/1
 - rdirectory/2
 - rdirectory/1
 - library/2
 - library/1
 - rlibrary/2
 - rlibrary/1

- all/1
- all/0
- predicates/2
- predicate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

entity/1

Scans a loaded entity for dead code. Fails if the entity does not exist.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

file/2

Scans all entities in a loaded source file for dead code using the given options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Scans all entities in a loaded source file for dead code using default options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans all entities in all loaded files from a given directory for dead code using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans all entities in all loaded files from a given directory for dead code using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

`rdirectory/2`

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using the given options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list(compound)) - one`

`rdirectory/1`

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`library/2`

Scans all entities in all loaded files from a given library for dead code using the given options.

Compilation flags:

`static`

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Scans all entities in all loaded files from a given library for dead code using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rlibrary/2

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all entities for dead code using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

all/0

Scans all entities for dead code using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

predicates/2

Returns an ordered set of local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

static

Template:

predicates(Entity,Predicates)

Mode and number of proofs:

predicates(+entity__identifier,-list(predicate__indicator)) - one

predicate/2

Enumerates, by backtracking, local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

static

Template:

predicate(Entity,Predicate)

Mode and number of proofs:

predicate(+entity__identifier,?predicate__indicator) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.11.2 dead_code_scanner_messages

Logtalk dead_code_scanner tool default message translations.

Availability:

```
logtalk_load(dead_code_scanner(loader))
```

Author: Barry Evans and Paulo Moura

Version: 0:8:0

Date: 2024-05-07

Compilation flags:

```
static
```

Provides:

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.12 debug_messages

object

1.12.1 debug_messages

Supports selective enabling and disabling of debug and debug(Group) messages.

Availability:

`logtalk_load(debug_messages(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2022-05-05

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`logtalk`

Remarks:

- Limitations: Debug messages are suppressed by the compiler when the optimize flag is turned on and thus cannot be enabled in this case.

Inherited public predicates:

(none)

- Public predicates
 - enable/1
 - disable/1
 - enabled/1
 - enable/2
 - disable/2
 - enabled/2
- Protected predicates
- Private predicates
 - enabled_/1
 - enabled_/2
- Operators

Public predicates

enable/1

Enables all debug and debug(Group) messages for the given component.

Compilation flags:

static

Template:

enable(Component)

Mode and number of proofs:

enable(@term) - one

disable/1

Disables all debug and debug(Group) messages for the given component.

Compilation flags:

static

Template:

disable(Component)

Mode and number of proofs:

disable(@term) - one

enabled/1

Enumerates by backtracking the components with enabled debug and debug(Group) messages.

Compilation flags:

static

Template:

enabled(Component)

Mode and number of proofs:

enabled(?term) - zero_or_more

enable/2

Enables debug(Group) messages for the given component and group.

Compilation flags:

static

Template:

enable(Component,Group)

Mode and number of proofs:

enable(@term,@term) - one

disable/2

Disables debug(Group) messages for the given component and group.

Compilation flags:

static

Template:

disable(Component,Group)

Mode and number of proofs:

disable(@term,@term) - one

enabled/2

Enumerates by backtracking the enabled debug(Group) messages for each component.

Compilation flags:

static

Template:

enabled(Component,Group)

Mode and number of proofs:

enabled(?term,?term) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

enabled_/1

Table of components with currently enabled debug and debug(Group) messages.

Compilation flags:

dynamic

Template:

enabled_(Component)

Mode and number of proofs:

enabled_(?term) - zero_or_more

enabled_/2

Table of currently enabled debug(Group) per component.

Compilation flags:

dynamic

Template:

enabled_(Component,Group)

Mode and number of proofs:

enabled_(?term,?term) - zero_or_more

Operators

(none)

1.13 debugger

object

1.13.1 debugger

Command-line debugger based on an extended procedure box model supporting execution tracing and spy points.

Availability:

logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 7:2:0

Date: 2024-06-03

Compilation flags:

static, context_switching_calls

Implements:

public debuggerp

Provides:

logtalk::debug_handler/1

logtalk::debug_handler/3

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

debug/0 debugging/0 debugging/1 leash/1 leashing/1 log/3 logging/3 nodebug/0 nolog/3
nologall/0 nospy/1 nospy/4 nospyall/0 notrace/0 reset/0 spy/1 spy/4 spying/1 spying/4
trace/0

- Public predicates
- Protected predicates
- Private predicates
 - debugging_/0
 - tracing_/0
 - skipping_/0
 - skipping_unleashed_/1
 - quasi_skipping_/0
 - leaping_/1
 - spying_line_number_/2
 - spying_predicate_/3
 - spying_context_/4
 - leashing_/1
 - invocation_number_/1
 - jump_to_invocation_number_/1
 - zap_to_port_/1
 - write_max_depth_/1
 - logging_line_number_/3
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`debugging_/0`

True iff debug is on.

Compilation flags:
dynamic

Mode and number of proofs:
debugging_ - zero_or_one

`tracing_/0`

True iff tracing is on.

Compilation flags:
dynamic

Mode and number of proofs:
tracing_ - zero_or_one

`skipping_/0`

True iff skipping.

Compilation flags:
dynamic

Mode and number of proofs:

 skipping_ - zero_or_one

skipping_unleashed_/1

True iff skipping (a goal with invocation number N) but showing intermediate ports as unleashed.

Compilation flags:

 dynamic

Template:

 skipping_unleashed_(N)

Mode and number of proofs:

 skipping_unleashed_(?integer) - zero_or_one

quasi_skipping_/0

True iff quasi-skipping.

Compilation flags:

 dynamic

Mode and number of proofs:

 quasi_skipping_ - zero_or_one

leaping_/1

True iff leaping in tracing or debugging mode.

Compilation flags:

 dynamic

Template:

leaping_(Mode)

Mode and number of proofs:

leaping_(?atom) - zero_or_one

spying_line_number_/2

Table of line number breakpoints.

Compilation flags:

dynamic

Template:

spying_line_number_(Entity,Line)

Mode and number of proofs:

spying_line_number_(?object_identifier,?integer) - zero_or_more

spying_line_number_(?category_identifier,?integer) - zero_or_more

spying_predicate_/3

Table of predicate spy points.

Compilation flags:

dynamic

Template:

spying_predicate_(Functor,Arity,Original)

Mode and number of proofs:

spying_predicate_(?atom,?integer,?predicate_indicator) - zero_or_more

spying_predicate_(?atom,?integer,?non_terminal_indicator) - zero_or_more

[spying_context_/4](#)

Table of context spy points.

Compilation flags:

dynamic

Template:

spying_context_(Sender,This,Self,Goal)

Mode and number of proofs:

spying_context_(?object_identifier,?object_identifier,?object_identifier,?callable) - zero_or_more

[leashing_/1](#)

Table of currently leashed ports.

Compilation flags:

dynamic

Template:

leashing_(Port)

Mode and number of proofs:

leashing_(?atom) - zero_or_more

[invocation_number_/1](#)

Current call stack invocation number.

Compilation flags:

dynamic

Template:

invocation_number_(N)

Mode and number of proofs:

invocation_number_(?integer) - zero_or_one

`jump_to_invocation_number_/1`

Invocation number to jump to.

Compilation flags:

`dynamic`

Template:

`jump_to_invocation_number_(N)`

Mode and number of proofs:

`jump_to_invocation_number_(?integer) - zero_or_one`

`zap_to_port_/1`

Port to zap to.

Compilation flags:

`dynamic`

Template:

`zap_to_port_(Port)`

Mode and number of proofs:

`zap_to_port_(?integer) - zero_or_one`

`write_max_depth_/1`

Current term maximum depth.

Compilation flags:

`dynamic`

Template:

`write_max_depth_(MaxDepth)`

Mode and number of proofs:

`write_max_depth_(?integer) - zero_or_one`

logging_line_number_/3

Table of log points.

Compilation flags:
dynamic

Template:

logging_line_number_(Entity,Line,Message)

Mode and number of proofs:

logging_line_number_(?object_identifier,?integer,?atom) - zero_or_more

logging_line_number_(?category_identifier,?integer,?atom) - zero_or_more

Operators

(none)

category

1.13.2 debugger_messages

Logtalk debugger tool default message translations.

Availability:
logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 3:3:0

Date: 2024-06-03

Compilation flags:
static

Provides:

logtalk::message_prefix_stream/4

logtalk::question_prompt_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.13.3 debuggerp

Debugger protocol.

Availability:

logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 3:1:0

Date: 2024-06-03

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Debugger help: Type the character `h` (condensed help) or the character `?` (extended help) at a leashed port.
- Predicate spy point: Specified as a ground term `Functor/Arity`.
- Non-terminal spy point: Specified as a ground term `Functor//Arity`.
- Line number spy point (aka breakpoint): Specified as an `Entity-Line` term with both `Entity` and `Line` bound. Line must be the first source file line of an entity clause.
- Context spy point: Specified as a `(Sender, This, Self, Goal)` tuple.
- Log point: Specified as a `(Entity, Line, Message)` tuple.
- Leash port shorthands: `none` - `[]`, `loose` - `[fact,rule,call]`, `half` - `[fact,rule,call,redo]`, `tight` - `[fact,rule,call,redo,fail,exception]`, and `full` - `[fact,rule,call,exit,redo,fail,exception]`.

Inherited public predicates:

(none)

- Public predicates
 - `reset/0`
 - `debug/0`
 - `nodebug/0`
 - `debugging/0`
 - `debugging/1`
 - `trace/0`
 - `notrace/0`
 - `spy/1`
 - `spying/1`
 - `spy/4`
 - `spying/4`
 - `nospy/1`
 - `nospy/4`
 - `nospyall/0`
 - `leash/1`
 - `leashing/1`
 - `log/3`
 - `logging/3`
 - `nolog/3`
 - `nologall/0`

- Protected predicates
- Private predicates
- Operators

Public predicates

`reset/0`

Resets all debugging settings (including log points, spy points, and leashed ports) and turns off debugging.

Compilation flags:

`static`

Mode and number of proofs:

`reset - one`

See also:

`nospysall/0`

`debug/0`

Starts debugging for all defined spy points.

Compilation flags:

`static`

Mode and number of proofs:

`debug - one`

`nodebug/0`

Stops debugging for all defined spy points. Also turns off tracing. Does not remove defined spy points.

Compilation flags:

`static`

Mode and number of proofs:

`nodebug - one`

See also:

`reset/0`

`debugging/0`

Reports current debugging settings, including spy points and log points.

Compilation flags:

`static`

Mode and number of proofs:

`debugging - one`

`debugging/1`

Enumerates, by backtracking, all entities compiled in debug mode.

Compilation flags:

`static`

Template:

`debugging(Entity)`

Mode and number of proofs:

`debugging(?entity_identifier) - zero_or_more`

trace/0

Starts tracing all calls compiled in debug mode.

Compilation flags:

static

Mode and number of proofs:

trace - one

notrace/0

Stops tracing of calls compiled in debug mode. Debugger will still stop at defined spy points.

Compilation flags:

static

Mode and number of proofs:

notrace - one

spy/1

Sets a line number spy point (removing any existing log point defined for the same location), a predicate spy point, a non-terminal spy point, or a list of spy points. Fails if a spy point is invalid.

Compilation flags:

static

Template:

spy(SpyPoint)

Mode and number of proofs:

spy(@spy__point) - zero_or_one

spy(@list(spy__point)) - zero_or_one

spying/1

Enumerates, by backtracking, all defined line number, predicate, and non-terminal spy points.

Compilation flags:

static

Template:

spying(SpyPoint)

Mode and number of proofs:

spying(?spy__point) - zero_or_more

spy/4

Sets a context spy point.

Compilation flags:

static

Template:

spy(Sender,This,Self,Goal)

Mode and number of proofs:

spy(@term,@term,@term,@term) - one

spying/4

Enumerates, by backtracking, all defined context spy points.

Compilation flags:

static

Template:

spying(Sender,This,Self,Goal)

Mode and number of proofs:

spying(?term,?term,?term,?term) - zero_or_more

`nospy/1`

Removes all matching line number, predicate, and non-terminal spy points.

Compilation flags:

`static`

Template:

`nospy(SpyPoint)`

Mode and number of proofs:

`nospy(@var) - one`

`nospy(@spy_point) - one`

`nospy(@list(spy_point)) - one`

`nospy/4`

Removes all matching context spy points.

Compilation flags:

`static`

Template:

`nospy(Sender,This,Self,Goal)`

Mode and number of proofs:

`nospy(@term,@term,@term,@term) - one`

`nospyall/0`

Removes all line number, predicate, non-terminal, and context spy points.

Compilation flags:

`static`

Mode and number of proofs:

`nospyall - one`

See also:

`reset/0`

`leash/1`

Sets the debugger leash ports using an abbreviation (none, loose, half, tight, or full) or a list of ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

`static`

Template:

`leash(Ports)`

Mode and number of proofs:

`leash(+atom) - one`

`leash(+list(atom)) - one`

`leashing/1`

Enumerates, by backtracking, all leashed ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

`static`

Template:

`leashing(Port)`

Mode and number of proofs:

`leashing(?atom) - zero_or_more`

log/3

Sets a log point (removing any existing line number spy point defined for the same location). Fails if the log point is invalid.

Compilation flags:

static

Template:

log(Entity,Line,Message)

Mode and number of proofs:

log(@object__identifier,+integer,+atom) - zero_or_one

log(@category__identifier,+integer,+atom) - zero_or_one

log(?object__identifier,?integer,?atom) - zero_or_more

log(?category__identifier,?integer,?atom) - zero_or_more

log(@var_or(object__identifier),@var_or(integer),@var_or(atom)) - one

log(@var_or(category__identifier),@var_or(integer),@var_or(atom)) - one

logging/3

Enumerates, by backtracking, all defined log points.

Compilation flags:

static

Template:

logging(Entity,Line,Message)

nolog/3

Removes all matching log points.

Compilation flags:

static

Template:

nolog(Entity,Line,Message)

`nologall/0`

Removes all log points.

Compilation flags:
`static`

Mode and number of proofs:
`nologall - one`

See also:
`reset/0`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`debugger`

`object`

1.13.4 `dump_trace`

Simple solution for redirecting a debugger trace to a file.

Availability:
`logtalk_load(debugger(loader))`

Author: Paulo Moura

Version: 1:0:1
Date: 2021-11-12

Compilation flags:
static, context_switching_calls

Uses:
debugger

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - start_redirect_to_file/2
 - stop_redirect_to_file/0
- Protected predicates
- Private predicates
- Operators

Public predicates

start_redirect_to_file/2

Starts redirecting debugger trace messages to a file.

Compilation flags:
static

Template:
start_redirect_to_file(File,Goal)

Meta-predicate template:
start_redirect_to_file(*,0)

Mode and number of proofs:
start_redirect_to_file(+atom,+callable) - zero_or_more

`stop_redirect_to_file/0`

Stops redirecting debugger trace messages to a file.

Compilation flags:

`static`

Mode and number of proofs:

`stop_redirect_to_file - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.14 dependents

category

1.14.1 observer

Smalltalk dependent protocol.

Availability:

`logtalk_load(dependents(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - update/1
- Protected predicates
- Private predicates
- Operators

Public predicates

update/1

Called when an observed object is updated.

Compilation flags:

static

Template:

update(Change)

Mode and number of proofs:

update(?nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[subject](#)

[category](#)

1.14.2 [subject](#)

Smalltalk dependent handling predicates.

Availability:

`logtalk_load(dependents(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [changed/0](#)
 - [changed/1](#)
 - [dependents/1](#)
 - [addDependent/1](#)

- removeDependent/1
- Protected predicates
- Private predicates
 - dependent_/1
- Operators

Public predicates

changed/0

Receiver changed in some way. Notify all dependents.

Compilation flags:

static

Mode and number of proofs:

changed - one

changed/1

Receiver changed as specified in the argument. Notify all dependents.

Compilation flags:

static

Template:

changed(Change)

Mode and number of proofs:

changed(?nonvar) - one

`dependents/1`

Returns a list of all dependent objects.

Compilation flags:

`static`

Template:

`dependents(Dependents)`

Mode and number of proofs:

`dependents(-list) - one`

`addDependent/1`

Adds a new dependent object.

Compilation flags:

`static`

Template:

`addDependent(Dependent)`

Mode and number of proofs:

`addDependent(@object) - one`

`removeDependent/1`

Removes a dependent object.

Compilation flags:

`static`

Template:

`removeDependent(Dependent)`

Mode and number of proofs:

`removeDependent(?object) - zero_or_more`

Protected predicates

(none)

Private predicates

`dependent_/1`

Table of dependent objects.

Compilation flags:

`dynamic`

Template:

`dependent_(Dependent)`

Mode and number of proofs:

`dependent_(?object) - zero_or_more`

Operators

(none)

See also:

`observer`

1.15 diagrams

`category`

1.15.1 `diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 3:5:0

Date: 2024-04-01

Compilation flags:

static

Extends:

public options

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Uses:

graph_language_registry

list

logtalk

modules_diagram_support

os

pairs

type

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
valid_option/1 valid_options/1

- Public predicates
 - libraries/3
 - libraries/2
 - libraries/1
 - all_libraries/1
 - all_libraries/0
 - rlibrary/2
 - rlibrary/1
 - library/2
 - library/1
 - directories/3
 - directories/2
 - rdirectory/3
 - rdirectory/2

- rdirectory/1
- directory/3
- directory/2
- directory/1
- files/3
- files/2
- files/1
- all_files/1
- all_files/0
- format_object/1
- diagram_description/1
- diagram_name_suffix/1
- Protected predicates
 - diagram_caption/3
 - output_rlibrary/3
 - output_library/3
 - output_rdirectory/3
 - output externals/1
 - output_files/2
 - output_file/4
 - output_sub_diagrams/1
 - reset/0
 - output_node/6
 - node/6
 - edge/5
 - output_edges/1
 - save_edge/5
 - output_missing externals/1
 - not_excluded_file/4
 - output_file_path/4
 - locate_library/2
 - locate_directory/2
 - locate_file/5
 - ground_entity_identifier/3
 - filter_file_extension/3

- filter_external_file_extension/3
- add_link_options/3
- omit_path_prefix/3
- add_node_zoom_option/4
- message_diagram_description/1
- Private predicates
 - node_/6
 - edge_/5
- Operators

Public predicates

libraries/3

Creates a diagram for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries,Options)

Mode and number of proofs:

libraries(+atom,+list(atom),+list(compound)) - one

libraries/2

Creates a diagram for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries)

Mode and number of proofs:

libraries(+atom,+list(atom)) - one

libraries/1

Creates a diagram for a set of libraries using the default options. The prefix libraries is used for the diagram file name.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates a diagram for all loaded libraries using the specified options.

Compilation flags:

static

Template:

all_libraries(Options)

Mode and number of proofs:

all_libraries(+list(compound)) - one

all_libraries/0

Creates a diagram for all loaded libraries using default options.

Compilation flags:

static

Mode and number of proofs:

all_libraries - one

`rlibrary/2`

Creates a diagram for a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

`rlibrary(Library,Options)`

Mode and number of proofs:

`rlibrary(+atom,+list(compound)) - one`

`rlibrary/1`

Creates a diagram for a library and its sub-libraries using default options.

Compilation flags:

`static`

Template:

`rlibrary(Library)`

Mode and number of proofs:

`rlibrary(+atom) - one`

`library/2`

Creates a diagram for a library using the specified options.

Compilation flags:

`static`

Template:

`library(Library,Options)`

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Creates a diagram for a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

directories/3

Creates a diagram for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates a diagram for a set of directories using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates a diagram for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+atom,+list(compound)) - one

rdirectory/2

Creates a diagram for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory)

Mode and number of proofs:

rdirectory(+atom,+atom) - one

rdirectory/1

Creates a diagram for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

directory/3

Creates a diagram for a directory using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory,Options)

Mode and number of proofs:

directory(+atom,+atom,+list(compound)) - one

directory/2

Creates a diagram for a directory using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory)

Mode and number of proofs:

directory(+atom,+atom) - one

directory/1

Creates a diagram for a directory using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates a diagram for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files)

Mode and number of proofs:

files(+atom,+list(atom)) - one

files/1

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix files is used for the diagram file name.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

all_files/1

Creates a diagram for all loaded files using the specified options.

Compilation flags:

static

Template:

all_files(Options)

Mode and number of proofs:

all_files(+list(compound)) - one

`all_files/0`

Creates a diagram for all loaded files using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all_files - one`

`format_object/1`

Returns the identifier of the object implementing the graph language currently being used. Fails if none is specified.

Compilation flags:

`static`

Template:

`format_object(Object)`

Mode and number of proofs:

`format_object(-object_identifier) - zero_or_one`

`diagram_description/1`

Returns the diagram description.

Compilation flags:

`static`

Template:

`diagram_description(Description)`

Mode and number of proofs:

`diagram_description(-atom) - one`

`diagram_name_suffix/1`

Returns the diagram name suffix.

Compilation flags:

`static`

Template:

`diagram_name_suffix(Suffix)`

Mode and number of proofs:

`diagram_name_suffix(-atom) - one`

Protected predicates

`diagram_caption/3`

Creates a diagram caption from the diagram description and the subject and its kind.

Compilation flags:

`static`

Template:

`diagram_caption(Kind,Subject,Description)`

Mode and number of proofs:

`diagram_caption(+atom,+callable,-atom) - one`

`output_rlibrary/3`

Generates diagram output for a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

```
output_rlibrary(Library,Path,Options)
```

Mode and number of proofs:

```
output_rlibrary(+atom,+atom,+list(compound)) - one
```

`output_library/3`

Generates diagram output for a library using the specified options.

Compilation flags:

```
static
```

Template:

```
output_library(Library,Path,Options)
```

Mode and number of proofs:

```
output_library(+atom,+atom,+list(compound)) - one
```

`output_rdirectory/3`

Generates diagram output for a directory and its sub-directories using the specified options.

Compilation flags:

```
static
```

Template:

```
output_rdirectory(Project,Path,Options)
```

Mode and number of proofs:

```
output_rdirectory(+atom,+atom,+list(compound)) - one
```

`output_externals/1`

Output external nodes using the specified options depending on the value of the boolean option `externals/1`.

Compilation flags:

`static`

Template:

`output_externals(Options)`

Mode and number of proofs:

`output_externals(+list(compound)) - one`

`output_files/2`

Generates diagram output for a list of files using the specified options.

Compilation flags:

`static`

Template:

`output_files(Files,Options)`

Mode and number of proofs:

`output_files(+list,+list(compound)) - one`

`output_file/4`

Generates diagram output for a file using the specified options.

Compilation flags:

`static`

Template:

`output_file(Path,Basename,Directory,Options)`

Mode and number of proofs:

`output_file(+atom,+atom,+atom,+list(compound)) - one`

`output_sub_diagrams/1`

Outputs sub-diagrams using the specified options.

Compilation flags:

`static`

Template:

`output_sub_diagrams(Options)`

Mode and number of proofs:

`output_sub_diagrams(+list(compound)) - one`

`reset/0`

Resets all temporary information used when generating a diagram.

Compilation flags:

`static`

Mode and number of proofs:

`reset - one`

`output_node/6`

Outputs a graph node.

Compilation flags:

`static`

Template:

`output_node(Identifier,Label,Caption,Contents,Kind,Options)`

Mode and number of proofs:

`output_node(+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one`

node/6

Enumerates, by backtracking, all saved nodes.

Compilation flags:

static

Template:

node(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:

node(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more

edge/5

Enumerates, by backtracking, all saved edges.

Compilation flags:

static

Template:

edge(From,To,Labels,Kind,Options)

Mode and number of proofs:

edge(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

output_edges/1

Outputs all edges.

Compilation flags:

static

Template:

output_edges(Options)

Mode and number of proofs:

output_edges(+list(compound)) - one

`save__edge/5`

Saves a graph edge.

Compilation flags:

`static`

Template:

`save__edge(From,To,Labels,Kind,Options)`

Mode and number of proofs:

`save__edge(+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one`

`output__missing__externals/1`

Outputs missing external nodes (usually due to unloaded resources) that are referenced from edges.

Compilation flags:

`static`

Template:

`output__missing__externals(Options)`

Mode and number of proofs:

`output__missing__externals(+list(compound)) - one`

`not__excluded__file/4`

True when the given file is not excluded from the generated output. Excluded files may be specified by full path or by basename and with or without extension. Excluded directories may be listed by full or relative path.

Compilation flags:

`static`

Template:

`not__excluded__file(Path,Basename,ExcludedDirectories,ExcludedFiles)`

Mode and number of proofs:

`not__excluded__file(+atom,+atom,+list(atom),+list(atom)) - zero_or_one`

`output_file_path/4`

Returns the output file path.

Compilation flags:

`static`

Template:

`output_file_path(Name,Options,Format,Path)`

Mode and number of proofs:

`output_file_path(+atom,+list(atom),+object_identifier,-atom) - one`

`locate_library/2`

Locates a library given its name.

Compilation flags:

`static`

Template:

`locate_library(Library,Path)`

Mode and number of proofs:

`locate_library(+atom,-atom) - one`

`locate_directory/2`

Locates a directory given its name or full path.

Compilation flags:

`static`

Template:

`locate_directory(Directory,Path)`

Mode and number of proofs:

`locate_directory(+atom,-atom) - one`

`locate_file/5`

Locates a file given its name, basename, full path, or library notation representation.

Compilation flags:

`static`

Template:

`locate_file(File,Basename,Extension,Directory,Path)`

Mode and number of proofs:

`locate_file(+atom,+atom,+atom,+atom,-atom) - one`

`ground_entity_identifier/3`

Converts an entity identifier to a ground term.

Compilation flags:

`static`

Template:

`ground_entity_identifier(Kind,Identifier,GroundIdentifier)`

Mode and number of proofs:

`ground_entity_identifier(+atom,+callable,-callable) - one`

`filter_file_extension/3`

Filters the file name extension depending on the `file_extensions/1` option.

Compilation flags:

`static`

Template:

```
filter_file_extension(Basename,Options,Name)
```

Mode and number of proofs:

```
filter_file_extension(+atom,+list(compound),-atom) - one
```

```
filter_external_file_extension/3
```

Filters the external file name extension depending on the file_extensions/1 option.

Compilation flags:

```
static
```

Template:

```
filter_external_file_extension(Path,Options,Name)
```

Mode and number of proofs:

```
filter_external_file_extension(+atom,+list(compound),-atom) - one
```

```
add_link_options/3
```

Adds url/1, urls/2, and tooltip/1 link options (for use by the graph language) based on the specified path to the list of options.

Compilation flags:

```
static
```

Template:

```
add_link_options(Path,Options,LinkingOptions)
```

Mode and number of proofs:

```
add_link_options(+atom,+list(compound),-list(compound)) - one
```

`omit_path_prefix/3`

Removes a prefix from a path, returning the relative path, when using the option `omit_path_prefixes/1`.
Used mainly for constructing directory and file node identifiers and captions.

Compilation flags:

`static`

Template:

`omit_path_prefix(Path,Options,Relative)`

Mode and number of proofs:

`omit_path_prefix(+atom,+list(compound),-atom) - one`

`add_node_zoom_option/4`

Adds node zoom options when using the zoom option.

Compilation flags:

`static`

Template:

`add_node_zoom_option(Identifier,Suffix,Options,NodeOptions)`

Mode and number of proofs:

`add_node_zoom_option(+atom,+atom,+list(compound),-list(compound)) - one`

`message_diagram_description/1`

Diagram description for progress messages.

Compilation flags:

`static`

Template:

`message_diagram_description(Description)`

Mode and number of proofs:

`message_diagram_description(?atom) - one`

Private predicates

node_/6

Table of saved nodes.

Compilation flags:
dynamic

Template:
node_(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:
node_(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more

edge_/5

Table of saved edges.

Compilation flags:
dynamic

Template:
edge_(From,To,Labels,Kind,Options)

Mode and number of proofs:
edge_(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

Operators

(none)

object

1.15.2 diagrams

Predicates for generating all supported diagrams for libraries, directories, and files in one step using the DOT format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:1:0

Date: 2019-04-07

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public diagrams(dot)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 directories/2 directories/3 directory/1
directory/2 directory/3 files/1 files/2 files/3 libraries/1 libraries/2 libraries/3 library/1
library/2 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.3 diagrams(Format)

- Format - Graph language file format.

Predicates for generating all supported diagrams for libraries, directories, or files in one step using the specified format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:8:0

Date: 2019-06-13

Compilation flags:

```
static, context_switching_calls
```

Uses:

[list](#)

[os](#)

Remarks:

- Common options: title/1, date/1, output_directory/1, relation_labels/1, node_type_captions/1, exclude_files/1, exclude_libraries/1, url_prefixes/1, omit_path_prefix/1, entity_url_suffix_target/2, and layout/1.
- Limitations: Some of the provided predicates only make sense for some types of diagrams. Also, fine tuning may require generating individual diagrams directly instead of as a batch using this utility object.

Inherited public predicates:

(none)

- Public predicates
 - libraries/3
 - libraries/2
 - libraries/1
 - all_libraries/1
 - all_libraries/0
 - rlibrary/2
 - rlibrary/1
 - library/2
 - library/1
 - directories/3
 - directories/2
 - rdirectory/3
 - rdirectory/2
 - rdirectory/1
 - directory/3
 - directory/2
 - directory/1
 - files/3
 - files/2
 - files/1
 - all_files/1
 - all_files/0
- Protected predicates
- Private predicates
- Operators

Public predicates

libraries/3

Creates all supported diagrams for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

libraries(Project,Libraries,Options)

Mode and number of proofs:

libraries(+atom,+list(atom),+list(compound)) - one

libraries/2

Creates all supported diagrams for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

libraries(Project,Libraries)

Mode and number of proofs:

libraries(+atom,+list(atom)) - one

libraries/1

Creates all supported diagrams for a set of libraries using the default options. The prefix libraries is used for the diagram file names.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates all supported diagrams for all loaded libraries using the specified options.

Compilation flags:

static

Template:

all_libraries(Options)

Mode and number of proofs:

all_libraries(+list(compound)) - one

all_libraries/0

Creates all supported diagrams for all loaded libraries using default options.

Compilation flags:

static

Mode and number of proofs:

all_libraries - one

rlibrary/2

Creates all supported diagrams for a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

```
rlibrary(Library,Options)
```

Mode and number of proofs:

```
rlibrary(+atom,+list(compound)) - one
```

`rlibrary/1`

Creates all supported diagrams for a library and its sub-libraries using default options.

Compilation flags:

```
static
```

Template:

```
rlibrary(Library)
```

Mode and number of proofs:

```
rlibrary(+atom) - one
```

`library/2`

Creates all supported diagrams for a library using the specified options.

Compilation flags:

```
static
```

Template:

```
library(Library,Options)
```

Mode and number of proofs:

```
library(+atom,+list(compound)) - one
```

library/1

Creates all supported diagrams for a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

directories/3

Creates all supported diagrams for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates all supported diagrams for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+atom,+list(compound)) - one

rdirectory/2

Creates all supported diagrams for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory)

Mode and number of proofs:

rdirectory(+atom,+atom) - one

rdirectory/1

Creates all supported diagrams for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

directory/3

Creates all supported diagrams for a directory using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Project,Directory,Options)

Mode and number of proofs:

directory(+atom,+atom,+list(compound)) - one

directory/2

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Project,Directory)

Mode and number of proofs:

directory(+atom,+atom) - one

directory/1

Creates all supported diagrams for a directory using default options. The name of the directory is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates all supported diagrams for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

files(Project,Files)

Mode and number of proofs:

files(+atom,+list(atom)) - one

files/1

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix “files” is used for the diagram file names.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

all_files/1

Creates all supported diagrams for all loaded files using the specified options.

Compilation flags:

static

Template:

all_files(Options)

Mode and number of proofs:

all_files(+list(compound)) - one

`all_files/0`

Creates all supported diagrams for all loaded files using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all_files - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

`object`

1.15.4 `directory__dependency__diagram`

Predicates for generating directory dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

`static, context__switching__calls`

Extends:

`public directory__dependency__diagram(dot)`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

directory_load_diagram, file_load_diagram

object

1.15.5 directory_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory dependency diagrams. A dependency exists when an entity in one directory makes a reference to an entity in another directory.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public directory_diagram(Format)
```

Uses:

```
file_dependency_diagram(Format)
```

```
list
```

```
logtalk
```

```
modules_diagram_support
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/2`

Table of directory sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(Project,Directory)`

Mode and number of proofs:

`sub_diagram_(?atom,?atom) - zero_or_more`

Operators

(none)

See also:

`directory_load_diagram(Format)`, `file_load_diagram(Format)`, `library_load_diagram(Format)`

`category`

1.15.6 `directory_diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating directory diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:12:1

Date: 2024-03-30

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - remember_included_directory/1
 - remember_referenced_logtalk_directory/1
 - remember_referenced_prolog_directory/1
- Private predicates
 - included_directory_/1
 - referenced_logtalk_directory_/1
 - referenced_prolog_directory_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`remember_included_directory/1`

Remember included Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_included_directory(Path)`

Mode and number of proofs:

`remember_included_directory(+atom) - one`

`remember_referenced_logtalk_directory/1`

Remember referenced Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_logtalk_directory(Path)`

Mode and number of proofs:

`remember_referenced_logtalk_directory(+atom) - one`

`remember_referenced_prolog_directory/1`

Remember referenced Prolog directory in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_prolog_directory(Path)

Mode and number of proofs:

remember_referenced_prolog_directory(+atom) - one

Private predicates

included_directory_/1

Table of Logtalk directories already included in the diagram.

Compilation flags:

dynamic

Template:

included_directory_(Path)

Mode and number of proofs:

included_directory_(?atom) - zero_or_more

referenced_logtalk_directory_/1

Table of referenced Logtalk directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_directory_(Path)

Mode and number of proofs:

referenced_logtalk_directory_(?atom) - zero_or_more

referenced_prolog_directory_/1

Table of referenced Prolog directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_directory_(Path)

Mode and number of proofs:

referenced_prolog_directory_(?atom) - zero_or_more

Operators

(none)

object

1.15.7 directory_load_diagram

Predicates for generating directory loading dependency diagrams in DOT format.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

static, context_switching_calls

Extends:

public directory_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

directory_dependency_diagram, file_dependency_diagram
 object

1.15.8 directory_load_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory loading dependency diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Imports:

public directory_diagram(Format)

Uses:

file_dependency_diagram(Format)

file_load_diagram(Format)

list

logtalk

modules_diagram_support

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/2`

Table of directory sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(Project,Directory)`

Mode and number of proofs:

`sub_diagram_(?atom,?atom) - zero_or_more`

Operators

(none)

See also:

`directory_dependency_diagram(Format),` `file_dependency_diagram(Format),` `li-`
`brary_dependency_diagram(Format)`
`object`

1.15.9 `dot_graph_language`

Predicates for generating graph files in the DOT language (version 2.36.0 or later).

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 3:8:1

Date: 2023-08-03

Compilation flags:

`static, context_switching_calls`

Implements:

`public graph_language_protocol`

Imports:

public options

Provides:

graph_language_registry::language_object/2

Uses:

list

os

term_io

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 edge/6 file_footer/3
file_header/3 graph_footer/5 graph_header/5 node/7 option/2 option/3 output_file_name/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.10 entity__diagram

Predicates for generating entity diagrams in DOT format with both inheritance and cross-referencing relation edges.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

`static, context_switching_calls`

Extends:

`public entity__diagram(dot)`

Remarks:

(none)

Inherited public predicates:

`all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[inheritance_diagram](#), [uses_diagram](#), [xref_diagram](#)
object

1.15.11 [entity_diagram](#)(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with both inheritance and cross-referencing relation edges.

Availability:

`logtalk__load(diagrams(loader))`

Author: Paulo Moura

Version: 2:57:2

Date: 2024-04-01

Compilation flags:

`static, context_switching_calls`

Imports:

`public diagram(Format)`

Uses:

`list`
`logtalk`
`modules__diagram__support`
`user`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
 - file/2
 - file/1
- Protected predicates
- Private predicates
 - included_entity_/1
 - included_module_/1
 - referenced_entity_/2
 - referenced_module_/2
- Operators

Public predicates

file/2

Creates a diagram for all entities in a loaded source file using the specified options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - one

file/1

Creates a diagram for all entities in a loaded source file using default options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

included_entity_/1

Table of Logtalk entities already included in the diagram.

Compilation flags:

dynamic

Template:

included_entity_(Entity)

Mode and number of proofs:

included_entity_(?entity_identifier) - zero_or_more

`included__module__`/1

Table of Prolog modules already included in the diagram.

Compilation flags:

dynamic

Template:

`included__module__(Module)`

Mode and number of proofs:

`included__module__(?module__identifier) - zero_or_more`

`referenced__entity__`/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

`referenced__entity__(Referencer,Entity)`

Mode and number of proofs:

`referenced__entity__(?entity__identifier,?entity__identifier) - zero_or_more`

`referenced__module__`/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

`referenced__module__(Referencer,Entity)`

Mode and number of proofs:

`referenced__module__(?entity__identifier,?module__identifier) - zero_or_more`

Operators

(none)

See also:

`inheritance_diagram(Format)`, `uses_diagram(Format)`, `xref_diagram(Format)`, `library_diagram(Format)`
object

1.15.12 `file_dependency_diagram`

Predicates for generating file contents dependency diagrams in DOT format. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public file_dependency_diagram(dot)`

Remarks:

(none)

Inherited public predicates:

`all_files/0` `all_files/1` `all_libraries/0` `all_libraries/1` `check_option/1` `check_options/1`
`default_option/1` `default_options/1` `diagram_description/1` `diagram_name_suffix/1` `directories/2`
`directories/3` `directory/1` `directory/2` `directory/3` `files/1` `files/2` `files/3` `format_object/1`
`libraries/1` `libraries/2` `libraries/3` `library/1` `library/2` `option/2` `option/3` `rdirectory/1`
`rdirectory/2` `rdirectory/3` `rlibrary/1` `rlibrary/2` `valid_option/1` `valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`file_load_diagram`, `directory_load_diagram`, `library_load_diagram`
`object`

1.15.13 `file_dependency_diagram`(Format)

- Format - Graph language file format.

Predicates for generating file contents dependency diagrams. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:28:3

Date: 2024-04-01

Compilation flags:

`static`, `context_switching_calls`

Imports:

`public file_diagram`(Format)

Uses:

`entity_diagram`(Format)
`list`
`logtalk`
`modules_diagram_support`
`os`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of file sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(File)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

`file_load_diagram(Format)`, `directory_load_diagram(Format)`, `library_load_diagram(Format)`

`category`

1.15.14 `file_diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating file diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:13:2

Date: 2022-05-31

Compilation flags:

`static`

Extends:

`public diagram(Format)`

Uses:

`list`

`logtalk`

`modules_diagram_support`

Remarks:

(none)

Inherited public predicates:

`all_files/0` `all_files/1` `all_libraries/0` `all_libraries/1` `check_option/1` `check_options/1`
`default_option/1` `default_options/1` `diagram_description/1` `diagram_name_suffix/1` `directories/2`
`directories/3` `directory/1` `directory/2` `directory/3` `files/1` `files/2` `files/3` `format_object/1`
`libraries/1` `libraries/2` `libraries/3` `library/1` `library/2` `option/2` `option/3` `rdirectory/1`
`rdirectory/2` `rdirectory/3` `rlibrary/1` `rlibrary/2` `valid_option/1` `valid_options/1`

- Public predicates

- Protected predicates
 - `remember_included_file/1`
 - `remember_referenced_logtalk_file/1`
 - `remember_referenced_prolog_file/1`
- Private predicates
 - `included_file_/1`
 - `referenced_logtalk_file_/1`
 - `referenced_prolog_file_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`remember_included_file/1`

Remember included Logtalk file in the diagram.

Compilation flags:

`static`

Template:

`remember_included_file(Path)`

Mode and number of proofs:

`remember_included_file(+atom) - one`

`remember_referenced_logtalk_file/1`

Remember referenced Logtalk file in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_logtalk_file(Path)`

Mode and number of proofs:

`remember_referenced_logtalk_file(+atom) - one`

`remember_referenced_prolog_file/1`

Remember referenced Prolog file in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_prolog_file(Path)`

Mode and number of proofs:

`remember_referenced_prolog_file(+atom) - one`

Private predicates

`included_file_/1`

Table of Logtalk files already included in the diagram.

Compilation flags:

`dynamic`

Template:

`included_file_(Path)`

Mode and number of proofs:

`included_file_(?atom) - zero_or_more`

`referenced_logtalk_file_/1`

Table of referenced Logtalk files in the diagram.

Compilation flags:

`dynamic`

Template:

`referenced_logtalk_file_(Path)`

Mode and number of proofs:

`referenced_logtalk_file_(?atom) - zero_or_more`

`referenced_prolog_file_/1`

Table of referenced Prolog files in the diagram.

Compilation flags:

`dynamic`

Template:

`referenced_prolog_file_(Path)`

Mode and number of proofs:

`referenced_prolog_file_(?atom) - zero_or_more`

Operators

(none)

object

1.15.15 `file_load_diagram`

Predicates for generating file loading dependency diagrams in DOT format. A dependency exists when a file loads or includes another file.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public file_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`file_dependency_diagram`, `directory_dependency_diagram`, `library_dependency_diagram`

object

1.15.16 `file_load_diagram`(Format)

- Format - Graph language file format.

Predicates for generating file loading dependency diagrams. A dependency exists when a file loads or includes another file.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:30:1

Date: 2024-04-01

Compilation flags:

`static`, `context_switching_calls`

Imports:

`public file_diagram`(Format)

Uses:

`entity_diagram`(Format)

`list`

`logtalk`

`modules_diagram_support`

`os`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of file sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(File)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

`file_dependency_diagram(Format),` `directory_dependency_diagram(Format),` `li-
brary_dependency_diagram(Format)`
`protocol`

1.15.17 graph_language_protocol

Predicates for generating graph files.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-12-30

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `output_file_name/2`
 - `file_header/3`
 - `file_footer/3`
 - `graph_header/5`
 - `graph_footer/5`
 - `node/7`
 - `edge/6`

- Protected predicates
- Private predicates
- Operators

Public predicates

`output_file_name/2`

Constructs the diagram file basename by adding a graph language dependent extension to the given name.

Compilation flags:

`static`

Template:

`output_file_name(Name,Basename)`

Mode and number of proofs:

`output_file_name(+atom,-atom) - one`

`file_header/3`

Writes the output file header using the specified options.

Compilation flags:

`static`

Template:

`file_header(Stream,Identifier,Options)`

Mode and number of proofs:

`file_header(+stream_or_alias,+atom,+list(compound)) - one`

`file_footer/3`

Writes the output file footer using the specified options.

Compilation flags:

`static`

Template:

`file_footer(Stream,Identifier,Options)`

Mode and number of proofs:

`file_footer(+stream_or_alias,+atom,+list(compound))` - one

`graph_header/5`

Writes a graph header using the specified options.

Compilation flags:

`static`

Template:

`graph_header(Stream,Identifier,Label,Kind,Options)`

Mode and number of proofs:

`graph_header(+stream_or_alias,+atom,+atom,+atom,+list(compound))` - one

`graph_footer/5`

Writes a graph footer using the specified options.

Compilation flags:

`static`

Template:

`graph_footer(Stream,Identifier,Label,Kind,Options)`

Mode and number of proofs:

`graph_footer(+stream_or_alias,+atom,+atom,+atom,+list(compound))` - one

node/7

Writes a node using the specified options.

Compilation flags:

static

Template:

node(Stream,Identifier,Label,Caption,Lines,Kind,Options)

Mode and number of proofs:

node(+stream_or_alias,+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

edge/6

Writes an edge between two nodes using the specified options.

Compilation flags:

static

Template:

edge(Stream,Start,End,Labels,Kind,Options)

Mode and number of proofs:

edge(+stream_or_alias,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.18 graph_language_registry

Registry of implemented graph languages.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-25

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - language_object/2
- Protected predicates
- Private predicates
- Operators

Public predicates

language__object/2

Table of defined graph languages and their implementation objects.

Compilation flags:
static, multifile

Template:
language__object(Language, Object)
Mode and number of proofs:
language__object(?atom, ?object__identifier) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.19 inheritance__diagram

Predicates for generating entity diagrams in DOT format with inheritance relation edges but no cross-referencing relation edges.

Availability:
logtalk__load(diagrams(loader))

Author: Paulo Moura
Version: 2:0:0
Date: 2014-01-15

Compilation flags:

static, context_switching_calls

Extends:

public inheritance_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

entity_diagram, uses_diagram, xref_diagram

object

1.15.20 inheritance_diagram(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with inheritance relation edges but no cross-referencing relation edges.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:20:0

Date: 2024-03-20

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public entity_diagram(Format)
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity__diagram(Format)`, `uses__diagram(Format)`, `xref__diagram(Format)`
object

1.15.21 library__dependency__diagram

Predicates for generating library dependency diagrams in DOT format.

Availability:

`logtalk__load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static`, `context__switching__calls`

Extends:

`public library__dependency__diagram(dot)`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

library_load_diagram, file_load_diagram, entity_diagram
 object

1.15.22 library_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating library dependency diagrams. A dependency exists when an entity in one library makes a reference to an entity in another library.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Imports:

public library_diagram(Format)

Uses:

entity_diagram(Format)

list

logtalk

modules_diagram_support

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/1`

Table of library sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(Library)`

Mode and number of proofs:

`sub_diagram_(?atom) - zero_or_more`

Operators

(none)

See also:

`library_load_diagram(Format)`, `directory_load_diagram(Format)`, `file_load_diagram(Format)`, `entity_diagram(Format)`

`category`

1.15.23 `library_diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating library diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:16:1

Date: 2024-03-30

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

user

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - add_library_documentation_url/4
 - remember_included_library/2
 - remember_referenced_logtalk_library/2
 - remember_referenced_prolog_library/2
- Private predicates
 - included_library_/2
 - referenced_logtalk_library_/2
 - referenced_prolog_library_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`add_library_documentation_url/4`

Adds a documentation URL when using the option `url_prefixes/2`.

Compilation flags:

`static`

Template:

`add_library_documentation_url(Kind,Options,Library,NodeOptions)`

Mode and number of proofs:

`add_library_documentation_url(+atom,+list(compound),+atom,-list(compound)) - one`

`remember_included_library/2`

Remember included Logtalk library in the diagram.

Compilation flags:

`static`

Template:

`remember_included_library(Library,Path)`

Mode and number of proofs:

`remember_included_library(+atom,+atom) - one`

`remember_referenced_logtalk_library/2`

Remember referenced Logtalk library in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_logtalk_library(Library,Path)

Mode and number of proofs:

remember_referenced_logtalk_library(+atom,+atom) - one

remember_referenced_prolog_library/2

Remember referenced Prolog library in the diagram.

Compilation flags:

static

Template:

remember_referenced_prolog_library(Library,Path)

Mode and number of proofs:

remember_referenced_prolog_library(+atom,+atom) - one

Private predicates

included_library_/2

Table of Logtalk libraries already included in the diagram.

Compilation flags:

dynamic

Template:

included_library_(Library,Path)

Mode and number of proofs:

included_library_(?atom,?atom) - zero_or_more

referenced_logtalk_library_/2

Table of referenced Logtalk libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_library_(Library,Path)

Mode and number of proofs:

referenced_logtalk_library_(?atom,?atom) - zero_or_more

referenced_prolog_library_/2

Table of referenced Prolog libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_library_(Library,Path)

Mode and number of proofs:

referenced_prolog_library_(?atom,?atom) - zero_or_more

Operators

(none)

See also:

inheritance_diagram(Format), uses_diagram(Format), xref_diagram(Format), entity_diagram(Format)
object

1.15.24 library_load_diagram

Predicates for generating library loading dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static, context_switching_calls`

Extends:

`public library_load_diagram(dot)`

Remarks:

`(none)`

Inherited public predicates:

`all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`library__dependency__diagram`, `file__dependency__diagram`, `entity__diagram`
object

1.15.25 `library__load__diagram`(Format)

- Format - Graph language file format.

Predicates for generating library loading dependency diagrams.

Availability:

`logtalk__load`(`diagrams`(`loader`))

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

`static`, `context__switching__calls`

Imports:

`public library__diagram`(Format)

Uses:

`entity__diagram`(Format)

`list`

`logtalk`

`modules__diagram__support`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of library sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Library)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

library_dependency_diagram(Format), directory_dependency_diagram(Format),
 file_dependency_diagram(Format), entity_diagram(Format)
 object

1.15.26 modules_diagram_support

Utility predicates for supporting Prolog modules in diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 0:19:5

Date: 2022-07-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, SICStus Prolog, SWI-Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - module_property/2
 - loaded_file_property/2
 - source_file_extension/1
- Protected predicates
- Private predicates
- Operators

Public predicates

`module_property/2`

Access to module properties, at least `exports/1`, `file/1`, and `file/2` but also `declares/2`, `defines/2`, `calls/2`, and `provides/3` when possible.

Compilation flags:

`static`

Template:

`module_property(Module,Property)`

Mode and number of proofs:

`module_property(?atom,?callable) - zero_or_more`

`loaded_file_property/2`

Access to loaded source file properties, at least `basename/1`, `directory/1` but also `parent/1` when possible.

Compilation flags:

`static`

Template:

`loaded_file_property(File,Property)`

Mode and number of proofs:

`loaded_file_property(?atom,?callable) - zero_or_more`

`source_file_extension/1`

Valid source file extension for Prolog source files.

Compilation flags:

`static`

Template:

`source_file_extension(Extension)`

Mode and number of proofs:

source_file_extension(?atom) - one_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.27 uses__diagram

Predicates for generating entity diagrams in DOT format with only uses/2 and use__module/2 relation edges.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:0:1

Date: 2020-03-27

Compilation flags:

static, context__switching__calls

Extends:

public uses__diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[entity_diagram](#), [inheritance_diagram](#), [xref_diagram](#)

object

1.15.28 [uses__diagram](#)(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams with only [uses/2](#) and [use__module/2](#) relation edges.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:21:0

Date: 2024-03-20

Compilation flags:

static, context_switching_calls

Extends:

public entity_diagram(Format)

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity_diagram(Format)`, `inheritance_diagram(Format)`, `xref_diagram(Format)`

object

1.15.29 xref_diagram

Predicates for generating predicate call cross-referencing diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public xref_diagram(dot)`

Remarks:

(none)

Inherited public predicates:

`all_files/0` `all_files/1` `all_libraries/0` `all_libraries/1` `check_option/1` `check_options/1`
`default_option/1` `default_options/1` `diagram_description/1` `diagram_name_suffix/1` `directories/2`
`directories/3` `directory/1` `directory/2` `directory/3` `entity/1` `entity/2` `file/1` `file/2` `files/1` `files/2`
`files/3` `format_object/1` `libraries/1` `libraries/2` `libraries/3` `library/1` `library/2` `option/2` `option/3`
`rdirectory/1` `rdirectory/2` `rdirectory/3` `rlibrary/1` `rlibrary/2` `valid_option/1` `valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity__diagram`, `inheritance__diagram`, `uses__diagram`
`object`

1.15.30 `xref__diagram`(Format)

- Format - Graph language file format.

Predicates for generating predicate call cross-referencing diagrams.

Availability:

`logtalk__load(diagrams(loader))`

Author: Paulo Moura

Version: 2:72:1

Date: 2024-04-02

Compilation flags:

`static`, `context__switching__calls`

Extends:

`public entity__diagram`(Format)

Uses:

`atom`

`list`

`logtalk`

`modules__diagram__support`

`os`

`user`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
 - entity/2
 - entity/1
- Protected predicates
- Private predicates
 - included_predicate_/1
 - referenced_predicate_/1
 - external_predicate_/1
- Operators

Public predicates

entity/2

Creates a diagram for a single entity using the specified options.

Compilation flags:

static

Template:

entity(Entity,Options)

Mode and number of proofs:

entity(+entity_identifier,+list(compound)) - one

entity/1

Creates a diagram for a single entity using default options.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

included_predicate_/1

Table of predicates already included in the diagram for the entity under processing.

Compilation flags:

dynamic

Template:

included_predicate_(Predicate)

Mode and number of proofs:

included_predicate_(?predicate_indicator) - zero_or_more

referenced_predicate_/1

Table of referenced predicates for the entity under processing.

Compilation flags:

dynamic

Template:

referenced_predicate_(Predicate)

Mode and number of proofs:

referenced_predicate_(?predicate_indicator) - zero_or_more

external_predicate_/1

Table of external predicate references for all the entities under processing.

Compilation flags:

dynamic

Template:

external_predicate_(Reference)

Mode and number of proofs:

external_predicate_(?compound) - zero_or_more

Operators

(none)

See also:

entity_diagram(Format), inheritance_diagram(Format), uses_diagram(Format)

1.16 dictionaries

object

1.16.1 avltree

AVL tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

logtalk_load(dictionaries(loader))

Author: R.A.O'Keefe, L.Damas, V.S.Costa, Glenn Burgess, Jiri Spitz, and Jan Wielemaker; Logtalk port and additional predicates by Paulo Moura

Version: 1:4:0
Date: 2021-04-12

Compilation flags:
static, context_switching_calls

Implements:
public [dictionary](#)

Extends:
public [term](#)

Uses:
[list](#)

Remarks:
(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[bintree](#), [rbtree](#)

object

1.16.2 [bintree](#)

Simple binary tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

`logtalk__load(dictionaries(loader))`

Author: Paulo Moura and Paul Fodor

Version: 2:11:1

Date: 2022-05-05

Compilation flags:

`static, context_switching_calls`

Implements:

`public dictionary`

Extends:

`public term`

Uses:

`list`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3`

- Public predicates
 - preorder/2
 - inorder/2
 - postorder/2
- Protected predicates
- Private predicates
- Operators

Public predicates

preorder/2

Preorder tree traversal.

Compilation flags:
static

Template:

preorder(Tree,List)

Mode and number of proofs:

preorder(@tree,-list) - one

inorder/2

Inorder tree traversal.

Compilation flags:
static

Template:

inorder(Tree,List)

Mode and number of proofs:

inorder(@tree,-list) - one

postorder/2

Postorder tree traversal.

Compilation flags:

static

Template:

postorder(Tree,List)

Mode and number of proofs:

postorder(@tree,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

avltree, rbtree

protocol

1.16.3 dictionaryp

Dictionary protocol.

Availability:

logtalk_load(dictionaries(loader))

Author: Paulo Moura

Version: 2:3:0

Date: 2021-04-12

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - as_dictionary/2
 - as_list/2
 - as_curly_bracketed/2
 - clone/3
 - clone/4
 - insert/4
 - delete/4
 - update/4
 - update/5
 - update/3
 - empty/1
 - lookup/3
 - lookup/2
 - intersection/2
 - intersection/3
 - previous/4
 - next/4
 - min/3
 - max/3
 - delete_min/4
 - delete_max/4
 - keys/2
 - values/2
 - map/2

- map/3
- apply/4
- size/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_dictionary/2`

Converts a list of key-value pairs to a dictionary.

Compilation flags:

static

Template:

`as_dictionary(Pairs,Dictionary)`

Mode and number of proofs:

`as_dictionary(@list(pairs),-dictionary) - one`

`as_list/2`

Converts a dictionary to an ordered list (as per standard order) of key-value pairs.

Compilation flags:

static

Template:

`as_list(Dictionary,Pairs)`

Mode and number of proofs:

`as_list(@dictionary,-list(pairs)) - one`

`as_curly_bracketed/2`

Creates a curly-bracketed term representation of a dictionary.

Compilation flags:

`static`

Template:

`as_curly_bracketed(Dictionary,Term)`

Mode and number of proofs:

`as_curly_bracketed(+dictionary,--term) - one`

`clone/3`

Clones a dictionary using the same keys but with all values unbound and returning a list of all the pairs in the new clone.

Compilation flags:

`static`

Template:

`clone(Dictionary,Clone,ClonePairs)`

Mode and number of proofs:

`clone(+dictionary,-dictionary,-list(pairs)) - one`

`clone/4`

Clones a dictionary using the same keys but with all values unbound and returning the list of all pairs in the dictionary and in the clone.

Compilation flags:

`static`

Template:

`clone(Dictionary,Pairs,Clone,ClonePairs)`

Mode and number of proofs:

`clone(+dictionary,-list(pairs),-dictionary,-list(pairs)) - one`

`insert/4`

Inserts a key-value pair into a dictionary, returning the updated dictionary. When the key already exists, the associated value is updated.

Compilation flags:

`static`

Template:

`insert(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`insert(+dictionary,+ground,@term,-dictionary) - one`

`delete/4`

Deletes a matching key-value pair from a dictionary, returning the updated dictionary.

Compilation flags:

`static`

Template:

`delete(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`delete(+dictionary,@ground,?term,-dictionary) - zero_or_one`

`update/4`

Updates the value associated with Key in a dictionary, returning the updated dictionary. Fails if it cannot find the key.

Compilation flags:

`static`

Template:

```
update(OldDictionary,Key,NewValue,NewDictionary)
```

Mode and number of proofs:

```
update(+dictionary,@ground,+term,-dictionary) - zero_or_one
```

update/5

Updates the value associated with a key in a dictionary, returning the updated dictionary. Fails if it cannot find the key or if the existing value does not match the old value.

Compilation flags:

```
static
```

Template:

```
update(OldDictionary,Key,OldValue,NewValue,NewDictionary)
```

Mode and number of proofs:

```
update(+dictionary,@ground,?term,+term,-dictionary) - zero_or_one
```

update/3

Updates the key-value pairs in a dictionary, returning the updated dictionary. Fails if it cannot find one of the keys.

Compilation flags:

```
static
```

Template:

```
update(OldDictionary,Pairs,NewDictionary)
```

Mode and number of proofs:

```
update(+dictionary,@list(pair),-dictionary) - zero_or_one
```

empty/1

True iff the dictionary is empty.

Compilation flags:

static

Template:

empty(Dictionary)

Mode and number of proofs:

empty(@dictionary) - zero_or_one

lookup/3

Lookups a matching key-value pair from a dictionary.

Compilation flags:

static

Template:

lookup(Key,Value,Dictionary)

Mode and number of proofs:

lookup(+ground,?term,@dictionary) - zero_or_one

lookup(-ground,?term,@dictionary) - zero_or_more

lookup/2

Lookups all matching key-value pairs from a dictionary. Fails if it cannot find one of the keys or if a value for a key does not unify.

Compilation flags:

static

Template:

lookup(Pairs,Dictionary)

Mode and number of proofs:

lookup(+list(pair),@dictionary) - zero_or_one

intersection/2

True iff the values of the dictionaries common keys unify. Trivially true when there are no common keys.

Compilation flags:

static

Template:

intersection(Dictionary1,Dictionary2)

Mode and number of proofs:

intersection(+dictionary,+dictionary) - zero_or_one

intersection/3

Returns the (possibly empty) intersection between two dictionaries when the values of their common keys unify.

Compilation flags:

static

Template:

intersection(Dictionary1,Dictionary2,Intersection)

Mode and number of proofs:

intersection(+dictionary,+dictionary,-dictionary) - zero_or_one

previous/4

Returns the previous pair in a dictionary given a key.

Compilation flags:

static

Template:

previous(Dictionary,Key,Previous,Value)

Mode and number of proofs:

previous(+dictionary,+key,-key,-value) - zero_or_one

next/4

Returns the next pair in a dictionary given a key.

Compilation flags:

static

Template:

next(Dictionary,Key,Next,Value)

Mode and number of proofs:

next(+dictionary,+key,-key,-value) - zero_or_one

min/3

Returns the pair with the minimum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

static

Template:

min(Dictionary,Key,Value)

Mode and number of proofs:

min(+dictionary,-key,-value) - zero_or_one

`max/3`

Returns the pair with the maximum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

`static`

Template:

`max(Dictionary,Key,Value)`

Mode and number of proofs:

`max(+dictionary,-key,-value) - zero_or_one`

`delete_min/4`

Deletes the pair with the minimum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary.

Compilation flags:

`static`

Template:

`delete_min(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`delete_min(+dictionary,-key,-value,-dictionary) - zero_or_one`

`delete_max/4`

Deletes the pair with the maximum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary.

Compilation flags:

`static`

Template:

`delete_max(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`delete_max(+dictionary,-key,-value,-dictionary) - zero_or_one`

`keys/2`

Returns a list with all the dictionary keys in ascending order (as per standard order).

Compilation flags:

`static`

Template:

`keys(Dictionary,Keys)`

Mode and number of proofs:

`keys(@dictionary,-list) - one`

`values/2`

Returns a list with all the dictionary values in ascending order of the keys (as per standard order).

Compilation flags:

`static`

Template:

`values(Dictionary,Values)`

Mode and number of proofs:

`values(@dictionary,-list) - one`

`map/2`

Maps a closure over each dictionary key-value pair. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

`static`

Template:


```
map(Closure,Dictionary)
```

Meta-predicate template:

```
map(1,*)
```

Mode and number of proofs:

```
map(@callable,+dictionary) - zero_or_more
```

map/3

Maps a closure over each dictionary key-value pair, returning the new dictionary. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

```
static
```

Template:

```
map(Closure,OldDictionary,NewDictionary)
```

Meta-predicate template:

```
map(2,*,*)
```

Mode and number of proofs:

```
map(@callable,+dictionary,-dictionary) - zero_or_more
```

apply/4

Applies a closure to a specific key-value pair, returning the new dictionary. Fails if the key cannot be found or if the mapped closure attempts to modify the key.

Compilation flags:

```
static
```

Template:

```
apply(Closure,OldDictionary,Key,NewDictionary)
```

Meta-predicate template:

```
apply(2,*,*,*)
```

Mode and number of proofs:

```
apply(+callable,+dictionary,+key,-dictionary) - zero_or_one
```

`size/2`

Number of dictionary entries.

Compilation flags:

`static`

Template:

`size(Dictionary,Size)`

Mode and number of proofs:

`size(@dictionary,?integer) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`avltree`, `bintree`, `rbtree`

object

1.16.4 `rbtree`

Red-Black tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

`logtalk_load(dictionaries(loader))`

Author: Vitor Santos Costa; Logtalk port and additional predicates by Paulo Moura.

Version: 1:9:0

Date: 2021-04-12

Compilation flags:

static, context_switching_calls

Implements:

public dictionaryp

Extends:

public term

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
 as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
 depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
 map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
 singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - partial_map/4
- Protected predicates
- Private predicates
- Operators

Public predicates

partial_map/4

Applies a closure to the tree pairs identified by a set of keys.

Compilation flags:

static

Template:

partial_map(Tree,Keys,Closure,NewTree)

Meta-predicate template:

partial_map(*,*,2,*)

Mode and number of proofs:

partial_map(+tree,+list,@closure,-tree) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[avltree](#), [bintree](#)

1.17 dif

object

1.17.1 dif

Provides dif/2 and derived predicates.

Availability:

`logtalk_load(dif(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2023-10-02

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - dif/2
 - dif/1
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:

static

Template:

dif(Term1,Term2)

Mode and number of proofs:

dif(+term,+term) - zero_or_one

dif/1

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:

static

Template:

dif(Terms)

Mode and number of proofs:

dif(+list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.18 doclet

object

1.18.1 doclet

Utility object to help automate (re)generating documentation for a project.

Availability:

`logtalk__load(doclet(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2017-01-05

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_tokens//2`

Uses:

`logtalk`

`os`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - update/0
 - doc_goal/1
 - shell_command/1
- Protected predicates
- Private predicates
- Operators

Public predicates

update/0

Updates the project documentation, first by calling a sequence of goals and second by executing a sequence of shell commands. Fails if any goal or shell command fails.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

doc_goal/1

Table of goals, typically using the diagrams and the lgtdoc tools, used to generate the documentation. Goals are called in the order they are defined and in the context of the user pseudo-object.

Compilation flags:

static

Template:

doc_goal(Goal)

Mode and number of proofs:

doc_goal(?callable) - one_or_more

`shell_command/1`

Table of shell commands to convert intermediate documentation files into user-friendly documentation. Commands are executed in the order they are defined.

Compilation flags:

`static`

Template:

`shell_command(Command)`

Mode and number of proofs:

`shell_command(?atom) - one_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`lgtdocp`, `diagram(Format)`

1.19 edcg

object

1.19.1 edcg

Multiple hidden parameters: an extension to Prolog's DCG notation. Ported to Logtalk as a hook object.

Availability:

`logtalk_load(edcg(loader))`

Author: Peter Van Roy; adapted to Logtalk by Paulo Moura.

Version: 1:4:2
Date: 2020-04-08

Copyright: Copyright (C) 1992 Peter Van Roy
License: MIT

Compilation flags:
static, context_switching_calls

Implements:
public expanding

Provides:
logtalk::message_tokens//2

Uses:
list
logtalk

Remarks:

- Usage: Compile source files with objects (or categories) defining EDCGs using the compiler option `hook(edcg)`.

Inherited public predicates:
goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
 - pred_info/3
 - acc_info/7
 - acc_info/5
 - pass_info/2
 - pass_info/1
- Operators
 - op(1200,xfx,-->>)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`pred_info/3`

Declares predicates that have the listed hidden parameters.

Compilation flags:

`dynamic`

Template:

`pred_info(Name,Arity,HiddenParameters)`

Mode and number of proofs:

`pred_info(?atom,?integer,?list(atom)) - zero_or_more`

`acc_info/7`

Long form for declaring accumulators.

Compilation flags:

`dynamic`

Template:

`acc_info(Accumulator,Term,Left,Right,Joiner,LStart,RStart)`

Mode and number of proofs:

`acc_info(?atom,?term,?term,?term,?callable,?term,?term) - zero_or_more`

`acc_info/5`

Short form for declaring accumulators.

Compilation flags:

`dynamic`

Template:

`acc_info(Accumulator,Term,Left,Right,Joiner)`

Mode and number of proofs:

`acc_info(?atom,?term,?term,?term,?callable) - zero_or_more`

`pass_info/2`

Long form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with `=/2` as the joiner function.

Compilation flags:

`dynamic`

Template:

`pass_info(Argument,PStart)`

Mode and number of proofs:

`pass_info(?atom,?term) - zero_or_more`

`pass_info/1`

Short form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with `=/2` as the joiner function.

Compilation flags:

`dynamic`

Template:

`pass_info(Argument)`

Mode and number of proofs:

`pass_info(?atom) - zero_or_more`

Operators

`op(1200,xfx,-->>)`

Scope:
 public

1.20 events

object

1.20.1 after_event_registry

After events registry predicates.

Availability:
 `logtalk_load(events(loader))`

Author: Paulo Moura
Version: 1:1:0
Date: 2009-10-08

Compilation flags:
 static, context_switching_calls, events

Implements:
 public `event_registry`

Remarks:
 (none)

Inherited public predicates:
 `del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4`

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[before__event__registry](#), [monitorp](#)
object

1.20.2 [before__event__registry](#)

Before events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static, context__switching__calls, events`

Implements:

`public event__registryp`

Remarks:

(none)

Inherited public predicates:

`del_monitors/0` `del_monitors/4` `monitor/1` `monitor/4` `monitored/1` `monitors/1` `set_monitor/4`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`after_event_registry`, `monitorp`

object

1.20.3 `event_registry`

Before and after events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static`, `context_switching_calls`, `events`

Implements:

`public event_registry`

Remarks:

(none)

Inherited public predicates:

`del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.20.4 `event_registry`

Event registry protocol.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - monitors/1
 - monitor/1
 - monitored/1
 - monitor/4
 - set_monitor/4
 - del_monitors/4
 - del_monitors/0
- Protected predicates
- Private predicates
- Operators

Public predicates

monitors/1

Returns a list of all current monitors.

Compilation flags:

static

Template:

monitors(Monitors)

Mode and number of proofs:

monitors(-list(object_identifier)) - one

monitor/1

Monitor is an object playing the role of a monitor.

Compilation flags:

static

Template:

monitor(Monitor)

Mode and number of proofs:

monitor(-object_identifier) - zero_or_more

monitor(+object_identifier) - zero_or_one

monitored/1

Returns a list of all currently monitored objects.

Compilation flags:

static

Template:

monitored(Objects)

Mode and number of proofs:

monitored(-list(object_identifier)) - one

monitor/4

True if the arguments describe a currently defined monitored event.

Compilation flags:

static

Template:

monitor(Object,Message,Sender,Monitor)

Mode and number of proofs:

monitor(?object_identifier,?nonvar,?object_identifier,?object_identifier) - zero_or_more

`set_monitor/4`

Sets a monitor for the set of matching events.

Compilation flags:

`static`

Template:

`set_monitor(Object,Message,Sender,Monitor)`

Mode and number of proofs:

`set_monitor(?object_identifier,?nonvar,?object_identifier,+object_identifier) - zero_or_one`

`del_monitors/4`

Deletes all matching monitored events.

Compilation flags:

`static`

Template:

`del_monitors(Object,Message,Sender,Monitor)`

Mode and number of proofs:

`del_monitors(?object_identifier,?nonvar,?object_identifier,?object_identifier) - one`

`del_monitors/0`

Deletes all monitored events.

Compilation flags:

`static`

Mode and number of proofs:

`del_monitors - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`event_registry`, `monitorp`

`category`

1.20.5 monitor

Monitor predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2019-03-08

Compilation flags:

`static, events`

Implements:

`public monitorp`

Remarks:

(none)

Inherited public predicates:

`activate_monitor/0` `del_spy_points/4` `monitor_activated/0` `reset_monitor/0` `set_spy_point/4`
`spy_point/4` `suspend_monitor/0`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
 - [spy__point__/4](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`spy__point__/4`

Stores current spy points.

Compilation flags:

`dynamic`

Template:

`spy__point__(Event,Object,Message,Sender)`

Mode and number of proofs:

`spy__point__(?event,?object,?callable,?object) - zero__or__more`

Operators

(none)

`protocol`

1.20.6 monitorp

Monitor protocol.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `monitor_activated/0`
 - `activate_monitor/0`
 - `suspend_monitor/0`
 - `reset_monitor/0`
 - `spy_point/4`
 - `set_spy_point/4`
 - `del_spy_points/4`
- Protected predicates
- Private predicates
- Operators

Public predicates

`monitor_activated/0`

True if monitor is currently active.

Compilation flags:
static

Mode and number of proofs:
`monitor_activated - zero_or_one`

`activate_monitor/0`

Activates all spy points and start monitoring.

Compilation flags:
static

Mode and number of proofs:
`activate_monitor - one`

`suspend_monitor/0`

Suspends monitoring, deactivating all spy points.

Compilation flags:
static

Mode and number of proofs:
`suspend_monitor - one`

`reset_monitor/0`

Resets monitor, deactivating and deleting all spy points.

Compilation flags:

`static`

Mode and number of proofs:

`reset_monitor - one`

`spy_point/4`

Current spy point.

Compilation flags:

`static`

Template:

`spy_point(Event, Object, Message, Sender)`

Mode and number of proofs:

`spy_point(?event, ?object, ?callable, ?object) - zero_or_more`

`set_spy_point/4`

Sets a spy point.

Compilation flags:

`static`

Template:

`set_spy_point(Event, Object, Message, Sender)`

Mode and number of proofs:

`set_spy_point(?event, ?object, ?callable, ?object) - one`

`del_spy_points/4`

Deletes all matching spy points.

Compilation flags:

`static`

Template:

`del_spy_points(Event, Object, Message, Sender)`

Mode and number of proofs:

`del_spy_points(@event, @object, @callable, @object) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`monitor`, `event_registry`

1.21 expand_library_alias_paths

object

1.21.1 expand_library_alias_paths

Hook object for expanding library alias paths in `logtalk_library_path/2` facts when compiling a source file.

Availability:

`logtalk_load(expand_library_alias_paths(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2018-04-12

Compilation flags:

static, context_switching_calls

Implements:

public [expanding](#)

Uses:

[logtalk](#)

[os](#)

Remarks:

(none)

Inherited public predicates:

[goal_expansion/2](#) [term_expansion/2](#)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.22 expecteds

object

1.22.1 either

Types and predicates for extended type-checking and handling of expected terms.

Availability:

`logtalk__load(expecteds(loader))`

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

`static, context_switching_calls`

Provides:

`type::type/1`

`type::check/2`

`arbitrary::arbitrary/1`

`arbitrary::arbitrary/2`

Uses:

`expected`

`expected(Expected)`

`random`

`type`

Remarks:

- Type-checking support: Defines a `either(ValueType, ErrorType)` type for checking expected terms where the value and error terms must be of the given types.
- QuickCheck support: Defines clauses for the `type::arbitrary/1-2` predicates to allow generating random values for the `either(ValueType, ErrorType)` type.

Inherited public predicates:

(none)

- Public predicates
 - `expecteds/2`
 - `unexpecteds/2`
 - `partition/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`expecteds/2`

Returns the values stored in the expected terms that hold a value.

Compilation flags:

`static`

Template:

`expecteds(Expecteds,Values)`

Mode and number of proofs:

`expecteds(+list(expected),-list) - one`

`unexpecteds/2`

Returns the errors stored in the expected terms that hold an error.

Compilation flags:

`static`

Template:

`unexpecteds(Expecteds,Errors)`

Mode and number of proofs:

`unexpecteds(+list(expected),-list) - one`

partition/3

Retrieves and partitions the values and errors hold by the expected terms.

Compilation flags:

static

Template:

partition(Expecteds,Values,Errors)

Mode and number of proofs:

partition(+list(expected),-list,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

expected, expected(Expected), type, arbitrary

object

1.22.2 expected

Constructors for expected terms. An expected term contains either a value or an error. Expected terms should be regarded as opaque terms and always used with the expected/1 object by passing the expected term as a parameter.

Availability:

logtalk_load(expecteds(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

static, context_switching_calls

Provides:

type::type/1
type::check/2

Remarks:

- Type-checking support: This object also defines a type expected for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - of_unexpected/2
 - of_expected/2
 - from_goal/4
 - from_goal/3
 - from_goal/2
 - from_generator/4
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

of_unexpected/2

Constructs an expected term from an error that represent that the expected value is missing.

Compilation flags:

static

Template:

of_unexpected(Error,Expected)

Mode and number of proofs:

of_unexpected(@term,--nonvar) - one

of_expected/2

Constructs an expected term from an expected value.

Compilation flags:

static

Template:

of_expected(Value,Expected)

Mode and number of proofs:

of_expected(@term,--nonvar) - one

from_goal/4

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

static

Template:

from_goal(Goal,Value,Error,Expected)

Meta-predicate template:

from_goal(0,*,*,*)

Mode and number of proofs:

from_goal(+callable,--term,@term,--nonvar) - one

`from_goal/3`

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or the atom fail representing the unexpected failure.

Compilation flags:

static

Template:

`from_goal(Goal,Value,Expected)`

Meta-predicate template:

`from_goal(0,*,*)`

Mode and number of proofs:

`from_goal(+callable,--term,--nonvar) - one`

`from_goal/2`

Constructs an expected term holding a value bound by calling the given closure. Otherwise returns an expected term holding the unexpected closure error or the atom fail representing the unexpected failure.

Compilation flags:

static

Template:

`from_goal(Closure,Expected)`

Meta-predicate template:

`from_goal(1,*)`

Mode and number of proofs:

`from_goal(+callable,--nonvar) - one`

`from_generator/4`

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

static

Template:

```
from_generator(Goal,Value,Error,Expected)
```

Meta-predicate template:

```
from_generator(0,*,*,*)
```

Mode and number of proofs:

```
from_generator(+callable,--term,@term,--nonvar) - one_or_more
```

`from_generator/3`

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with, respectively, the unexpected goal error or the atom fail representing the unexpected goal failure.

Compilation flags:

```
static
```

Template:

```
from_generator(Goal,Value,Expected)
```

Meta-predicate template:

```
from_generator(0,*,*)
```

Mode and number of proofs:

```
from_generator(+callable,--term,--nonvar) - one_or_more
```

`from_generator/2`

Constructs expected terms with the values generated by calling the given closure. On closure error or failure, returns an expected term with, respectively, the unexpected closure error or the atom fail representing the unexpected closure failure.

Compilation flags:

```
static
```

Template:

```
from_generator(Closure,Expected)
```

Meta-predicate template:

```
from_generator(1,*)
```

Mode and number of proofs:

```
from_generator(+callable,--nonvar) - one_or_more
```

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`expected(Expected)`, type

object

1.22.3 `expected(Expected)`

Expected term predicates. Requires passing an expected term (constructed using the expected object predicates) as a parameter.

Availability:

`logtalk_load(expecteds(loader))`

Author: Paulo Moura

Version: 1:5:0

Date: 2020-01-06

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `is_expected/0`
 - `is_unexpected/0`
 - `if_expected/1`
 - `if_unexpected/1`
 - `if_expected_or_else/2`
 - `unexpected/1`
 - `expected/1`
 - `map/2`
 - `flat_map/2`
 - `either/3`
 - `or_else/2`
 - `or_else_get/2`
 - `or_else_call/2`
 - `or_else_throw/1`
 - `or_else_fail/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`is_expected/0`

True if the `expected` term holds a value. See also the `if_expected/1` predicate.

Compilation flags:

`static`

Mode and number of proofs:

`is_expected - zero_or_one`

`is_unexpected/0`

True if the expected term holds an error. See also the `if_unexpected/1` predicate.

Compilation flags:

`static`

Mode and number of proofs:

`is_unexpected - zero_or_one`

`if_expected/1`

Applies a closure when the expected term holds a value using the value as argument. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_expected(Closure)`

Meta-predicate template:

`if_expected(1)`

Mode and number of proofs:

`if_expected(+callable) - zero_or_more`

`if_unexpected/1`

Applies a closure when the expected term holds an error using the error as argument. Succeeds otherwise. Can be used to throw the exception hold by the expected term by calling it the `atom throw`.

Compilation flags:

`static`

Template:

`if_unexpected(Closure)`

Meta-predicate template:

`if_unexpected(1)`

Mode and number of proofs:

`if_unexpected(+callable) - zero_or_more`

`if_expected_or_else/2`

Applies either `ExpectedClosure` or `UnexpectedClosure` depending on the `expected` term holding a value or an error.

Compilation flags:

`static`

Template:

`if_expected_or_else(ExpectedClosure,UnexpectedClosure)`

Meta-predicate template:

`if_expected_or_else(1,1)`

Mode and number of proofs:

`if_expected_or_else(+callable,+callable) - zero_or_more`

`unexpected/1`

Returns the error hold by the `expected` term. Throws an error otherwise.

Compilation flags:

`static`

Template:

`unexpected(Error)`

Mode and number of proofs:

`unexpected(--term) - one_or_error`

Exceptions:

Expected term holds a value:

`existence_error(unexpected_error,Expected)`

`expected/1`

Returns the value hold by the expected term. Throws an error otherwise.

Compilation flags:

`static`

Template:

`expected(Value)`

Mode and number of proofs:

`expected(--term) - one_or_error`

Exceptions:

Expected term holds an error:

`existence_error(expected_value,Expected)`

`map/2`

When the expected term does not hold an error and mapping a closure with the expected value and the new value as additional arguments is successful, returns an expected term with the new value. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`map(Closure,NewExpected)`

Meta-predicate template:

`map(2,*)`

Mode and number of proofs:

`map(+callable,--nonvar) - one`

`flat_map/2`

When the expected term does not hold an error and mapping a closure with the expected value and the new expected term as additional arguments is successful, returns the new expected term. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`flat_map(Closure,NewExpected)`

Meta-predicate template:

`flat_map(2,*)`

Mode and number of proofs:

`flat_map(+callable,--nonvar) - one`

`either/3`

Applies either `ExpectedClosure` if the expected term holds a value or `UnexpectedClosure` if the expected term holds an error. Returns a new expected term if the applied closure is successful. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`either(ExpectedClosure,UnexpectedClosure,NewExpected)`

Meta-predicate template:

`either(2,2,*)`

Mode and number of proofs:

`either(+callable,+callable,--nonvar) - one`

`or_else/2`

Returns the value hold by the expected term if it does not hold an error or the given default term if the expected term holds an error.

Compilation flags:

`static`

Template:

`or_else(Value,Default)`

Mode and number of proofs:

`or_else(--term,@term) - one`

`or_else_get/2`

Returns the value hold by the expected term if it does not hold an error. Otherwise applies a closure to compute the expected value. Throws an error when the expected term holds an error and a value cannot be computed.

Compilation flags:

`static`

Template:

`or_else_get(Value,Closure)`

Meta-predicate template:

`or_else_get(*,1)`

Mode and number of proofs:

`or_else_get(--term,+callable) - one_or_error`

Exceptions:

Expected term holds an unexpected error and an expected value cannot be computed:

`existence_error(expected_value,Expected)`

`or_else_call/2`

Returns the value hold by the expected term if it does not hold an error. Calls a goal deterministically otherwise.

Compilation flags:

`static`

Template:

`or_else_call(Value,Goal)`

Meta-predicate template:

`or_else_call(*,0)`

Mode and number of proofs:

`or_else_call(--term,+callable) - zero_or_one`

`or_else_throw/1`

Returns the value hold by the expected term if present. Throws the error hold by the expected term as an exception otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value)`

Mode and number of proofs:

`or_else_throw(--term) - one_or_error`

`or_else_fail/1`

Returns the value hold by the expected term if it does not hold an error. Fails otherwise. Usually called to skip over expected terms holding errors.

Compilation flags:

`static`

Template:

`or_else_fail(Value)`

Mode and number of proofs:

`or_else_fail(--term) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`expected`

1.23 fcube

object

1.23.1 fcube

FCube: An Efficient Prover for Intuitionistic Propositional Logic.

Availability:

`logtalk_load(fcube(loader))`

Author: Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; ported to Logtalk by Paulo Moura.

Version: 5:0:1

Date: 2024-03-14

Copyright: Copyright 2012 Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; Copyright 2020-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

`static, context_switching_calls`

Uses:

integer
list
os
set
user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - gnu/0
 - fcube/0
 - decide/1
 - decide/2
- Protected predicates
- Private predicates
- Operators
 - op(1200,xfy,<=>)
 - op(1110,xfy,=>)
 - op(1000,xfy,&&&)
 - op(500,fy,~)
 - op(1100,xfy,v)

Public predicates

gnu/0

Prints banner with copyright and license information.

Compilation flags:

static

Mode and number of proofs:

gnu - one

fcube/0

Reads a formula and applies the prover to it, printing its counter-model.

Compilation flags:

static

Mode and number of proofs:

fcube - one

decide/1

Applies the prover to the given formula and prints its counter-model.

Compilation flags:

static

Template:

decide(Formula)

Mode and number of proofs:

decide(++compound) - one

decide/2

Applies the prover to the given formula and returns its counter-model.

Compilation flags:

static

Template:

decide(Formula,CounterModel)

Mode and number of proofs:

decide(++compound,--compound) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

`op(1200,xfy,<=>)`

Scope:
public

`op(1110,xfy,=>)`

Scope:
public

`op(1000,xfy,&&)`

Scope:
public

`op(500,fy,~)`

Scope:
public

`op(1100,xfy,v)`

Scope:
public

1.24 flags

category

1.24.1 flags

Implementation of persistent object flags.

Availability:

logtalk_load(flags(loader))

Author: Theofrastos Mantadelis

Version: 1:0:0

Date: 2010-11-27

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - get_flag_value/2
 - set_flag_value/2
 - set_flag_value/3
 - reset_flags/0
 - reset_flags/1
 - flag_groups/1
 - flag_group_chk/1
 - print_flags/0
 - print_flags/1
 - defined_flag/6

- built_in_flag/2
- Protected predicates
 - unsafe_set_flag_value/2
 - define_flag/1
 - define_flag/2
- Private predicates
 - defined_flag_/6
 - flag_value_/2
 - validate/3
 - validate_type/1
 - is_validator/1
- Operators

Public predicates

`get_flag_value/2`

Gets or tests the value of a flag.

Compilation flags:

static

Template:

`get_flag_value(Flag,Value)`

Mode and number of proofs:

`get_flag_value(+atom,?nonvar) - zero_or_one`

`set_flag_value/2`

Sets the value of a flag.

Compilation flags:

static

Template:

`set_flag_value(Flag,NewValue)`

Mode and number of proofs:

```
set_flag_value(+atom,@nonvar) - one
```

set_flag_value/3

Sets the value of a flag, returning the old value.

Compilation flags:

static

Template:

```
set_flag_value(Flag,OldValue,NewValue)
```

Mode and number of proofs:

```
set_flag_value(+atom,?nonvar,@nonvar) - one
```

reset_flags/0

Resets all flags to their default values.

Compilation flags:

static

Mode and number of proofs:

```
reset_flags - one
```

reset_flags/1

Resets all flags in a group to their default values.

Compilation flags:

static

Template:

```
reset_flags(Group)
```

Mode and number of proofs:

`reset_flags(+atom) - one`

`flag_groups/1`

Returns a list of all flag groups.

Compilation flags:

`static`

Template:

`flag_groups(Groups)`

Mode and number of proofs:

`flag_groups(-list(atom)) - one`

`flag_group_chk/1`

Checks if a given atom is a flag group.

Compilation flags:

`static`

Template:

`flag_group_chk(Group)`

Mode and number of proofs:

`flag_group_chk(+atom) - zero_or_one`

`print_flags/0`

Prints a listing of all flags.

Compilation flags:

`static`

Mode and number of proofs:

`print_flags` - one

`print_flags/1`

Prints a listing of all flags in a group.

Compilation flags:

`static`

Template:

`print_flags(Group)`

Mode and number of proofs:

`print_flags(+atom)` - one

`defined_flag/6`

Gets or test the existing (visible) flag definitions.

Compilation flags:

`static`

Template:

`defined_flag(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag(?atom,?atom,?nonvar,?nonvar,?atom,?atom)` - zero_or_more

`built_in_flag/2`

True if the argument is a built-in flag type with the specified default value.

Compilation flags:

`static`

Template:

```
built_in_flag(Type,DefaultValue)
```

Mode and number of proofs:

```
built_in_flag(?atom,?nonvar) - zero_or_more
```

Protected predicates

`unsafe_set_flag_value/2`

Sets the value of a flag without performing any validation checks.

Compilation flags:

```
static
```

Template:

```
unsafe_set_flag_value(Flag,NewValue)
```

Mode and number of proofs:

```
unsafe_set_flag_value(+atom,@nonvar) - one
```

`define_flag/1`

Defines a new flag using default options.

Compilation flags:

```
static
```

Template:

```
define_flag(Flag)
```

Mode and number of proofs:

```
define_flag(+atom) - one
```

`define_flag/2`

Defines a new flag using a given set of options (for example, `[group(general), type(nonvar), default(true), description(Flag), access(read_write)]`).

Compilation flags:

`static`

Template:

`define_flag(Flag,Options)`

Mode and number of proofs:

`define_flag(+atom,@list) - one`

Private predicates

`defined_flag_/6`

Gets or test the existing flag definitions.

Compilation flags:

`dynamic`

Template:

`defined_flag_(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag_(?atom,?atom,?nonvar,?nonvar,?atom,?atom) - zero_or_more`

`flag_value_/2`

Table of flag values.

Compilation flags:

`dynamic`

Template:

`flag_value_(Flag,Value)`

Mode and number of proofs:

`flag_value_(?atom,?nonvar) - zero_or_more`

`validate/3`

Compilation flags:
static

`validate_type/1`

Compilation flags:
static

`is_validator/1`

Compilation flags:
static

Operators

(none)
protocol

1.24.2 flags_validator

Flag validation protocol. Must be implemented by validator objects.

Availability:
`logtalk_load(flags(loader))`

Author: Theofrastos Mantadelis
Version: 1:0:0
Date: 2010-11-27

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - print_flags/0
 - validate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

print_flags/0

Validates the validator object itself.

Compilation flags:
static

Mode and number of proofs:
print_flags - zero_or_one

validate/1

Validates a flag value.

Compilation flags:

static

Template:

validate(Value)

Mode and number of proofs:

validate(@term) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.25 format

object

1.25.1 format

Formatted output predicates.

Availability:

logtalk_load(format(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2023-10-02

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - format/3
 - format/2
- Protected predicates
- Private predicates
- Operators

Public predicates

format/3

Writes a list of arguments after a format specification to the specified output stream.

Compilation flags:

static

Template:

format(Stream,Format,Arguments)

Mode and number of proofs:

format(@stream_or_alias,+atom,@list) - zero_or_one

format(@stream_or_alias,+list(character_code),@list) - zero_or_one

format(@stream_or_alias,+list(character),@list) - zero_or_one

`format/2`

Writes a list of arguments after a format specification to the current output stream.

Compilation flags:

`static`

Template:

`format(Format,Arguments)`

Mode and number of proofs:

`format(+atom,@list) - zero_or_one`

`format(+list(character_code),@list) - zero_or_one`

`format(+list(character),@list) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.26 genint

object

1.26.1 genint

Global object for generating increasing non-negative integers for named counters. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

`logtalk_load(genint(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public `genint_core`

Remarks:

(none)

Inherited public predicates:

`genint/2` `reset_genint/0` `reset_genint/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

`category`

1.26.2 `genint_core`

Predicates for generating increasing non-negative integers. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(genint(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-26

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - `reset_genint/0`
 - `reset_genint/1`
 - `genint/2`
- Protected predicates
- Private predicates
 - `counter_/2`
- Operators

Public predicates

`reset_genint/0`

Resets all counters.

Compilation flags:

static, synchronized

Mode and number of proofs:

`reset_genint` - one

`reset_genint/1`

Resets the given counter.

Compilation flags:

static, synchronized

Template:

`reset_genint(Counter)`

Mode and number of proofs:

`reset_genint(+atom)` - one

`genint/2`

Returns the next integer for a given counter.

Compilation flags:

static, synchronized

Template:

`genint(Counter,Integer)`

Mode and number of proofs:

`genint(+atom,-non_negative_integer)` - one

Protected predicates

(none)

Private predicates

counter_/2

Table of current state of counters.

Compilation flags:

dynamic

Template:

counter_(Counter,Latest)

Mode and number of proofs:

counter_(?atom,?non_negative_integer) - zero_or_more

Operators

(none)

1.27 gensym

object

1.27.1 gensym

Global object for generating unique atoms. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public gensym_core

Remarks:

(none)

Inherited public predicates:

gensym/2 reset_gensym/0 reset_gensym/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.27.2 gensym_core

Predicates for generating unique atoms. Protocol based on the gensym module of SWI-Prolog. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2022-07-26

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - reset_gensym/0
 - reset_gensym/1
 - gensym/2
- Protected predicates
- Private predicates
 - base_/2
- Operators

Public predicates

reset_gensym/0

Resets the generator counter for all bases.

Compilation flags:
static, synchronized

Mode and number of proofs:
reset_gensym - one

`reset_gensym/1`

Resets the generator counter for a given base.

Compilation flags:

static, synchronized

Template:

`reset_gensym(Base)`

Mode and number of proofs:

`reset_gensym(+atom) - one`

`gensym/2`

Returns a new unique atom with a given base (prefix).

Compilation flags:

static, synchronized

Template:

`gensym(Base,Unique)`

Mode and number of proofs:

`gensym(+atom,-atom) - one`

Protected predicates

(none)

Private predicates

`base_/2`

Table of generator bases and respective counters.

Compilation flags:

dynamic

Template:

base_(Base,Counter)

Mode and number of proofs:

base_(?atom,?integer) - zero_or_more

Operators

(none)

1.28 git

object

1.28.1 git

Predicates for accessing a git project current branch and latest commit data.

Availability:

logtalk_load([git\(loader\)](#))

Author: Paulo Moura

Version: 2:1:2

Date: 2024-03-11

Compilation flags:

static, context_switching_calls

Implements:

public [git_protocol](#)

Uses:

[os](#)

[user](#)

Remarks:

(none)

Inherited public predicates:

[branch/2](#) [commit_author/2](#) [commit_date/2](#) [commit_hash/2](#) [commit_hash_abbreviated/2](#)
[commit_log/3](#) [commit_message/2](#)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.28.2 git_protocol

Predicates for accessing a git project current branch and latest commit data.

Availability:

`logtalk_load(git(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2022-01-21

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - branch/2
 - commit_author/2
 - commit_date/2
 - commit_hash/2
 - commit_hash_abbreviated/2
 - commit_message/2
 - commit_log/3
- Protected predicates
- Private predicates
- Operators

Public predicates

branch/2

Returns the name of the current git branch. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

branch(Directory,Branch)

Mode and number of proofs:

branch(+atom,?atom) - zero_or_one

`commit_author/2`

Returns the latest commit author. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_author(Directory,Author)`

Mode and number of proofs:

`commit_author(+atom,-atom) - zero_or_one`

`commit_date/2`

Returns the latest commit date (strict ISO 8601 format). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_date(Directory,Date)`

Mode and number of proofs:

`commit_date(+atom,-atom) - zero_or_one`

`commit_hash/2`

Returns the latest commit hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_hash(Directory,Hash)`

Mode and number of proofs:

`commit_hash(+atom,-atom) - zero_or_one`

`commit_hash_abbreviated/2`

Returns the latest commit abbreviated hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_hash_abbreviated(Directory,Hash)`

Mode and number of proofs:

`commit_hash_abbreviated(+atom,-atom) - zero_or_one`

`commit_message/2`

Returns the latest commit message. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_message(Directory,Message)`

Mode and number of proofs:

`commit_message(+atom,-atom) - zero_or_one`

`commit_log/3`

Returns the git latest commit log output for the given format (see e.g. <https://git-scm.com/docs/pretty-formats>). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_log(Directory,Format,Output)`

Mode and number of proofs:

`commit_log(+atom,+atom,-atom) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.29 grammars

object

1.29.1 `blank_grammars(Format)`

Blank grammars.

Availability:

`logtalk_load(grammars(loader))`

Author: Paulo Moura

Version: 0:3:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - white_space//0
 - white_spaces//0
 - space//0
 - spaces//0
 - tab//0
 - tabs//0
 - new_line//0
 - new_lines//0
 - blank//0
 - blanks//0
 - non_blank//1
 - non_blanks//1
 - control//0
 - controls//0
- Protected predicates
- Private predicates
- Operators

Public predicates

`white_space//0`

Consumes a single space or tab.

Compilation flags:

`static`

Mode and number of proofs:

`white_space - zero_or_one`

`white_spaces//0`

Consumes zero or more spaces and tabs.

Compilation flags:

`static`

Mode and number of proofs:

`white_spaces - one`

`space//0`

Consumes a single space.

Compilation flags:

`static`

Mode and number of proofs:

`space - zero_or_one`

`spaces//0`

Consumes zero or more spaces.

Compilation flags:

`static`

Mode and number of proofs:

`spaces - one`

`tab//0`

Consumes a single tab.

Compilation flags:

`static`

Mode and number of proofs:

`tab - zero_or_one`

`tabs//0`

Consumes zero or more tabs.

Compilation flags:

`static`

Mode and number of proofs:

`tabs - one`

`new_line//0`

Consumes a single new line.

Compilation flags:

`static`

Mode and number of proofs:

`new_line - zero_or_one`

`new_lines//0`

Consumes zero or more new lines.

Compilation flags:

`static`

Mode and number of proofs:

`new_lines - one`

`blank//0`

Consumes a single space, tab, vertical tab, line feed, or new line.

Compilation flags:

`static`

Mode and number of proofs:

`blank - zero_or_one`

`blanks//0`

Consumes zero or more spaces, tabs, vertical tabs, line feeds, or new lines.

Compilation flags:

`static`

Mode and number of proofs:

`blanks - one`

`non_blank//1`

Returns a single non-blank character or character code.

Compilation flags:

`static`

Template:

`non_blank(NonBlank)`

Mode and number of proofs:

`non_blank(-atomic) - zero_or_one`

`non_blanks//1`

Returns a (possibly empty) list of non-blank characters or character codes.

Compilation flags:

`static`

Template:

`non_blanks(NonBlanks)`

Mode and number of proofs:

`non_blanks(-list(atomic)) - one`

`control//0`

Consumes a single control character or character code. Support for the null control character depends on the Prolog backend.

Compilation flags:

`static`

Mode and number of proofs:

`control - zero_or_one`

`controls//0`

Consumes zero or more control characters or character codes. Support for the null control character depends on the Prolog backend.

Compilation flags:

`static`

Mode and number of proofs:

`controls - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.29.2 ip_grammars(Format)

IP address grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:1:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Uses:

number_grammars(Format)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - ipv4//1
 - ipv6//1
- Protected predicates
- Private predicates
- Operators

Public predicates

ipv4//1

Parses an IPv4 network address in the format XXX.XXX.XXX.XXX where each XXX is an octet (i.e. an integer between 0 and 255).

Compilation flags:

static

Template:

ipv4(Octets)

Mode and number of proofs:

ipv4(?list(integer)) - zero_or_one

ipv6//1

Parses an IPv6 network address in the format XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX where each X is a hexadecimal digit.

Compilation flags:

static

Template:

ipv6(HexDigits)

Mode and number of proofs:

ipv6(?list(integer)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.3 number_grammars(Format)

Number grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:2:2

Date: 2024-03-14

Compilation flags:

static, context_switching_calls

Uses:

list

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - bit//1
 - bits//1
 - digit//1
 - digits//1
 - hex_digit//1
 - hex_digits//1
 - natural//1
 - integer//1
 - float//1
 - number//1
 - sign//1
 - dot//1
- Protected predicates
- Private predicates
- Operators

Public predicates

`bit//1`

Parses a single bit.

Compilation flags:
static

Template:
bit(Bit)
Mode and number of proofs:
bit(?integer) - zero_or_one

`bits//1`

Parses a sequence of one or more bits.

Compilation flags:
static

Template:
bits(Bits)
Mode and number of proofs:
bits(?list(integer)) - zero_or_one

`digit//1`

Parses a single decimal digit.

Compilation flags:
static

Template:
digit(Digit)
Mode and number of proofs:
digit(?atomic) - zero_or_one

`digits//1`

Parses a sequence of zero or more digits.

Compilation flags:
 `static`

Template:
 `digits(Digits)`
Mode and number of proofs:
 `digits(?list(atomic)) - one`

`hex_digit//1`

Parses a single hexa-decimal digit.

Compilation flags:
 `static`

Template:
 `hex_digit(HexDigit)`
Mode and number of proofs:
 `hex_digit(?atomic) - zero_or_one`

`hex_digits//1`

Parses a sequence of zero or more hexa-decimal digits.

Compilation flags:
 `static`

Template:
 `hex_digits(HexDigits)`
Mode and number of proofs:

`hex_digits(?list(atomic)) - one`

`natural//1`

Parses a natural number (a non signed integer).

Compilation flags:

`static`

Template:

`natural(Natural)`

Mode and number of proofs:

`natural(?non_negative_integer) - zero_or_one`

`integer//1`

Parses an integer.

Compilation flags:

`static`

Template:

`integer(Integer)`

Mode and number of proofs:

`integer(?integer) - zero_or_one`

`float//1`

Parses a float.

Compilation flags:

`static`

Template:

`float(Float)`

Mode and number of proofs:

`float(?float) - zero_or_one`

`number//1`

Parses a number (an integer or a float).

Compilation flags:

`static`

Template:

`number(Number)`

Mode and number of proofs:

`number(?number) - zero_or_one`

`sign//1`

Parses a number sign (plus or minus).

Compilation flags:

`static`

Template:

`sign(Sign)`

Mode and number of proofs:

`sign(?atomic) - zero_or_one`

`dot//1`

Parses a decimal dot.

Compilation flags:

`static`

Template:

`dot(Dot)`

Mode and number of proofs:

`dot(?atomic) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.4 `sequence_grammars`

Sequence grammars.

Availability:

`logtalk_load(grammars(loader))`

Author: Paulo Moura

Version: 0:3:0

Date: 2023-12-09

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `zero_or_more//2`
 - `one_or_more//2`
 - `zero_or_more//1`
 - `one_or_more//1`
 - `zero_or_more//0`
 - `one_or_more//0`
 - `without//2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`zero_or_more//2`

Eagerly collect zero or more terminals that satisfy the given closure.

Compilation flags:

`static`

Template:

`zero_or_more(Closure,Terminals)`

Meta-predicate template:

`zero_or_more(1,*)`

Mode and number of proofs:

`zero_or_more(+callable,-list(atomic)) - one`

`one_or_more//2`

Eagerly collect one or more terminals that satisfy the given closure.

Compilation flags:

`static`

Template:

`one_or_more(Closure,Terminals)`

Meta-predicate template:

`one_or_more(1,*)`

Mode and number of proofs:

`one_or_more(+callable,-list(atomic)) - zero_or_one`

`zero_or_more//1`

Eagerly collect zero or more terminals.

Compilation flags:

`static`

Template:

`zero_or_more(Terminals)`

Mode and number of proofs:

`zero_or_more(-list(atomic)) - one`

`one_or_more//1`

Eagerly collect one or more terminals.

Compilation flags:

`static`

Template:

`one_or_more(Terminals)`

Mode and number of proofs:

`one_or_more(-list(atomic)) - zero_or_one`

`zero_or_more//0`

Eagerly parse zero or more terminals.

Compilation flags:

`static`

Mode and number of proofs:

`zero_or_more - one`

`one_or_more//0`

Eagerly parse one or more terminals.

Compilation flags:

`static`

Mode and number of proofs:

`one_or_more - zero_or_one`

`without//2`

Collects input terminals until one of the stop terminals is found. The stop terminals are excluded from the collected terminals.

Compilation flags:

`static`

Template:

`without(StopTerminals,Terminals)`

Mode and number of proofs:

`without(+list(atomic),-list(atomic)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.30 heaps

object

1.30.1 heap(Order)

Heap implementation, parameterized by the order to be used to compare keys (< or >).

Availability:

logtalk__load(heaps(loader))

Author: Richard O’Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:1:0

Date: 2019-05-18

Compilation flags:

static, context__switching__calls

Implements:

public `heapp`

Extends:

public `compound`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[minheap](#), [maxheap](#)

[protocol](#)

1.30.2 heapp

Heap protocol. Key-value pairs are represented as Key-Value.

Availability:

`logtalk_load(heaps(loader))`

Author: Richard O'Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:0:1

Date: 2010-11-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - insert/4
 - insert_all/3
 - delete/4
 - merge/3
 - empty/1
 - size/2
 - as_list/2
 - as_heap/2
 - top/3
 - top_next/5
- Protected predicates
- Private predicates
- Operators

Public predicates

insert/4

Inserts the new pair into a heap, returning the updated heap.

Compilation flags:

static

Template:

insert(Key, Value, Heap, NewHeap)

Mode and number of proofs:

`insert(+key,+value,+heap,-heap) - one`

`insert_all/3`

Inserts a list of pairs into a heap, returning the updated heap.

Compilation flags:

`static`

Template:

`insert_all(List,Heap,NewHeap)`

Mode and number of proofs:

`insert_all(@list(pairs),+heap,-heap) - one`

`delete/4`

Deletes and returns the top pair in a heap returning the updated heap.

Compilation flags:

`static`

Template:

`delete(Heap,TopKey,TopValue,NewHeap)`

Mode and number of proofs:

`delete(+heap,?key,?value,-heap) - zero_or_one`

`merge/3`

Merges two heaps.

Compilation flags:

`static`

Template:

```
merge(Heap1,Heap2,NewHeap)
```

Mode and number of proofs:

```
merge(+heap,+heap,-heap) - one
```

empty/1

True if the heap is empty.

Compilation flags:

```
static
```

Template:

```
empty(Heap)
```

Mode and number of proofs:

```
empty(@heap) - zero_or_one
```

size/2

Returns the number of heap elements.

Compilation flags:

```
static
```

Template:

```
size(Heap,Size)
```

Mode and number of proofs:

```
size(+heap,?integer) - zero_or_one
```

`as_list/2`

Returns the current set of pairs in the heap as a list, sorted into ascending order of the keys.

Compilation flags:

`static`

Template:

`as_list(Heap,List)`

Mode and number of proofs:

`as_list(+heap,-list) - one`

`as_heap/2`

Constructs a heap from a list of pairs.

Compilation flags:

`static`

Template:

`as_heap(List,Heap)`

Mode and number of proofs:

`as_heap(+list,-heap) - one`

`top/3`

Returns the top pair in the heap. Fails if the heap is empty.

Compilation flags:

`static`

Template:

`top(Heap,TopKey,TopValue)`

Mode and number of proofs:

`top(+heap,?key,?value) - zero_or_one`

`top_next/5`

Returns the top pair and the next pair in the heap. Fails if the heap does not have at least two elements.

Compilation flags:

`static`

Template:

`top_next(Heap,TopKey,TopValue,NextKey,NextValue)`

Mode and number of proofs:

`top_next(+heap,?key,?value,?key,?value) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`heap(Order)`

object

1.30.3 maxheap

Max-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

static, context_switching_calls

Extends:

public heap(>)

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.30.4 minheap

Min-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

`static, context__switching__calls`

Extends:

`public heap(<)`

Remarks:

`(none)`

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.31 help

object

1.31.1 help

Command-line help for Logtalk libraries, entities, plus built-in control constructs, predicates, non-terminals, and methods.

Availability:

`logtalk__load(help(loader))`

Author: Paulo Moura

Version: 0:33:0

Date: 2023-06-01

Compilation flags:

`static, context_switching_calls, complements(allow)`

Implements:

`public forwarding`

Uses:

`atom`

`os`

`user`

Remarks:

(none)

Inherited public predicates:

apis/0 apis/1 forward/1 handbook/0 handbook/1 man/1

- Public predicates
 - help/0
 - (/)/2
 - (//)/2
 - completion/2
 - completions/2
 - built_in_directive/4
 - built_in_predicate/4
 - built_in_method/4
 - control_construct/4
 - built_in_non_terminal/4
 - library/0
 - library/1
 - entity/1
 - manuals/0
- Protected predicates
- Private predicates
- Operators

Public predicates

help/0

Prints instructions on how to use the help tool.

Compilation flags:
static

Mode and number of proofs:
help - one

`(/)/2`

Provides help on the Functor/Arity built-in control construct, directive, predicate, or method.

Compilation flags:

`static`

Template:

`Functor/Arity`

Mode and number of proofs:

`+atom/ +integer - zero_or_one`

`(//)/2`

Provides help on the Functor//Arity built-in non-terminal.

Compilation flags:

`static`

Template:

`Functor//Arity`

Mode and number of proofs:

`+atom// +integer - zero_or_one`

`completion/2`

Provides a completion pair, Completion-Page, for a given prefix.

Compilation flags:

`static`

Template:

`completion(Prefix,Completion)`

Mode and number of proofs:

`completion(+atom,-pair) - zero_or_more`

`completions/2`

Provides a list of completions pairs, Completion-Page, for a given prefix.

Compilation flags:

`static`

Template:

`completions(Prefix,Completions)`

Mode and number of proofs:

`completions(+atom,-lists(pair)) - zero_or_more`

`built_in_directive/4`

Provides access to the HTML documenting files describing built-in directives.

Compilation flags:

`static`

Template:

`built_in_directive(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_directive(?atom,?integer,-atom,-atom) - zero_or_more`

`built_in_predicate/4`

Provides access to the HTML documenting files describing built-in predicates.

Compilation flags:

`static`

Template:

`built_in_predicate(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_predicate(?atom,?integer,-atom,-atom) - zero_or_more`

`built_in_method/4`

Provides access to the HTML documenting files describing built-in methods.

Compilation flags:

`static`

Template:

`built_in_method(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_method(?atom,?integer,-atom,-atom) - zero_or_more`

`control_construct/4`

Provides access to the HTML documenting files describing built-in control constructs.

Compilation flags:

`static`

Template:

`control_construct(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`control_construct(?atom,?integer,-atom,-atom) - zero_or_more`

`built_in_non_terminal/4`

Provides access to the HTML documenting files describing built-in DCG non-terminals.

Compilation flags:

`static`

Template:

`built_in_non_terminal(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_non_terminal(?atom,?integer,-atom,-atom) - zero_or_more`

library/0

Provides help on the standard Logtalk library.

Compilation flags:

static

Mode and number of proofs:

library - one

library/1

Provides help on the standard Logtalk libraries, library predicates, and library non-terminals.

Compilation flags:

static

Template:

library(Topic)

Mode and number of proofs:

library(+atom) - zero_or_one

library(+predicate_indicator) - zero_or_one

library(+non_terminal_indicator) - zero_or_one

entity/1

Provides help on Logtalk entities (objects, protocols, or categories).

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

manuals/0

Provides access to the Logtalk User and Reference manuals.

Compilation flags:

static

Mode and number of proofs:

manuals - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.31.2 help_info_support

Experimental help predicates for inline browsing of the Texinfo versions of the Handbook and APIs documentation. Currently requires Ciao Prolog, ECLiPSe, GNU Prolog, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, or YAP as the backend running on a POSIX system.

Availability:

logtalk_load(help(loader))

Author: Paulo Moura

Version: 0:8:1

Date: 2024-04-08

Compilation flags:

static

Complements:

help

Uses:

os

user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - handbook/0
 - handbook/1
 - apis/0
 - apis/1
 - man/1
- Protected predicates
- Private predicates
- Operators

Public predicates

handbook/0

Opens inline the Texinfo version of the Handbook.

Compilation flags:

static

Mode and number of proofs:

handbook - one

[handbook/1](#)

Opens inline the Texinfo version of the Handbook at the given topic.

Compilation flags:

static

Template:

handbook(Topic)

Mode and number of proofs:

handbook(+atom) - one

handbook(+predicate_indicator) - one

handbook(+non_terminal_indicator) - one

[apis/0](#)

Opens inline the Texinfo version of the APIs documentation.

Compilation flags:

static

Mode and number of proofs:

apis - one

[apis/1](#)

Opens inline the Texinfo version of the APIs documentation at the given topic.

Compilation flags:

static

Template:

apis(Topic)

Mode and number of proofs:

apis(+atom) - one

apis(+predicate_indicator) - one

apis(+non_terminal_indicator) - one

man/1

Opens inline the man page of the given script.

Compilation flags:

static

Template:

man(Script)

Mode and number of proofs:

man(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.32 hierarchies

category

1.32.1 class_hierarchy

Class hierarchy predicates.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Implements:

public class_hierarchy

Remarks:

(none)

Inherited public predicates:

ancestor/1 ancestors/1 class/1 classes/1 descendant/1 descendant_class/1 descendant_classes/1
descendant_instance/1 descendant_instances/1 descendants/1 instance/1 instances/1 leaf/1
leaf_class/1 leaf_classes/1 leaf_instance/1 leaf_instances/1 leaves/1 subclass/1 subclasses/1
superclass/1 superclasses/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.32.2 class_hierarchy

Class hierarchy protocol.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

static

Extends:

public hierarchy

Remarks:

(none)

Inherited public predicates:

ancestor/1 ancestors/1 descendant/1 descendants/1 leaf/1 leaves/1

- Public predicates
 - class/1
 - classes/1
 - instance/1
 - instances/1
 - subclass/1
 - subclasses/1
 - superclass/1
 - superclasses/1
 - leaf_instance/1

- leaf_instances/1
- leaf_class/1
- leaf_classes/1
- descendant_instance/1
- descendant_instances/1
- descendant_class/1
- descendant_classes/1
- Protected predicates
- Private predicates
- Operators

Public predicates

class/1

Returns, by backtracking, all object classes.

Compilation flags:

static

Template:

class(Class)

Mode and number of proofs:

class(?object) - zero_or_more

classes/1

List of all object classes.

Compilation flags:

static

Template:

classes(Classes)

Mode and number of proofs:

classes(-list) - one

`instance/1`

Returns, by backtracking, all class instances.

Compilation flags:

`static`

Template:

`instance(Instance)`

Mode and number of proofs:

`instance(?object) - zero_or_more`

`instances/1`

List of all class instances.

Compilation flags:

`static`

Template:

`instances(Instances)`

Mode and number of proofs:

`instances(-list) - one`

`subclass/1`

Returns, by backtracking, all class subclasses.

Compilation flags:

`static`

Template:

`subclass(Subclass)`

Mode and number of proofs:

`subclass(?object) - zero_or_more`

`subclasses/1`

List of all class subclasses.

Compilation flags:

`static`

Template:

`subclasses(Subclasses)`

Mode and number of proofs:

`subclasses(-list) - one`

`superclass/1`

Returns, by backtracking, all class superclasses.

Compilation flags:

`static`

Template:

`superclass(Superclass)`

Mode and number of proofs:

`superclass(?object) - zero_or_more`

`superclasses/1`

List of all class superclasses.

Compilation flags:

`static`

Template:

superclasses(Superclasses)

Mode and number of proofs:

superclasses(-list) - one

[leaf_instance/1](#)

Returns, by backtracking, all class leaf instances.

Compilation flags:

static

Template:

leaf_instance(Leaf)

Mode and number of proofs:

leaf_instance(?object) - zero_or_more

[leaf_instances/1](#)

List of all class leaf instances.

Compilation flags:

static

Template:

leaf_instances(Leaves)

Mode and number of proofs:

leaf_instances(-list) - one

`leaf_class/1`

Returns, by backtracking, all class leaf subclasses.

Compilation flags:

`static`

Template:

`leaf_class(Leaf)`

Mode and number of proofs:

`leaf_class(?object) - zero_or_more`

`leaf_classes/1`

List of all class leaf leaf subclasses.

Compilation flags:

`static`

Template:

`leaf_classes(Leaves)`

Mode and number of proofs:

`leaf_classes(-list) - one`

`descendant_instance/1`

Returns, by backtracking, all class descendant instances.

Compilation flags:

`static`

Template:

`descendant_instance(Descendant)`

Mode and number of proofs:

`descendant_instance(?object) - zero_or_more`

`descendant_instances/1`

List of all class descendant instances.

Compilation flags:

`static`

Template:

`descendant_instances(Descendants)`

Mode and number of proofs:

`descendant_instances(-list) - one`

`descendant_class/1`

Returns, by backtracking, all class descendant subclasses.

Compilation flags:

`static`

Template:

`descendant_class(Descendant)`

Mode and number of proofs:

`descendant_class(?object) - zero_or_more`

`descendant_classes/1`

List of all class descendant subclasses.

Compilation flags:

`static`

Template:

`descendant_classes(Descendants)`

Mode and number of proofs:

`descendant_classes(-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[class_hierarchy](#)

[protocol](#)

1.32.3 hierarchy

Common hierarchy protocol for prototype and class hierarchies.

Availability:

`logtalk_load(hierarchies(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [ancestor/1](#)

- ancestors/1
- leaf/1
- leaves/1
- descendant/1
- descendants/1
- Protected predicates
- Private predicates
- Operators

Public predicates

ancestor/1

Returns, by backtracking, all object ancestors.

Compilation flags:

static

Template:

ancestor(Ancestor)

Mode and number of proofs:

ancestor(?object) - zero_or_more

ancestors/1

List of all object ancestors.

Compilation flags:

static

Template:

ancestors(Ancestors)

Mode and number of proofs:

ancestors(-list) - one

leaf/1

Returns, by backtracking, all object leaves.

Compilation flags:

static

Template:

leaf(Leaf)

Mode and number of proofs:

leaf(?object) - zero_or_more

leaves/1

List of all object leaves.

Compilation flags:

static

Template:

leaves(Leaves)

Mode and number of proofs:

leaves(-list) - one

descendant/1

Returns, by backtracking, all object descendants.

Compilation flags:

static

Template:

descendant(Descendant)

Mode and number of proofs:

descendant(?object) - zero_or_more

descendants/1

List of all object descendants.

Compilation flags:

static

Template:

descendants(Descendants)

Mode and number of proofs:

descendants(-list) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.32.4 proto_hierarchy

Prototype hierarchy predicates.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Implements:

public proto_hierarchy

Remarks:

(none)

Inherited public predicates:

ancestor/1 ancestors/1 descendant/1 descendants/1 extension/1 extensions/1 leaf/1 leaves/1
parent/1 parents/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.32.5 proto_hierarchy

Prototype hierarchy protocol.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Extends:

public [hierarchyp](#)

Remarks:

(none)

Inherited public predicates:

[ancestor/1](#) [ancestors/1](#) [descendant/1](#) [descendants/1](#) [leaf/1](#) [leaves/1](#)

- Public predicates
 - [parent/1](#)
 - [parents/1](#)
 - [extension/1](#)
 - [extensions/1](#)
- Protected predicates
- Private predicates
- Operators

Public predicates

[parent/1](#)

Returns, by backtracking, all object parents.

Compilation flags:

static

Template:

[parent](#)(Parent)

Mode and number of proofs:

[parent](#)(?object) - zero_or_more

parents/1

List of all object parents.

Compilation flags:

static

Template:

parents(Parents)

Mode and number of proofs:

parents(-list) - one

extension/1

Returns, by backtracking, all object direct descendants.

Compilation flags:

static

Template:

extension(Extension)

Mode and number of proofs:

extension(?object) - zero_or_more

extensions/1

List of all object direct descendants.

Compilation flags:

static

Template:

extensions(Extensions)

Mode and number of proofs:

extensions(-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`proto_hierarchy`

1.33 hook_flows

object

1.33.1 hook_pipeline(Pipeline)

- Pipeline - List of hook objects.

Use a pipeline (represented using a list) of hook objects to expand terms and goals. The expansion results from a hook object are passed to the next hook object in the pipeline.

Availability:

`logtalk_load(hook_flows(loader))`

Author: Paulo Moura

Version: 1:0:3

Date: 2019-09-23

Compilation flags:

`static, context_switching_calls`

Implements:

public `expanding`

Remarks:

- Usage: Compile source files that should be expanded using the pipeline of hook objects using the compiler option `hook(hook_pipeline(Pipeline))`.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`hook_set(Set)`

object

1.33.2 `hook_set(Set)`

- Set - Set (list) of hook objects.

Use a set (represented using a list) of hook objects to expand terms and goals. The hook objects are tried in sequence until one of them succeeds in expanding the current term (goal) into a different term (goal).

Availability:

`logtalk_load(hook_flows(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Implements:

public `expanding`

Remarks:

- Usage: Compile source files that should be expanded using the set of hook objects using the compiler option `hook(hook_set(Set))`.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`hook_pipeline(Pipeline)`

1.34 hook_objects

object

1.34.1 backend_adapter_hook

This hook object applies the expansion rules defined in the Prolog backend adapter file.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

`static, context_switching_calls`

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.2 `default_workflow_hook`

Use this object as the default hook object to restore the default expansion pipeline semantics used by the compiler.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-24

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.3 `grammar_rules_hook`

This hook object expands grammar rules into clauses.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-14

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, prolog_module_hook(Module),
object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream),
print_goal_hook, suppress_goal_hook

object

1.34.4 identity_hook

Use this object as a file specific hook object to prevent any (other) user-defined expansion rules to be applied when compiling the file.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`,
`object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`,
`print_goal_hook`, `suppress_goal_hook`

object

1.34.5 `object_wrapper_hook`

Use this object to wrap the contents of a plain Prolog file in an object named after the file. The wrapper sets the `context_switching_calls` flag to allow, enabling calling of the wrapped predicates using the `<</2` control construct.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2020-10-30

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public expanding`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

```
object_wrapper_hook(Protocol),          object_wrapper_hook(Name,Relations),          back-  
end_adapter_hook, default_workflow_hook, grammar_rules_hook, prolog_module_hook(Module),  
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-  
press_goal_hook
```

object

1.34.6 object_wrapper_hook(Protocol)

Use this object to wrap the contents of a plain Prolog file in an object named after the file that implements the given protocol.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2021-11-24

Compilation flags:

```
static, context_switching_calls
```

Implements:

public expanding

Uses:

os

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

object_wrapper_hook, object_wrapper_hook(Name,Relations), backend_adapter_hook,
 default_workflow_hook, grammar_rules_hook, prolog_module_hook(Module),
 write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
 press_goal_hook
 object

1.34.7 object_wrapper_hook(Name,Relations)

Use this object to wrap the contents of a plain Prolog file in an object with the given name and object entity relations (a list).

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-02-03

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

```

object_wrapper_hook,          object_wrapper_hook(Protocol),          backend_adapter_hook,
default_workflow_hook,       grammar_rules_hook,          prolog_module_hook(Module),
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
press_goal_hook

```

object

1.34.8 print_goal_hook

Use this object to easily print entity predicate goals before, after, or before and after calling them.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-03-14

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

- Usage: Mark a goal to be printed by prefixing it with an operator. Printing uses a comment message.
- To print goal before calling it: - Goal.
- To print goal after calling it: + Goal.
- To print goal before and after calling it: * Goal.

- **Operators:** This hook object uses the standard - and + prefix operators and also defines a global * prefix operator with the same type and priority.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `identity_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `suppress_goal_hook`

object

1.34.9 `prolog_module_hook(Module)`

This hook object applies the expansion rules defined in a Prolog module (e.g. `user`).

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

static, context_switching_calls

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.10 `suppress_goal_hook`

Use this object to easily suppress a goal in a clause body.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-05-04

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

- Usage: Mark a goal to be suppressed by prefixing it with the `--` operator.
- Operators: This hook object uses the `--` prefix operator declared by Logtalk for use in `mode/2` directives.

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- `Public predicates`
 - `Protected predicates`
 - `Private predicates`
 - `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `identity_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`

object

1.34.11 `write_to_file_hook(File)`

This hook object writes term-expansion results to a file in canonical format. The terms are terminated by a period and a new line.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public write_to_file_hook(File,[quoted(true),ignore_ops(true)])`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`,
`prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_file_hook(File,Options)`,
`write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `sup-`
`press_goal_hook`
`object`

1.34.12 `write_to_file_hook(File,Options)`

This hook object writes term-expansion results to a file using a list of `write_term/3` options. The terms are terminated by a period and a new line.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

`static`, `context_switching_calls`

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook,
 prolog_module_hook(Module), object_wrapper_hook, write_to_file_hook(File),
 write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
 press_goal_hook

object

1.34.13 `write_to_stream_hook(Stream)`

This hook object writes term-expansion results to a stream in canonical format. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public write_to_stream_hook(Stream,[quoted(true),ignore_ops(true)])
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - Protected predicates
 - Private predicates
 - Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`
object

1.34.14 `write_to_stream_hook(Stream,Options)`

This hook object writes term-expansion results to a stream using a list of `write_term/3` options. The terms are terminated by a period and a new line.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`,
`prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream)`,
`write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`

1.35 html

category

1.35.1 html

HTML generation.

Availability:

`logtalk_load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 0:3:0

Date: 2021-03-30

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - generate/2
 - void_element/1
 - normal_element/2
- Protected predicates
- Private predicates
 - doctype/1
- Operators

Public predicates

generate/2

Generates HTML content using the representation specified in the first argument (stream(Stream) or file(Path)) for the term in the second argument.

Compilation flags:

static

Template:

generate(Sink,Term)

Mode and number of proofs:

generate(+compound,++term) - one_or_error

`void_element/1`

Enumerates, by backtracking, all void elements.

Compilation flags:

`static`

Template:

`void_element(Element)`

Mode and number of proofs:

`void_element(?atom) - zero_or_more`

`normal_element/2`

Enumerates, by backtracking, all normal elements. The value of the `Display` argument is either `inline` or `block`.

Compilation flags:

`static`

Template:

`normal_element(Element,Display)`

Mode and number of proofs:

`normal_element(?atom,?atom) - zero_or_more`

Protected predicates

(none)

Private predicates

`doctype/1`

Doctype text.

Compilation flags:

`static`

Template:

doctype(DocType)

Mode and number of proofs:

doctype(?atom) - one

Operators

(none)

object

1.35.2 `html5`

HTML content generation using the HTML 5 doctype.

Availability:

logtalk_load(html(loader))

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

static, context_switching_calls

Imports:

public `html`

Remarks:

(none)

Inherited public predicates:

`generate/2` `normal_element/2` `void_element/1`

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.35.3 xhtml11

XHTML content generation using the XHTML 1.1 doctype.

Availability:

`logtalk__load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

`static, context_switching_calls`

Imports:

`public html`

Remarks:

(none)

Inherited public predicates:

`generate/2 normal_element/2 void_element/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.36 ids

object

1.36.1 ids

Generator of random identifiers with 160 bits (20 bytes) of randomness.

Availability:

```
logtalk_load(ids(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-23

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public ids(atom,20)
```

Remarks:

(none)

Inherited public predicates:

`generate/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ids(Representation,Bytes)`, `uuid`, `ulid`

object

1.36.2 `ids(Representation,Bytes)`

- Representation - Text representation for the identifier. Possible values are `atom`, `chars`, and `codes`.
- Bytes - Number of bytes of randomness.

Generator of random identifiers.

Availability:

`logtalk_load(ids(loader))`

Author: Paulo Moura

Version: 1:0:0
Date: 2022-11-23

Compilation flags:
static, context_switching_calls

Uses:
base64
fast_random
list
os

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - generate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

generate/1

Generate a random identifier.

Compilation flags:
static

Template:
generate(Identifier)
Mode and number of proofs:
generate(--textids) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ids`, `uuid`, `ulid`

1.37 intervals

object

1.37.1 interval

Basic temporal interval relations. An interval is represented by a compound term, `i/2`, with two ground arguments, the start and end points.

Availability:

`logtalk_load(intervals(loader))`

Author: Paulo Moura

Version: 1:2:1

Date: 2022-01-15

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `intervalp`

Aliases:

`intervalp before/2` as `b/2`

`intervalp after/2` as `bi/2`

`intervalp meets/2` as `m/2`

`intervalp met_by/2` as `mi/2`

`intervalp overlaps/2` as `o/2`

`intervalp overlapped_by/2` as `oi/2`

`intervalp starts/2` as `s/2`

intervalp started_by/2 as si/2
 intervalp during/2 as d/2
 intervalp contains/2 as di/2
 intervalp finishes/2 as f/2
 intervalp finished_by/2 as fi/2
 intervalp equal/2 as eq/2

Remarks:

(none)

Inherited public predicates:

after/2 before/2 contains/2 during/2 equal/2 finished_by/2 finishes/2 meets/2 met_by/2
 new/3 overlapped_by/2 overlaps/2 started_by/2 starts/2 valid/1

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.37.2 intervalp

Basic temporal interval relations protocol (based on James F. Allen Interval Algebra work).

Availability:

`logtalk_load(intervals(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2014-04-26

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `new/3`
 - `valid/1`
 - `before/2`
 - `after/2`
 - `meets/2`
 - `met_by/2`
 - `overlaps/2`
 - `overlapped_by/2`
 - `starts/2`
 - `started_by/2`
 - `during/2`
 - `contains/2`
 - `finishes/2`

- finished_by/2
- equal/2
- Protected predicates
- Private predicates
- Operators

Public predicates

new/3

Constructs a new interval given start and end points. The start point must strictly precede the end point.

Compilation flags:

static

Template:

new(Start,End,Interval)

Mode and number of proofs:

new(@ground,@ground,-interval) - zero_or_one

valid/1

True if Interval is a valid interval.

Compilation flags:

static

Template:

valid(Interval)

Mode and number of proofs:

valid(@interval) - zero_or_one

before/2

True if Interval1 takes place before Interval2.

Compilation flags:

static

Template:

before(Interval1,Interval2)

Mode and number of proofs:

before(@interval,@interval) - zero_or_one

after/2

True if Interval1 takes place after Interval2.

Compilation flags:

static

Template:

after(Interval1,Interval2)

Mode and number of proofs:

after(@interval,@interval) - zero_or_one

meets/2

True if Interval1 meets Interval2.

Compilation flags:

static

Template:

meets(Interval1,Interval2)

Mode and number of proofs:

meets(@interval,@interval) - zero_or_one

met_by/2

True if Interval1 is met by Interval2.

Compilation flags:

static

Template:

met_by(Interval1,Interval2)

Mode and number of proofs:

met_by(@interval,@interval) - zero_or_one

overlaps/2

True if Interval1 overlaps with Interval2.

Compilation flags:

static

Template:

overlaps(Interval1,Interval2)

Mode and number of proofs:

overlaps(@interval,@interval) - zero_or_one

overlapped_by/2

True if Interval1 is overlapped by Interval2.

Compilation flags:

static

Template:

overlapped_by(Interval1,Interval2)

Mode and number of proofs:

overlapped_by(@interval,@interval) - zero_or_one

`starts/2`

True if Interval1 starts Interval2.

Compilation flags:

`static`

Template:

`starts(Interval1,Interval2)`

Mode and number of proofs:

`starts(@interval,@interval) - zero_or_one`

`started_by/2`

True if Interval1 is started by Interval2.

Compilation flags:

`static`

Template:

`started_by(Interval1,Interval2)`

Mode and number of proofs:

`started_by(@interval,@interval) - zero_or_one`

`during/2`

True if Interval1 occurs during Interval2.

Compilation flags:

`static`

Template:

`during(Interval1,Interval2)`

Mode and number of proofs:

`during(@interval,@interval) - zero_or_one`

`contains/2`

True if Interval1 contains Interval2.

Compilation flags:

`static`

Template:

`contains(Interval1,Interval2)`

Mode and number of proofs:

`contains(@interval,@interval) - zero_or_one`

`finishes/2`

True if Interval1 finishes Interval2.

Compilation flags:

`static`

Template:

`finishes(Interval1,Interval2)`

Mode and number of proofs:

`finishes(@interval,@interval) - zero_or_one`

`finished_by/2`

True if Interval1 is finished by Interval2.

Compilation flags:

`static`

Template:

`finished_by(Interval1,Interval2)`

Mode and number of proofs:

`finished_by(@interval,@interval) - zero_or_one`

`equal/2`

True if Interval1 is equal to Interval2.

Compilation flags:

`static`

Template:

`equal(Interval1,Interval2)`

Mode and number of proofs:

`equal(@interval,@interval) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`interval`

1.38 iso8601

object

1.38.1 iso8601

ISO 8601 (and European civil calendar) compliant library of date predicates.

Availability:

`logtalk_load(iso8601(loader))`

Author: Daniel L. Dudley

Version: 1:0:3

Date: 2019-10-09

Compilation flags:

static, context_switching_calls

Uses:

os

Remarks:

- Scope: This object currently provides a powerful, versatile and efficient set of date-handling predicates, which—thanks to Logtalk—may be used as is on a wide range of Prolog compilers. Besides taking time to familiarize oneself with each predicate, the user should take note of the following information.
- Validation of dates: Date parts are not validated—that is the caller’s responsibility! However, not being quite heartless yet, we do provide a predicate for this purpose.
- Date arithmetic: Many of the examples illustrate a simplified method of doing date arithmetic. Note, however, that we do not generally recommend this practice—it is all too easy to make mistakes. The safest way of finding the day difference between two dates is to first convert the dates to their Julian day numbers and then subtract one from the other. Similarly, the safe way to add or subtract a day offset to a particular date is to first convert the date to its Julian day number, add or subtract the day offset, and then convert the result to its corresponding date.
- BC years: ISO 8601 specifies that the Gregorian calendar be used, yet requires that years prior to 1 AD be handled arithmetically, i.e., the year we know as 1 BC is year 0, 2 BC is year -1, 3 BC is year -2 and so on. We do not follow ISO 8601 with regard to the handling of BC years. Our date predicates will accept and interpret an input year 0 as 1 BC; however, a negative year, Year, should always be interpreted as $\text{abs}(\text{Year}) =: \text{Year BC}$. We believe that the average person will find our handling of BC years more user-friendly than the ISO 8601 one, but we encourage feedback from users with a view to a possible change in future versions.
- Week numbers: It is possible for a day (date) to have a week number that belongs to another year. Up to three of the first days of a calendar year may belong to the last week (number) of the prior calendar year, and up to three days of the last days of a calendar year may belong to the first week (number) of the next calendar year. It for this reason that the Week parameter in date/6-7 is a compound term, namely week(WeekNo,ActualYear).
- Computation of Gregorian Easter Sunday: The algorithm is based upon the “Gaussian rule”. Proleptic use is limited to years > 1582 AD, that is, after the introduction of the Gregorian calendar.
- Some Christian feast day offsets from Easter Sunday: Carnival Monday: -48 days, Mardi Gras (Shrove Tuesday): -47 days, Ash Wednesday: -46 days, Palm Sunday: -7 days, Easter Friday: -2 days, Easter Saturday: -1 day, Easter Monday: +1 day, Ascension of Christ: +39 days, Whitsunday: +49 days, Whitmonday: +50 days, Feast of Corpus Christi: +60 days.

Inherited public predicates:

(none)

- Public predicates
 - date/4
 - date/5
 - date/6
 - date/7
 - date_string/3
 - valid_date/3
 - leap_year/1
 - calendar_month/3
 - easter_day/3
- Protected predicates
- Private predicates
- Operators

Public predicates

date/4

Get the system date and/or its Julian Day # or convert a Julian Day # to/from given date parts.

Compilation flags:

static

Template:

date(JD,Year,Month,Day)

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

Mode and number of proofs:

date(?integer,?integer,?integer,?integer) - zero_or_one

Examples:

Current date (i.e., today)

date(JD,Year,Month,Day)

JD=2453471,Year=2005,Month=4,Day=10

Convert a date to its Julian day number

date(JD,2000,2,29)

JD=2451604

Convert a Julian day number to its date


```

date(2451604,Year,Month,Day)
Year=2000,Month=2,Day=29
What is the date of day # 60 in year 2000?
date(JD,2000,1,60)
JD=2451604
What is the Julian of the 1st day prior to 2000-1-1?
date(JD,2000,1,0)
JD=2451544
What is the Julian of the 60th day prior to 2000-1-1?
date(JD,2000,1,-59)
JD=2451485
Illegal date is auto-adjusted (see also next query)
date(JD,1900,2,29)
JD=2415080
This is the correct date!
date(2415080,Year,Month,Day)
Year=1900,Month=3,Day=1

```

date/5

Ditto date/4 + get/check its day-of-week #.

Compilation flags:

static

Template:

```

date(JD,Year,Month,Day,DoW)
JD - Julian day serial number.
Year - 0 or negative if converted BC year, positive otherwise.
Month - Normally an integer between 1 and 12 inclusive.
Day - Normally an integer between 1 and 31 inclusive depending upon month.
DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.

```

Mode and number of proofs:

```

date(?integer,?integer,?integer,?integer,?integer) - zero_or_one

```

Examples:

```

Get the Julian and the day-of-week # of a date
date(JD,2000,2,29,DoW)
JD=2451604,DoW=2
Check the validity of a given date (day-of-week is 2, not 4)
date(_,2002,3,5,4)
no

```

Get the Julian day of a given date if it is a Sunday

```
date(JD,2004,2,29,7)
```

```
JD=2453065
```

Get the date and day-of-week # of a Julian

```
date(2451545,Year,Month,Day,DoW)
```

```
Year=2000,Month=1,Day=1,DoW=6
```

date/6

Ditto date/5 + get/check its week #.

Compilation flags:

```
static
```

Template:

```
date(JD,Year,Month,Day,DoW,Week)
```

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.

Week - Compound term, week(WeekNo,ActualYear), of a day.

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer,?compound) - zero_or_one
```

Examples:

Get the day-of-week and week number of a date

```
date(_,2000,1,1,DoW,Week)
```

```
DoW=6,Week=week(52,1999)
```

Get the week number and year of this week

```
date(_,_,_,_,_,Week)
```

```
Week=week(7,2004)
```

Get the Julian number and the week of a date if it is a Sunday

```
date(JD,2004,2,29,7,Week)
```

```
JD=2453065,Week=week(9,2004)
```

Get the day-of-week and week of a Julian day number

```
date(2453066,_,_,_,DoW,Week)
```

```
DoW=1,Week=week(10,2004)
```

Check that given date data matches

```
date(_,2004,3,1,1,week(10,2004))
```

```
yes
```

What is the date of a day of week (default is 1) in given week # and year?

```

date(__,Year,Month,Day,DoW,week(26,2004))
Year=2004,Month=6,Day=21,DoW=1
Ditto for Sunday
date(__,Year,Month,Day,7,week(1,2005))
Year=2005,Month=1,Day=9
Ditto for Tuesday in following week
date(__,Year,Month,Day,9,week(1,2005))
Year=2005,Month=1,Day=11
Ditto for Thursday in the prior week
date(__,Year,Month,Day,4,week(0,2005))
Year=2004,Month=12,Day=30
Ditto for Tuesday two weeks prior
date(__,Year,Month,Day,2,week(-1,2005))
Year=2004,Month=12,Day=21
Ditto for Saturday
date(__,Year,Month,Day,6,week(53,2004))
Year=2005,Month=1,Day=1
Ditto for Monday (note automatic compensation of nonexistent week number)
date(__,Year,Month,Day,1,week(60,2004))
Year=2005,Month=2,Day=14

```

date/7

Ditto date/6 + get/check its day-of-year #.

Compilation flags:

static

Template:

```

date(JD,Year,Month,Day,DoW,Week,DoY)
JD - Julian day serial number.
Year - 0 or negative if converted BC year, positive otherwise.
Month - Normally an integer between 1 and 12 inclusive.
Day - Normally an integer between 1 and 31 inclusive depending upon month.
DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.
Week - Compound term, week(WeekNo,ActualYear), of a day.
DoY - Day of year (NB! calendar year, not week # year).

```

Mode and number of proofs:

```

date(?integer,?integer,?integer,?integer,?integer,?compound,?integer) - zero_or_one

```

Examples:

Get the date and day-of-year of a Julian number

```
date(2451649,Year,Month,Day,_,_,DoY)
Year=2000,Month=4,Day=14,DoY=105
Get the Julian number, week number and day-of-year of a date, confirming that it is a Sunday
date(JD,2004,2,29,7,Week,DoY)
JD=2453065,Week=week(9,2004),DoY=60
Confirm that a date is, in fact, a specific day-of-year
date(_,2004,3,1,_,_,61)
yes
Get the Julian number, week day and day-of-year of a date
date(JD,2004,10,18,DoW,_,DoY)
JD=2453297,DoW=1,DoY=292
Get today's day-of-year
date(_,_,_,_,_,_,DoY)
DoY=54
Get all missing date data (excl. Julian number) for the 60th calendar day of 2004
date(_,2004,Month,Day,DoW,Week,60)
Month=2,Day=29,DoW=7,Week=week(9,2004)
Match given date data and, if true, return the missing data (excl. Julian number)
date(_,2004,3,Day,DoW,Week,61)
Day=1,DoW=1,Week=week(10,2004)
Ditto (the 61st day-of-year cannot be both day 1 and 2 of the month)
date(_,2004,_,2,_,_,61)
no
```

date_string/3

Conversion between an ISO 8601 compliant date string and its components (truncated and expanded date representations are currently unsupported). Note that date components are not validated; that is the caller's responsibility!

Compilation flags:

static

Template:

date_string(Format,Components,String)

Format - ISO 8601 format.

Components - When bound and String is free, either a Julian number or a [Year,Month,Day] term; it binds to the system day/date if free When free and String is bound, it binds to an integer list representing the numeric elements of String.

String - ISO 8601 formatted string correspondent to Components.

Mode and number of proofs:

date_string(+atom,+integer,?atom) - zero_or_one

date_string(+atom,?list,?atom) - zero_or_one

Examples:

```

Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',[2004,2,29],String)
  String='20040229'
Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',Components,'20040229')
  Components=[2004,2,29]
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',[2003,12,16],String)
  String='2003-12-16'
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',Components,'2003-12-16')
  Components=[2003,12,16]
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',_,String)
  String='2004-02-17'
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',Components,'2004-02-17')
  Components=[2004,2,17]
Date, reduced, month (section 5.2.1.2 a)
  date_string('YYYY-MM',[2004,9,18],String)
  String='2004-09'
Date, reduced, month (section 5.2.1.2 a)
  date_string('YYYY-MM',Components,'2004-09')
  Components=[2004,9]
Date, reduced, year (section 5.2.1.2 b)
  date_string('YYYY',[1900,7,24],String)
  String='1900'
Date, reduced, year (section 5.2.1.2 b)
  date_string('YYYY',Components,'1900')
  Components=[1900]
Date, reduced, century (section 5.2.1.2 c)
  date_string('YY',2456557,String)
  String='20'
Date, reduced, century (section 5.2.1.2 c)
  date_string('YY',Components,'20')
  Components=[20]
Date, ordinal, complete (section 5.2.2.1)
  date_string('YYYYDDD',[2005,3,25],String)
  String='2005084'
Date, ordinal, complete (section 5.2.2.1)
  date_string('YYYYDDD',Components,'2005084')
  Components=[2005,84]
Date, ordinal, extended (section 5.2.2.1)
  date_string('YYYY-DDD',[1854,12,4],String)
  String='1854-338'
Date, ordinal, extended (section 5.2.2.1)

```

```
date_string('YYYY-DDD',Components,'1854-338')
Components=[1854,338]
Week, complete, basic (section 5.2.3.1)
date_string('YYYYWwwD',[2000,1,2],String)
String='1999W527'
Week, complete, basic (section 5.2.3.1)
date_string('YYYYWwwD',Components,'1999W527')
Components=[1999,52,7]
Week, complete, extended (section 5.2.3.1)
date_string('YYYY-Www-D',[2003,12,29],String)
String='2004-W01-1'
Week, complete, extended (section 5.2.3.1)
date_string('YYYY-Www-D',Components,'2004-W01-1')
Components=[2004,1,1]
Week, complete, extended (section 5.2.3.1)
date_string('YYYY-Www-D',2453167,String)
String='2004-W24-4'
Week, complete, extended (section 5.2.3.1)
date_string('YYYY-Www-D',Components,'2004-W24-4')
Components=[2004,24,4]
Week, reduced, basic (section 5.2.3.2)
date_string('YYYYWww',[2004,2,29],String)
String='2004W09'
Week, reduced, basic (section 5.2.3.2)
date_string('YYYYWww',Components,'2004W09')
Components=[2004,9]
Week, reduced, extended (section 5.2.3.2)
date_string('YYYY-Www',[2004,2,29],String)
String='2004-W09'
Week, reduced, extended (section 5.2.3.2)
date_string('YYYY-Www',Components,'2004-W09')
Components=[2004,9]
```

`valid_date/3`

Validate a given date in the Gregorian calendar.

Compilation flags:

static

Template:

`valid_date(Year,Month,Day)`

Mode and number of proofs:

`valid_date(+integer,+integer,+integer) - zero_or_one`

Examples:

Yes, the recent millennium was a leap year

`valid_date(2000,2,29)`

yes

2004 was also a leap year

`valid_date(2004,2,29)`

yes

Only 30 days in April

`valid_date(2004,4,31)`

no

1 BC was a leap year

`valid_date(-1,2,29)`

yes

`leap_year/1`

Succeed if given year is a leap year in the Gregorian calendar.

Compilation flags:

static

Template:

`leap_year(Year)`

Year - The Gregorian calendar year to investigate. If free, it binds to the system year.

Mode and number of proofs:

`leap_year(?integer) - zero_or_one`

Examples:

No, the prior centenary was not a leap year

`leap_year(1900)`

no

The recent millennium

`leap_year(2000)`

yes

This year

`leap_year(Year)`

Year=2004

This year (equivalent to prior query)

`leap_year(_)`

```
yes
Next centennial
  leap_year(2100)
no
Year 0, equivalent to 1 BC
  leap_year(0)
yes
1 BC
  leap_year(-1)
yes
4 BC
  leap_year(-4)
no
5 BC
  leap_year(-5)
yes
```

`calendar_month/3`

Compute a calendar month.

Compilation flags:

static

Template:

`calendar_month(Year,Month,Calendar)`

Year - The calendar year.

Month - The calendar month.

Calendar - A compound term, `m/3`, composed of three main arguments specifying year, month, and a list of week and week day numbers (calendar body).

Mode and number of proofs:

`calendar_month(?integer,?integer,-compound) - zero_or_one`

Examples:

Compute the calendar of March, 2005

`calendar_month(2005,3,Calendar)`

`Calendar=m(2005,3,[w(9,[0,1,2,3,4,5,6]),w(10,[7,8,9,10,11,12,13]),w(11,[14,15,16,17,18,19,20]),w(12,[21,22,23,24,25,26,27]),w(13,[28,29,30,31,0,0,0]),w(0,[0,0,0,0,0,0,0])])`

easter_day/3

Compute a Gregorian Easter Sunday.

Compilation flags:

static

Template:

easter_day(Year,Month,Day)

Year - Integer specifying the year to be investigated.

Month - Month in which Easter Sunday falls for given year.

Day - Day of month in which Easter Sunday falls for given year.

Mode and number of proofs:

easter_day(?integer,-integer,-integer) - zero_or_one

Examples:

Compute Easter Sunday for a particular year

easter_day(2006,Month,Day)

Month=4,Day=16

Compute Easter Sunday for the current year

easter_day(Year,Month,Day)

Year=2005,Month=3,Day=27

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.39 issue_creator

object

1.39.1 issue_creator

Support for automatically creating bug report issues for failed tests in GitHub or GitLab servers.

Availability:

```
logtalk_load(issue_creator(loader))
```

Author: Paulo Moura

Version: 0:12:0

Date: 2022-01-20

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
git
```

```
os
```

```
term_io
```

```
user
```

Remarks:

- Usage: This tool is automatically loaded and used from the `logtalk_tester` automation script when using its `-b` option. See the script man page for details.

Inherited public predicates:

```
(none)
```

- [Public predicates](#)
 - [Protected predicates](#)
 - [Private predicates](#)
 - [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.40 java

object

1.40.1 java

Abstract interface to JPL API utility predicates.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:8:0

Date: 2023-03-15

Compilation flags:

`static, context_switching_calls`

Implements:

`public java_utils_protocol`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

array_list/2 array_to_list/2 array_to_terms/2 array_to_terms/3 decode_exception/2
decode_exception/3 false/1 is_false/1 is_null/1 is_object/1 is_true/1 is_void/1
iterator_element/2 list_to_array/2 map_element/2 null/1 set_element/2 terms_to_array/2
true/1 value_reference/2 void/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

java(Reference,ReturnValue), java(Reference), java_hook
object

1.40.2 java(Reference)

- Reference - Either a class name or a Java reference to an object.

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message sending syntax and a forward/1 handler to resolve methods.

Availability:

logtalk_load(java(loader))

Author: Paulo Moura and Sergio Castro

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public java(Reference,_)

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

java(Reference,ReturnValue), java, java_hook

object

1.40.3 java(Reference,ReturnValue)

- Reference - Either a class name or a Java reference to an object.
- ReturnValue - Value returned by a method call (possibly the Java value void).

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message sending syntax and a forward/1 handler to resolve methods.

Availability:

```
logtalk_load(java(loader))
```

Author: Paulo Moura and Sergio Castro

Version: 1:4:0

Date: 2023-03-13

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public forwarding
public java__access__protocol
```

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

```
forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[java\(Reference\)](#), [java](#), [java_hook](#)
[protocol](#)

1.40.4 [java_access_protocol](#)

Protocol for a minimal abstraction for calling Java from Logtalk using familiar message sending syntax.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura and Sergio Castro

Version: 1:2:1

Date: 2023-03-16

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `get_field/2`
 - `set_field/2`
 - `new/2`
 - `new/1`
 - `invoke/1`
 - `invoke/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`get_field/2`

Gets the value of a class or object field.

Compilation flags:

`static`

Template:

`get_field(Field,Value)`

Mode and number of proofs:

`get_field(+atom,?nonvar) - zero_or_one`

`set_field/2`

Sets the value of a class or object field.

Compilation flags:

`static`

Template:

`set_field(Field,Value)`

Mode and number of proofs:

`set_field(+atom,+nonvar) - one`

`new/2`

Creates a new instance using the specified parameter values.

Compilation flags:

`static`

Template:

`new(Parameters,Instance)`

Mode and number of proofs:

`new(+list(nonvar),-reference) - one`

`new/1`

Creates a new instance using default parameter values.

Compilation flags:

`static`

Template:

`new(Instance)`

Mode and number of proofs:

`new(-reference) - one`

`invoke/1`

Invokes a method. This is a more efficient compared with relying on the `forward/1` handler to resolve methods.

Compilation flags:

`static`

Template:

`invoke(Method)`

Mode and number of proofs:

`invoke(@nonvar)` - one

`invoke/2`

Invokes a method. This is a more efficient compared with relying on the `forward/1` handler to resolve methods.

Compilation flags:

`static`

Template:

`invoke(Functor,Arguments)`

Mode and number of proofs:

`invoke(@nonvar,@list)` - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.40.5 `java_hook`

Hook object to optimize messages to the `java/1-2` objects that otherwise would trigger the `forward/1` handler.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:0:1
Date: 2019-06-13

Compilation flags:
static, context_switching_calls

Implements:
public [expanding](#)

Remarks:

- Usage: Compile source files with messages to the java/1-2 objects using the compiler option `hook(java_hook)`.

Inherited public predicates:
[goal_expansion/2](#) [term_expansion/2](#)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`java(Reference,ReturnValue)`, `java(Reference)`

`protocol`

1.40.6 `java_utils_protocol`

Abstract interface to Java utility predicates.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:6:0

Date: 2023-03-13

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `value__reference/2`
 - `true/1`
 - `false/1`
 - `void/1`
 - `null/1`
 - `is_true/1`
 - `is_false/1`

- is_void/1
- is_null/1
- is_object/1
- terms_to_array/2
- array_to_terms/3
- array_to_terms/2
- array_to_list/2
- list_to_array/2
- array_list/2
- iterator_element/2
- map_element/2
- set_element/2
- decode_exception/2
- decode_exception/3
- Protected predicates
- Private predicates
- Operators

Public predicates

value_reference/2

Returns an opaque term that represents the Java value with the given name.

Compilation flags:

static

Template:

value_reference(Value,Reference)

Mode and number of proofs:

value_reference(?atom,--ground) - one_or_more

true/1

Returns an opaque term that represents the Java value true.

Compilation flags:

static

Template:

true(Reference)

Mode and number of proofs:

true(--ground) - one

false/1

Returns an opaque term that represents the Java value false.

Compilation flags:

static

Template:

false(Reference)

Mode and number of proofs:

false(--ground) - one

void/1

Returns an opaque term that represents the Java value void.

Compilation flags:

static

Template:

void(Reference)

Mode and number of proofs:

void(--ground) - one

`null/1`

Returns an opaque term that represents the Java value `null`.

Compilation flags:

`static`

Template:

`null(Reference)`

Mode and number of proofs:

`null(--ground) - one`

`is_true/1`

True when the argument is the Java value `true`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_true(Reference)`

Mode and number of proofs:

`is_true(@term) - zero_or_one`

`is_false/1`

True when the argument is the Java value `false`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_false(Reference)`

Mode and number of proofs:

`is_false(@term) - zero_or_one`

`is_void/1`

True when the argument is the Java value `void`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_void(Reference)`

Mode and number of proofs:

`is_void(@term) - zero_or_one`

`is_null/1`

True when the argument is the Java value `null`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_null(Reference)`

Mode and number of proofs:

`is_null(@term) - zero_or_one`

`is_object/1`

True when the argument is a reference to a Java object. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_object(Reference)`

Mode and number of proofs:

`is_object(@term) - zero_or_one`

terms_to_array/2

Converts a list of ground Prolog terms to an array (a Java reference).

Compilation flags:

static

Template:

terms_to_array(Terms,Array)

Mode and number of proofs:

terms_to_array(++list(ground),-array) - one

array_to_terms/3

Converts an array (a Java reference) to a list of ground Prolog terms returning also its length. The array elements must be atoms, integers, floats, or compound terms. Fails otherwise.

Compilation flags:

static

Template:

array_to_terms(Array,Terms,Length)

Mode and number of proofs:

array_to_terms(+array,-list(ground),-integer) - one

array_to_terms/2

Converts an array (a Java reference) to a list of ground Prolog terms. The array elements must be atoms, integers, floats, or ground compound terms. Fails otherwise.

Compilation flags:

static

Template:

array_to_terms(Array,Terms)

Mode and number of proofs:

array_to_terms(+array,-list(term)) - one

`array_to_list/2`

Converts an array (a Java reference) to a list of Java references or their values.

Compilation flags:

`static`

Template:

`array_to_list(Array,List)`

Mode and number of proofs:

`array_to_list(+array,-list) - one`

`list_to_array/2`

Converts a list of Java references or values to an array (a Java reference).

Compilation flags:

`static`

Template:

`list_to_array(List,Array)`

Mode and number of proofs:

`list_to_array(+list,-array) - one`

`array_list/2`

Converts between an array (a Java reference) and a list of Java references or their values. Deprecated. Use the `array_to_list/2` and `list_to_array/2` predicates instead.

Compilation flags:

`static`

Template:

`array_list(Array,List)`

Mode and number of proofs:

array_list(+array,-list) - one

array_list(-array,+list) - one

iterator_element/2

Enumerates, by backtracking, all iterator elements.

Compilation flags:

static

Template:

iterator_element(Iterator,Element)

Mode and number of proofs:

iterator_element(+iterator,-element) - zero_or_more

map_element/2

Enumerates, by backtracking, all map elements.

Compilation flags:

static

Template:

map_element(Map,Element)

Mode and number of proofs:

map_element(+iterator,-element) - zero_or_more

`set_element/2`

Enumerates, by backtracking, all set elements.

Compilation flags:

`static`

Template:

`set_element(Set,Element)`

Mode and number of proofs:

`set_element(+iterator,-element) - zero_or_more`

`decode_exception/2`

Decodes an exception into its corresponding cause. Fails if the exception is not a Java exception.

Compilation flags:

`static`

Template:

`decode_exception(Exception,Cause)`

Mode and number of proofs:

`decode_exception(+callable,-atom) - zero_or_one`

`decode_exception/3`

Decodes an exception into its corresponding cause and a stack trace. Fails if the exception is not a Java exception.

Compilation flags:

`static`

Template:

`decode_exception(Exception,Cause,StackTrace)`

Mode and number of proofs:

`decode_exception(+callable,-atom,-list(atom)) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.41 json

object

1.41.1 json

JSON parser and generator. Uses curly terms for parsed JSON objects, dashes for parsed JSON pairs, and atoms for parsed JSON strings.

Availability:

`logtalk_load(json(loader))`

Author: Paulo Moura and Jacinto Dávila

Version: 1:1:0

Date: 2022-11-14

Compilation flags:

`static, context_switching_calls`

Extends:

`public json(curly,dash,atom)`

Remarks:

(none)

Inherited public predicates:

`generate/2 parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.2 json(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator. Uses curly terms for parsed JSON objects and dashes for parsed JSON pairs.

Availability:

```
logtalk_load(json(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-14

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json(curly,dash,StringRepresentation)
```

Remarks:

(none)

Inherited public predicates:

`generate/2` `parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.3 `json(ObjectRepresentation,PairRepresentation,StringRepresentation)`

- `ObjectRepresentation` - Object representation to be used when decoding JSON objects. Possible values are curly (default) and list.
- `PairRepresentation` - Pair representation to be used when decoding JSON objects. Possible values are dash (default), equal, and colon.
- `StringRepresentation` - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator.

Availability:

`logtalk_load(json(loader))`

Author: Paulo Moura and Jacinto Dávila

Version: 0:12:2

Date: 2024-01-14

Compilation flags:

static, context_switching_calls

Implements:

public json_protocol

Uses:

reader

Remarks:

(none)

Inherited public predicates:

generate/2 parse/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.41.4 json_protocol

JSON parser and generator protocol.

Availability:

logtalk_load(json(loader))

Author: Paulo Moura and Jacinto Dávila

Version: 0:11:0

Date: 2022-11-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse/2`

Parses the JSON contents read from the given source (`codes(List)`, `stream(Stream)`, `line(Stream)`, `file(Path)`, `chars(List)`, or `atom(Atom)`) into a term. Fails if the JSON contents cannot be parsed.

Compilation flags:

`static`

Template:

`parse(Source,Term)`

Mode and number of proofs:

`parse(++compound,--term) - one_or_error`

`generate/2`

Generates the content using the representation specified in the first argument (`codes(List)`, `stream(Stream)`, `file(Path)`, `chars(List)`, or `atom(Atom)`) for the term in the second argument. Fails if this term cannot be processed.

Compilation flags:

`static`

Template:

`generate(Sink,Term)`

Mode and number of proofs:

`generate(+compound,++term) - one_or_error`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.42 lgtdoc

object

1.42.1 lgtdoc

Documenting tool. Generates XML documenting files for loaded entities and for library, directory, entity, and predicate indexes.

Availability:

```
logtalk_load(lgtdoc(loader))
```

Author: Paulo Moura

Version: 11:0:1

Date: 2024-05-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public lgtdocp
```

Imports:

```
public options
```

Uses:

```
date  
list  
logtalk  
os  
type  
user  
varlist
```

Remarks:

(none)

Inherited public predicates:

all/0 all/1 check_option/1 check_options/1 default_option/1 default_options/1 directories/1
directories/2 directory/1 directory/2 file/1 file/2 files/1 files/2 fix_option/2 fix_options/2
libraries/1 libraries/2 library/1 library/2 merge_options/2 option/2 option/3 rdirectories/1
rdirectories/2 rdirectory/1 rdirectory/2 rlibraries/1 rlibraries/2 rlibrary/1 rlibrary/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - library_entity_/4
 - directory_entity_/4
 - type_entity_/4
 - predicate_entity_/4
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

library_entity_/4

Table of documented entities per library.

Compilation flags:

dynamic

Template:

library_entity_(Library,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

library_entity_(?atom,?nonvar,?nonvar,?atom) - zero_or_more

directory_entity_/4

Table of documented entities per directory.

Compilation flags:

dynamic

Template:

directory_entity__(Directory,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

directory_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more

type_entity_/4

Table of documented entities per type.

Compilation flags:

dynamic

Template:

type_entity__(Type,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

type_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more

predicate_entity_/4

Table of public predicates for all documented entities.

Compilation flags:

dynamic

Template:

predicate_entity__(Predicate,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

predicate_entity__(?predicate_indicator,?nonvar,?nonvar,?entity_identifier) - zero_or_more

Operators

(none)

category

1.42.2 lgtdoc_messages

Logtalk documentation tool default message translations.

Availability:

`logtalk_load(lgtdoc(loader))`

Author: Paulo Moura

Version: 4:0:0

Date: 2024-05-07

Compilation flags:

`static`

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.42.3 lgtdocp

Documenting tool protocol.

Availability:

logtalk__load(lgtdoc(loader))

Author: Paulo Moura

Version: 6:0:0

Date: 2024-03-08

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Compiling files for generating XML documentation: All source files must be compiled with the `source_data` flag turned on.
- `xml_spec(Specification)` option: XML documenting files specification format. Possible option values are `dtd` (DTD specification; default) and `xsd` (XML Schema specification).
- `xml_spec_reference(Reference)` option: Reference to the XML specification file in XML documenting files. Possible values are `local` (default; DTD/XSD file in same folder as XML files), `web` (logtalk.org website DTD/XSD file), and `standalone` (no reference to specification files).

- `entity_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_entity_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `index_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_index_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `xml_docs_directory(Directory)` option: Directory where the XML documenting files will be generated. The default value is `./xml_docs`, a sub-directory of the source files directory.
- `bom(Boolean)` option: Defines if a BOM should be added to the generated XML documenting files.
- `encoding(Encoding)` option: Encoding to be used for the generated XML documenting files.
- `omit_path_prefixes(Prefixes)` option: List of path prefixes (atoms) to omit when writing directory paths. The default value is to omit the home directory.
- `exclude_files(List)` option: List of files to exclude when generating the XML documenting files.
- `exclude_paths(List)` option: List of relative library paths to exclude when generating the XML documenting files (default is []). All sub-directories of the excluded directories are also excluded.
- `exclude_prefixes(List)` option: List of path prefixes to exclude when generating the XML documenting files (default is []).
- `exclude_entities(List)` option: List of entities to exclude when generating the XML documenting files (default is []).
- `sort_predicates(Boolean)` option: Sort entity predicates (default is false).
- Known issues: Some options may depend on the used XSL processor. Most XSL processors support DTDs but only some of them support XML Schemas. Some processors (e.g. fop2) reject reference to a DTD.

Inherited public predicates:

(none)

- Public predicates
 - `rlibraries/2`
 - `rlibraries/1`
 - `rlibrary/2`
 - `rlibrary/1`
 - `libraries/2`
 - `libraries/1`
 - `library/2`
 - `library/1`
 - `rdirectories/2`
 - `rdirectories/1`
 - `rdirectory/2`

- rdirectory/1
- directories/2
- directories/1
- directory/2
- directory/1
- files/2
- files/1
- file/2
- file/1
- all/1
- all/0
- Protected predicates
- Private predicates
- Operators

Public predicates

rlibraries/2

Creates XML documenting files for all entities in all given libraries and their sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibraries(Libraries,Options)

Mode and number of proofs:

rlibraries(+list(atom),+list) - one

`rlibraries/1`

Creates XML documenting files for all entities in all given libraries and their sub-libraries using default options.

Compilation flags:

`static`

Template:

`rlibraries(Libraries)`

Mode and number of proofs:

`rlibraries(+list(atom)) - one`

`rlibrary/2`

Creates XML documenting files for all entities in a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

`rlibrary(Library,Options)`

Mode and number of proofs:

`rlibrary(+atom,+list) - one`

Examples:

Generate XML documenting files for all tool entities for later conversion to Markdown files

`rlibrary(tools,[xslfile('lgtmd.xml')])`

`yes`

`rlibrary/1`

Creates XML documenting files for all entities in a library and its sub-libraries using default options.

Compilation flags:

`static`

Template:

`rlibrary(Library)`

Mode and number of proofs:

`rlibrary(+atom) - one`

Examples:

Generate XML documenting files for all tool entities for direct viewing in a browser (after indexing using the `lgt2xml` script)

`rlibrary(tools)`

`yes`

`libraries/2`

Creates XML documenting files for all entities in all given libraries using the specified options.

Compilation flags:

`static`

Template:

`libraries(Libraries,Options)`

Mode and number of proofs:

`libraries(+list(atom),+list) - one`

libraries/1

Creates XML documenting files for all entities in all given libraries using default options.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

library/2

Creates XML documenting files for all entities in a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list) - one

Examples:

Generate XML documenting files for all library entities for later conversion to PDF A4 files

```
library(library,[xslfile('logtalk_entity_to_pdf_a4.xml')])
yes
```

library/1

Creates XML documenting files for all entities in a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rdirectories/2

Creates XML documenting files for all entities in all given directories and their sub-directories using the specified options.

Compilation flags:

static

Template:

rdirectories(Directories,Options)

Mode and number of proofs:

rdirectories(+list(atom),+list) - one

rdirectories/1

Creates XML documenting files for all entities in all given directories and their sub-directories using default options.

Compilation flags:

static

Template:

rdirectories(Directories)

Mode and number of proofs:

rdirectories(+list(atom)) - one

`rdirectory/2`

Creates XML documenting files for all entities in a directory and its sub-directories using the specified options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list) - one`

Examples:

Generate XML documenting files for all entities in the tools directory for later conversion to Markdown files

```
rdirectory('./tools',[xslfile('lgtmd.xml')])
yes
```

`rdirectory/1`

Creates XML documenting files for all entities in a directory and its sub-directories using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

Examples:

Generate XML documenting files for all entities in the tools directory for direct viewing in a browser (after indexing using the `lgt2xml` script)

```
rdirectory('./tools')
yes
```

directories/2

Creates XML documenting files for all entities in all given directories using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list) - one

directories/1

Creates XML documenting files for all entities in all given directories using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

directory/2

Creates XML documenting files for all entities in a directory using the specified options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list) - one

Examples:

Generate XML documenting files for all the entities in the current directory for later conversion to PDF A4 files

```
directory('.',[xslfile('logtalk_entity_to_pdf_a4.xsl')])
yes
```

[directory/1](#)

Creates XML documenting files for all entities in a directory using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

[files/2](#)

Creates XML documenting files for all entities in loaded source files using the specified options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list) - one

files/1

Creates XML documenting files for all entities in loaded source files using default options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

file/2

Creates XML documenting files for all entities in a loaded source file using the specified options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list) - one

file/1

Creates XML documenting files for all entities in a loaded source file using default options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

all/1

Creates XML documenting files for all loaded entities using the specified options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list) - one

all/0

Creates XML documenting files for all loaded entities using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`lgtdoc`

1.43 lgtunit

object

1.43.1 automation_report

Intercepts unit test execution messages and generates a *.totals files for parsing by the `logtalk_tester.sh` automation shell script.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 5:0:0

Date: 2024-02-20

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`user`

Remarks:

- Usage: Automatically loaded by the `logtalk_tester.sh` shell script.

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.2 `coverage_report`

Intercepts unit test execution messages and generates a `coverage_report.xml` file with a test suite code coverage results.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 3:2:0

Date: 2023-04-11

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`logtalk`

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(coverage_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `timestamp_/6`
 - `object_file_/2`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`timestamp_/6`

Cache of the starting tests timestamp.

Compilation flags:

dynamic

Template:

`timestamp_(Year,Month,Day,Hours,Minutes,Seconds)`

Mode and number of proofs:

`timestamp_(-integer,-integer,-integer,-integer,-integer,-integer) - one`

`object_file_/2`

Cache of test object - file pairs.

Compilation flags:

`dynamic`

Template:

`object_file__(Object,File)`

Mode and number of proofs:

`object_file__(?object_identifier,?atom) - zero_or_more`

Operators

(none)

object

1.43.3 lgtunit

A unit test framework supporting predicate clause coverage, determinism testing, input/output testing, property-based testing, and multiple test dialects.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 17:0:0

Date: 2024-02-19

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Provides:

`logtalk::trace_event/2`

Uses:

`fast_random`

`list`

`logtalk`

```

os
type
user

```

Remarks:

- Usage: Define test objects as extensions of the lgtunit object and compile their source files using the compiler option `hook(lgtunit)`.
- Portability: Deterministic unit tests are currently not available when using Quintus Prolog as the backend compiler.
- Known issues: Parameter variables cannot currently be used in the definition of test options.

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - `cover/1`
 - `run/0`
 - `run/1`
 - `run/2`
 - `run_test_sets/1`
 - `test/1`
 - `number_of_tests/1`
 - `deterministic/1`
 - `deterministic/2`
 - `assertion/1`
 - `assertion/2`
 - `quick_check/3`
 - `quick_check/2`
 - `quick_check/1`
 - `benchmark/2`
 - `benchmark_reified/3`
 - `benchmark/3`
 - `benchmark/4`
 - `variant/2`
 - `approximately_equal/2`
 - `approximately_equal/3`

- `essentially_equal/3`
- `tolerance_equal/4`
- `==~/2`
- `epsilon/1`
- Protected predicates
 - `run_tests/0`
 - `run_tests/1`
 - `run_test_set/0`
 - `run_quick_check_tests/5`
 - `condition/0`
 - `setup/0`
 - `cleanup/0`
 - `make/1`
 - `note/1`
 - `file_path/2`
 - `suppress_text_output/0`
 - `suppress_binary_output/0`
 - `set_text_input/3`
 - `set_text_input/2`
 - `set_text_input/1`
 - `check_text_input/2`
 - `check_text_input/1`
 - `text_input_assertion/3`
 - `text_input_assertion/2`
 - `clean_text_input/0`
 - `set_binary_input/3`
 - `set_binary_input/2`
 - `set_binary_input/1`
 - `check_binary_input/2`
 - `check_binary_input/1`
 - `binary_input_assertion/3`
 - `binary_input_assertion/2`
 - `clean_binary_input/0`
 - `set_text_output/3`
 - `set_text_output/2`

- set_text_output/1
- check_text_output/3
- check_text_output/2
- check_text_output/1
- text_output_assertion/4
- text_output_assertion/3
- text_output_assertion/2
- text_output_contents/3
- text_output_contents/2
- text_output_contents/1
- clean_text_output/0
- set_binary_output/3
- set_binary_output/2
- set_binary_output/1
- check_binary_output/2
- check_binary_output/1
- binary_output_assertion/3
- binary_output_assertion/2
- binary_output_contents/2
- binary_output_contents/1
- clean_binary_output/0
- create_text_file/3
- create_text_file/2
- create_binary_file/2
- check_text_file/3
- check_text_file/2
- text_file_assertion/4
- text_file_assertion/3
- check_binary_file/2
- binary_file_assertion/3
- clean_file/1
- clean_directory/1
- closed_input_stream/2
- closed_output_stream/2
- stream_position/1

- test/2
- Private predicates
 - running_test_sets_/0
 - test/3
 - auxiliary_predicate_counter_/1
 - test_/2
 - skipped_/1
 - passed_/3
 - failed_/3
 - flaky_/1
 - fired_/3
 - covered_/4
- Operators
 - op(700,xfx,==)

Public predicates

cover/1

Declares entities being tested for which code coverage information should be collected.

Compilation flags:

static

Template:

cover(Entity)

Mode and number of proofs:

cover(?entity__identifier) - zero_or_more

run/0

Runs the unit tests, writing the results to the current output stream.

Compilation flags:

static

Mode and number of proofs:

run - one

run/1

Runs a unit test or a list of unit tests, writing the results to the current output stream. Runs the global setup and cleanup steps when defined. Fails when given a partial list of tests or when one of the test identifiers is not valid.

Compilation flags:

static

Template:

run(Tests)

Mode and number of proofs:

run(++callable) - zero_or_one

run(++list(callable)) - zero_or_one

run/2

Runs the unit tests, writing the results to the specified file. Mode can be either write (to create a new file) or append (to add results to an existing file).

Compilation flags:

static

Template:

run(File,Mode)

Mode and number of proofs:

run(+atom,+atom) - one

`run_test_sets/1`

Runs two or more test sets as a unified set generating a single code coverage report if one is requested. Fails if the list does not contains at least two test objects.

Compilation flags:

static

Template:

`run_test_sets(TestObjects)`

Mode and number of proofs:

`run_test_sets(+list(object_identifier)) - zero_or_one`

`test/1`

Enumerates, by backtracking, the identifiers of all defined unit tests.

Compilation flags:

static

Template:

`test(Identifier)`

Mode and number of proofs:

`test(?callable) - zero_or_more`

`number_of_tests/1`

Number of defined unit tests.

Compilation flags:

static

Template:

`number_of_tests(NumerOfTests)`

Mode and number of proofs:

`number_of_tests(?integer) - zero_or_one`

`deterministic/1`

True if the goal succeeds once without leaving choice-points.

Compilation flags:

`static`

Template:

`deterministic(Goal)`

Meta-predicate template:

`deterministic(0)`

Mode and number of proofs:

`deterministic(+callable) - zero_or_one`

`deterministic/2`

Reified version of the `deterministic/1` predicate. True if the goal succeeds. Returns a boolean value (true or false) indicating if the goal succeeded without leaving choice-points.

Compilation flags:

`static`

Template:

`deterministic(Goal,Deterministic)`

Meta-predicate template:

`deterministic(0,*)`

Mode and number of proofs:

`deterministic(+callable,--atom) - zero_or_one`

assertion/1

True if the assertion goal succeeds. Throws an error using the assertion goal as argument if the assertion goal throws an error or fails.

Compilation flags:

static

Template:

assertion(Assertion)

Meta-predicate template:

assertion(::)

Mode and number of proofs:

assertion(@callable) - one

Exceptions:

Assertion goal fails:

assertion__failure(Assertion)

Assertion goal throws Error:

assertion__error(Assertion,Error)

assertion/2

True if the assertion goal succeeds. Throws an error using the description as argument if the assertion goal throws an error or fails. The description argument helps to distinguish between different assertions in the same test body.

Compilation flags:

static

Template:

assertion(Description,Assertion)

Meta-predicate template:

assertion(*,0)

Mode and number of proofs:

assertion(+nonvar,@callable) - one

Exceptions:

Assertion goal fails:

assertion__failure(Description)

Assertion goal throws Error:

```
assertion_error(Description,Error)
```

[quick_check/3](#)

Reified version of the [quick_check/2](#) predicate. Reports `passed(SequenceSeed,Discarded,Labels)`, `failed(Goal,SequenceSeed,TestSeed)`, `error(Error,Goal,SequenceSeed,TestSeed)`, or `broken(Why,Culprit)`. Goal is the failed test.

Compilation flags:

```
static
```

Template:

```
quick_check(Template,Result,Options)
```

Meta-predicate template:

```
quick_check(:,*,::)
```

Mode and number of proofs:

```
quick_check(@callable,-callable,++list(compound)) - one
```

Remarks:

- `SequenceSeed` argument: Can be used to re-run the same exact sequence of pseudo-random tests by using the `rs/1` option after changes to the code being tested.
 - `TestSeed` argument: Can be used to re-run the test that failed by using the `rs/1` option after changes to the code being tested.
 - `Discarded` argument: Number of generated tests that were discarded for failing to comply a pre-condition specified using the `pc/1` option.
 - `Labels` argument: List of pairs `Label-N` where `N` is the number of generated tests that are classified as `Label` by a closure specified using the `l/1` option.
 - `broken(Why,Culprit)` result: This result signals a broken setup. For example, an invalid template, a broken pre-condition or label goal, or broken test generation.
-

`quick_check/2`

Generates and runs random tests for a predicate given its mode template and a set of options. Fails when a generated test fails printing the test. Also fails on an invalid option, printing the option.

Compilation flags:

`static`

Template:

`quick_check(Template,Options)`

Meta-predicate template:

`quick_check(:,::,::)`

Mode and number of proofs:

`quick_check(@callable,++list(compound)) - zero_or_one`

Remarks:

- Number of tests: Use the `n(NumberOfTests)` option to specify the number of random tests. Default is 100.
- Maximum number of shrink operations: Use the `s(MaxShrinks)` option to specify the number of shrink operations when a counter example is found. Default is 64.
- Type edge cases: Use the `ec(Boolean)` option to specify if type edge cases are tested (before generating random tests). Default is true.
- Starting seed: Use the `rs(Seed)` option to specify the random generator starting seed to be used when generating tests. No default. Seeds should be regarded as opaque terms.
- Test generation filtering: Use the `pc/1` option to specify a pre-condition closure for filtering generated tests (extended with the test arguments; no default).
- Generated tests classification: Use the `l/1` option to specify a label closure for classifying the generated tests (extended with the test arguments plus the labels argument; no default). The labelling predicate can return a single test label or a list of test labels.
- Verbose test generation: Use the `v(Boolean)` option to specify verbose reporting of generated random tests. Default is false.
- Progress bar: Use the `pb(Boolean,Tick)` option to print a progress bar for the executed tests, advancing at every Tick tests. Default is false. Only applies when the verbose option is false.

quick_check/1

Generates and runs random tests using default options for a predicate given its mode template. Fails when a generated test fails printing the test.

Compilation flags:

static

Template:

quick_check(Template)

Mode and number of proofs:

quick_check(@callable) - zero_or_one

benchmark/2

Benchmarks a goal and returns the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

static

Template:

benchmark(Goal,Time)

Meta-predicate template:

benchmark(0,*)

Mode and number of proofs:

benchmark(+callable,-float) - one

benchmark_reified/3

Benchmarks a goal and returns the total execution time in seconds plus its result (success, failure, or error(Error)). Uses CPU clock.

Compilation flags:

static

Template:

```
benchmark_reified(Goal,Time,Result)
```

Meta-predicate template:

```
benchmark_reified(0,*,*)
```

Mode and number of proofs:

```
benchmark_reified(+callable,-float,-callable) - one
```

[benchmark/3](#)

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Time)
```

Meta-predicate template:

```
benchmark(0,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,-float) - one
```

[benchmark/4](#)

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds using the given clock (cpu or wall). Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Clock,Time)
```

Meta-predicate template:

```
benchmark(0,*,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,+atom,-float) - one
```

variant/2

True when the two arguments are a variant of each other. I.e. if is possible to rename the term variables to make them identical. Useful for checking expected test results that contain variables.

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

approximately_equal/2

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2)

Mode and number of proofs:

approximately_equal(+number,+number) - zero_or_one

approximately_equal/3

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2,Epsilon)

Mode and number of proofs:

`approximately_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
 - Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.
-

`essentially_equal/3`

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

`static`

Template:

`essentially_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`essentially_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.
-

`tolerance_equal/4`

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. Type-checked.

Compilation flags:

`static`

Template:

`tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)`

Mode and number of proofs:

```
tolerance_equal(+number,+number,+number,+number) - zero_or_one
```

```
=~= / 2
```

Compares two numbers (or lists of numbers) for approximate equality using 100*epsilon for the absolute error and, if that fails, 99.999% accuracy for the relative error. But these precision values may not be adequate for all cases. Type-checked.

Compilation flags:

```
static
```

Template:

```
=~=(Number1,Number2)
```

Mode and number of proofs:

```
=~=(+number,+number) - zero_or_one
```

```
=~=(+list(number),+list(number)) - zero_or_one
```

```
epsilon/1
```

Returns the value of epsilon used in the definition of the (`=~`)/2 predicate.

Compilation flags:

```
static
```

Template:

```
epsilon(Epsilon)
```

Mode and number of proofs:

```
epsilon(-float) - one
```

Protected predicates

`run_tests/0`

Runs all defined unit tests.

Compilation flags:

`static`

Mode and number of proofs:

`run_tests - one`

`run_tests/1`

Runs all the tests defined in the given file.

Compilation flags:

`static`

Template:

`run_tests(File)`

Mode and number of proofs:

`run_tests(+atom) - one`

`run_test_set/0`

Runs a test set as part of running two or more test sets as a unified set.

Compilation flags:

`static`

Mode and number of proofs:

`run_test_set - one`

`run_quick_check_tests/5`

Runs a list of defined tests using the given options. Returns the starting seed used to generate the random tests, the number of discarded tests, and the test label statistics.

Compilation flags:

`static`

Template:

`run_quick_check_tests(Template,Options,Seed,Discarded,Labels)`

Meta-predicate template:

`run_quick_check_tests(:,::,*,*,*)`

Mode and number of proofs:

`run_quick_check_tests(@callable,+list,--nonvar,--number,--list(pair)) - one_or_error`

`condition/0`

Verifies conditions for running the tests. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`condition - zero_or_one`

`setup/0`

Setup environment before running the test set. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`setup - zero_or_one`

cleanup/0

Cleanup environment after running the test set. Defaults to the goal true.

Compilation flags:

static

Mode and number of proofs:

cleanup - zero_or_one

make/1

Make target for automatically running the test set when calling the logtalk_make/1 built-in predicate. No default. Possible values are all and check.

Compilation flags:

static

Template:

make(Target)

Mode and number of proofs:

make(?atom) - zero_or_one

note/1

Note to be printed after the test results. Defaults to the empty atom.

Compilation flags:

static

Template:

note(Note)

Mode and number of proofs:

note(?atom) - zero_or_one

`file_path/2`

Returns the absolute path for a file path that is relative to the tests object path. When the file path is already an absolute path, it is expanded to resolve any remaining relative file path parts.

Compilation flags:

`static`

Template:

`file_path(File,Path)`

Mode and number of proofs:

`file_path(+atom,-atom) - one`

See also:

`clean_file/1`

`clean_directory/1`

`suppress_text_output/0`

Suppresses text output. Useful to avoid irrelevant text output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_text_output - one`

`suppress_binary_output/0`

Suppresses binary output. Useful to avoid irrelevant binary output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_binary_output` - one

`set_text_input/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the additional options. If no `eof_action/1` option is specified, its value will be the default used by the backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_input(+atom,+atom,+list(stream_option))` - one

`set_text_input(+atom,+list(atom),+list(stream_option))` - one

See also:

`text_input_assertion/3`

`check_text_input/2`

`clean_text_input/0`

`set_text_input/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents)`

Mode and number of proofs:

`set_text_input(+atom,+atom)` - one

`set_text_input(+atom,+list(atom))` - one

See also:

```
text_input_assertion/3  
check_text_input/2  
clean_text_input/0
```

```
set_text_input/1
```

Creates a temporary file, in the same directory as the tests object, with the given text contents, opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

```
static
```

Template:

```
set_text_input(Contents)
```

Mode and number of proofs:

```
set_text_input(+atom) - one
```

```
set_text_input(+list(atom)) - one
```

See also:

```
text_input_assertion/2  
check_text_input/1  
clean_text_input/0
```

```
check_text_input/2
```

Checks that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

```
static
```

Template:

```
check_text_input(Alias,Contents)
```

Mode and number of proofs:

```
check_text_input(+atom,+atom) - zero_or_one
```

See also:

```
set_text_input/2  
set_text_input/2  
text_input_assertion/3  
clean_text_input/0
```

`check_text_input/1`

Checks that the temporary file being read have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_input(Contents)`

Mode and number of proofs:

`check_text_input(+atom) - zero_or_one`

See also:

```
set_text_input/1  
text_input_assertion/2  
clean_text_input/0
```

`text_input_assertion/3`

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

`static`

Template:

`text_input_assertion(Alias,Contents,Assertion)`

Mode and number of proofs:

`text_input_assertion(+atom,+atom,--callable) - one`

See also:

```
set_text_input/3
```

[check_text_input/2](#)
[clean_text_input/0](#)

[text_input_assertion/2](#)

Returns an assertion for checking that the temporary file being read have the expected text contents.

Compilation flags:

static

Template:

`text_input_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_input_assertion(+atom,--callable) - one`

See also:

[set_text_input/1](#)
[check_text_input/1](#)
[clean_text_input/0](#)

[clean_text_input/0](#)

Cleans the temporary file used when testing text input.

Compilation flags:

static

Mode and number of proofs:

`clean_text_input - one`

See also:

[set_text_input/3](#)
[set_text_input/2](#)
[set_text_input/1](#)

[set_binary_input/3](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the additional options. If no eof_action/1 option is specified, its value will be the default used by the backend compiler.

Compilation flags:

static

Template:

set_binary_input(Alias,Bytes,Options)

Mode and number of proofs:

set_binary_input(+atom,+list(byte),+list(stream_option)) - one

See also:

[binary_input_assertion/3](#)

[check_binary_input/2](#)

[clean_binary_input/0](#)

[set_binary_input/2](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

static

Template:

set_binary_input(Alias,Bytes)

Mode and number of proofs:

set_binary_input(+atom,+list(byte)) - one

See also:

[binary_input_assertion/3](#)

[check_binary_input/2](#)

[clean_binary_input/0](#)

[set_binary_input/1](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

static

Template:

`set_binary_input(Bytes)`

Mode and number of proofs:

`set_binary_input(+list(byte)) - one`

See also:

[binary_input_assertion/2](#)

[check_binary_input/1](#)

[clean_binary_input/0](#)

[check_binary_input/2](#)

Checks that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

static

Template:

`check_binary_input(Alias,Bytes)`

Mode and number of proofs:

`check_binary_input(+atom,+list(byte)) - zero_or_one`

See also:

[set_binary_input/3](#)

[set_binary_input/2](#)

[binary_input_assertion/3](#)

[clean_binary_input/0](#)

[check_binary_input/1](#)

Checks that the temporary file being read have the expected binary contents.

Compilation flags:

static

Template:

`check_binary_input(Bytes)`

Mode and number of proofs:

`check_binary_input(+list(byte)) - zero_or_one`

See also:

[binary_input_assertion/2](#)

[set_binary_input/1](#)

[clean_binary_input/0](#)

[binary_input_assertion/3](#)

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

static

Template:

`binary_input_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_input/2](#)

[set_binary_input/3](#)

[set_binary_input/2](#)

[clean_binary_input/0](#)

[binary_input_assertion/2](#)

Returns an assertion for checking that the temporary file being read have the expected binary contents.

Compilation flags:

static

Template:

`binary_input_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+list(byte),--callable) - one`

See also:

[check_binary_input/1](#)

[set_binary_input/1](#)

[clean_binary_input/0](#)

[clean_binary_input/0](#)

Cleans the temporary file used when testing binary input.

Compilation flags:

static

Mode and number of proofs:

`clean_binary_input - one`

See also:

[set_binary_input/3](#)

[set_binary_input/2](#)

[set_binary_input/1](#)

`set_text_output/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_output(+atom,+atom,+list(stream_option)) - one`

`set_text_output(+atom,+list(atom),+list(stream_option)) - one`

See also:

`text_output_assertion/4`

`check_text_output/3`

`clean_text_output/0`

`set_text_output/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and referenced by the given alias.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents)`

Mode and number of proofs:

`set_text_output(+atom,+atom) - one`

`set_text_output(+atom,+list(atom)) - one`

See also:

`text_output_assertion/3`

`check_text_output/2`

`clean_text_output/0`

`set_text_output/1`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and sets the current output stream to the file.

Compilation flags:

`static`

Template:

`set_text_output(Contents)`

Mode and number of proofs:

`set_text_output(+atom) - one`

`set_text_output(+list(atom)) - one`

See also:

`text_output_assertion/2`

`check_text_output/1`

`clean_text_output/0`

`check_text_output/3`

Checks that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`check_text_output(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

`set_text_output/3`

`text_output_assertion/4`

`clean_text_output/0`

`check_text_output/2`

Checks that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents)`

Mode and number of proofs:

`check_text_output(+atom,+atom) - zero_or_one`

See also:

`set_text_output/2`

`text_output_assertion/3`

`clean_text_output/0`

`check_text_output/1`

Checks that the temporary file being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Contents)`

Mode and number of proofs:

`check_text_output(+atom) - zero_or_one`

See also:

`set_text_output/1`

`text_output_assertion/2`

`clean_text_output/0`

`text_output_assertion/4`

Returns an assertion for checking that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Options,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

`set_text_output/3`

`check_text_output/3`

`clean_text_output/0`

`text_output_assertion/3`

Returns an assertion for checking that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,--callable) - one`

See also:

`set_text_output/2`

`check_text_output/2`

`clean_text_output/0`

`text_output_assertion/2`

Returns an assertion for checking that the temporary file (open with default options in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,--callable) - one`

See also:

`set_text_output/1`

`check_text_output/1`

`clean_text_output/0`

`text_output_contents/3`

Returns the contents of the temporary file (open with the given options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents,Options)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character),+list(stream_option)) - one`

`text_output_contents/2`

Returns the contents of the temporary file (open with default options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character)) - one`

`text_output_contents/1`

Returns the contents of the temporary file (open with default options in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Contents)`

Mode and number of proofs:

`text_output_contents(-list(character)) - one`

`clean_text_output/0`

Cleans the temporary file used when testing text output.

Compilation flags:

`static`

Mode and number of proofs:

`clean_text_output - one`

See also:

```
set_text_output/3  
set_text_output/2  
set_text_output/1
```

`set_binary_output/3`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

`static`

Template:

`set_binary_output(Alias,Contents,Options)`

Mode and number of proofs:

`set_binary_output(+atom,+list(byte),+list(stream_option)) - one`

See also:

```
binary_output_assertion/3  
check_binary_output/2  
clean_binary_output/0
```

`set_binary_output/2`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced with the given alias.

Compilation flags:

`static`

Template:

`set_binary_output(Alias,Bytes)`

Mode and number of proofs:

`set_binary_output(+atom,+list(byte)) - one`

See also:

```
binary_output_assertion/3
```

[check_binary_output/2](#)
[clean_binary_output/0](#)

[set_binary_output/1](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and sets the current output stream to the file.

Compilation flags:

static

Template:

[set_binary_output\(Bytes\)](#)

Mode and number of proofs:

[set_binary_output\(+list\(byte\)\)](#) - one

See also:

[binary_output_assertion/2](#)

[check_binary_output/1](#)

[clean_binary_output/0](#)

[check_binary_output/2](#)

Checks that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

static

Template:

[check_binary_output\(Alias,Bytes\)](#)

Mode and number of proofs:

[check_binary_output\(+atom,+list\(byte\)\)](#) - zero_or_one

See also:

[set_binary_output/3](#)

[set_binary_output/2](#)

[binary_output_assertion/3](#)

`clean_binary_output/0`

`check_binary_output/1`

Checks that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`check_binary_output(Bytes)`

Mode and number of proofs:

`check_binary_output(+list(byte)) - zero_or_one`

See also:

`set_binary_output/1`

`binary_output_assertion/2`

`clean_binary_output/0`

`binary_output_assertion/3`

Returns an assertion for checking that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+atom,+list(byte),--callable) - one`

See also:

`set_binary_output/2`

`check_binary_output/2`

`clean_binary_output/0`

`binary_output_assertion/2`

Returns an assertion for checking that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+list(byte),--callable) - one`

See also:

`set_binary_output/1`

`check_binary_output/1`

`clean_binary_output/0`

`binary_output_contents/2`

Returns the binary contents of the temporary file (referenced by the given alias) being written.

Compilation flags:

`static`

Template:

`binary_output_contents(Alias,Bytes)`

Mode and number of proofs:

`binary_output_contents(+atom,-list(byte)) - one`

`binary_output_contents/1`

Returns the binary contents of the temporary file being written.

Compilation flags:

`static`

Template:

`binary_output_contents(Bytes)`

Mode and number of proofs:

`binary_output_contents(-list(byte)) - one`

`clean_binary_output/0`

Cleans the temporary file used when testing binary output.

Compilation flags:

`static`

Mode and number of proofs:

`clean_binary_output - one`

See also:

`set_binary_output/3`

`set_binary_output/2`

`set_binary_output/1`

`create_text_file/3`

Creates a text file with the given contents. The file is open for writing using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

`static`

Template:

```
create_text_file(File,Contents,Options)
```

Mode and number of proofs:

```
create_text_file(+atom,+atom,+list(stream_option)) - one
```

```
create_text_file(+atom,+list(atom),+list(stream_option)) - one
```

`create_text_file/2`

Creates a text file with the given contents. The file is open for writing using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

```
static
```

Template:

```
create_text_file(File,Contents)
```

Mode and number of proofs:

```
create_text_file(+atom,+atom) - one
```

```
create_text_file(+atom,+list(atom)) - one
```

`create_binary_file/2`

Creates a binary file with the given contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

```
static
```

Template:

```
create_binary_file(File,Bytes)
```

Mode and number of proofs:

```
create_binary_file(+atom,+list(byte)) - one
```

[check_text_file/3](#)

Checks that the contents of a text file match the expected contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents,Options)`

Mode and number of proofs:

`check_text_file(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

[text_file_assertion/4](#)

[check_text_file/2](#)

Checks that the contents of a text file (open for reading using default options) match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents)`

Mode and number of proofs:

`check_text_file(+atom,+atom) - zero_or_one`

See also:

[text_file_assertion/3](#)

[text_file_assertion/4](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Options,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

[check_text_file/3](#)

[text_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,--callable) - one`

See also:

[check_text_file/2](#)

[check_binary_file/2](#)

Checks the contents of a binary file match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_binary_file(File,Bytes)`

Mode and number of proofs:

`check_binary_file(+atom,+list(byte)) - zero_or_one`

See also:

[binary_file_assertion/3](#)

[binary_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected binary contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`binary_file_assertion(File,Bytes,Assertion)`

Mode and number of proofs:

`binary_file_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_file/2](#)

[clean_file/1](#)

Closes any existing stream associated with the file and deletes the file if it exists. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_file(File)`

Mode and number of proofs:

`clean_file(+atom) - one`

See also:

[clean_directory/1](#)

[file_path/2](#)

[clean_directory/1](#)

Deletes an empty directory if it exists. Relative directory paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_directory(Directory)`

Mode and number of proofs:

`clean_directory(+atom) - one`

See also:

[clean_file/1](#)

[file_path/2](#)

`closed_input_stream/2`

Opens a temporary file in the same directory as the tests object with the given options for reading, closes it, and returns its stream handle.

Compilation flags:

`static`

Template:

`closed_input_stream(Stream,Options)`

Mode and number of proofs:

`closed_input_stream(-stream,+list(stream_option)) - one`

`closed_output_stream/2`

Opens a temporary file in the same directory as the tests object with the given options for writing, closes it, and returns its stream handle.

Compilation flags:

`static`

Template:

`closed_output_stream(Stream,Options)`

Mode and number of proofs:

`closed_output_stream(-stream,+list(stream_option)) - zero_or_one`

`stream_position/1`

Returns a syntactically valid stream position by opening a temporary file in the same directory as the tests object.

Compilation flags:

`static`

Template:

`stream_position(Position)`

Mode and number of proofs:

`stream_position(-stream_position) - one`

`test/2`

Table of defined tests.

Compilation flags:

`static`

Template:

`test(Identifier,Test)`

Mode and number of proofs:

`test(?callable,?compound) - zero_or_more`

Private predicates

`running_test_sets_/0`

Internal flag used when running two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`running_test_sets_ - zero_or_one`

`test/3`

Compiled unit tests. The list of variables is used to ensure variable sharing between a test with its test options.

Compilation flags:

`static`

Template:

`test(Identifier,Variables,Outcome)`

Meta-predicate template:

`test(*,*,*)`

Mode and number of proofs:

`test(?callable,?list(variable),?nonvar) - zero_or_more`

`auxiliary_predicate_counter_/1`

Counter for generating unique auxiliary predicate names.

Compilation flags:

`dynamic`

Template:

`auxiliary_predicate_counter_(Counter)`

Mode and number of proofs:

`auxiliary_predicate_counter_(?integer) - one_or_more`

`test_/2`

Table of compiled tests.

Compilation flags:

`dynamic`

Template:

`test_(Identifier,Test)`

Mode and number of proofs:

`test_(?callable,?compound) - zero_or_more`

skipped_/1

Counter for skipped tests.

Compilation flags:

dynamic

Template:

skipped_(Counter)

Mode and number of proofs:

skipped_(?integer) - zero_or_one

passed_/3

Counter and total time for passed tests.

Compilation flags:

dynamic

Template:

passed_(Counter,CPUTime,WallTime)

Mode and number of proofs:

passed_(?integer,-float,-float) - zero_or_one

failed_/3

Counter and total time for failed tests.

Compilation flags:

dynamic

Template:

failed_(Counter,CPUTime,WallTime)

Mode and number of proofs:

failed_(?integer,-float,-float) - zero_or_one

flaky_/1

Counter for failed tests that are marked as flaky.

Compilation flags:

dynamic

Template:

flaky_(Counter)

Mode and number of proofs:

flaky_(?integer) - zero_or_one

fired_/3

Fired clauses when running the unit tests.

Compilation flags:

dynamic

Template:

fired_(Entity,Predicate,Clause)

Mode and number of proofs:

fired_(?entity_identifier,?predicate_indicator,?integer) - zero_or_more

covered_/4

Auxiliary predicate for collecting statistics on clause coverage.

Compilation flags:

dynamic

Template:

covered_(Entity,Predicate,Covered>Total)

Mode and number of proofs:

covered_(?entity_identifier,?callable,?integer,?integer) - zero_or_more

Operators

`op(700,xfx,==)`

Scope:

public

category

1.43.4 lgtunit_messages

Logtalk unit test framework default message translations.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 9:0:0

Date: 2024-02-20

Compilation flags:

static

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.5 `minimal_output`

Intercepts unit test execution messages and outputs a minimal report.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 3:0:0

Date: 2021-05-27

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(minimal_output))`.
- Limitations: Cannot be used when the test objects also intercept lgtunit messages.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.6 tap_output

Intercepts unit test execution messages and outputs a report using the TAP format to the current output stream.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `generating_/0`
 - `partial_/1`
 - `test_count_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`generating_/0`

Flag to detect report in progress when processing two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`generating_ - zero_or_one`

partial_/1

Cache of total of tests per test set.

Compilation flags:

dynamic

Template:

partial_(Count)

Mode and number of proofs:

partial_(?integer) - zero_or_more

test_count_/1

Test counter.

Compilation flags:

dynamic

Template:

test_count_(Count)

Mode and number of proofs:

test_count_(?integer) - zero_or_one

Operators

(none)

object

1.43.7 tap_report

Intercepts unit test execution messages and generates a tap_report.txt file using the TAP output format in the same directory as the tests object file.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - partial_/1
 - test_count_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

partial_/1

Cache of total of tests per test set.

Compilation flags:
dynamic

Template:
partial_(Count)
Mode and number of proofs:
partial_(?integer) - zero_or_more

test_count_/1

Test counter.

Compilation flags:
dynamic

Template:
test_count_(Count)
Mode and number of proofs:
test_count_(?integer) - zero_or_one

Operators

(none)
object

1.43.8 xunit_net_v2_output

Intercepts unit test execution messages and outputs a report using the xUnit.net v2 XML format to the current output stream.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
user
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `message_cache_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

object

1.43.9 xunit_net_v2_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit.net v2 XML format in the same directory as the tests object file.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:


```
message_cache_(Message)
Mode and number of proofs:
message_cache_(?callable) - zero_or_more
```

Operators

(none)
object

1.43.10 xunit_output

Intercepts unit test execution messages and outputs a report using the xUnit XML format to the current output stream.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
logtalk
user
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_output))`.

Inherited public predicates:

```
(none)
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
 - [message_cache_/1](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`message_cache_/1`

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

`dynamic`

Template:

`message_cache_(Message)`

Mode and number of proofs:

`message_cache_(?callable) - zero_or_more`

Operators

(none)

object

1.43.11 xunit_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit XML format in the same directory as the tests object file.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`logtalk`

`user`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `message_cache_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`message__cache__`/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

`dynamic`

Template:

`message__cache__(Message)`

Mode and number of proofs:

`message__cache__(?callable) - zero__or__more`

Operators

(none)

1.44 library

protocol

1.44.1 cloning

Object cloning protocol.

Availability:

`logtalk__load(library(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2010-09-14

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - clone/1
- Protected predicates
- Private predicates
- Operators

Public predicates

clone/1

Clones an object, returning the identifier of the new object if none is given.

Compilation flags:

static

Template:

clone(Clone)

Mode and number of proofs:

clone(?object) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.44.2 counters

Named integer counters. Counter names can be any nonvar term.

Availability:

`logtalk_load(library(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2022-02-11

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `counter/2`
 - `increment_counter/1`
 - `decrement_counter/1`

- reset_counter/1
- reset_counters/0
- Protected predicates
- Private predicates
 - counter_/2
- Operators

Public predicates

counter/2

True if Counter is a counter with value Value.

Compilation flags:

static

Template:

counter(Counter, Value)

Mode and number of proofs:

counter(?nonvar, ?integer) - zero_or_more

increment_counter/1

Increments the named counter.

Compilation flags:

static

Template:

increment_counter(Counter)

Mode and number of proofs:

increment_counter(+nonvar) - one

`decrement_counter/1`

Decrements the named counter.

Compilation flags:

`static`

Template:

`decrement_counter(Counter)`

Mode and number of proofs:

`decrement_counter(+nonvar) - one`

`reset_counter/1`

Resets the named counter to zero. Creates the counter if it does not exist.

Compilation flags:

`static`

Template:

`reset_counter(Counter)`

Mode and number of proofs:

`reset_counter(+nonvar) - one`

`reset_counters/0`

Resets all existing named counters to zero.

Compilation flags:

`static`

Mode and number of proofs:

`reset_counters - one`

Protected predicates

(none)

Private predicates

counter_/2

Table of named counters.

Compilation flags:

dynamic

Template:

counter_(Counter,Value)

Mode and number of proofs:

counter_(?nonvar,?integer) - zero_or_more

Operators

(none)

object

1.44.3 streamvars

Stream variables (supporting logical, backtracable, adding and retrieving of terms).

Availability:

logtalk_load(library(loader))

Author: Nobukuni Kino and Paulo Moura

Version: 1:3:0

Date: 2019-06-15

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - new/1
 - new/2
 - (\leq)/2
 - (\geq)/2
- Protected predicates
- Private predicates
- Operators
 - op(100,xfx, \leq)
 - op(100,xfx, \geq)

Public predicates

new/1

Makes Variable a stream variable. Initial state will be empty.

Compilation flags:

static

Template:

new(Variable)

Mode and number of proofs:

new(--streamvar) - one

Exceptions:

Variable is not a variable:

type__error(variable,Variable)

`new/2`

Makes `Variable` a stream variable and sets its initial state to `Value`.

Compilation flags:

`static`

Template:

`new(Variable,Value)`

Mode and number of proofs:

`new(--streamvar,@nonvar) - one`

Exceptions:

Variable is not a variable:

`type_error(variable,Variable)`

`(<=)/2`

Sets the state of the stream variable `Variable` to `Value` (initializing the variable if needed).

Compilation flags:

`static`

Template:

`Variable<=Value`

Mode and number of proofs:

`(?streamvar)<=(@nonvar) - one`

`(=>)/2`

Unifies `Value` with the current state of the stream variable `Variable`.

Compilation flags:

`static`

Template:

Variable=>Value
Mode and number of proofs:
+streamvar=> ?nonvar - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

op(100,xfx,<=)

Scope:
public

op(100,xfx,=>)

Scope:
public

1.45 listing

category

1.45.1 listing

Listing predicates.

Availability:
logtalk_load(listing(loader))

Author: Paulo Moura
Version: 1:0:0
Date: 2024-01-26

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - listing/0
 - listing/1
 - portray_clause/1
- Protected predicates
- Private predicates
- Operators

Public predicates

listing/0

Lists all clauses of all visible dynamic predicates to the current output stream.

Compilation flags:

static

Mode and number of proofs:

listing - one

listing/1

Lists all clauses of a visible dynamic predicate or non-terminal to the current output stream. When the argument is a clause head, lists all matching clauses.

Compilation flags:

static

Template:

listing(Spec)

Mode and number of proofs:

listing(+predicate_indicator) - one_or_error

listing(+non_terminal_indicator) - one_or_error

listing(+callable) - one_or_error

Exceptions:

Spec is not ground:

instantiation_error

Spec is ground but not a valid predicate indicator:

type_error(predicate_indicator,Spec)

Spec is ground but not a valid non-terminal indicator:

type_error(non_terminal_indicator,Spec)

Spec is a predicate indicator but not a visible predicate:

existence_error(predicate,Spec)

Spec is a non-terminal indicator but not a visible non-terminal:

existence_error(non_terminal,Spec)

Spec is a callable term with a Functor/Arity indicator but not a visible predicate:

existence_error(predicate,Functor/Arity)

Spec is a predicate indicator of a visible predicate but not a dynamic predicate:

permission_error(access,predicate,Spec)

Spec is a non-terminal indicator of a visible non-terminal but not a dynamic non-terminal:

permission_error(access,non_terminal,Spec)

Spec is a callable term for a visible predicate with a Functor/Arity indicator but not a dynamic predicate:

permission_error(access,predicate,Functor/Arity)

portray_clause/1

Pretty prints a clause to the current output stream.

Compilation flags:

static

Template:

portray_clause(Clause)

Mode and number of proofs:

portray_clause(+clause) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.46 logging

object

1.46.1 logger

Global logger object for logging events to files.

Availability:

logtalk_load(logging(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

static, context_switching_calls

Implements:

public loggingp

Remarks:

(none)

Inherited public predicates:

define_log_file/2 disable_logging/1 enable_logging/1 init_log_file/2 log_event/2 log_file/2
logging/1

- Public predicates
- Protected predicates
- Private predicates
 - log_file_/2
 - logging_to_file_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

log_file_/2

Table of log files.

Compilation flags:

dynamic

Template:

log_file_(Alias,File)

Mode and number of proofs:

`log_file_(?atom,?nonvar) - zero_or_more`

`logging_to_file_/2`

Table of logging file status for log files.

Compilation flags:

`dynamic`

Template:

`logging_to_file_(Alias,Status)`

Mode and number of proofs:

`logging_to_file_(?atom,?atom) - zero_or_more`

Operators

(none)

category

1.46.2 logging

Logging events to files category.

Availability:

`logtalk_load(logging(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

`static`

Implements:

`public loggingp`

Remarks:

(none)

Inherited public predicates:

`define_log_file/2` `disable_logging/1` `enable_logging/1` `init_log_file/2` `log_event/2` `log_file/2`
`logging/1`

- Public predicates
- Protected predicates
- Private predicates
 - `log_file_/2`
 - `logging_to_file_/2`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`log_file_/2`

Table of log files.

Compilation flags:

`dynamic`

Template:

`log_file_(Alias,File)`

Mode and number of proofs:

`log_file_(?atom,?nonvar) - zero_or_more`

logging_to_file_/2

Table of logging file status for log files.

Compilation flags:

dynamic

Template:

logging_to_file_(Alias,Status)

Mode and number of proofs:

logging_to_file_(?atom,?atom) - zero_or_more

Operators

(none)

protocol

1.46.3 loggingp

Logging events to files protocol.

Availability:

logtalk_load(logging(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `log_file/2`
 - `define_log_file/2`
 - `init_log_file/2`
 - `log_event/2`
 - `logging/1`
 - `enable_logging/1`
 - `disable_logging/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`log_file/2`

Access to the table of log files.

Compilation flags:

`static`

Template:

`log_file(Alias,File)`

Mode and number of proofs:

`log_file(?atom,?atom) - zero_or_more`

`define_log_file/2`

Defines a log file with alias `Alias` and file name `File`. If the log file already exists, its contents are kept. Logging is enabled by default.

Compilation flags:

`static`

Template:

```
define_log_file(Alias,File)
```

Mode and number of proofs:

```
define_log_file(+atom,+atom) - one
```

`init_log_file/2`

Initializes a new log file with alias `Alias` and file name `File`. If the log file already exists, its contents are erased. Logging is enabled by default.

Compilation flags:

```
static
```

Template:

```
init_log_file(Alias,File)
```

Mode and number of proofs:

```
init_log_file(+atom,+atom) - one
```

`log_event/2`

Logs an event `Event` to a log file with alias `Alias`. Fails if a log file with alias `Alias` is not defined.

Compilation flags:

```
static
```

Template:

```
log_event(Alias,Event)
```

Mode and number of proofs:

```
log_event(+atom,+nonvar) - zero_or_one
```

logging/1

True if logging to file with alias Alias is enabled.

Compilation flags:

static

Template:

logging(Alias)

Mode and number of proofs:

logging(+atom) - zero_or_one

enable_logging/1

Enables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

static

Template:

enable_logging(Alias)

Mode and number of proofs:

enable_logging(+atom) - zero_or_one

disable_logging/1

Disables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

static

Template:

disable_logging(Alias)

Mode and number of proofs:

disable_logging(+atom) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[logging](#)

1.47 loops

object

1.47.1 loop

Loop control structures predicates.

Availability:

`logtalk__load(loops(loader))`

Author: Paulo Moura

Version: 1:4:1

Date: 2020-12-20

Compilation flags:

`static, context_switching_calls`

Implements:

`public looppp`

Remarks:

(none)

Inherited public predicates:

`dowhile/2 fordownto/3 fordownto/4 fordownto/5 foreach/3 foreach/4 forto/3 forto/4 forto/5 whiledo/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.47.2 loopp

Loop control constructs protocol.

Availability:

`logtalk_load(loops(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2017-03-20

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - whiledo/2
 - dowhile/2
 - foreach/3
 - foreach/4
 - forto/3
 - forto/4
 - forto/5
 - fordownto/3
 - fordownto/4
 - fordownto/5
- Protected predicates
- Private predicates
- Operators

Public predicates

whiledo/2

While Condition is true do Action.

Compilation flags:

static

Template:

whiledo(Condition,Action)

Meta-predicate template:

whiledo(0,0)

Mode and number of proofs:

whiledo(+callable,@callable) - zero_or_one

dowhile/2

Do Action while Condition is true.

Compilation flags:

static

Template:

dowhile(Action,Condition)

Meta-predicate template:

dowhile(0,0)

Mode and number of proofs:

dowhile(@callable,+callable) - zero_or_one

foreach/3

For each Element in List call Goal.

Compilation flags:

static

Template:

foreach(Element,List,Goal)

Meta-predicate template:

foreach(*,*,0)

Mode and number of proofs:

foreach(@var,+list(term),@callable) - zero_or_one

foreach/4

For each Element in List at position Index call Goal. Index starts at 1.

Compilation flags:

static

Template:

foreach(Element,Index,List,Goal)

Meta-predicate template:

```
foreach(*,*,*,0)
```

Mode and number of proofs:

```
foreach(@var,@var,+list(term),@callable) - zero_or_one
```

forto/3

Calls Goal counting up from First to Last. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,0)
```

Mode and number of proofs:

```
forto(+number,+number,@callable) - zero_or_one
```

forto/4

Calls Goal counting up from First to Last and binding Count to each successive value. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(Count,First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,*,0)
```

Mode and number of proofs:

```
forto(@var,+number,+number,@callable) - zero_or_one
```

forto/5

Calls Goal counting up from First to Last and binding Count to each successive value. For convenience, First, Last, and Increment can be arithmetic expressions (uses Increment absolute value). Fails iff Goal fails.

Compilation flags:

static

Template:

forto(Count,First,Last,Increment,Goal)

Meta-predicate template:

forto(*,*,*,*,0)

Mode and number of proofs:

forto(@var,+number,+number,+number,@callable) - zero_or_one

fordownto/3

Calls Goal counting down from First to Last. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

fordownto(First,Last,Goal)

Meta-predicate template:

fordownto(*,*,0)

Mode and number of proofs:

fordownto(+number,+number,@callable) - zero_or_one

fordownto/4

Calls Goal counting down from First to Last and binding Count to each successive value. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

```
fordownto(Count,First,Last,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,@callable) - zero_or_one
```

`fordownto/5`

Calls Goal counting down from First to Last and binding Count to each successive value. For convenience, First, Last, and Decrement can be arithmetic expressions (uses Decrement absolute value). Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
fordownto(Count,First,Last,Decrement,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,+number,@callable) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`loop`

1.48 meta

object

1.48.1 meta

Some useful meta-predicates.

Availability:

```
logtalk_load(meta(loader))
```

Author: Paulo Moura

Version: 5:2:0

Date: 2016-10-06

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public metap
```

Aliases:

```
metap map/2 as succeeds/2
metap map/2 as maplist/2
metap map/3 as maplist/3
metap map/4 as maplist/4
metap map/5 as maplist/5
metap map/6 as maplist/6
metap map/7 as maplist/7
metap map/8 as maplist/8
metap include/3 as filter/3
metap fold_left/4 as foldl/4
metap fold_left_1/3 as foldl1/3
metap fold_right/4 as foldr/4
metap fold_right_1/3 as foldr1/3
metap scan_left/4 as scanl/4
metap scan_left_1/3 as scanl1/3
metap scan_right/4 as scanr/4
metap scan_right_1/3 as scanr1/3
```

Remarks:

```
(none)
```

Inherited public predicates:

exclude/3 findall_member/4 findall_member/5 fold_left/4 fold_left_1/3 fold_right/4
 fold_right_1/3 include/3 map/2 map/3 map/4 map/5 map/6 map/7 map/8 map_reduce/5
 partition/4 partition/6 scan_left/4 scan_left_1/3 scan_right/4 scan_right_1/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[meta_compiler](#)

[protocol](#)

1.48.2 metap

Useful meta-predicates protocol.

Availability:

`logtalk_load(meta(loader))`

Author: Paulo Moura

Version: 6:1:0

Date: 2015-12-23

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - include/3
 - exclude/3
 - findall_member/4
 - findall_member/5
 - partition/4
 - partition/6
 - fold_left/4
 - fold_left_1/3
 - scan_left/4
 - scan_left_1/3
 - fold_right/4
 - fold_right_1/3
 - scan_right/4
 - scan_right_1/3
 - map/2
 - map/3
 - map/4
 - map/5
 - map/6
 - map/7
 - map/8
 - map_reduce/5
- Protected predicates
- Private predicates
- Operators

Public predicates

`include/3`

Returns a list of all list elements that satisfy a predicate.

Compilation flags:

`static`

Template:

`include(Closure,List,Included)`

Meta-predicate template:

`include(1,*,*)`

Mode and number of proofs:

`include(+callable,+list,-list) - one`

`exclude/3`

Returns a list of all list elements that fail to satisfy a predicate.

Compilation flags:

`static`

Template:

`exclude(Closure,List,Excluded)`

Meta-predicate template:

`exclude(1,*,*)`

Mode and number of proofs:

`exclude(+callable,+list,-list) - one`

`findall_member/4`

Finds all members of a list that satisfy a given test.

Compilation flags:

`static`

Template:

```
findall_member(Member,List,Test,Result)
```

Meta-predicate template:

```
findall_member(*,*,0,*)
```

Mode and number of proofs:

```
findall_member(@term,+list,@callable,-list) - one
```

[findall_member/5](#)

Finds all members of a list that satisfy a given test appending the given tail to the result.

Compilation flags:

```
static
```

Template:

```
findall_member(Member,List,Test,Result,Tail)
```

Meta-predicate template:

```
findall_member(*,*,0,*,*)
```

Mode and number of proofs:

```
findall_member(@term,+list,@callable,-list,+list) - one
```

[partition/4](#)

Partition a list of elements in two lists using a predicate.

Compilation flags:

```
static
```

Template:

```
partition(Closure,List,Included,Excluded)
```

Meta-predicate template:

```
partition(1,*,*,*)
```

Mode and number of proofs:

```
partition(+callable,+list,-list,-list) - one
```

`partition/6`

Partitions a list in lists with values less, equal, and greater than a given value using a comparison predicate with the same argument order as `compare/3`.

Compilation flags:

`static`

Template:

`partition(Closure,List,Value,Less,Equal,Greater)`

Meta-predicate template:

`partition(3,*,*,*,*)`

Mode and number of proofs:

`partition(+callable,+list,@term,-list,-list,-list) - one`

`fold_left/4`

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

`static`

Template:

`fold_left(Closure,Accumulator,List,Result)`

Meta-predicate template:

`fold_left(3,*,*,*)`

Mode and number of proofs:

`fold_left(+callable,?term,+list,?term) - zero_or_more`

`fold_left_1/3`

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

`static`

Template:

```
fold_left_1(Closure,List,Result)
```

Meta-predicate template:

```
fold_left_1(3,*,*)
```

Mode and number of proofs:

```
fold_left_1(+callable,+list,?term) - zero_or_more
```

`scan_left/4`

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

```
static
```

Template:

```
scan_left(Closure,Accumulator,List,Results)
```

Meta-predicate template:

```
scan_left(3,*,*,*)
```

Mode and number of proofs:

```
scan_left(+callable,?term,+list,?list) - zero_or_more
```

`scan_left_1/3`

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

```
static
```

Template:

```
scan_left_1(Closure,List,Results)
```

Meta-predicate template:

```
scan_left_1(3,*,*)
```

Mode and number of proofs:

```
scan_left_1(+callable,+list,?list) - zero_or_more
```

fold_right/4

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

static

Template:

fold_right(Closure,Accumulator,List,Result)

Meta-predicate template:

fold_right(3,*,*,*)

Mode and number of proofs:

fold_right(+callable,?term,+list,?term) - zero_or_more

fold_right_1/3

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

static

Template:

fold_right_1(Closure,List,Result)

Meta-predicate template:

fold_right_1(3,*,*)

Mode and number of proofs:

fold_right_1(+callable,+list,?term) - zero_or_more

scan_right/4

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

static

Template:

```
scan_right(Closure,Accumulator,List,Results)
```

Meta-predicate template:

```
scan_right(3,*,*,*)
```

Mode and number of proofs:

```
scan_right(+callable,?term,+list,?list) - zero_or_more
```

`scan_right_1/3`

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

```
static
```

Template:

```
scan_right_1(Closure,List,Results)
```

Meta-predicate template:

```
scan_right_1(3,*,*)
```

Mode and number of proofs:

```
scan_right_1(+callable,+list,?list) - zero_or_more
```

`map/2`

True if the predicate succeeds for each list element.

Compilation flags:

```
static
```

Template:

```
map(Closure,List)
```

Meta-predicate template:

```
map(1,*)
```

Mode and number of proofs:

```
map(+callable,?list) - zero_or_more
```

map/3

List mapping predicate taken arguments from two lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(+callable,?list,?list) - zero_or_more

map/4

List mapping predicate taken arguments from three lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3)

Meta-predicate template:

map(3,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list) - zero_or_more

map/5

List mapping predicate taken arguments from four lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4)

Meta-predicate template:

```
map(4,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list) - zero_or_more
```

map/6

List mapping predicate taken arguments from five lists of elements.

Compilation flags:

```
static
```

Template:

```
map(Closure,List1,List2,List3,List4,List5)
```

Meta-predicate template:

```
map(5,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list) - zero_or_more
```

map/7

List mapping predicate taken arguments from six lists of elements.

Compilation flags:

```
static
```

Template:

```
map(Closure,List1,List2,List3,List4,List5,List6)
```

Meta-predicate template:

```
map(6,*,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list,?list) - zero_or_more
```

map/8

List mapping predicate taken arguments from seven lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4,List5,List6,List7)

Meta-predicate template:

map(7,*,*,*,*,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list,?list,?list,?list,?list) - zero_or_more

map_reduce/5

Map a list and apply a fold left (reduce) to the resulting list.

Compilation flags:

static

Template:

map_reduce(Map,Reduce,Accumulator,List,Result)

Meta-predicate template:

map_reduce(2,3,*,*,*)

Mode and number of proofs:

map_reduce(+callable,+callable,+term,?list,?term) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[meta](#)

1.49 meta_compiler

object

1.49.1 meta_compiler

Compiler for the meta object meta-predicates. Generates auxiliary predicates in order to avoid meta-call overheads.

Availability:

`logtalk_load(meta_compiler(loader))`

Author: Paulo Moura

Version: 0:13:1

Date: 2022-05-06

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Uses:

[gensym](#)

[list](#)

[logtalk](#)

Remarks:

- Usage: Compile source files with calls to the meta object meta-predicates using the compiler option `hook(meta_compiler)`.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
 - generated_predicate_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

generated_predicate_/1

Table of generated auxiliary predicates.

Compilation flags:

dynamic

Template:

generated_predicate_(Predicate)

Mode and number of proofs:

generated_predicate_(?predicate_indicator) - zero_or_more

Operators

(none)

See also:

meta

1.50 metagol

object

1.50.1 metagol

Inductive logic programming (ILP) system based on meta-interpretive learning.

Availability:

```
logtalk_load(metagol(loader))
```

Author: Metagol authors; adapted to Logtalk by Paulo Moura.

Version: 0:24:4

Date: 2024-03-15

Copyright: Copyright 2016 Metagol authors; Copyright 2018-2024 Paulo Moura

License: BSD-3-Clause

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_tokens//2
```

```
logtalk::message_prefix_stream/4
```

Uses:

```
coroutining
```

```
integer
```

```
list
```

```
logtalk
```

```
meta
```

```
timeout
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - learn/3
 - learn/2
 - learn_seq/2
 - learn_with_timeout/4
 - program_to_clauses/2
 - pprint/1
 - metarule/6
 - head_pred/1
 - body_pred/1
 - ibk/3
 - func_test/3
 - functional/0
 - min_clauses/1
 - max_clauses/1
 - max_inv_preds/1
 - metarule_next_id/1
 - timeout/1
- Protected predicates
 - pprint_clause/1
 - pprint_clauses/1
 - compiled_pred_call/2
 - body_pred_call/2
 - type/3
- Private predicates
- Operators

Public predicates

learn/3

Learns from a set of positive examples and a set of negative examples and returns the learned program.

Compilation flags:

static

Template:

```
learn(PositiveExamples,NegativeExamples,Program)
```

Mode and number of proofs:

```
learn(@list(example),@list(example),-list(term)) - zero_or_more
```

[learn/2](#)

Learns from a set of positive examples and a set of negative examples and pretty prints the learned program.

Compilation flags:

```
static
```

Template:

```
learn(PositiveExamples,NegativeExamples)
```

Mode and number of proofs:

```
learn(@list(example),@list(example)) - zero_or_more
```

[learn_seq/2](#)

Learns from a sequence of examples represented as a list of PositiveExamples/NegativeExamples elements and returns the learned program.

Compilation flags:

```
static
```

Template:

```
learn_seq(Examples,Program)
```

Mode and number of proofs:

```
learn_seq(@list(example),-list(clause)) - zero_or_one
```

`learn_with_timeout/4`

Learns from a set of positive examples and a set of negative examples and returns the learned program constrained by the given timeout or its default value.

Compilation flags:

`static`

Template:

`learn_with_timeout(PositiveExamples,NegativeExamples,Program,Timeout)`

Mode and number of proofs:

`learn_with_timeout(@list(example),@list(example),-list(term),+number) - zero_or_one_or_error`

`learn_with_timeout(@list(example),@list(example),-list(term),-number) - zero_or_one_or_error`

Exceptions:

Learning does not complete in the allowed time:

`timeout(learn(PositiveExamples,NegativeExamples,Program))`

`program_to_clauses/2`

Converts a learned program into a list of clauses.

Compilation flags:

`static`

Template:

`program_to_clauses(Program,Clauses)`

Mode and number of proofs:

`program_to_clauses(@list(term),-list(clause)) - one`

`pprint/1`

Pretty prints a learned program.

Compilation flags:

`static`

Template:

`pprint(Program)`

Mode and number of proofs:

`pprint(@list(term)) - one`

`metarule/6`

Compilation flags:

`static`

`head_pred/1`

Compilation flags:

`static`

`body_pred/1`

Compilation flags:

`dynamic`

ibk/3

Compilation flags:
static

func_test/3

Compilation flags:
static

functional/0

Compilation flags:
dynamic

min_clauses/1

Compilation flags:
dynamic

max_clauses/1

Compilation flags:
dynamic

max_inv_preds/1

Compilation flags:
dynamic

metarule_next_id/1

Compilation flags:
dynamic

timeout/1

Compilation flags:
dynamic

Protected predicates

pprint_clause/1

Compilation flags:
static

pprint_clauses/1

Compilation flags:
static

compiled_pred_call/2

Compilation flags:
dynamic

body_pred_call/2

Compilation flags:
dynamic

type/3

Compilation flags:
dynamic

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
protocol

1.50.2 metagol_example_protocol

Convenient learning predicates for use in examples and unit tests.

Availability:
logtalk_load(metagol(loader))

Author: Paulo Moura.
Version: 0:1:1
Date: 2024-03-15

License: BSD-3-Clause

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - learn/1
 - learn/0
- Protected predicates
- Private predicates
- Operators

Public predicates

learn/1

Learns and returns set of clauses.

Compilation flags:

static

Template:

learn(Clauses)

Mode and number of proofs:

learn(-list(clause)) - zero_or_more

learn/0

Learns and prints a set of clauses.

Compilation flags:

static

Mode and number of proofs:

learn - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.51 mutations

object

1.51.1 default_atom_mutations

Default atom mutations.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Provides:

`mutations_store::mutation/4`

Uses:

`fast_random`

`list`

`type`

Remarks:

(none)

Inherited public predicates:

(none)

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`type`

`object`

1.51.2 default_compound_mutations

Default compound mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

`static, context_switching_calls`

Provides:

`mutations_store::mutation/4`

Uses:

`mutations_store`

Remarks:

(none)

Inherited public predicates:

(none)

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[type](#)

[object](#)

1.51.3 `default_float_mutations`

Default float mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

`static, context_switching_calls`

Provides:

`mutations_store::mutation/4`

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)

- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[type](#)

[object](#)

1.51.4 default_integer_mutations

Default integer mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

`static, context_switching_calls`

Provides:

`mutations_store::mutation/4`

Uses:

`fast_random`

`list`

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[type](#)

[object](#)

1.51.5 `default_list_mutations`

Default list mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Provides:

mutations_store::mutation/4

Uses:

fast_random

list

mutations_store

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[type](#)

[category](#)

1.51.6 mutations

Adds mutations support to the library type object.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-11-23

Compilation flags:

`static`

Complements:

[type](#)

Uses:

[mutations_store](#)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [mutation/3](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

mutation/3

Returns a random mutation of a term into another term of the same type. The input Term is assume to be valid for the given Type.

Compilation flags:

static

Template:

mutation(Type,Term,Mutation)

Mode and number of proofs:

mutation(@callable,@term,-term) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.51.7 mutations_store

Stores mutation definitions for selected types. User extensible by defining objects or categories defining clauses for the mutation/3 predicate and using this object as a hook object for their compilation.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Uses:

fast_random

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
 - mutation/3
 - counter/2
- Protected predicates
- Private predicates
 - mutation/4
 - counter_/2
- Operators

Public predicates

mutation/3

Returns a random mutation of a term into another term of the same type. The input Term is assumed to be valid for the given Type.

Compilation flags:

static

Template:

mutation(Type,Term,Mutation)

Mode and number of proofs:

mutation(@callable,@term,-term) - one

counter/2

Table of the number of mutations available per type.

Compilation flags:

static

Template:

counter(Type,N)

Mode and number of proofs:

counter(?callable,?positive_integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

mutation/4

Returns a random mutation of a term into another term of the same type using mutator N. The input Term is assume to be valid for the given Type.

Compilation flags:

static, multifile

Template:

mutation(Type,N,Term,Mutation)

Mode and number of proofs:

mutation(?callable,?positive_integer,@term,-term) - zero_or_more

counter_/2

Internal counter for the number of mutations available for a given type.

Compilation flags:

dynamic

Template:

counter_(Type,N)

Mode and number of proofs:

counter_(?callable,?positive_integer) - zero_or_more

Operators

(none)

See also:

type

1.52 nested_dictionaries

object

1.52.1 navltree

Nested dictionary implementation based on the AVL tree implementation. Uses standard order to compare keys.

Availability:

logtalk_load(nested_dictionaries(loader))

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

static, context_switching_calls

Implements:

public nested_dictionary_protocol

Extends:

private avltree

Remarks:

(none)

Inherited public predicates:

as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

nrbtree, nbintree

object

1.52.2 nbintree

Nested dictionary implementation based on the simple binary tree implementation. Uses standard order to compare keys.

Availability:

```
logtalk_load(nested_dictionaries(loader))
```

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public nested_dictionary_protocol
```

Extends:

```
private bintree
```

Remarks:

(none)

Inherited public predicates:

```
as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3  
new/1 update_in/4 update_in/5
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[nrbtree](#), [navltree](#)

protocol

1.52.3 nested_dictionary_protocol

Nested dictionary protocol.

Availability:

`logtalk_load(nested_dictionaries(loader))`

Author: Paul Brown and Paulo Moura

Version: 0:1:0

Date: 2021-04-07

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - new/1
 - empty/1
 - as_nested_dictionary/2
 - as_curly_bracketed/2
 - lookup_in/3
 - update_in/4
 - update_in/5
 - insert_in/4
 - delete_in/4
- Protected predicates
- Private predicates
- Operators

Public predicates

new/1

Create an empty (nested) dictionary.

Compilation flags:

static

Template:

new(Dictionary)

Mode and number of proofs:

new(--dictionary) - one

empty/1

True iff the dictionary is empty.

Compilation flags:

static

Template:

```
empty(Dictionary)
Mode and number of proofs:
empty(@dictionary) - zero_or_one
```

`as_nested_dictionary/2`

Creates a (nested) dictionary term from a curly-bracketed term representation.

Compilation flags:
static

Template:

```
as_nested_dictionary(Term,Dictionary)
Mode and number of proofs:
as_nested_dictionary(++term,--dictionary) - one_or_error
```

`as_curly_bracketed/2`

Creates a a curly-bracketed term representation from a (nested) dictionary.

Compilation flags:
static

Template:

```
as_curly_bracketed(Dictionary,Term)
Mode and number of proofs:
as_curly_bracketed(+dictionary,--term) - one_or_error
```

lookup_in/3

Lookup a chain of keys in a nested dictionary. Unifies Value with Dictionary when Keys is the empty list.

Compilation flags:

static

Template:

lookup_in(Keys,Value,Dictionary)

Mode and number of proofs:

lookup_in(++list(ground),?term,+dictionary) - zero_or_more

update_in/4

Updates the value found by traversing through the nested keys.

Compilation flags:

static

Template:

update_in(OldDictionary,Keys,Value,NewDictionary)

Mode and number of proofs:

update_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one

update_in/5

Updates the value found by traversing through the nested keys, only succeeding if the value found after traversal matches the old value.

Compilation flags:

static

Template:

update_in(OldDictionary,Keys,OldValue,NewValue,NewDictionary)

Mode and number of proofs:

update_in(+dictionary,++list(ground),?term,++term,--dictionary) - zero_or_one

`insert_in/4`

Inserts a key-value pair into a dictionary by traversing through the nested keys. When the key already exists, the associated value is updated.

Compilation flags:

`static`

Template:

`insert_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

`insert_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one`

`delete_in/4`

Deletes a matching key-value pair from a dictionary by traversing through the nested keys, returning the updated dictionary.

Compilation flags:

`static`

Template:

`delete_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

`delete_in(+dictionary,++list(ground),?term,--dictionary) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[navltree](#), [nbintree](#), [nrbtree](#)

object

1.52.4 nrbtree

Nested dictionary implementation based on the red-black tree implementation. Uses standard order to compare keys.

Availability:

`logtalk__load(nested__dictionaries(loader))`

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

`static, context__switching__calls`

Implements:

`public nested__dictionary__protocol`

Extends:

`private rbtree`

Remarks:

(none)

Inherited public predicates:

`as__curly__bracketed/2 as__nested__dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5`

- [Public predicates](#)
- [Protected predicates](#)

- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[navltree](#), [nbintree](#)

1.53 optionals

object

1.53.1 maybe

Types and predicates for type-checking and handling optional terms. Inspired by Haskell.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

`static, context_switching_calls`

Provides:

`type::type/1`

```
type::check/2
arbitrary::arbitrary/1
arbitrary::arbitrary/2
```

Uses:

```
optional
optional(Optional)
random
type
```

Remarks:

- Type-checking support: Defines type maybe(Type) for checking optional terms where the value hold by the optional term must be of the given type.
- QuickCheck support: Defines clauses for the arbitrary::arbitrary/1-2 predicates to allow generating random values for the maybe(Type) type.

Inherited public predicates:

(none)

- Public predicates
 - cat/2
 - Protected predicates
 - Private predicates
 - Operators

Public predicates

cat/2

Returns the values stored in the non-empty optional terms.

Compilation flags:

static

Template:

cat(Optionals,Values)

Mode and number of proofs:

cat(+list(optional),-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`optional`, `optional(Optional)`, `type`, `arbitrary`
`object`

1.53.2 optional

Constructors for optional terms. An optional term is either empty or holds a value. Optional terms should be regarded as opaque terms and always used with the `optional/1` object by passing the optional term as a parameter.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

`static`, `context_switching_calls`

Provides:

`type::type/1`
`type::check/2`

Remarks:

- Type-checking support: This object also defines a type optional for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - of/2
 - from_goal/3
 - from_goal/2
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

Constructs an empty optional term.

Compilation flags:

static

Template:

empty(Optional)

Mode and number of proofs:

empty(--nonvar) - one

of/2

Constructs an optional term holding the given value.

Compilation flags:

static

Template:

of(Value,Optional)

Mode and number of proofs:

of(@term,--nonvar) - one

from_goal/3

Constructs an optional term holding a value bound by calling the given goal. Returns an empty optional term if the goal fails or throws an error.

Compilation flags:

static

Template:

from_goal(Goal,Value,Optional)

Meta-predicate template:

from_goal(0,*,*)

Mode and number of proofs:

from_goal(+callable,--term,--nonvar) - one

from_goal/2

Constructs an optional term holding a value bound by calling the given closure. Returns an empty optional term if the closure fails or throws an error.

Compilation flags:

static

Template:

from_goal(Closure,Optional)

Meta-predicate template:

from_goal(1,*)

Mode and number of proofs:

from_goal(+callable,--nonvar) - one

`from_generator/3`

Constructs optional terms with the values generated by calling the given goal. On goal error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Goal, Value, Optional)`

Meta-predicate template:

`from_generator(0, *, *)`

Mode and number of proofs:

`from_generator(+callable, --term, --nonvar) - one_or_more`

`from_generator/2`

Constructs optional terms with the values generated by calling the given closure. On closure error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Closure, Optional)`

Meta-predicate template:

`from_generator(1, *)`

Mode and number of proofs:

`from_generator(+from_generator, --nonvar) - one_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`optional(Optional)`, type

object

1.53.3 `optional(Optional)`

Optional term handling predicates. Requires passing an optional term (constructed using the optional object predicates) as a parameter.

Availability:

`logtalk__load(optionals(loader))`

Author: Paulo Moura

Version: 1:7:0

Date: 2019-11-26

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `is_empty/0`
 - `is_present/0`
 - `if_empty/1`

- if_present/1
- if_present_or_else/2
- filter/2
- map/2
- flat_map/2
- or/2
- get/1
- or_else/2
- or_else_get/2
- or_else_call/2
- or_else_fail/1
- or_else_throw/2
- Protected predicates
- Private predicates
- Operators

Public predicates

is_empty/0

True if the optional term is empty. See also the if_empty/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_empty - zero_or_one

is_present/0

True if the optional term holds a value. See also the if_present/1 predicate.

Compilation flags:

static

Mode and number of proofs:

`is_present - zero_or_one`

`if_empty/1`

Calls a goal if the optional term is empty. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_empty(Goal)`

Meta-predicate template:

`if_empty(0)`

Mode and number of proofs:

`if_empty(+callable) - zero_or_more`

`if_present/1`

Applies a closure to the value hold by the optional term if not empty. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_present(Closure)`

Meta-predicate template:

`if_present(1)`

Mode and number of proofs:

`if_present(+callable) - zero_or_more`

`if_present_or_else/2`

Applies a closure to the value hold by the optional term if not empty. Otherwise calls the given goal.

Compilation flags:

`static`

Template:

`if_present_or_else(Closure,Goal)`

Meta-predicate template:

`if_present_or_else(1,0)`

Mode and number of proofs:

`if_present_or_else(+callable,+callable) - zero_or_more`

`filter/2`

Returns the optional term when it is not empty and the value it holds satisfies a closure. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`filter(Closure,NewOptional)`

Meta-predicate template:

`filter(1,*)`

Mode and number of proofs:

`filter(+callable,--nonvar) - one`

`map/2`

When the optional term is not empty and mapping a closure with the value it holds and the new value as additional arguments is successful, returns an optional term with the new value. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`map(Closure,NewOptional)`

Meta-predicate template:

`map(2,*)`

Mode and number of proofs:

`map(+callable,--nonvar) - one`

`flat_map/2`

When the optional term is not empty and mapping a closure with the value it holds and the new optional term as additional arguments is successful, returns the new optional term. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`flat_map(Closure,NewOptional)`

Meta-predicate template:

`flat_map(2,*)`

Mode and number of proofs:

`flat_map(+callable,--nonvar) - one`

`or/2`

Returns the same optional term if not empty. Otherwise calls closure to generate a new optional term. Fails if optional term is empty and calling the closure fails or throws an error.

Compilation flags:

`static`

Template:

`or(NewOptional,Closure)`

Meta-predicate template:

`or(*,1)`

Mode and number of proofs:

`or(--term,@callable) - zero_or_one`

`get/1`

Returns the value hold by the optional term if not empty. Throws an error otherwise.

Compilation flags:

`static`

Template:

`get(Value)`

Mode and number of proofs:

`get(--term) - one_or_error`

Exceptions:

Optional is empty:

`existence_error(optional_term,Optional)`

`or_else/2`

Returns the value hold by the optional term if not empty or the given default value if the optional term is empty.

Compilation flags:

`static`

Template:

`or_else(Value,Default)`

Mode and number of proofs:

`or_else(--term,@term) - one`

`or_else_get/2`

Returns the value hold by the optional term if not empty. Applies a closure to compute the value otherwise. Throws an error when the optional term is empty and the value cannot be computed.

Compilation flags:

`static`

Template:

```
or_else_get(Value,Closure)
```

Meta-predicate template:

```
or_else_get(*,1)
```

Mode and number of proofs:

```
or_else_get(--term,+callable) - one_or_error
```

Exceptions:

Optional is empty and the term cannot be computed:

```
existence_error(optional_term,Optional)
```

`or_else_call/2`

Returns the value hold by the optional term if not empty or calls a goal deterministically if the optional term is empty.

Compilation flags:

```
static
```

Template:

```
or_else_call(Value,Goal)
```

Meta-predicate template:

```
or_else_call(*,0)
```

Mode and number of proofs:

```
or_else_call(--term,+callable) - zero_or_one
```

`or_else_fail/1`

Returns the value hold by the optional term if not empty. Fails otherwise. Usually called to skip over empty optional terms.

Compilation flags:

```
static
```

Template:

```
or_else_fail(Value)
```

Mode and number of proofs:

```
or_else_fail(--term) - zero_or_one
```

`or_else_throw/2`

Returns the value hold by the optional term if not empty. Throws the given error otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value,Error)`

Mode and number of proofs:

`or_else_throw(--term,@nonvar) - one_or_error`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`optional`

1.54 options

`category`

1.54.1 options

Options processing predicates. Options are represented by compound terms where the functor is the option name.

Availability:

`logtalk_load(options(loader))`

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

`static`

Implements:

`public options_protocol`

Uses:

`list`

Remarks:

`(none)`

Inherited public predicates:

`check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
valid_option/1 valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.54.2 options__protocol

Options protocol.

Availability:

logtalk__load(options(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `check_option/1`
 - `check_options/1`
 - `valid_option/1`
 - `valid_options/1`
 - `default_option/1`
 - `default_options/1`
 - `option/2`
 - `option/3`
- Protected predicates
 - `merge_options/2`
 - `fix_options/2`
 - `fix_option/2`
- Private predicates
- Operators

Public predicates

`check_option/1`

Succeeds if the option is valid. Throws an error otherwise.

Compilation flags:

`static`

Template:

`check_option(Option)`

Mode and number of proofs:

`check_option(@term) - one_or_error`

Exceptions:

Option is a variable:

`instantiation_error`

Option is neither a variable nor a compound term:

`type_error(compound,Option)`

Option is a compound term but not a valid option:

`domain_error(option,Option)`

`check_options/1`

Succeeds if all the options in a list are valid. Throws an error otherwise.

Compilation flags:

`static`

Template:

`check_options(Options)`

Mode and number of proofs:

`check_options(@term) - one_or_error`

Exceptions:

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

`valid_option/1`

Succeeds if the option is valid.

Compilation flags:

`static`

Template:

`valid_option(Option)`

Mode and number of proofs:

`valid_option(@term) - zero_or_one`

`valid_options/1`

Succeeds if all the options in a list are valid.

Compilation flags:

`static`

Template:

`valid_options(Options)`

Mode and number of proofs:

`valid_options(@term) - one`

`default_option/1`

Enumerates, by backtracking, the default options.

Compilation flags:

`static`

Template:

`default_option(Option)`

Mode and number of proofs:

`default_option(?compound) - zero_or_more`

`default_options/1`

Returns a list of the default options.

Compilation flags:

`static`

Template:

`default_options(Options)`

Mode and number of proofs:

`default_options(-list(compound)) - one`

`option/2`

True iff Option unifies with the first occurrence of the same option in the Options list.

Compilation flags:

static

Template:

`option(Option,Options)`

Mode and number of proofs:

`option(+compound,+list(compound)) - zero_or_one`

`option/3`

True iff Option unifies with the first occurrence of the same option in the Options list or, when that is not the case, if Option unifies with Default.

Compilation flags:

static

Template:

`option(Option,Options,Default)`

Mode and number of proofs:

`option(+compound,+list(compound),+compound) - zero_or_one`

Protected predicates

`merge_options/2`

Merges the user options with the default options, returning the final list of options. Calls the `fix_options/2` predicate to preprocess the options after merging. Callers must ensure, if required, that the user options are valid.

Compilation flags:

static

Template:

```
merge_options(UserOptions,Options)
```

Mode and number of proofs:

```
merge_options(+list(compound),-list(compound)) - one
```

`fix_options/2`

Fixes a list of options, returning the list of options.

Compilation flags:

```
static
```

Template:

```
fix_options(Options,FixedOptions)
```

Mode and number of proofs:

```
fix_options(+list(compound),-list(compound)) - one
```

`fix_option/2`

Fixes an option.

Compilation flags:

```
static
```

Template:

```
fix_option(Option,FixedOption)
```

Mode and number of proofs:

```
fix_option(+compound,-compound) - zero_or_one
```

Private predicates

(none)

Operators

(none)

See also:

[options](#)

1.55 os

object

1.55.1 os

Portable operating-system access predicates.

Availability:

`logtalk_load(os(loader))`

Author: Paulo Moura

Version: 1:100:2

Date: 2024-03-25

Compilation flags:

`static, context_switching_calls`

Implements:

`public osp`

Uses:

[list](#)

Aliases:

`osp absolute_file_name/2` as `expand_path/2`

Remarks:

- File path expansion: To ensure portability, all file paths are expanded before being handed to the backend Prolog system.
- Exception terms: Currently, there is no standardization of the exception terms thrown by the different backend Prolog systems.
- B-Prolog portability: The `wall_time/1` predicate is not supported.

- CxProlog portability: The `date_time/7` predicate returns zeros for all arguments.
- JIProlog portability: The `file_permission/2` and `command_line_arguments/1` predicates are not supported.
- Quintus Prolog: The `pid/1` and `shell/2` predicates are not supported.
- XSB portability: The `command_line_arguments/1` predicate is not supported.

Inherited public predicates:

`absolute_file_name/2` `change_directory/1` `command_line_arguments/1` `copy_file/2` `cpu_time/1`
`date_time/7` `decompose_file_name/3` `decompose_file_name/4` `delete_directory/1` `delete_file/1`
`directory_exists/1` `directory_files/2` `directory_files/3` `ensure_directory/1` `ensure_file/1`
`environment_variable/2` `file_exists/1` `file_modification_time/2` `file_permission/2` `file_size/2`
`full_device_path/1` `internal_os_path/2` `is_absolute_file_name/1` `make_directory/1`
`make_directory_path/1` `null_device_path/1` `operating_system_machine/1`
`operating_system_name/1` `operating_system_release/1` `operating_system_type/1`
`path_concat/3` `pid/1` `read_only_device_path/1` `rename_file/2` `shell/1` `shell/2` `sleep/1`
`temporary_directory/1` `time_stamp/1` `wall_time/1` `working_directory/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`os_types`

`category`

1.55.2 `os_types`

A set of operating-system related types.

Availability:

```
logtalk_load(os(loader))
```

Author: Paulo Moura

Version: 1:4:0

Date: 2021-02-12

Compilation flags:

```
static
```

Provides:

```
type::type/1  
type::check/2
```

Uses:

```
list  
os
```

Remarks:

- Provided types: This category adds `file`, `file(Extensions)`, `file(Extensions,Permissions)`, `directory`, `directory(Permissions)`, and `environment_variable` types for type-checking when using the type library object.
- Type `file`: For checking if a term is an atom and an existing file.
- Type `file(Extensions)`: For checking if a term is an atom and an existing file with one of the listed extensions (specified as `'.ext'`).
- Type `file(Extensions,Permissions)`: For checking if a term is an atom and an existing file with one of the listed extensions (specified as `'.ext'`) and listed permissions (`{read, write, execute}`).
- Type `directory`: For checking if a term is an atom and an existing directory.
- Type `directory(Permissions)`: For checking if a term is an atom and an existing directory with the listed permissions (`{read, write, execute}`).
- Type `environment_variable`: For checking if a term is an atom and an existing environment variable.

Inherited public predicates:

```
(none)
```


- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[osp](#), [os](#), [type](#)

[protocol](#)

1.55.3 osp

Portable operating-system access protocol.

Availability:

`logtalk_load(os(loader))`

Author: Paulo Moura

Version: 1:38:1

Date: 2024-03-25

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- Error handling: Predicates that require a file or directory to exist throw an error when that is not the case. But the exact exception term is currently backend Prolog compiler dependent.

Inherited public predicates:

(none)

- Public predicates
 - pid/1
 - shell/2
 - shell/1
 - is_absolute_file_name/1
 - absolute_file_name/2
 - decompose_file_name/3
 - decompose_file_name/4
 - path_concat/3
 - internal_os_path/2
 - make_directory/1
 - make_directory_path/1
 - delete_directory/1
 - change_directory/1
 - working_directory/1
 - temporary_directory/1
 - null_device_path/1
 - full_device_path/1
 - read_only_device_path/1
 - directory_files/2
 - directory_files/3
 - directory_exists/1
 - ensure_directory/1
 - file_exists/1
 - file_modification_time/2
 - file_size/2
 - file_permission/2
 - copy_file/2

- rename_file/2
- delete_file/1
- ensure_file/1
- environment_variable/2
- time_stamp/1
- date_time/7
- cpu_time/1
- wall_time/1
- operating_system_type/1
- operating_system_name/1
- operating_system_machine/1
- operating_system_release/1
- command_line_arguments/1
- sleep/1
- Protected predicates
- Private predicates
- Operators

Public predicates

pid/1

Returns the process identifier of the running process.

Compilation flags:

static

Template:

pid(PID)

Mode and number of proofs:

pid(-integer) - one

shell/2

Runs an operating-system shell command and returns its exit status.

Compilation flags:

static

Template:

shell(Command,Status)

Mode and number of proofs:

shell(+atom,-integer) - one

shell/1

Runs an operating-system shell command.

Compilation flags:

static

Template:

shell(Command)

Mode and number of proofs:

shell(+atom) - zero_or_one

is_absolute_file_name/1

True iff the argument is an absolute file path. On POSIX systems, this predicate is true if File starts with a /. On Windows systems, this predicate is true if File starts with a drive letter. No attempt is made to expand File as a path.

Compilation flags:

static

Template:

is_absolute_file_name(File)

Mode and number of proofs:

is_absolute_file_name(+atom) - zero_or_one

`absolute_file_name/2`

Expands a file name to an absolute file path. An environment variable at the beginning of the file name is also expanded.

Compilation flags:

static

Template:

`absolute_file_name(File,Path)`

Mode and number of proofs:

`absolute_file_name(+atom,-atom) - one`

`decompose_file_name/3`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent) and its basename (which can be the empty atom).

Compilation flags:

static

Template:

`decompose_file_name(File,Directory,Basename)`

Mode and number of proofs:

`decompose_file_name(+atom,?atom,?atom) - one`

`decompose_file_name/4`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent), name (that can be the empty atom), and extension (which starts with a `.` when defined; the empty atom otherwise).

Compilation flags:

static

Template:

```
decompose_file_name(File,Directory,Name,Extension)
```

Mode and number of proofs:

```
decompose_file_name(+atom,?atom,?atom,?atom) - one
```

`path_concat/3`

Concatenates a path prefix and a path suffix, adding a / separator if required. Returns Suffix when it is an absolute path. Returns Prefix with a trailing / appended if missing when Suffix is the empty atom.

Compilation flags:

```
static
```

Template:

```
path_concat(Prefix,Suffix,Path)
```

Mode and number of proofs:

```
path_concat(+atom,+atom,--atom) - one
```

`internal_os_path/2`

Converts between the internal path representation (which is backend dependent) and the operating-system native path representation.

Compilation flags:

```
static
```

Template:

```
internal_os_path(InternalPath,OSPath)
```

Mode and number of proofs:

```
internal_os_path(+atom,-atom) - one
```

```
internal_os_path(-atom,+atom) - one
```

`make_directory/1`

Makes a new directory. Succeeds if the directory already exists.

Compilation flags:

`static`

Template:

`make_directory(Directory)`

Mode and number of proofs:

`make_directory(+atom) - one`

`make_directory_path/1`

Makes a new directory creating all the intermediate directories if necessary. Succeeds if the directory already exists.

Compilation flags:

`static`

Template:

`make_directory_path(Directory)`

Mode and number of proofs:

`make_directory_path(+atom) - one`

`delete_directory/1`

Deletes an empty directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`delete_directory(Directory)`

Mode and number of proofs:

`delete_directory(+atom) - one_or_error`

`change_directory/1`

Changes current working directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`change_directory(Directory)`

Mode and number of proofs:

`change_directory(+atom) - one_or_error`

`working_directory/1`

Current working directory.

Compilation flags:

`static`

Template:

`working_directory(Directory)`

Mode and number of proofs:

`working_directory(?atom) - zero_or_one`

`temporary_directory/1`

Temporary directory. Tries first environment variables: TEMP and TMP on Windows systems; TMPDIR, TMP, TEMP, and TEMPDIR on POSIX systems. When not defined, tries default locations. Returns the working directory as last resort.

Compilation flags:

`static`

Template:

temporary_directory(Directory)

Mode and number of proofs:

temporary_directory(?atom) - one

null_device_path/1

Null device path: nul on Windows systems and /dev/null on POSIX systems.

Compilation flags:

static

Template:

null_device_path(Path)

Mode and number of proofs:

null_device_path(?atom) - one

full_device_path/1

Full device path: /dev/full on Linux and BSD systems. Fails on other systems. Experimental.

Compilation flags:

static

Template:

full_device_path(Path)

Mode and number of proofs:

full_device_path(?atom) - zero_or_one

`read_only_device_path/1`

Read-only device path: `/dev/urandom` on macOS. Fails on other systems. Experimental.

Compilation flags:

`static`

Template:

`read_only_device_path(Path)`

Mode and number of proofs:

`read_only_device_path(?atom) - zero_or_one`

`directory_files/2`

Returns a list of all files (including directories, regular files, and hidden directories and files) in a directory. File paths are relative to the directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`directory_files(Directory,Files)`

Mode and number of proofs:

`directory_files(+atom,-list(atom)) - one_or_error`

`directory_files/3`

Returns a list of files filtered using the given list of options. Invalid options are ignored. Default option values are equivalent to `directory_files/2`. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`directory_files(Directory,Files,Options)`

Mode and number of proofs:

`directory_files(+atom,-list(atom),+list(compound)) - one_or_error`

Remarks:

- Option paths/1: Possible values are relative and absolute. Default is relative.
 - Option type/1: Possible values are all, regular, directory. Default is all.
 - Option extensions/1: Argument is a list of required extensions (using the format '.ext'). Default is the empty list.
 - Option prefixes/1: Argument is a list of required file prefixes (atoms). Default is the empty list.
 - Option suffixes/1: Argument is a list of required file suffixes (atoms). Default is the empty list.
 - Option dot_files/1: Possible values are true and false. Default is true.
-

directory_exists/1

True if the specified directory exists (irrespective of directory permissions).

Compilation flags:

static

Template:

directory_exists(Directory)

Mode and number of proofs:

directory_exists(+atom) - zero_or_one

ensure_directory/1

Ensures that a directory exists, creating it if necessary.

Compilation flags:

static

Template:

ensure_directory(Directory)

Mode and number of proofs:

ensure_directory(+atom) - one

`file_exists/1`

True if the specified file exists and is a regular file (irrespective of file permissions).

Compilation flags:

`static`

Template:

`file_exists(File)`

Mode and number of proofs:

`file_exists(+atom) - zero_or_one`

`file_modification_time/2`

File modification time (which can be used for comparison). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_modification_time(File,Time)`

Mode and number of proofs:

`file_modification_time(+atom,-integer) - one_or_error`

`file_size/2`

File size (in bytes). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_size(File,Size)`

Mode and number of proofs:

`file_size(+atom,-integer) - one_or_error`

`file_permission/2`

True iff the specified file has the specified permission (read, write, or execute). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_permission(File,Permission)`

Mode and number of proofs:

`file_permission(+atom,+atom) - zero_or_one_or_error`

`copy_file/2`

Copies a file. Throws an error if the original file does not exist or if the copy cannot be created.

Compilation flags:

`static`

Template:

`copy_file(File,Copy)`

Mode and number of proofs:

`copy_file(+atom,+atom) - one_or_error`

`rename_file/2`

Renames a file or a directory. Throws an error if the file or directory does not exist.

Compilation flags:

`static`

Template:

`rename_file(Old,New)`

Mode and number of proofs:

`rename_file(+atom,+atom) - one_or_error`

`delete_file/1`

Deletes a file. Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`delete_file(File)`

Mode and number of proofs:

`delete_file(+atom) - one_or_error`

`ensure_file/1`

Ensures that a file exists, creating it if necessary.

Compilation flags:

`static`

Template:

`ensure_file(File)`

Mode and number of proofs:

`ensure_file(+atom) - one`

`environment_variable/2`

Returns an environment variable value. Fails if the variable does not exists.

Compilation flags:

`static`

Template:

`environment_variable(Variable,Value)`

Mode and number of proofs:

`environment_variable(+atom,?atom) - zero_or_one`

`time_stamp/1`

Returns a system-dependent time stamp, which can be used for sorting, but should be regarded otherwise as an opaque term.

Compilation flags:

`static`

Template:

`time_stamp(Time)`

Mode and number of proofs:

`time_stamp(-ground) - one`

`date_time/7`

Returns the current date and time. Note that most backends do not provide sub-second accuracy and in those cases the value of the Milliseconds argument is always zero.

Compilation flags:

`static`

Template:

`date_time(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)`

Mode and number of proofs:

`date_time(-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one`

`cpu_time/1`

System cpu time in seconds.

Compilation flags:

`static`

Template:

`cpu_time(Seconds)`

Mode and number of proofs:

`cpu_time(-number) - one`

`wall_time/1`

Wall time in seconds.

Compilation flags:

`static`

Template:

`wall_time(Seconds)`

Mode and number of proofs:

`wall_time(-number) - one`

`operating_system_type/1`

Operating system type. Possible values are unix, windows, and unknown.

Compilation flags:

`static`

Template:

`operating_system_type(Type)`

Mode and number of proofs:

`operating_system_type(?atom) - zero_or_one`

`operating_system_name/1`

Operating system name. On POSIX systems, it returns the value of `uname -s`. On Windows systems, it returns `'Windows'`.

Compilation flags:

`static`

Template:

`operating_system_name(Name)`

Mode and number of proofs:

`operating_system_name(?atom) - zero_or_one`

`operating_system_machine/1`

Operating system hardware platform. On POSIX systems, it returns the value of `uname -m`. On Windows systems, it returns the value of the `PROCESSOR_ARCHITECTURE` environment variable.

Compilation flags:

`static`

Template:

`operating_system_machine(Machine)`

Mode and number of proofs:

`operating_system_machine(?atom) - zero_or_one`

`operating_system_release/1`

Operating system release. On POSIX systems, it returns the value of `uname -r`. On Windows systems, it uses WMI code.

Compilation flags:

`static`

Template:

`operating_system_release(Release)`

Mode and number of proofs:

`operating_system_release(?atom) - zero_or_one`

`command_line_arguments/1`

Returns a list with the command line arguments that occur after --.

Compilation flags:

`static`

Template:

`command_line_arguments(Arguments)`

Mode and number of proofs:

`command_line_arguments(-list(atom)) - one`

`sleep/1`

Suspends execution the given number of seconds.

Compilation flags:

`static`

Template:

`sleep(Seconds)`

Mode and number of proofs:

`sleep(+number) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`os`, `os_types`

1.56 packs

protocol

1.56.1 pack_protocol

Pack specification protocol. Objects implementing this protocol should be named after the pack with a `_pack` suffix and saved in a file with the same name as the object.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:17:0

Date: 2024-02-29

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)

- name/1
- description/1
- license/1
- home/1
- version/6
- note/3
- Protected predicates
- Private predicates
- Operators

Public predicates

name/1

Pack name.

Compilation flags:
static

Template:
name(Name)
Mode and number of proofs:
name(?atom) - zero_or_one

description/1

Pack one line description.

Compilation flags:
static

Template:
description(Description)
Mode and number of proofs:
description(?atom) - zero_or_one

license/1

Pack license. Specified using the identifier from the SPDX License List (<https://spdx.org/licenses/>) when possible.

Compilation flags:

static

Template:

license(License)

Mode and number of proofs:

license(?atom) - zero_or_one

home/1

Pack home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

version/6

Table of available versions.

Compilation flags:

static

Template:

version(Version,Status,URL,Checksum,Dependencies,Portability)

Mode and number of proofs:

version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),?atom) - zero_or_more

```
version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),-list(atom)) -  
zero_or_more
```

Remarks:

- Version: This argument uses the same format as entity versions: Major:Minor:Patch. Semantic versioning should be used.
 - Status: Version development status. E.g stable, rc, beta, alpha, or deprecated.
 - URL: File URL for a local directory, file URL for a local archive, download HTTPS URL for the pack archive, or download git archive URL for the pack archive.
 - Checksum: A pair where the key is the hash algorithm and the value is the checksum. Currently, the hash algorithm must be sha256. For file:// URLs of local directories, use none instead of a pair.
 - Dependencies: Pack dependencies list. Each dependency is a Dependency Operator Version term. Operator is a term comparison operator. Valid Dependency values are Registry::Pack, os(Name,Machine), logtalk, and a backend identifier atom.
 - Portability: Either the atom all or a list of the supported backend Prolog compilers (using the identifier atoms used by the prolog_dialect flag).
 - Clause order: Versions must be listed ordered from newest to oldest.
-

[note/3](#)

Table of notes per action and version.

Compilation flags:

static

Template:

```
note(Action,Version>Note)
```

Mode and number of proofs:

```
note(?atom,?term,-atom) - zero_or_more
```

Remarks:

- Action: Possible values are install, update, and uninstall. When unbound, the note apply to all actions.
 - Version: Version acted on (i.e. version being installed, updated to, or uninstalled). When unbound, the note apply to all versions.
 - Note: Note to print when performing an action on a pack version.
-

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.56.2 packs

Pack handling predicates.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:74:0

Date: 2024-05-24

Compilation flags:

static, context_switching_calls

Imports:

public packs_common

public options

Uses:

list

logtalk

os

registries

type

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1
verify_commands_availability/0

- Public predicates

- available/2
- available/1
- available/0
- installed/4
- installed/3
- installed/1
- installed/0
- outdated/4
- outdated/1
- outdated/0
- orphaned/2
- orphaned/0
- versions/3
- describe/2
- describe/1
- search/1
- install/4
- install/3
- install/2
- install/1
- update/3
- update/2
- update/1
- update/0
- uninstall/2
- uninstall/1
- uninstall/0
- clean/2
- clean/1
- clean/0

- save/2
- save/1
- restore/2
- restore/1
- dependents/3
- dependents/2
- dependents/1
- lint/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

available/2

Enumerates, by backtracking, all available packs.

Compilation flags:

static

Template:

available(Registry,Pack)

Mode and number of proofs:

available(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

available/1

Lists all the packs that are available for installation from the given registry.

Compilation flags:

static

Template:

available(Registry)

Mode and number of proofs:

available(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

available/0

Lists all the packs that are available for installation from all defined registries.

Compilation flags:

static

Mode and number of proofs:

available - one

installed/4

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version,Pinned)

Mode and number of proofs:

installed(?atom,?atom,?compound,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

Pinned is neither a variable nor a boolean:

type__error(boolean,Pinned)

installed/3

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version)

Mode and number of proofs:

installed(?atom,?atom,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

installed/1

Lists all the packs that are installed from the given registry. Fails if the registry is unknown.

Compilation flags:

static

Template:

installed(Registry)

Mode and number of proofs:

installed(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

installed/0

Lists all the packs that are installed.

Compilation flags:

static

Mode and number of proofs:

installed - one

outdated/4

Enumerates by backtracking all installed but outdated packs (together with the current version installed and the latest version available).

Compilation flags:

static

Template:

outdated(Registry,Pack,Version,LatestVersion)

Mode and number of proofs:

outdated(?atom,?atom,?compound,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

LatestVersion is neither a variable nor a compound term:

type__error(compound,LatestVersion)

outdated/1

Lists all the packs from the given registry that are installed but outdated.

Compilation flags:

static

Template:

outdated(Registry)

Mode and number of proofs:

outdated(+atom) - one

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

outdated/0

Lists all the packs that are installed but outdated.

Compilation flags:

static

Mode and number of proofs:
outdated - one

orphaned/2

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:
static

Template:
orphaned(Registry,Pack)
Mode and number of proofs:
orphaned(?atom,?atom) - zero_or_more

Exceptions:
Registry is neither a variable nor an atom:
type__error(atom,Registry)
Pack is neither a variable nor an atom:
type__error(atom,Pack)

orphaned/0

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:
static

Mode and number of proofs:
orphaned - one

versions/3

Returns a list of all available pack versions. Fails if the pack is unknown.

Compilation flags:

static

Template:

versions(Registry,Pack,Versions)

Mode and number of proofs:

versions(+atom,+atom,-list) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/2

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Registry,Pack)

Mode and number of proofs:

describe(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/1

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Pack)

Mode and number of proofs:

describe(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

search/1

Searches packs whose name or description includes the search term (case sensitive).

Compilation flags:

static

Template:

search(Term)

Mode and number of proofs:

search(+atom) - one

Exceptions:

Term is a variable:

instantiation_error

Term is neither a variable nor an atom:

```
type__error(atom,Term)
```

install/4

Installs a new pack using the specified options. Fails if the pack is unknown or already installed but not using `update(true)` or `force(true)` options. Fails also if the pack version is unknown.

Compilation flags:

```
static
```

Template:

```
install(Registry,Pack,Version,Options)
```

Mode and number of proofs:

```
install(+atom,+atom,++compound,++list(compound)) - zero__or__one
```

Exceptions:

Registry is a variable:

```
instantiation__error
```

Registry is neither a variable nor an atom:

```
type__error(atom,Registry)
```

Pack is a variable:

```
instantiation__error
```

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

Version is a variable:

```
instantiation__error
```

Version is neither a variable nor a valid version:

```
type__error(pack__version,Version)
```

Options is a variable:

```
instantiation__error
```

Options is neither a variable nor a list:

```
type__error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation__error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type__error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain__error(option,Option)
```

Remarks:

- `update(Boolean)` option: Update pack if already installed. Default is false. Overrides the `force/1` option.
 - `force(Boolean)` option: Force pack re-installation if already installed. Default is false.
 - `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
 - `clean(Boolean)` option: Clean pack archive after installation. Default is false.
 - `verbose(Boolean)` option: Verbose installing steps. Default is false.
 - `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
 - `checksig(Boolean)` option: Verify pack archive signature. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`install/3`

Installs the specified version of a pack from the given registry using default options. Fails if the pack is already installed or unknown. Fails also if the pack version is unknown.

Compilation flags:

`static`

Template:

`install(Registry,Pack,Version)`

Mode and number of proofs:

`install(+atom,+atom,?compound) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Version is a variable:

`instantiation_error`

Version is neither a variable nor a valid version:

`type_error(pack_version,Version)`

install/2

Installs the latest version of a pack from the given registry using default options. Fails if the pack is already installed or unknown.

Compilation flags:

static

Template:

install(Registry,Pack)

Mode and number of proofs:

install(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

install/1

Installs a pack (if its name is unique among all registries) using default options. Fails if the pack is already installed or unknown. Fails also if the pack is available from multiple registries.

Compilation flags:

static

Template:

install(Pack)

Mode and number of proofs:

install(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is not an atom:

```
type__error(atom,Pack)
```

update/3

Updates an outdated pack to the specified version using the specified options. Fails if the pack or the pack version is unknown or if the pack is not installed. Fails also if the pack is orphaned or pinned and not using a `force(true)` option.

Compilation flags:

static

Template:

```
update(Pack,Version,Options)
```

Mode and number of proofs:

```
update(+atom,++callable,++list(callable)) - zero_or_one
```

Exceptions:

Pack is a variable:

```
instantiation__error
```

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

Version is a variable:

```
instantiation__error
```

Version is neither a variable nor a valid version:

```
type__error(pack_version,Version)
```

Options is a variable:

```
instantiation__error
```

Options is neither a variable nor a list:

```
type__error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation__error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type__error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain__error(option,Option)
```

Remarks:

- `install(Boolean)` option: Install pack latest version if not already installed. Default is false.
- `force(Boolean)` option: Force update if the pack is pinned or breaks installed packs. Default is false.
- `compatible(Boolean)` option: Restrict updating to compatible packs. Default is true.

- `clean(Boolean)` option: Clean pack archive after updating. Default is false.
- `verbose(Boolean)` option: Verbose updating steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
- `checksig(Boolean)` option: Verify pack archive signature. Default is false.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

update/2

Updates an outdated pack to its latest version using the specified options. Fails if the pack is orphaned, unknown, or not installed. Fails also if the pack is pinned and not using a `force(true)` option.

Compilation flags:

`static`

Template:

`update(Pack,Options)`

Mode and number of proofs:

`update(+atom,++list(callable)) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `install(Boolean)` option: Install pack latest version if not already installed. Default is false.

- `force(Boolean)` option: Force update if the pack is pinned or breaks installed packs. Default is false.
 - `compatible(Boolean)` option: Restrict updating to compatible packs. Default is true.
 - `clean(Boolean)` option: Clean pack archive after updating. Default is false.
 - `verbose(Boolean)` option: Verbose updating steps. Default is false.
 - `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
 - `checksig(Boolean)` option: Verify pack archive signature. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`update/1`

Updates an outdated pack to its latest version using default options. Fails if the pack is pinned, orphaned, not installed, unknown, or breaks installed packs.

Compilation flags:

`static`

Template:

`update(Pack)`

Mode and number of proofs:

`update(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiate_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

`update/0`

Updates all outdated packs (that are not pinned) using default options.

Compilation flags:

`static`

Mode and number of proofs:

update - zero_or_one

uninstall/2

Uninstalls a pack using the specified options. Fails if the pack is unknown or not installed. Fails also if the pack is pinned or have dependents and not using a force(true) option.

Compilation flags:

static

Template:

uninstall(Pack,Options)

Mode and number of proofs:

uninstall(+atom,++list(compound)) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- force(Boolean) option: Force deletion if the pack is pinned. Default is false.
 - clean(Boolean) option: Clean pack archive after deleting. Default is false.
 - verbose(Boolean) option: Verbose uninstalling steps. Default is false.
-

uninstall/1

Uninstalls a pack using default options. Fails if the pack is pinned, have dependents, not installed, or unknown.

Compilation flags:

static

Template:

uninstall(Pack)

Mode and number of proofs:

uninstall(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

uninstall/0

Uninstalls all packs using the force(true) option.

Compilation flags:

static

Mode and number of proofs:

uninstall - zero_or_one

clean/2

Cleans all pack archives. Fails if the the pack is unknown.

Compilation flags:

static

Template:

clean(Registry,Pack)

Mode and number of proofs:

clean(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

clean/1

Cleans all pack archives. Fails if the pack is unknown.

Compilation flags:

static

Template:

clean(Pack)

Mode and number of proofs:

clean(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

clean/0

Cleans all archives for all packs.

Compilation flags:

static

Mode and number of proofs:

clean - one

save/2

Saves a list of all installed packs and registries plus pinning status to a file using the given options. Registries without installed packs are saved when using the option `save(all)` and skipped when using the option `save(installed)` (default).

Compilation flags:

static

Template:

`save(File,Options)`

Mode and number of proofs:

`save(+atom,++list(compound)) - one_or_error`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an existing file but cannot be written:

`permission_error(open,source_sink,File)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

save/1

Saves a list of all installed packs and their registries plus pinning status to a file using default options.

Compilation flags:

static

Template:

save(File)

Mode and number of proofs:

save(+atom) - one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an existing file but cannot be written:

permission_error(open,source_sink,File)

restore/2

Restores a list of registries and packs plus their pinning status from a file using the given options. Fails if restoring is not possible.

Compilation flags:

static

Template:

restore(File,Options)

Mode and number of proofs:

restore(+atom,++list(compound)) - zero_or_one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

```
type_error(atom,File)
File is an atom but not an existing file:
existence_error(file,File)
File is an existing file but cannot be read:
permission_error(open,source_sink,File)
Options is a variable:
instantiation_error
Options is neither a variable nor a list:
type_error(list,Options)
An element Option of the list Options is a variable:
instantiation_error
An element Option of the list Options is neither a variable nor a compound term:
type_error(compound,Option)
An element Option of the list Options is a compound term but not a valid option:
domain_error(option,Option)
```

Remarks:

- `force(Boolean)` option: Force restoring if a registry is already defined or a pack is already installed. Default is true.
- `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
- `clean(Boolean)` option: Clean registry and pack archives after restoring. Default is false.
- `verbose(Boolean)` option: Verbose restoring steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksums. Default is true.
- `checksig(Boolean)` option: Verify pack archive signatures. Default is false.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

`restore/1`

Restores a list of registries and packs plus their pinning status from a file using default options. Fails if restoring is not possible.

Compilation flags:

```
static
```

Template:

```
restore(File)
```

Mode and number of proofs:

```
restore(+atom) - zero_or_one_or_error
```

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be read:

`permission_error(open,source_sink,File)`

`dependents/3`

Returns a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

`static`

Template:

`dependents(Registry,Pack,Dependents)`

Mode and number of proofs:

`dependents(+atom,+atom,-list(atom)) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

dependents/2

Prints a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

static

Template:

dependents(Registry,Pack)

Mode and number of proofs:

dependents(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

dependents/1

Prints a list of all installed packs that depend on the given pack if unique from all defined registries. Fails if the pack is unknown or available from multiple registries.

Compilation flags:

static

Template:

dependents(Pack)

Mode and number of proofs:

dependents(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

lint/2

Checks the pack specification. Fails if the pack is unknown or if linting detects errors.

Compilation flags:

```
static
```

Template:

```
lint(Registry,Pack)
```

Mode and number of proofs:

```
lint(+atom,+atom) - zero_or_one
```

Exceptions:

Registry is a variable:

```
instantiation_error
```

Registry is neither a variable nor an atom:

```
type__error(atom,Registry)
```

Pack is a variable:

```
instantiation_error
```

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

lint/1

Checks the pack specification. Fails if the pack is unknown, or available from multiple registries, or if linting detects errors.

Compilation flags:

```
static
```

Template:

```
lint(Pack)
```

Mode and number of proofs:

```
lint(+atom) - zero_or_one
```

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/0

Checks all pack specifications.

Compilation flags:

static

Mode and number of proofs:

lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.56.3 packs_common

Common predicates for the packs tool objects.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:31:0
Date: 2023-11-23

Compilation flags:
static

Provides:
type::type/1
type::check/2

Uses:
list
logtalk
os
type
user

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - setup/0
 - reset/0
 - verify_commands_availability/0
 - help/0
 - pin/1
 - pin/0
 - unpin/1
 - unpin/0
 - pinned/1
 - directory/2
 - directory/1
 - readme/2
 - readme/1
 - logtalk_packs/1
 - logtalk_packs/0

- prefix/1
 - prefix/0
- Protected predicates
 - readme_file_path/2
 - print_readme_file_path/1
 - command/2
 - load_registry/1
 - tar_command/1
 - supported_archive/1
 - supported_url_archive/1
 - decode_url_spaces/2
- Private predicates
- Operators

Public predicates

setup/0

Ensures that registries and packs directory structure exists. Preserves any defined registries and installed packs.

Compilation flags:

static

Mode and number of proofs:

setup - one

reset/0

Resets registries and packs directory structure. Deletes any defined registries and installed packs.

Compilation flags:

static

Mode and number of proofs:

reset - one

`verify_commands_availability/0`

Verifies required shell commands availability. Fails printing an error message if a command is missing.

Compilation flags:

`static`

Mode and number of proofs:

`verify_commands_availability - zero_or_one`

`help/0`

Provides help about the main predicates.

Compilation flags:

`static`

Mode and number of proofs:

`help - one`

`pin/1`

Pins a resource (pack or registry) preventing it from being updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

`static`

Template:

`pin(Resource)`

Mode and number of proofs:

`pin(+atom) - zero_or_one`

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

pin/0

Pins all resource (packs or registries) preventing them from being updated, uninstalled, or deleted. Note that resources added after calling this predicate will not be pinned.

Compilation flags:

static

Mode and number of proofs:

pin - one

unpin/1

Unpins a resource (pack or registry), allowing it to be updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

static

Template:

unpin(Resource)

Mode and number of proofs:

unpin(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

unpin/0

Unpins all resources (packs or registries), allowing them to be updated, uninstalled, or deleted.

Compilation flags:

static

Mode and number of proofs:

unpin - one

pinned/1

True iff the resource (pack or registry) is defined or installed and if it is pinned.

Compilation flags:

static

Template:

pinned(Resource)

Mode and number of proofs:

pinned(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

directory/2

Enumerates by backtracking all packs or registries and respective installation or definition directories (using the internal backend format).

Compilation flags:

static

Template:

directory(Resource,Directory)

Mode and number of proofs:

directory(?atom,?atom) - zero_or_more

Exceptions:

Resource is neither a variable nor an atom:

type_error(atom,Resource)

Directory is neither a variable nor an atom:

type_error(atom,Directory)

directory/1

Prints the directory where the registry or the pack is installed (using the native operating-system format).

Compilation flags:

static

Template:

directory(Resource)

Mode and number of proofs:

directory(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

readme/2

Returns the path to the resource (pack or registry) readme file (using the internal backend format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

static

Template:

```
readme(Resource,ReadMeFile)
```

Mode and number of proofs:

```
readme(+atom,-atom) - zero_or_one
```

Exceptions:

Resource is a variable:

```
instantiation_error
```

Resource is neither a variable nor an atom:

```
type_error(atom,Resource)
```

ReadMeFile is neither a variable nor an atom:

```
type_error(atom,ReadMeFile)
```

`readme/1`

Prints the path to the resource (pack or registry) readme file (using the native operating-system format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

```
static
```

Template:

```
readme(Resource)
```

Mode and number of proofs:

```
readme(+atom) - zero_or_one
```

Exceptions:

Resource is a variable:

```
instantiation_error
```

Resource is neither a variable nor an atom:

```
type_error(atom,Resource)
```

`logtalk_packs/1`

Returns the directory prefix (using the internal backend format) where the registries, packs, and archives are installed.

Compilation flags:

`static`

Template:

`logtalk_packs(LogtalkPacks)`

Mode and number of proofs:

`logtalk_packs(-atom) - one`

Exceptions:

LogtalkPacks is neither a variable nor an atom:

`type_error(atom,LogtalkPacks)`

`logtalk_packs/0`

Prints the directory prefix (using the native operating-system format) where the registries, packs, and archives are installed.

Compilation flags:

`static`

Mode and number of proofs:

`logtalk_packs - one`

`prefix/1`

Returns the directory prefix (using the internal backend format) where the registries or packs are installed.

Compilation flags:

`static`

Template:

prefix(Prefix)

Mode and number of proofs:

prefix(-atom) - one

Exceptions:

Prefix is neither a variable nor an atom:

type__error(atom,Prefix)

prefix/0

Prints the directory prefix (using the native operating-system format) where the registries or packs are installed.

Compilation flags:

static

Mode and number of proofs:

prefix - one

Protected predicates

readme__file__path/2

Returns the absolute path for the given directory readme file if it exists.

Compilation flags:

static

Template:

readme__file__path(Directory,ReadMeFile)

Mode and number of proofs:

readme__file__path(+atom,-atom) - zero_or_one

Remarks:

- Valid file names: Case variations of README and NOTES with or without a .md or .txt extension. The recommended file name is README.md.
-

`print_readme_file_path/1`

Prints the absolute path for the given directory readme file if it exists. Succeeds otherwise.

Compilation flags:

`static`

Template:

`print_readme_file_path(Directory)`

Mode and number of proofs:

`print_readme_file_path(+atom) - one`

`command/2`

Executes a shell command. Prints an error message and fails if the command fails.

Compilation flags:

`static`

Template:

`command(Command,FailureMessage)`

Mode and number of proofs:

`command(+atom,@nonvar) - zero_or_one`

`load_registry/1`

Loads all registry files from the given directory.

Compilation flags:

`static`

Template:

`load_registry(Directory)`

Mode and number of proofs:

`load_registry(+atom) - zero_or_one`

`tar_command/1`

Returns the name of the tar command to be used depending on the operating-system.

Compilation flags:

`static`

Template:

`tar_command(Command)`

Mode and number of proofs:

`tar_command(-atom) - one`

`supported_archive/1`

True iff the archive format is supported.

Compilation flags:

`static`

Template:

`supported_archive(Extension)`

Mode and number of proofs:

`supported_archive(+atom) - zero_or_one`

`supported_url_archive/1`

True iff the URL archive is supported.

Compilation flags:

`static`

Template:

`supported_url_archive(URL)`

Mode and number of proofs:

`supported_url_archive(+atom) - zero_or_one`

`decode_url_spaces/2`

Decodes encoded spaces (%20) in URLs to spaces.

Compilation flags:

`static`

Template:

`decode_url_spaces(URL,Decoded)`

Mode and number of proofs:

`decode_url_spaces(+atom,-atom) - one`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.56.4 `packs_messages`

Packs default message translations.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:34:0

Date: 2024-05-24

Compilation flags:

`static`

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.5 packs__specs__hook

Hook object for filtering registry and pack specification file contents.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:13:0

Date: 2022-06-28

Compilation flags:

`static, context__switching__calls`

Implements:

public expanding

Uses:

character

logtalk

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.6 registries

Registry handling predicates.

Availability:

```
logtalk_load(packs(loader))
```

Author: Paulo Moura

Version: 0:58:0

Date: 2024-03-25

Compilation flags:

```
static, context__switching__calls
```

Imports:

```
public packs_common
```

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1
verify_commands_availability/0
```

- Public predicates

- list/0
- describe/1
- defined/4
- add/3
- add/2
- add/1

- update/2
- update/1
- update/0
- delete/2
- delete/1
- delete/0
- clean/1
- clean/0
- provides/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

list/0

Prints a list of all defined registries, including how defined (git, archive, or directory) and if they are pinned.

Compilation flags:

static

Mode and number of proofs:

list - one

describe/1

Prints all registry entries.

Compilation flags:

static

Template:

describe(Registry)

Mode and number of proofs:

describe(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

defined/4

Enumerates by backtracking all defined registries, their definition URL, how they are defined (git, archive, or directory), and if they are pinned.

Compilation flags:

static

Template:

defined(Registry,URL,HowDefined,Pinned)

Mode and number of proofs:

defined(?atom,?atom,?atom,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is neither a variable nor an atom:

type_error(atom,URL)

HowDefined is neither a variable nor an atom:

type_error(atom,HowDefined)

Pinned is neither a variable nor a boolean:

type_error(boolean,Pinned)

add/3

Adds a new registry using the given options. Fails if the registry cannot be added or if it is already defined but not using `update(true)` or `force(true)` options. A `file:// URL` can be used for a local directory.

Compilation flags:

static

Template:

add(Registry,URL,Options)

Mode and number of proofs:

add(+atom,+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
- HTTPS URLs: Must end with either a `.git` extension or an archive extension.
- `update(Boolean)` option: Update registry if already defined. Default is false. Overrides the `force/1` option.
- `force(Boolean)` option: Force registry re-installation if already defined by first deleting the previous installation. Default is false.
- `clean(Boolean)` option: Clean registry archive after updating. Default is false.

- `verbose(Boolean)` option: Verbose adding steps. Default is `false`.
 - `curl(Atom)` option: Extra command-line options. Default is `''`.
 - `gpg(Atom)` option: Extra command-line options. Default is `''`.
 - `tar(Atom)` option: Extra command-line options. Default is `''`.
-

`add/2`

Adds a new registry using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with either a `.git` extension or a an archive extension. A `file://` URL can be used for a local directory.

Compilation flags:

`static`

Template:

`add(Registry,URL)`

Mode and number of proofs:

`add(+atom,+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

URL is a variable:

`instantiation_error`

URL is neither a variable nor an atom:

`type_error(atom,URL)`

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
-

add/1

Adds a new registry from a git cloning or local directory URL using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with a .git extension. A file:// URL can be used for a local directory.

Compilation flags:

static

Template:

add(URL)

Mode and number of proofs:

add(+atom) - zero_or_one

Exceptions:

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Remarks:

- Limitations: Cannot be used for archive download URLs.
 - Registry name: Taken from the URL basename.
-

update/2

Updates a defined registry using the specified options. Fails if the registry is not defined.

Compilation flags:

static

Template:

update(Registry,Options)

Mode and number of proofs:

update(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

```

    type_error(atom,Registry)
Options is a variable:
    instantiation_error
Options is neither a variable nor a list:
    type_error(list,Options)
An element Option of the list Options is a variable:
    instantiation_error
An element Option of the list Options is neither a variable nor a compound term:
    type_error(compound,Option)
An element Option of the list Options is a compound term but not a valid option:
    domain_error(option,Option)

```

Remarks:

- `force(Boolean)` option: Force update if the registry is pinned. Default is false.
- `clean(Boolean)` option: Clean registry archive after updating. Default is false.
- `verbose(Boolean)` option: Verbose updating steps. Default is false.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

`update/1`

Updates a defined registry using default options. Fails if the registry is not defined.

Compilation flags:

```
static
```

Template:

```
update(Registry)
```

Mode and number of proofs:

```
update(+atom) - zero_or_one
```

Exceptions:

Registry is a variable:

```
instantiation_error
```

Registry is neither a variable nor an atom:

```
type_error(atom,Registry)
```

update/0

Updates all defined registries using default options.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

delete/2

Deletes a registry using the specified options (if not pinned).

Compilation flags:

static

Template:

delete(Registry,Options)

Mode and number of proofs:

delete(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- `force(Boolean)` option: Force deletion if the registry is pinned or there are installed registry packs. Default is false.
 - `clean(Boolean)` option: Clean registry archive after deleting. Default is false.
 - `verbose(Boolean)` option: Verbose deleting steps. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`delete/1`

Deletes a registry using default options.

Compilation flags:

`static`

Template:

`delete(Registry)`

Mode and number of proofs:

`delete(+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

`delete/0`

Deletes all registries using the `force(true)` option.

Compilation flags:

`static`

Mode and number of proofs:

`delete - zero_or_one`

clean/1

Cleans all registry archives. Fails if the registry is not defined.

Compilation flags:

static

Template:

clean(Registry)

Mode and number of proofs:

clean(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

clean/0

Cleans all archives for all registries.

Compilation flags:

static

Mode and number of proofs:

clean - one

provides/2

Enumerates by backtracking all packs provided by a registry.

Compilation flags:

static

Template:

provides(Registry,Pack)

Mode and number of proofs:

provides(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

lint/1

Checks the registry specification. Fails if the registry is not defined or if linting detects errors.

Compilation flags:

static

Template:

lint(Registry)

Mode and number of proofs:

lint(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type__error(atom,Registry)

lint/0

Checks all registry specifications.

Compilation flags:

static

Mode and number of proofs:

lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.7 registry_loader_hook

Hook object for filtering registry loader file contents.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:13:0

Date: 2022-11-20

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Uses:

character

logtalk

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.56.8 registry__protocol

Registry specification protocol. Objects implementing this protocol should be named after the pack with a `__registry` suffix and saved in a file with the same name as the object.

Availability:

```
logtalk_load(packs(loader))
```

Author: Paulo Moura

Version: 0:12:0

Date: 2022-06-28

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - name/1
 - description/1
 - home/1
 - clone/1
 - archive/1
 - note/2
- Protected predicates
- Private predicates
- Operators

Public predicates

name/1

Registry name. Preferably a valid unquoted atom.

Compilation flags:

static

Template:

name(Name)

Mode and number of proofs:

name(?atom) - zero_or_one

description/1

Registry one line description.

Compilation flags:

static

Template:

description(Description)

Mode and number of proofs:

description(?atom) - zero_or_one

home/1

Registry home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

clone/1

Registry git clone HTTPS URL (must end with the .git extension). Git repos should have the same name as the registry.

Compilation flags:

static

Template:

clone(URL)

Mode and number of proofs:

clone(?atom) - zero_or_one

archive/1

Registry archive download HTTPS URL.

Compilation flags:
static

Template:
archive(URL)
Mode and number of proofs:
archive(?atom) - zero_or_one

note/2

Table of notes per action.

Compilation flags:
static

Template:
note(Action,Note)
Mode and number of proofs:
note(?atom,-atom) - zero_or_more

Remarks:

- Action: Possible values are add, update, and delete. When unbound, the note apply to all actions.
 - Note: Note to print when performing an action on a registry.
-

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.57 pddl_parser

object

1.57.1 pddl

Simple parser of PDDL 3.0 files.

Availability:

`logtalk__load(pddl_parser(loader))`

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:2:2

Date: 2024-03-14

Compilation flags:

`static, context_switching_calls`

Imports:

`public read_file`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

`read_file/2`

- Public predicates
 - `parse_domain/3`
 - `parse_domain/2`
 - `parse_problem/2`
 - `parse_problem/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse_domain/3`

Parses a PDDL 3.0 domain file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

`static`

Template:

`parse_domain(File,Output,RestOfFile)`

Mode and number of proofs:

`parse_domain(+atom,-compound,-list(atom)) - one`

`parse_domain/2`

Parses a PDDL 3.0 domain file, returning a compound term representing its contents.

Compilation flags:

`static`

Template:

`parse_domain(File,Output)`

Mode and number of proofs:

`parse_domain(+atom,-compound) - one`

parse_problem/2

Parses a PDDL 3.0 problem file, returning a compound term representing its contents.

Compilation flags:

static

Template:

parse_problem(File,Output)

Mode and number of proofs:

parse_problem(+atom,-compound) - one

parse_problem/3

Parses a PDDL 3.0 problem file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

static

Template:

parse_problem(File,Output,RestOfFile)

Mode and number of proofs:

parse_problem(+atom,-compound,-list(atom)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.57.2 read_file

Utility predicates for parsing a file as a list of atoms.

Availability:

logtalk_load(pddl_parser(loader))

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:0:0

Date: 2011-08-04

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - read_file/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`read_file/2`

Reads a file character by character, parsing it into a list of atoms.

Compilation flags:

`static`

Template:

`read_file(File,List)`

Mode and number of proofs:

`read_file(+atom,-list(atom)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.58 ports_profiler

object

1.58.1 ports_profiler

Predicate execution box model port profiler.

Availability:

`logtalk_load(ports_profiler(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2024-05-18

Compilation flags:

static, context_switching_calls

Provides:

logtalk::debug_handler/1

logtalk::debug_handler/3

Uses:

logtalk

user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - start/0
 - stop/0
 - data/0
 - data/1
 - data/2
 - reset/0
 - reset/1
 - port/5
 - clause_location/6
 - clause/5
- Protected predicates
- Private predicates
 - clause_location_/6
 - port_/5
 - clause_/5
 - entity_defines_/2
- Operators

Public predicates

start/0

Activates thr ports profiler for followup goals.

Compilation flags:
static

Mode and number of proofs:
start - one

stop/0

Deactivates thr ports profiler.

Compilation flags:
static

Mode and number of proofs:
stop - one

data/0

Prints a table with all port profiling data.

Compilation flags:
static

Mode and number of proofs:
data - one

data/1

Prints a table with all port profiling data for the specified entity.

Compilation flags:

static

Template:

data(Entity)

Mode and number of proofs:

data(+entity__identifier) - one

data/2

Prints a table with all port profiling data for the specified entity predicate (or non-terminal).

Compilation flags:

static

Template:

data(Entity,Predicate)

Mode and number of proofs:

data(+entity__identifier,+predicate__indicator) - one

data(+entity__identifier,+non__terminal__indicator) - one

reset/0

Resets all port profiling data.

Compilation flags:

static

Mode and number of proofs:

reset - one

reset/1

Resets all port profiling data for the specified entity.

Compilation flags:

static

Template:

reset(Entity)

Mode and number of proofs:

reset(+entity__identifier) - one

port/5

Enumerates, by backtracking, all collected port profiling data.

Compilation flags:

static

Template:

port(Port,Entity,Functor,Arity,Count)

Mode and number of proofs:

port(?atom,?entity__identifier,?atom,?integer,?integer) - zero_or_more

clause_location/6

Enumerates, by backtracking, all collected profiled clause location data.

Compilation flags:

static

Template:

clause_location(Entity,Functor,Arity,ClauseNumber,File,BeginLine)

Mode and number of proofs:

clause_location(?entity__identifier,?atom,?integer,?integer,?atom,?integer) - zero_or_more

clause/5

Enumerates, by backtracking, all collected clause profiling data.

Compilation flags:

dynamic

Template:

clause(Entity, Functor, Arity, ClauseNumber, Count)

Mode and number of proofs:

clause(?entity__identifier, ?atom, ?integer, ?integer, ?integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

clause_location_/6

Internal table of collected profiled clause location data.

Compilation flags:

dynamic

Template:

clause_location_(Entity, Functor, Arity, ClauseNumber, File, BeginLine)

Mode and number of proofs:

clause_location_(?entity__identifier, ?atom, ?integer, ?integer, ?atom, ?integer) - zero_or_more

port_/5

Internal table of collected port profiling data.

Compilation flags:

dynamic

Template:

port_(Port,Entity,Functor,Arity,Count)

Mode and number of proofs:

port_(?atom,?entity__identifier,?atom,?integer,?integer) - zero_or_more

clause_/5

Internal table of collected clause profiling data.

Compilation flags:

dynamic

Template:

clause_(Entity,Functor,Arity,ClauseNumber,Count)

Mode and number of proofs:

clause_(?entity__identifier,?atom,?integer,?integer,?integer) - zero_or_more

entity__defines_/2

Internal cache for profiled predicates.

Compilation flags:

dynamic

Template:

entity__defines_(Entity,Predicate)

Mode and number of proofs:

entity__defines_(?entity__identifier,?predicate__indicator) - zero_or_more

Operators

(none)

1.59 queues

object

1.59.1 queue

Queue predicates implemented using difference lists.

Availability:

`logtalk_load(queues(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

`static, context_switching_calls`

Implements:

`public queuep`

Extends:

`public compound`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/3 as_list/2 check/1 depth/2
empty/1 ground/1 head/2 join/3 join_all/3 jump/3 jump_all/3 jump_all_block/3 length/2
map/2 map/3 new/1 numbervars/1 numbervars/3 occurs/2 serve/3 singletons/2 subsumes/2
subterm/2 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.59.2 queuep

Queue protocol.

Availability:

logtalk__load(queues(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - head/2
 - join/3
 - join_all/3
 - jump/3
 - jump_all/3
 - jump_all_block/3
 - append/3
 - length/2
 - serve/3
 - as_list/2
 - map/2
 - map/3
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

True if the queue is empty.

Compilation flags:

static

Template:

empty(Queue)

Mode and number of proofs:

empty(@queue) - zero_or_one

head/2

Unifies Head with the first element of the queue.

Compilation flags:

static

Template:

head(Queue,Head)

Mode and number of proofs:

head(+queue,?term) - zero_or_one

join/3

Adds the new element at the end of the queue.

Compilation flags:

static

Template:

join(Element,Queue,NewQueue)

Mode and number of proofs:

join(@term,+queue,-queue) - zero_or_one

join_all/3

Adds the new elements at the end of the queue. The elements are added in the same order that they appear in the list.

Compilation flags:

static

Template:

join_all(List,Queue,NewQueue)

Mode and number of proofs:

join_all(+list,+queue,-queue) - zero_or_one

jump/3

Adds the new element at the front of the queue.

Compilation flags:

static

Template:

jump(Element,Queue,NewQueue)

Mode and number of proofs:

jump(@term,+queue,-queue) - zero_or_one

jump_all/3

Adds the new elements at the front of the queue. The last element in the list will be at the front of the queue.

Compilation flags:

static

Template:

jump_all(Elements,Queue,NewQueue)

Mode and number of proofs:

jump_all(+list,+queue,-queue) - zero_or_one

jump_all_block/3

Adds the new elements as a block at the front of the queue. The first element in the list will be at the front of the queue.

Compilation flags:

static

Template:

```
jump_all_block(Elements,Queue,NewQueue)
```

Mode and number of proofs:

```
jump_all_block(+list,+queue,-queue) - zero_or_one
```

`append/3`

Appends two queues. The new queue will have the elements of the first queue followed by the elements of the second queue.

Compilation flags:

```
static
```

Template:

```
append(Queue1,Queue2,NewQueue)
```

Mode and number of proofs:

```
append(+queue,+queue,-queue) - one
```

`length/2`

Queue length.

Compilation flags:

```
static
```

Template:

```
length(Queue,Length)
```

Mode and number of proofs:

```
length(+heap,?integer) - zero_or_one
```

`serve/3`

Removes the first element of the queue for service.

Compilation flags:

`static`

Template:

`serve(Queue,Head,NewQueue)`

Mode and number of proofs:

`serve(+queue,?term,-queue) - zero_or_one`

`as_list/2`

Converts a queue to a list.

Compilation flags:

`static`

Template:

`as_list(Queue,List)`

Mode and number of proofs:

`as_list(+queue,-list) - one`

`map/2`

Applies a closure to all elements of a queue.

Compilation flags:

`static`

Template:

`map(Closure,Queue)`

Meta-predicate template:

`map(1,*)`

Mode and number of proofs:

`map(+callable,+queue) - zero_or_one`

map/3

Applies a closure to all elements of a queue constructing a new queue.

Compilation flags:

static

Template:

map(Closure,Queue,NewQueue)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(+callable,+queue,?queue) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[queue](#)

1.60 random

object

1.60.1 backend_random

Random number generator predicates using the backend Prolog compiler built-in random generator.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 1:20:0

Date: 2023-11-24

Compilation flags:

`static, context_switching_calls`

Implements:

`public pseudo_random_protocol`

Uses:

`list`

Remarks:

- Implementation: The backend Prolog compiler built-in random generator is only used for the basic `random/1`, `get_seed/1`, and `set_seed/1` predicates.
- Portability: B-Prolog, CxProlog, ECLiPSe, JIProlog, Qu-Prolog, and Quintus Prolog do not provide implementations for the `get_seed/1` and `set_seed/1` predicates and calling these predicates simply succeed without performing any action.

Inherited public predicates:

`between/3 enumerate/2 get_seed/1 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2
member/2 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4
sequence/4 set/4 set_seed/1 swap/2 swap_consecutive/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[random](#), [fast_random](#)

object

1.60.2 [fast_random](#)

Fast portable random number generator predicates. Core predicates originally written by Richard O’Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 2:11:0

Date: 2023-11-24

Compilation flags:

`static, context_switching_calls`

Implements:

`public pseudo_random_protocol`

Uses:

[list](#)

Remarks:

- Single random number generator: This object provides a faster version of the random library object but does not support being extended to define multiple random number generators.

- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The `randomize/1` predicate can be used to initialize the seed with a random value.

Inherited public predicates:

`between/3` `enumerate/2` `get_seed/1` `maybe/0` `maybe/1` `maybe/2` `maybe_call/1` `maybe_call/2`
`member/2` `permutation/2` `random/1` `random/3` `randseq/4` `randset/4` `select/3` `select/4`
`sequence/4` `set/4` `set_seed/1` `swap/2` `swap_consecutive/2`

- Public predicates
 - `reset_seed/0`
 - `randomize/1`
- Protected predicates
- Private predicates
 - `seed_/3`
- Operators

Public predicates

`reset_seed/0`

Resets the random generator seed to its default value. Use `get_seed/1` and `set_seed/1` instead if you need reproducibility.

Compilation flags:

`static`, `synchronized`

Mode and number of proofs:

`reset_seed` - one

`randomize/1`

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

`static`, `synchronized`

Template:

 randomize(Seed)

Mode and number of proofs:

 randomize(+positive_integer) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

seed_/3

Stores the current random generator seed values.

Compilation flags:

 dynamic

Template:

 seed_(S0,S1,S2)

Mode and number of proofs:

 seed_(-integer,-integer,-integer) - one

Operators

(none)

See also:

[random](#), [backend_random](#)

[protocol](#)

1.60.3 pseudo_random_protocol

Pseudo-random number generator protocol for seed handling predicates. These predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

 logtalk_load(random(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2021-02-21

Compilation flags:

static

Extends:

public random_protocol

Remarks:

(none)

Inherited public predicates:

between/3 enumerate/2 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2 member/2
permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4
swap/2 swap_consecutive/2

- Public predicates
 - get_seed/1
 - set_seed/1
- Protected predicates
- Private predicates
- Operators

Public predicates

get_seed/1

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:

static, synchronized

Template:

get_seed(Seed)

Mode and number of proofs:

get_seed(-ground) - one

`set_seed/1`

Sets the random generator seed to a given value returned by calling the `get_seed/1` predicate.

Compilation flags:

`static, synchronized`

Template:

`set_seed(Seed)`

Mode and number of proofs:

`set_seed(+ground) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`random`, `backend_random`, `fast_random`

object

1.60.4 random

Portable random number generator predicates. Core predicates originally written by Richard O’Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 2:11:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Implements:

public pseudo_random_protocol

Uses:

list

Remarks:

- Multiple random number generators: To define multiple random number generators, simply extend this object. The derived objects must send to self the reset_seed/0 message.
- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The randomize/1 predicate can be used to initialize the seed with a random value.

Inherited public predicates:

between/3 enumerate/2 get_seed/1 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2
member/2 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4
sequence/4 set/4 set_seed/1 swap/2 swap_consecutive/2

- Public predicates
 - reset_seed/0
 - randomize/1
- Protected predicates
- Private predicates
 - seed_/3
- Operators

Public predicates

reset_seed/0

Resets the random generator seed to its default value. Use get_seed/1 and set_seed/1 instead if you need reproducibility.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_seed - one

randomize/1

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

static, synchronized

Template:

randomize(Seed)

Mode and number of proofs:

randomize(+positive_integer) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

seed_/3

Stores the current random generator seed values.

Compilation flags:

dynamic

Template:

seed__(S0,S1,S2)

Mode and number of proofs:

seed__(-integer,-integer,-integer) - one

Operators

(none)

See also:

`fast_random`, `backend_random`

`protocol`

1.60.5 `random_protocol`

Random number generator protocol. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 3:3:0

Date: 2023-11-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `random/1`
 - `between/3`
 - `member/2`
 - `select/3`
 - `select/4`
 - `swap/2`
 - `swap_consecutive/2`

- enumerate/2
- permutation/2
- sequence/4
- set/4
- random/3
- randseq/4
- randset/4
- maybe/0
- maybe/1
- maybe/2
- maybe_call/1
- maybe_call/2
- Protected predicates
- Private predicates
- Operators

Public predicates

random/1

Returns a new random float value in the interval [0.0, 1.0[.

Compilation flags:

static, synchronized

Template:

random(Random)

Mode and number of proofs:

random(-float) - one

between/3

Returns a new random integer in the interval [Lower, Upper]. Fails if Lower or Upper are not integers or if Lower > Upper.

Compilation flags:

static

Template:

between(Lower,Upper,Random)

Mode and number of proofs:

between(+integer,+integer,-integer) - zero_or_one

member/2

Returns a random member of a list. Fails if the list is empty.

Compilation flags:

static

Template:

member(Random,List)

Mode and number of proofs:

member(-term,+list(term)) - zero_or_one

select/3

Returns a random member of a list and the rest of the list. Fails if the list is empty.

Compilation flags:

static

Template:

select(Random,List,Rest)

Mode and number of proofs:

select(-term,+list(term),-list(term)) - zero_or_one

`select/4`

Returns a random member of a list, replacing it with a new element and returning the resulting list.

Compilation flags:

`static`

Template:

`select(Random,OldList,New,NewList)`

Mode and number of proofs:

`select(-term,+list(term),@term,-list(term)) - zero_or_one`

`swap/2`

Swaps two randomly selected elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

`static`

Template:

`swap(OldList,NewList)`

Mode and number of proofs:

`swap(-term,+list(term)) - zero_or_one`

`swap_consecutive/2`

Swaps two randomly selected consecutive elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

`static`

Template:

`swap_consecutive(OldList,NewList)`

Mode and number of proofs:

swap_consecutive(-term,+list(term)) - zero_or_one

enumerate/2

Enumerates the elements of a list in random order. Fails if the list is empty.

Compilation flags:

static

Template:

enumerate(List,Random)

Mode and number of proofs:

enumerate(+list(term),--term) - zero_or_more

permutation/2

Returns a random permutation of a list.

Compilation flags:

static, synchronized

Template:

permutation(List,Permutation)

Mode and number of proofs:

permutation(+list,-list) - one

sequence/4

Returns list of random integers of given length in random order in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers or if Lower > Upper.

Compilation flags:

static, synchronized

Template:

sequence(Length,Lower,Upper,List)

Mode and number of proofs:

sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

set/4

Returns ordered set of random integers of given size in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers, if Lower > Upper, or if Length > Upper - Lower + 1.

Compilation flags:

static, synchronized

Template:

set(Length,Lower,Upper,Set)

Mode and number of proofs:

set(+integer,+integer,+integer,-list(integer)) - zero_or_one

random/3

Returns a new random value in the interval [Lower, Upper[. Fails if Lower > Upper. Deprecated. Use between/3 for integers.

Compilation flags:

static, synchronized

Template:

random(Lower,Upper,Random)

Mode and number of proofs:

random(+integer,+integer,-integer) - zero_or_one

random(+float,+float,-float) - zero_or_one

randseq/4

Returns list of random values of given length in random order in interval [Lower, Upper[. Fails if Lower > Upper or if the arguments are neither integers or floats. Deprecated. Use sequence/4 for integers.

Compilation flags:

static, synchronized

Template:

randseq(Length,Lower,Upper,List)

Mode and number of proofs:

randseq(+integer,+integer,+integer,-list(integer)) - zero_or_one

randseq(+integer,+float,+float,-list(float)) - zero_or_one

randset/4

Returns ordered set of random values of given size in interval [Lower, Upper[. Fails if the arguments are neither integers or floats, Lower > Upper, or Length > Upper - Lower when arguments are integers. Deprecated. Use set/4 for integers.

Compilation flags:

static, synchronized

Template:

randset(Length,Lower,Upper,Set)

Mode and number of proofs:

randset(+integer,+integer,+integer,-list(integer)) - zero_or_one

randset(+integer,+float,+float,-list(float)) - zero_or_one

maybe/0

Succeeds or fails with equal probability.

Compilation flags:

static

Mode and number of proofs:

maybe - zero_or_one

maybe/1

Succeeds with probability Probability or fails with probability 1 - Probability. Fails if Probability is not a float or is outside the interval [0.0, 1.0].

Compilation flags:

static

Template:

maybe(Probability)

Mode and number of proofs:

maybe(+probability) - zero_or_one

maybe/2

Succeeds with probability K/N where K and N are integers satisfying the equation $0 \leq K \leq N$. Fails otherwise.

Compilation flags:

static

Template:

maybe(K,N)

Mode and number of proofs:

maybe(+non_negative_integer,+non_negative_integer) - zero_or_one

`maybe_call/1`

Calls a goal or fails without calling it with equal probability. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

`static`

Template:

`maybe_call(Goal)`

Meta-predicate template:

`maybe_call(0)`

Mode and number of proofs:

`maybe_call(+callable) - zero_or_one`

`maybe_call/2`

Calls a goal or fails without calling it with probability `Probability`. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

`static`

Template:

`maybe_call(Probability,Goal)`

Meta-predicate template:

`maybe_call(*,0)`

Mode and number of proofs:

`maybe_call(+probability,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`random`, `backend_random`, `fast_random`

1.61 reader

object

1.61.1 reader

Predicates for reading text file and text stream contents to lists of terms, characters, or character codes and for reading binary file and binary stream contents to lists of bytes.

Availability:

`logtalk_load(reader(loader))`

Author: Paulo Moura

Version: 2:2:0

Date: 2023-11-14

Compilation flags:

`static`, `context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)

- file_to_codes/2
- file_to_codes/3
- file_to_chars/2
- file_to_chars/3
- file_to_terms/2
- file_to_terms/3
- file_to_bytes/2
- file_to_bytes/3
- stream_to_codes/2
- stream_to_codes/3
- stream_to_chars/2
- stream_to_chars/3
- stream_to_terms/2
- stream_to_terms/3
- stream_to_bytes/2
- stream_to_bytes/3
- line_to_chars/2
- line_to_chars/3
- line_to_codes/2
- line_to_codes/3
- Protected predicates
- Private predicates
- Operators

Public predicates

file_to_codes/2

Reads a text file into a list of character codes.

Compilation flags:

static

Template:

file_to_codes(File,Codes)

Mode and number of proofs:

file_to_codes(+atom,-list(character_code)) - one

`file_to_codes/3`

Reads a text file into a list of character codes. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_codes(File,Codes,Tail)`

Mode and number of proofs:

`file_to_codes(+atom,-list(character_code),@term) - one`

`file_to_chars/2`

Reads a text file into a list of characters.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character)) - one`

`file_to_chars/3`

Reads a text file into a list of characters. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars,Tail)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character),@term) - one`

`file_to_terms/2`

Reads a text file into a list of terms.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term)) - one`

`file_to_terms/3`

Reads a text file into a list of terms. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms,Tail)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term),@term) - one`

`file_to_bytes/2`

Reads a binary file into a list of bytes.

Compilation flags:

`static`

Template:

```
file_to_bytes(File,Bytes)
```

Mode and number of proofs:

```
file_to_bytes(+atom,-list(byte)) - one
```

`file_to_bytes/3`

Reads a binary file into a list of bytes. The list is terminated by the given tail.

Compilation flags:

```
static
```

Template:

```
file_to_bytes(File,Bytes,Tail)
```

Mode and number of proofs:

```
file_to_bytes(+atom,-list(byte),@term) - one
```

`stream_to_codes/2`

Reads a text stream into a list of character codes. Does not close the stream.

Compilation flags:

```
static
```

Template:

```
stream_to_codes(Stream,Codes)
```

Mode and number of proofs:

```
stream_to_codes(+stream_or_alias,-list(character_code)) - one
```

`stream_to_codes/3`

Reads a text stream into a list of character codes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_codes(Stream,Codes,Tail)`

Mode and number of proofs:

`stream_to_codes(+stream_or_alias,-list(character_code),@term) - one`

`stream_to_chars/2`

Reads a text stream into a list of characters. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_chars(Stream,Chars)`

Mode and number of proofs:

`stream_to_chars(+stream_or_alias,-list(char)) - one`

`stream_to_chars/3`

Reads a text stream into a list of characters. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_chars(Stream,Chars,Tail)`

Mode and number of proofs:

`stream_to_chars(+stream_or_alias,-list(char),@term) - one`

`stream__to__terms/2`

Reads a text stream into a list of terms. Does not close the stream.

Compilation flags:

`static`

Template:

`stream__to__terms(Stream, Terms)`

Mode and number of proofs:

`stream__to__terms(+stream_or_alias, -list(term)) - one`

`stream__to__terms/3`

Reads a text stream into a list of terms. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream__to__terms(Stream, Terms, Tail)`

Mode and number of proofs:

`stream__to__terms(+stream_or_alias, -list(term), @term) - one`

`stream__to__bytes/2`

Reads a binary stream into a list of bytes. Does not close the stream.

Compilation flags:

`static`

Template:

`stream__to__bytes(Stream, Bytes)`

Mode and number of proofs:

```
stream_to_bytes(+stream_or_alias,-list(byte)) - one
```

`stream_to_bytes/3`

Reads a binary stream into a list of bytes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

```
static
```

Template:

```
stream_to_bytes(Stream,Bytes,Tail)
```

Mode and number of proofs:

```
stream_to_bytes(+stream_or_alias,-list(byte),@term) - one
```

`line_to_chars/2`

Reads a line from a text stream into a list of characters. Discards the end-of-line characters. Unifies Chars with end_of_file at the end of the file.

Compilation flags:

```
static
```

Template:

```
line_to_chars(Stream,Chars)
```

Mode and number of proofs:

```
line_to_chars(+stream_or_alias,-types([atom,list(character)])) - one
```

`line_to_chars/3`

Reads a line from a text stream into a list of characters. Keeps the end-of-line marker normalized to the line feed control character. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

`static`

Template:

`line_to_chars(Stream,Chars,Tail)`

Mode and number of proofs:

`line_to_chars(+stream_or_alias,-list(character),?term) - one`

`line_to_codes/2`

Reads a line from a text stream into a list of character codes. Discards the end-of-line character codes. Unifies Codes with `end_of_file` at the end of the file.

Compilation flags:

`static`

Template:

`line_to_codes(Stream,Codes)`

Mode and number of proofs:

`line_to_codes(+stream_or_alias,-types([atom,list(character_code)])) - one`

`line_to_codes/3`

Reads a line from a text stream into a list of character codes. Keeps the end-of-line marker normalized to the line feed control character code. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

`static`

Template:

```
line_to_codes(Stream, Codes, Tail)
Mode and number of proofs:
line_to_codes(+stream_or_alias, -list(character_code), ?term) - one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.62 recorded_database

object

1.62.1 recorded_database

Legacy recorded database predicates. Provides an application global database.

Availability:

```
logtalk_load(recorded_database(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public recorded_database_core
```

Remarks:

(none)

Inherited public predicates:

`erase/1` `instance/2` `recorda/2` `recorda/3` `recorded/2` `recorded/3` `recordz/2` `recordz/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.62.2 `recorded__database__core`

Legacy recorded database predicates. Can be imported into an object to provide a local database.

Availability:

`logtalk_load(recorded__database(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- References: Opaque ground terms.

Inherited public predicates:

(none)

- Public predicates
 - recorda/3
 - recorda/2
 - recordz/3
 - recordz/2
 - recorded/3
 - recorded/2
 - erase/1
 - instance/2
- Protected predicates
- Private predicates
 - record_/3
 - reference_/1
- Operators

Public predicates

recorda/3

Adds a term as the first term for the given key, returning its reference.

Compilation flags:

static

Template:

recorda(Key,Term,Reference)

Mode and number of proofs:

recorda(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is a not a variable:

uninstantiation_error(Reference)

`recorda/2`

Adds a term as the first term for the given key.

Compilation flags:

static

Template:

recorda(Key,Term)

Mode and number of proofs:

recorda(+recorded_database_key,+term) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

`recordz/3`

Adds a term as the last term for the given key, returning its reference.

Compilation flags:

static

Template:

recordz(Key,Term,Reference)

Mode and number of proofs:

recordz(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is a not a variable:

uninstantiation_error(Reference)

recordz/2

Adds a term as the last term for the given key.

Compilation flags:

static

Template:

recordz(Key,Term)

Mode and number of proofs:

recordz(+recorded_database_key,+term) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

recorded/3

Enumerates, by backtracking, all record key-term pairs and their references.

Compilation flags:

static

Template:

recorded(Key,Term,Reference)

Mode and number of proofs:

recorded(?recorded_database_key,?term,-recorded_database_reference) - zero_or_more

recorded(?recorded_database_key,?term,+recorded_database_reference) - zero_or_one

recorded/2

Enumerates, by backtracking, all record key-term pairs.

Compilation flags:

static

Template:

recorded(Key,Term)

Mode and number of proofs:

recorded(?recorded_database_key,?term) - zero_or_more

erase/1

Erases the record indexed by the given reference. Fails if there is no record with the given reference.

Compilation flags:

static

Template:

erase(Reference)

Mode and number of proofs:

erase(@recorded_database_reference) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

instance/2

.

Compilation flags:

static

Template:

instance(Reference,Term)

Mode and number of proofs:

instance(@recorded_database_reference,?term) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

Protected predicates

(none)

Private predicates

record_/3

Records table.

Compilation flags:

dynamic

Template:

record_(Key,Term,Reference)

Mode and number of proofs:

record_(?recorded_database_key,?term,?recorded_database_reference) - zero_or_more

`reference_/1`

Reference count.

Compilation flags:

`dynamic`

Template:

`reference_(Reference)`

Mode and number of proofs:

`reference_(?non_negative_integer) - zero_or_one`

Operators

(none)

1.63 redis

object

1.63.1 redis

Redis client. Inspired by Sean Charles GNU Prolog Redis client.

Availability:

`logtalk_load(redis(loader))`

Author: Paulo Moura

Version: 0:5:1

Date: 2021-12-06

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_tokens//2`

Uses:

`list`

`logtalk`

Remarks:

- Command representation: Use the Redis command name as the functor of a compound term where the arguments are the command arguments.
- Valid arguments: Atoms, integers, and floats. Always use atoms instead of double-quoted “strings”. This helps portability by not depending on the value of the `double_quotes` flag.

Inherited public predicates:

(none)

- Public predicates
 - `connect/1`
 - `connect/3`
 - `disconnect/1`
 - `send/3`
 - `console/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`connect/1`

Connect to a Redis server running on localhost using the default 6379 port.

Compilation flags:

`static`

Template:

`connect(Connection)`

Mode and number of proofs:

`connect(--ground) - one`

`connect/3`

Connect to a Redis server running on the given host and port.

Compilation flags:

`static`

Template:

`connect(Host,Port,Connection)`

Mode and number of proofs:

`connect(+atom,+integer,--ground) - one`

`disconnect/1`

Disconnect from a Redis server.

Compilation flags:

`static`

Template:

`disconnect(Connection)`

Mode and number of proofs:

`disconnect(++ground) - one`

`send/3`

Sends a request to the a Redis server and returns its reply.

Compilation flags:

`static`

Template:

`send(Connection,Request,Reply)`

Mode and number of proofs:

`send(++ground,++callable,--callable) - one`

console/1

Sends a request to a Redis server running on localhost at the default 6379 port and prints the reply.

Compilation flags:

static

Template:

console(Request)

Mode and number of proofs:

console(++callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.64 sets

object

1.64.1 set

Set predicates implemented using ordered lists. Uses `==/2` for element comparison and standard term ordering.

Availability:

logtalk__load(sets(loader))

Author: Richard O’Keefe (main predicates); adapted to Logtalk by Paulo Moura.

Version: 1:12:0

Date: 2019-05-23

Compilation flags:

static, context_switching_calls

Implements:

public `setp`

Extends:

public `compound`

Aliases:

`setp` size/2 as length/2

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[set\(Type\)](#)

object

1.64.2 [set\(Type\)](#)

Set predicates with elements constrained to a single type and custom comparing rules.

Availability:

`logtalk__load(sets(loader))`

Author: Paulo Moura and Adrian Arroyo

Version: 1:24:0

Date: 2022-02-03

Compilation flags:

`static, context_switching_calls`

Extends:

`public set`

Uses:

`list`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
 - [sort/2](#)

- `partition/4`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sort/2`

Sorts a list in ascending order.

Compilation flags:

`static`

Template:

`sort(List,Sorted)`

Mode and number of proofs:

`sort(+list,-list) - one`

`partition/4`

List partition in two sub-lists using a pivot.

Compilation flags:

`static`

Template:

`partition(List,Pivot,Lowers,Biggers)`

Mode and number of proofs:

`partition(+list,+nonvar,-list,-list) - one`

Operators

(none)

protocol

1.64.3 setp

Set protocol.

Availability:

logtalk_load(sets(loader))

Author: Paulo Moura

Version: 1:6:0

Date: 2019-05-23

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - as_set/2
 - as_list/2
 - delete/3
 - disjoint/2
 - equal/2
 - empty/1
 - insert/3
 - insert_all/3
 - intersect/2

- intersection/3
- intersection/4
- size/2
- member/2
- memberchk/2
- powerset/2
- product/3
- select/3
- selectchk/3
- subset/2
- subtract/3
- symdiff/3
- union/3
- union/4
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_set/2`

Returns a set with all unique elements from the given list.

Compilation flags:

`static`

Template:

`as_set(List,Set)`

Mode and number of proofs:

`as_set(@list,-set) - one`

`as_list/2`

Returns a list with all elements of the given set.

Compilation flags:

`static`

Template:

`as_list(Set,List)`

Mode and number of proofs:

`as_list(@set,-list) - one`

`delete/3`

Deletes an element from a set returning the set of remaining elements.

Compilation flags:

`static`

Template:

`delete(Set,Element,Remaining)`

Mode and number of proofs:

`delete(+set,@term,?set) - one`

`disjoint/2`

True if the two sets have no element in common.

Compilation flags:

`static`

Template:

`disjoint(Set1,Set2)`

Mode and number of proofs:

`disjoint(+set,+set) - zero_or_one`

`equal/2`

True if the two sets are equal.

Compilation flags:

`static`

Template:

`equal(Set1,Set2)`

Mode and number of proofs:

`equal(+set,+set) - zero_or_one`

`empty/1`

True if the set is empty.

Compilation flags:

`static`

Template:

`empty(Set)`

Mode and number of proofs:

`empty(+set) - zero_or_one`

`insert/3`

Inserts an element in a set, returning the resulting set.

Compilation flags:

`static`

Template:

`insert(In,Element,Out)`

Mode and number of proofs:

`insert(+set,+term,?set) - one`

`insert_all/3`

Inserts a list of elements in a set, returning the resulting set.

Compilation flags:

`static`

Template:

`insert_all(List,In,Out)`

Mode and number of proofs:

`insert_all(+list,+set,?set) - one`

`intersect/2`

True if the two sets have at least one element in common.

Compilation flags:

`static`

Template:

`intersect(Set1,Set2)`

Mode and number of proofs:

`intersect(+set,+set) - zero_or_one`

`intersection/3`

Returns the intersection of Set1 and Set2.

Compilation flags:

`static`

Template:

`intersection(Set1,Set2,Intersection)`

Mode and number of proofs:

`intersection(+set,+set,?set) - zero_or_one`

intersection/4

True if Intersection is the intersection of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

intersection(Set1,Set2,Intersection,Difference)

Mode and number of proofs:

intersection(+set,+set,?set,?set) - zero_or_one

size/2

Number of set elements.

Compilation flags:

static

Template:

size(Set,Size)

Mode and number of proofs:

size(+set,?integer) - zero_or_one

member/2

Element is a member of set Set.

Compilation flags:

static

Template:

member(Element,Set)

Mode and number of proofs:

member(+term,+set) - zero_or_one

member(-term,+set) - zero_or_more

memberchk/2

Checks if a term is a member of a set.

Compilation flags:

static

Template:

memberchk(Element,Set)

Mode and number of proofs:

memberchk(+term,+set) - zero_or_one

powerset/2

Returns the power set of a set, represented as a list of sets.

Compilation flags:

static

Template:

powerset(Set,Powerset)

Mode and number of proofs:

powerset(+set,-list) - one

product/3

Returns the cartesian product of two sets.

Compilation flags:

static

Template:

product(Set1,Set2,Product)

Mode and number of proofs:

`product(+set,+set,-set) - one`

`select/3`

Selects an element from a set, returning the set of remaining elements.

Compilation flags:

`static`

Template:

`select(Element,Set,Remaining)`

Mode and number of proofs:

`select(?term,+set,?set) - zero_or_more`

`selectchk/3`

Checks that an element can be selected from a set, returning the set of remaining elements.

Compilation flags:

`static`

Template:

`selectchk(Element,Set,Remaining)`

Mode and number of proofs:

`selectchk(?term,+set,?set) - zero_or_one`

`subset/2`

True if Subset is a subset of Set.

Compilation flags:

`static`

Template:

subset(Subset,Set)

Mode and number of proofs:

subset(+set,+set) - zero_or_one

subtract/3

True when Difference contains all and only the elements of Set1 which are not also in Set2.

Compilation flags:

static

Template:

subtract(Set1,Set2,Difference)

Mode and number of proofs:

subtract(+set,+set,?set) - zero_or_one

symdiff/3

True if Difference is the symmetric difference of Set1 and Set2, containing all elements that are not in the sets intersection.

Compilation flags:

static

Template:

symdiff(Set1,Set2,Difference)

Mode and number of proofs:

symdiff(+set,+set,?set) - zero_or_one

union/3

True if Union is the union of Set1 and Set2.

Compilation flags:

static

Template:

union(Set1,Set2,Union)

Mode and number of proofs:

union(+set,+set,?set) - zero_or_one

union/4

True if Union is the union of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

union(Set1,Set2,Union,Difference)

Mode and number of proofs:

union(+set,+set,?set,?set) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

set, set(Type)

1.65 statistics

object

1.65.1 population

Statistical population represented as a list of numbers.

Availability:

logtalk_load(statistics(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-02-02

Compilation flags:

static, context_switching_calls

Imports:

public statistics

Remarks:

(none)

Inherited public predicates:

arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[sample](#)

object

1.65.2 [sample](#)

Statistical sample represented as a list of numbers.

Availability:

`logtalk_load(statistics(loader))`

Author: Paulo Moura

Version: 1:4:0

Date: 2020-02-02

Compilation flags:

`static, context__switching__calls`

Imports:

public [statistics](#)

Remarks:

(none)

Inherited public predicates:

arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[population](#)

[category](#)

1.65.3 statistics

Statistical calculations over a list of numbers.

Availability:

`logtalk_load(statistics(loader))`

Author: Paulo Moura

Version: 1:7:1

Date: 2023-05-29

Compilation flags:

static

Implements:

public `statisticsp`

Uses:

`list`

`numberlist`

Remarks:

(none)

Inherited public predicates:

`arithmetic_mean/2` `average_deviation/3` `coefficient_of_variation/2` `fractile/3` `geometric_mean/2`
`harmonic_mean/2` `kurtosis/2` `max/2` `mean_deviation/2` `median/2` `median_deviation/2` `min/2`
`min_max/3` `modes/2` `product/2` `range/2` `relative_standard_deviation/2` `skewness/2`
`standard_deviation/2` `sum/2` `valid/1` `variance/2` `weighted_mean/3` `z_normalization/2`

- Public predicates
- Protected predicates
- Private predicates
 - `arithmetic_mean/5`
 - `squares_and_cubes/6`
 - `squares_and_hypers/6`
 - `variance/6`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`arithmetic_mean/5`

Auxiliary predicate for computing the arithmetic mean.

Compilation flags:

`static`

Template:

`arithmetic_mean(List,Length0,Length,Sum,Mean)`

Mode and number of proofs:

`arithmetic_mean(+list(number),+integer,-integer,+number,-float) - one`

`squares_and_cubes/6`

Auxiliary predicate for computing the skewness.

Compilation flags:

`static`

Template:

`squares_and_cubes(List,Mean,Squares0,Squares,Cubes0,Cubes)`

Mode and number of proofs:

`squares_and_cubes(+list(number),+float,+float,-float,+float,-float) - one`

`squares_and_hypers/6`

Auxiliary predicate for computing the kurtosis.

Compilation flags:

`static`

Template:

`squares_and_hypers(List,Mean,Squares0,Squares,Hypers0,Hypers)`

Mode and number of proofs:

`squares_and_hypers(+list(number),+float,+float,-float,+float,-float) - one`

variance/6

Auxiliary predicate for computing the variance.

Compilation flags:

static

Template:

variance(List,Length0,Length,Mean,M20,M2)

Mode and number of proofs:

variance(+list(number),+integer,-integer,+float,+float,-float) - one

Operators

(none)

protocol

1.65.4 statisticsp

Statistical calculations over a list of numbers protocol.

Availability:

logtalk_load(statistics(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2022-06-20

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - product/2
 - sum/2
 - min/2
 - max/2
 - min_max/3
 - range/2
 - arithmetic_mean/2
 - geometric_mean/2
 - harmonic_mean/2
 - weighted_mean/3
 - median/2
 - modes/2
 - average_deviation/3
 - mean_deviation/2
 - median_deviation/2
 - standard_deviation/2
 - coefficient_of_variation/2
 - relative_standard_deviation/2
 - skewness/2
 - kurtosis/2
 - variance/2
 - z_normalization/2
 - fractile/3
 - valid/1
- Protected predicates
- Private predicates
- Operators

Public predicates`product/2`

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`product(List,Product)`

Mode and number of proofs:

`product(+list(number),-number) - zero_or_one``sum/2`

Calculates the sum of all list numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`sum(List,Sum)`

Mode and number of proofs:

`sum(+list(number),-number) - zero_or_one``min/2`

Determines the minimum value in a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`min(List,Minimum)`

Mode and number of proofs:

`min(+list,-number) - zero_or_one`

`max/2`

Determines the list maximum value in a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`max(List,Maximum)`

Mode and number of proofs:

`max(+list,-number) - zero_or_one`

`min_max/3`

Determines the minimum and maximum values in a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`min_max(List,Minimum,Maximum)`

Mode and number of proofs:

`min_max(+list(number),-number,-number) - zero_or_one`

`range/2`

Range is the length of the smallest interval which contains all the numbers in List. Fails if the list is empty.

Compilation flags:

`static`

Template:

`range(List,Range)`

Mode and number of proofs:

`range(+list,-number) - zero_or_one`

`arithmetic_mean/2`

Calculates the arithmetic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`arithmetic_mean(List,Mean)`

Mode and number of proofs:

`arithmetic_mean(+list(number),-float) - zero_or_one`

`geometric_mean/2`

Calculates the geometric mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`geometric_mean(List,Mean)`

Mode and number of proofs:

`geometric_mean(+list(number),-float) - zero_or_one`

`harmonic_mean/2`

Calculates the harmonic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

```
harmonic_mean(List,Mean)
```

Mode and number of proofs:

```
harmonic_mean(+list(number),-float) - zero_or_one
```

[weighted_mean/3](#)

Calculates the weighted mean of a list of numbers. Fails if the list is empty or if the two lists have different lengths. Wights are assume to be non-negative.

Compilation flags:

```
static
```

Template:

```
weighted_mean(Weights,List,Mean)
```

Mode and number of proofs:

```
weighted_mean(+list(number),+list(number),-float) - zero_or_one
```

[median/2](#)

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

```
static
```

Template:

```
median(List,Median)
```

Mode and number of proofs:

```
median(+list(number),-float) - zero_or_one
```

modes/2

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

static

Template:

modes(List,Modes)

Mode and number of proofs:

modes(+list(number),-list(number)) - zero_or_one

average_deviation/3

Calculates the average absolute deviation of a list of numbers given a central tendency (e.g. mean, median, or mode). Fails if the list is empty.

Compilation flags:

static

Template:

average_deviation(List,CentralTendency,Deviation)

Mode and number of proofs:

average_deviation(+list(number),+float,-float) - zero_or_one

mean_deviation/2

Calculates the mean absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

mean_deviation(List,Deviation)

Mode and number of proofs:

mean_deviation(+list(number),-float) - zero_or_one

`median_deviation/2`

Calculates the median absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`median_deviation(List,Deviation)`

Mode and number of proofs:

`median_deviation(+list(number),-float) - zero_or_one`

`standard_deviation/2`

Calculates the standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`standard_deviation(List,Deviation)`

Mode and number of proofs:

`standard_deviation(+list(number),-float) - zero_or_one`

`coefficient_of_variation/2`

Calculates the coefficient of variation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`coefficient_of_variation(List,Coefficient)`

Mode and number of proofs:

`coefficient_of_variation(+list(number),-float) - zero_or_one`

`relative_standard_deviation/2`

Calculates the relative standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`relative_standard_deviation(List,Percentage)`

Mode and number of proofs:

`relative_standard_deviation(+list(number),-float) - zero_or_one`

`skewness/2`

Calculates the (moment) skewness of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`skewness(List,Skewness)`

Mode and number of proofs:

`skewness(+list(number),-float) - zero_or_one`

`kurtosis/2`

Calculates the (excess) kurtosis of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

kurtosis(List,Kurtosis)

Mode and number of proofs:

kurtosis(+list(number),-float) - zero_or_one

variance/2

Calculates the unbiased variance of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

variance(List,Variance)

Mode and number of proofs:

variance(+list(number),-float) - zero_or_one

z_normalization/2

Normalizes a list of number such that for the resulting list the mean of is close to zero and the standard deviation is close to 1. Fails if the list is empty.

Compilation flags:

static

Template:

z_normalization(List,NormalizedList)

Mode and number of proofs:

z_normalization(+list(number),-list(float)) - zero_or_one

fractile/3

Calculates the smallest value in a list of numbers such that the list elements in its fraction P are less or equal to that value (with P in the open interval (0.0, 1.0)). Fails if the list is empty.

Compilation flags:

static

Template:

fractile(P,List,Fractile)

Mode and number of proofs:

fractile(+float,+list(integer),-integer) - zero_or_one

fractile(+float,+list(float),-float) - zero_or_one

valid/1

Term is a closed list of numbers.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

statistics, sample, population

1.66 term_io

object

1.66.1 term_io

Term input/output from/to atom, chars, and codes.

Availability:

`logtalk_load(term_io(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2023-11-14

Compilation flags:

`static, context_switching_calls`

Implements:

`public term_io_protocol`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

`format_to_atom/3 format_to_chars/3 format_to_chars/4 format_to_codes/3
format_to_codes/4 read_from_atom/2 read_from_chars/2 read_from_codes/2
read_term_from_atom/3 read_term_from_chars/3 read_term_from_chars/4
read_term_from_codes/3 read_term_from_codes/4 with_output_to/2 write_term_to_atom/3
write_term_to_chars/3 write_term_to_chars/4 write_term_to_codes/3
write_term_to_codes/4 write_to_atom/2 write_to_chars/2 write_to_codes/2`

- Public predicates
- Protected predicates
- Private predicates
 - temporary_file_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

temporary_file_/1

Logtalk session and term_io specific temporary file path.

Compilation flags:

dynamic

Template:

temporary_file_(Path)

Mode and number of proofs:

temporary_file_(-atom) - one

Operators

(none)

protocol

1.66.2 term_io_protocol

Predicates for term input/output from/to atom, chars, and codes. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(term_io(loader))
```

Author: Paulo Moura

Version: 1:3:0

Date: 2021-10-04

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

- Portability notes: To keep calls to these library predicates portable, use only standard read/write options and specify output formats using atoms.

Inherited public predicates:

```
(none)
```

- Public predicates
 - read_term_from_atom/3
 - read_from_atom/2
 - read_term_from_chars/3
 - read_term_from_chars/4
 - read_from_chars/2
 - read_term_from_codes/3
 - read_term_from_codes/4
 - read_from_codes/2
 - write_term_to_atom/3
 - write_to_atom/2
 - write_term_to_chars/3

- write_term_to_chars/4
- write_to_chars/2
- write_term_to_codes/3
- write_term_to_codes/4
- write_to_codes/2
- format_to_atom/3
- format_to_chars/3
- format_to_chars/4
- format_to_codes/3
- format_to_codes/4
- with_output_to/2
- Protected predicates
- Private predicates
- Operators

Public predicates

read_term_from_atom/3

Reads a term from an atom using the given read options. A period at the end of the atom is optional. Valid options are those supported by the standard read_term/3 predicate.

Compilation flags:

static, synchronized

Template:

read_term_from_atom(Atom,Term,Options)

Mode and number of proofs:

read_term_from_atom(+atom,-term,+list(read_option)) - one_or_error

`read_from_atom/2`

Reads a term from an atom using default read options. Shorthand for `read_term_from_atom(Atom,Term,[])`. A period at the end of the atom is optional.

Compilation flags:

`static`

Template:

`read_from_atom(Atom,Term)`

Mode and number of proofs:

`read_from_atom(+atom,-term) - one_or_error`

`read_term_from_chars/3`

Reads a term from a list of characters using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

`read_term_from_chars(Chars,Term,Options)`

Mode and number of proofs:

`read_term_from_chars(+list(character),-term,+list(read_option)) - one_or_error`

`read_term_from_chars/4`

Reads a term from a list of characters using the given read options, also returning the remaining characters. A period at the end of the term is required. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static`

Template:

`read_term_from_chars(Chars,Term,Tail,Options)`

Mode and number of proofs:

```
read_term_from_chars(+list(character),-term,-list(character),+list(read_option)) - one_or_error
```

`read_from_chars/2`

Reads a term from a list of characters using default read options. Shorthand for `read_term_from_chars(Chars,Term,[])`. A period at the end of the list is optional.

Compilation flags:

```
static
```

Template:

```
read_from_chars(Chars,Term)
```

Mode and number of proofs:

```
read_from_chars(+list(character),-term) - one_or_error
```

`read_term_from_codes/3`

Reads a term from a list of character codes using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

```
static, synchronized
```

Template:

```
read_term_from_codes(Codes,Term,Options)
```

Mode and number of proofs:

```
read_term_from_codes(+list(character_code),-term,+list(read_option)) - one_or_error
```

`read_term_from_codes/4`

Reads a term from a list of character codes using the given read options, also returning the remaining character codes. A period at the end of the term is required. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static`

Template:

`read_term_from_codes(Codes,Term,Tail,Options)`

Mode and number of proofs:

`read_term_from_codes(+list(character_code),-term,-list(character_code),+list(read_option)) - one_or_error`

`read_from_codes/2`

Reads a term from a list of character codes using default read options. Shorthand for `read_term_from_codes(Codes,Term,[])`. A period at the end of the list is optional.

Compilation flags:

`static`

Template:

`read_from_codes(Codes,Term)`

Mode and number of proofs:

`read_from_codes(+list(character_code),-term) - one_or_error`

`write_term_to_atom/3`

Writes a term to an atom using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

```
write_term_to_atom(Term,Atom,Options)
```

Mode and number of proofs:

```
write_term_to_atom(@term,-atom,+list(write_option)) - one
```

`write_to_atom/2`

Writes a term to an atom using default write options. Shorthand for `write_term_to_atom(Term,Atom,[])`.

Compilation flags:

```
static
```

Template:

```
write_to_atom(Term,Atom)
```

Mode and number of proofs:

```
write_to_atom(@term,-atom) - one
```

`write_term_to_chars/3`

Writes a term to a list of characters using the given write options. Shorthand for `write_term_to_chars(Term,Chars,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

```
static
```

Template:

```
write_term_to_chars(Term,Chars,Options)
```

Mode and number of proofs:

```
write_term_to_chars(@term,-list(character),+list(write_option)) - one
```

`write_term_to_chars/4`

Writes a term to a list of characters with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static, synchronized

Template:

`write_term_to_chars(Term,Chars,Tail,Options)`

Mode and number of proofs:

`write_term_to_chars(@term,-list(character),@term,+list(write_option))` - one

`write_to_chars/2`

Writes a term to a list of characters using default write options. Shorthand for `write_term_to_chars(Term,Chars,[],[])`.

Compilation flags:

static

Template:

`write_to_chars(Term,Chars)`

Mode and number of proofs:

`write_to_chars(@term,-list(character))` - one

`write_term_to_codes/3`

Writes a term to a list of character codes using the given write options. Shorthand for `write_term_to_codes(Term,Codes,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static

Template:

`write_term_to_codes(Term,Codes,Options)`

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),+list(write_option)) - one
```

`write_term_to_codes/4`

Writes a term to a list of character codes with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

```
static, synchronized
```

Template:

```
write_term_to_codes(Term,Codes,Tail,Options)
```

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),@term,+list(write_option)) - one
```

`write_to_codes/2`

Writes a term to a list of character codes using default write options. Shorthand for `write_term_to_chars(Term,Codes,[],[])`.

Compilation flags:

```
static
```

Template:

```
write_to_codes(Term,Codes)
```

Mode and number of proofs:

```
write_to_codes(@term,-list(character_code)) - one
```

`format__to__atom/3`

Writes a list of arguments to an atom using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format__to__atom(Format,Arguments,Atom)`

Mode and number of proofs:

`format__to__atom(@atom,+list(term),-atom) - one`

`format__to__chars/3`

Writes a list of arguments to a list of characters using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format__to__chars(Format,Arguments,Chars,[])`.

Compilation flags:

static

Template:

`format__to__chars(Format,Arguments,Chars)`

Mode and number of proofs:

`format__to__chars(@term,+list(term),-list(character)) - one`

`format__to__chars/4`

Writes a term to a list of characters with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format__to__chars(Format,Arguments,Chars,Tail)`

Mode and number of proofs:

`format__to__chars(@term,+list(term),-list(character),@term) - one`

`format__to__codes/3`

Writes a list of arguments to a list of character codes using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format__to__codes(Format,Arguments,Codes,[])`.

Compilation flags:

`static`

Template:

`format__to__codes(Format,Arguments,Codes)`

Mode and number of proofs:

`format__to__codes(@term,+list(term),-list(character_code)) - one`

`format__to__codes/4`

Writes a list of arguments to a list of character codes with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

`static, synchronized`

Template:

`format__to__codes(Format,Arguments,Codes,Tail)`

Mode and number of proofs:

`format__to__codes(@term,+list(term),-list(character_code),@term) - one`

`with_output_to/2`

Calls a goal deterministically with output to the given format: `atom(Atom)`, `chars(Chars)`, `chars(Chars,Tail)`, `codes(Codes)`, or `codes(Codes,Tail)`.

Compilation flags:

`static`, `synchronized`

Template:

`with_output_to(Output,Goal)`

Meta-predicate template:

`with_output_to(*,0)`

Mode and number of proofs:

`with_output_to(+compound,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.67 timeout

object

1.67.1 timeout

Predicates for calling goal with a time limit.

Availability:

`logtalk_load(timeout(loader))`

Author: Paulo Moura

Version: 0:10:0

Date: 2022-06-15

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - call_with_timeout/2
 - call_with_timeout/3
- Protected predicates
- Private predicates
- Operators

Public predicates

call_with_timeout/2

Calls a goal deterministically with the given time limit (expressed in seconds). Note that the goal may fail or throw an error before exhausting the time limit.

Compilation flags:

static

Template:

call_with_timeout(Goal,Timeout)

Meta-predicate template:

call_with_timeout(0,*)

Mode and number of proofs:

call_with_timeout(+callable,+positive_number) - zero_or_one

Exceptions:

Goal does not complete in the allowed time:
 timeout(Goal)

`call_with_timeout/3`

Calls a goal deterministically with the given time limit (expressed in seconds) returning a reified result: true, fail, timeout, or error(Error).

Compilation flags:

 static

Template:

 call_with_timeout(Goal,Timeout,Result)

Meta-predicate template:

 call_with_timeout(0,*,*)

Mode and number of proofs:

 call_with_timeout(+callable,+positive_number,--atom) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.68 toychr

object

1.68.1 toychrdb

Simple CHR interpreter/debugger based on the refined operational semantics of CHRs.

Availability:

```
logtalk_load(toychr(loader))
```

Author: Gregory J. Duck; adapted to Logtalk by Paulo Moura.

Version: 0:7:1

Date: 2024-03-15

Copyright: Copyright 2004 Gregory J. Duck; Copyright 2019-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
list
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - chr_is/2
 - chr_trace/0
 - chr_notrace/0
 - chr_spy/1
 - chr_nospy/0
 - chr_no_spy/1
 - chr_option/2
- Protected predicates

- `current_prog/1`
- `chr_option_print_trace/0`
- `chr_option_trace_interactive/0`
- `chr_option_optimization_level/1`
- `chr_option_show_stack/0`
- `chr_option_show_store/0`
- `chr_option_show_history/0`
- `chr_option_show_id/0`
- `chr_option_allow_deep_guards/0`
- `chr_next_state/1`
- `chr_spy_point/1`
- Private predicates
 - `chr_rule_/1`
- Operators

Public predicates

`chr_is/2`

Compilation flags:
static

`chr_trace/0`

Compilation flags:
static

`chr_notrace/0`

Compilation flags:
static

chr_spy/1

Compilation flags:
static

chr_nospy/0

Compilation flags:
static

chr_no_spy/1

Compilation flags:
static

chr_option/2

Compilation flags:
static

Protected predicates

current_prog/1

Compilation flags:
static

`chr_option_print_trace/0`

Compilation flags:
dynamic

`chr_option_trace_interactive/0`

Compilation flags:
dynamic

`chr_option_optimization_level/1`

Compilation flags:
dynamic

`chr_option_show_stack/0`

Compilation flags:
dynamic

`chr_option_show_store/0`

Compilation flags:
dynamic

`chr_option_show_history/0`

Compilation flags:
dynamic

`chr_option_show_id/0`

Compilation flags:
dynamic

`chr_option_allow_deep_guards/0`

Compilation flags:
dynamic

`chr_next_state/1`

Compilation flags:
dynamic

`chr_spy_point/1`

Compilation flags:
dynamic

Private predicates

`chr_rule_/1`

Compilation flags:
dynamic

Operators

(none)

1.69 tsv

object

1.69.1 tsv

TSV files reading and writing predicates using the option Header-keep.

Availability:
`logtalk_load(tsv(loader))`

Author: Paulo Moura
Version: 1:0:0
Date: 2023-11-15

Compilation flags:
static, context_switching_calls

Extends:
public `tsv(keep)`

Remarks:
(none)

Inherited public predicates:
`read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2`
`read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.69.2 tsv(Header)

- Header - Header handling option with possible values skip and keep (default).

TSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(tsv(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2024-03-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public tsv_protocol
```

Uses:

list
logtalk
reader
type

Remarks:

(none)

Inherited public predicates:

read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2
read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.69.3 tsv_protocol

TSV file and stream reading and writing protocol.

Availability:

logtalk_load(tsv(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2023-11-15

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

(none)

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
- Protected predicates
- Private predicates

- Operators

Public predicates

`read_file/3`

Reads a TSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Object,Predicate)`

Mode and number of proofs:

`read_file(+atom,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_stream/3`

Reads a TSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream, Object, Predicate)`

Mode and number of proofs:

`read_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias, Stream)`

Stream is not an open stream:

`existence_error(stream, Stream)`

Stream is an output stream:

`permission_error(input, stream, Stream)`

Stream is a binary stream:

`permission_error(input, binary_stream, Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier, Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object, Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator, Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate, Predicate)`

`read_file/2`

Reads a TSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Rows)`

Mode and number of proofs:

`read_file(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream/2`

Reads a TSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Rows)`

Mode and number of proofs:

`read_stream(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```

    domain_error(stream_or_alias,Stream)
Stream is not an open stream:
    existence_error(stream,Stream)
Stream is an output stream:
    permission_error(input,stream,Stream)
Stream is a binary stream:
    permission_error(input,binary_stream,Stream)

```

`read_file_by_line/3`

Reads a TSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:
static

Template:

```
read_file_by_line(File,Object,Predicate)
```

Mode and number of proofs:

```
read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be opened for reading:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`read_stream_by_line/3`

Reads a TSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_file_by_line/2`

Reads a TSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file_by_line(File,Rows)`

Mode and number of proofs:

`read_file_by_line(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream_by_line/2`

Reads a TSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```
domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)
```

`write_file/3`

Writes a TSV file with the data represented by the clauses of the specified object predicate.

Compilation flags:

```
static
```

Template:

```
write_file(File,Object,Predicate)
```

Mode and number of proofs:

```
write_file(+atom,+object_identifier,+predicate_indicator) - one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but cannot be opened for writing:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`write_stream/3`

Writes a TSV stream with the data represented by the clauses of the specified object predicate.

Compilation flags:

`static`

Template:

`write_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`write_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an input stream:

`permission_error(output,stream,Stream)`

Stream is a binary stream:

`permission_error(output,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.70 tutor

object

1.70.1 tutor

This object adds explanations and suggestions to selected compiler warning and error messages.

Availability:

`logtalk__load(tutor(loader))`

Author: Paulo Moura

Version: 0:65:0

Date: 2024-05-28

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`list`

`logtalk`

Remarks:

- Usage: Simply load this object at startup using the goal `logtalk__load(tutor(loader))`.

Inherited public predicates:

(none)

- Public predicates
 - explain//1
- Protected predicates
- Private predicates
- Operators

Public predicates

explain//1

Generates an explanation for a message.

Compilation flags:
static

Mode and number of proofs:
explain(@callable) - zero_or_one

aergnames:
[Message]

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.71 types

object

1.71.1 atom

Atom data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:9:0

Date: 2023-04-12

Compilation flags:

`static, context__switching__calls`

Extends:

`public atomic`

Uses:

`user`

Remarks:

`(none)`

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
 - `replace_sub_atom/4`
 - `split/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`replace_sub_atom/4`

Replaces all occurrences of Old by New in Input returning Output. Returns Input if Old is the empty atom. Fails when Output does not unify with the resulting atom.

Compilation flags:

`static`

Template:

`replace_sub_atom(Old,New,Input,Output)`

Mode and number of proofs:

`replace_sub_atom(+atom,+atom,+atom,?atom) - zero_or_one`

`split/3`

Splits an atom at a given delimiter into a list of sub-atoms.

Compilation flags:

`static`

Template:

`split(Atom,Delimiter,SubAtoms)`

Mode and number of proofs:

`split(+atom,+atom,-list(atom)) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.2 atomic

Atomic data type predicates.

Availability:

`logtalk__load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2018-07-11

Compilation flags:

`static, context_switching_calls`

Extends:

`public term`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.3 callable

Callable term type predicates.

Availability:

`logtalk__load(types(loader))`

Author: Paulo Moura

Version: 1:4:0

Date: 2018-07-11

Compilation flags:

`static, context_switching_calls`

Extends:

public `term`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.4 character

Character predicates (most of them assume an ASCII representation).

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:9:0

Date: 2019-06-29

Compilation flags:

`static, context_switching_calls`

Implements:

`public characterp`

Extends:

`public atom`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 is_alpha/1
is_alphanumeric/1 is_ascii/1 is_bin_digit/1 is_control/1 is_dec_digit/1 is_end_of_line/1
is_hex_digit/1 is_layout/1 is_letter/1 is_lower_case/1 is_newline/1 is_octal_digit/1
is_period/1 is_punctuation/1 is_quote/1 is_upper_case/1 is_vowel/1 is_white_space/1
lower_upper/2 new/1 numbervars/1 numbervars/3 occurs/2 parenthesis/2 replace_sub_atom/4
singletons/2 split/3 subsumes/2 subterm/2 valid/1 variables/2 variant/2 varnumbers/2
varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.71.5 characterp

Character protocol.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2019-06-29

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - is_ascii/1
 - is_alphanumeric/1
 - is_alpha/1
 - is_letter/1
 - is_bin_digit/1
 - is_octal_digit/1
 - is_dec_digit/1
 - is_hex_digit/1
 - is_lower_case/1
 - is_upper_case/1
 - is_vowel/1
 - is_white_space/1
 - is_layout/1
 - is_quote/1
 - is_punctuation/1
 - is_period/1
 - is_control/1
 - is_newline/1
 - is_end_of_line/1
 - parenthesis/2

- lower_upper/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`is_ascii/1`

True if the argument is an ASCII character.

Compilation flags:

static

Template:

`is_ascii(Char)`

Mode and number of proofs:

`is_ascii(+char) - zero_or_one`

`is_alphanumeric/1`

True if the argument is an alphanumeric character.

Compilation flags:

static

Template:

`is_alphanumeric(Char)`

Mode and number of proofs:

`is_alphanumeric(+char) - zero_or_one`

is_alpha/1

True if the argument is a letter or an underscore.

Compilation flags:

static

Template:

is_alpha(Char)

Mode and number of proofs:

is_alpha(+char) - zero_or_one

is_letter/1

True if the argument is a letter.

Compilation flags:

static

Template:

is_letter(Char)

Mode and number of proofs:

is_letter(+char) - zero_or_one

is_bin_digit/1

True if the argument is a binary digit.

Compilation flags:

static

Template:

is_bin_digit(Char)

Mode and number of proofs:

is_bin_digit(+char) - zero_or_one

`is_octal_digit/1`

True if the argument is an octal digit.

Compilation flags:

`static`

Template:

`is_octal_digit(Char)`

Mode and number of proofs:

`is_octal_digit(+char) - zero_or_one`

`is_dec_digit/1`

True if the argument is a decimal digit.

Compilation flags:

`static`

Template:

`is_dec_digit(Char)`

Mode and number of proofs:

`is_dec_digit(+char) - zero_or_one`

`is_hex_digit/1`

True if the argument is an hexadecimal digit.

Compilation flags:

`static`

Template:

`is_hex_digit(Char)`

Mode and number of proofs:

`is_hex_digit(+char) - zero_or_one`

`is_lower_case/1`

True if the argument is a lower case letter.

Compilation flags:

`static`

Template:

`is_lower_case(Char)`

Mode and number of proofs:

`is_lower_case(+char) - zero_or_one`

`is_upper_case/1`

True if the argument is a upper case letter.

Compilation flags:

`static`

Template:

`is_upper_case(Char)`

Mode and number of proofs:

`is_upper_case(+char) - zero_or_one`

`is_vowel/1`

True if the argument is a vowel.

Compilation flags:

`static`

Template:

`is_vowel(Char)`

Mode and number of proofs:

`is_vowel(+char) - zero_or_one`

`is_white_space/1`

True if the argument is a white space character (a space or a tab) inside a line of characters.

Compilation flags:

`static`

Template:

`is_white_space(Char)`

Mode and number of proofs:

`is_white_space(+char) - zero_or_one`

`is_layout/1`

True if the argument is a layout character.

Compilation flags:

`static`

Template:

`is_layout(Char)`

Mode and number of proofs:

`is_layout(+char) - zero_or_one`

`is_quote/1`

True if the argument is a quote character.

Compilation flags:

`static`

Template:

`is_quote(Char)`

Mode and number of proofs:

`is_quote(+char) - zero_or_one`

`is_punctuation/1`

True if the argument is a sentence punctuation character.

Compilation flags:

`static`

Template:

`is_punctuation(Char)`

Mode and number of proofs:

`is_punctuation(+char) - zero_or_one`

`is_period/1`

True if the argument is a character that ends a sentence.

Compilation flags:

`static`

Template:

`is_period(Char)`

Mode and number of proofs:

`is_period(+char) - zero_or_one`

`is_control/1`

True if the argument is an ASCII control character.

Compilation flags:

`static`

Template:

`is_control(Char)`

Mode and number of proofs:

`is_control(+char) - zero_or_one`

`is_newline/1`

True if the argument is the ASCII newline character.

Compilation flags:

`static`

Template:

`is_newline(Char)`

Mode and number of proofs:

`is_newline(+char) - zero_or_one`

`is_end_of_line/1`

True if the argument is the ASCII end-of-line character (either a carriage return or a line feed).

Compilation flags:

`static`

Template:

`is_end_of_line(Char)`

Mode and number of proofs:

`is_end_of_line(+char) - zero_or_one`

`parenthesis/2`

Recognizes and converts between open and close parenthesis.

Compilation flags:

`static`

Template:

`parenthesis(Char1,Char2)`

Mode and number of proofs:

`parenthesis(?char,?char) - zero_or_more`

`parenthesis(+char,?char) - zero_or_one`

`parenthesis(?char,+char) - zero_or_one`

`lower_upper/2`

Recognizes and converts between lower and upper case letters.

Compilation flags:

`static`

Template:

`lower_upper(Char1,Char2)`

Mode and number of proofs:

`lower_upper(?char,?char) - zero_or_more`

`lower_upper(+char,?char) - zero_or_one`

`lower_upper(?char,+char) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`character`

`protocol`

1.71.6 comparingp

Comparing protocol using overloading of standard operators.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:0:0
Date: 2000-07-24

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - ($<$)/2
 - ($=<$)/2
 - ($>$)/2
 - ($>=$)/2
 - ($=:=$)/2
 - ($=\backslash=$)/2
- Protected predicates
- Private predicates
- Operators

Public predicates

($<$)/2

True if Term1 is less than Term2.

Compilation flags:
static

Template:
Term1<Term2

Mode and number of proofs:

+term< +term - zero_or_one

(=<)/2

True if Term1 is less or equal than Term2.

Compilation flags:

static

Template:

Term1=<Term2

Mode and number of proofs:

+term=< +term - zero_or_one

(>)/2

True if Term1 is greater than Term2.

Compilation flags:

static

Template:

Term1>Term2

Mode and number of proofs:

+term> +term - zero_or_one

(>=)/2

True if Term1 is equal or grater than Term2.

Compilation flags:

static

Template:

Term1>=Term2

Mode and number of proofs:

+term>= +term - zero_or_one

(=:=)/2

True if Term1 is equal to Term2.

Compilation flags:

static

Template:

Term1:=Term2

Mode and number of proofs:

+term:= +term - zero_or_one

(=\=)/2

True if Term1 is not equal to Term2.

Compilation flags:

static

Template:

Term1=\=Term2

Mode and number of proofs:

+term=\= +term - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.71.7 compound

Compound data type.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2018-07-11

Compilation flags:

`static, context_switching_calls`

Extends:

`public term`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- `Public predicates`
- `Protected predicates`

- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.8 [difflist](#)

Difference list predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

`static, context_switching_calls`

Implements:

public [listp](#)

Extends:

public [compound](#)

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 check/1 delete/3
delete_matches/3 depth/2 drop/3 empty/1 flatten/2 ground/1 hamming_distance/3 keysort/2
last/2 length/2 max/2 member/2 memberchk/2 min/2 msort/2 msort/3 new/1 nextto/3
nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
occurs/2 partition/5 permutation/2 prefix/2 prefix/3 proper_prefix/2 proper_prefix/3
proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3
select/3 select/4 selectchk/3 selectchk/4 sequential_occurrences/2 sequential_occurrences/3
singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4
subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 take/3 valid/1 variables/2 variant/2
varnumbers/2 varnumbers/3

- Public predicates
 - add/3
 - as_list/2
- Protected predicates
- Private predicates
- Operators

Public predicates

add/3

Adds a term to the end of a difference list.

Compilation flags:

static

Template:

add(Term,DiffList,NewDiffList)

Mode and number of proofs:

add(@term,+difference_list,-difference_list) - one

`as_list/2`

Returns a list with the elements of the difference list.

Compilation flags:

`static`

Template:

`as_list(DiffList,List)`

Mode and number of proofs:

`as_list(@difference_list,-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`list`, `list(Type)`, `numberlist`, `varlist`

`object`

1.71.9 float

Floating point numbers data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:5:0

Date: 2018-07-15

Compilation flags:

static, context_switching_calls

Extends:

public number

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 =~= / 2 (>)/2 (>=)/2 approximately_equal/2
approximately_equal/3 check/1 depth/2 essentially_equal/3 ground/1 new/1 numbervars/1
numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 tolerance_equal/4 valid/1
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.10 integer

Integer data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:55:0

Date: 2022-06-21

Compilation flags:

`static, context_switching_calls`

Extends:

`public number`

Remarks:

- Portability notes: This object will use the backend Prolog system `between/3`, `plus/3`, and `succ/2` built-in predicates when available.

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `=~/2` `(>)/2` `(>=)/2` `approximately_equal/2`
`approximately_equal/3` `check/1` `depth/2` `essentially_equal/3` `ground/1` `new/1` `numbervars/1`
`numbervars/3` `occurs/2` `singletons/2` `subsumes/2` `subterm/2` `tolerance_equal/4` `valid/1`
`variables/2` `variant/2` `varnumbers/2` `varnumbers/3`

- Public predicates
 - `between/3`
 - `plus/3`
 - `succ/2`
 - `sequence/3`
 - `sequence/4`
- Protected predicates
- Private predicates
- Operators

Public predicates

between/3

Returns integers in the interval defined by the two first arguments.

Compilation flags:

static

Template:

between(Lower,Upper,Integer)

Mode and number of proofs:

between(+integer,+integer,+integer) - zero_or_one

between(+integer,+integer,-integer) - zero_or_more

plus/3

Reversible integer sum. At least two of the arguments must be instantiated to integers.

Compilation flags:

static

Template:

plus(I,J,Sum)

Mode and number of proofs:

plus(+integer,+integer,?integer) - zero_or_one

plus(+integer,?integer,+integer) - zero_or_one

plus(?integer,+integer,+integer) - zero_or_one

succ/2

Successor of a natural number. At least one of the arguments must be instantiated to a natural number.

Compilation flags:

static

Template:

succ(I,J)

Mode and number of proofs:

succ(+integer,?integer) - zero_or_one

succ(?integer,+integer) - zero_or_one

sequence/3

Generates a list with the sequence of all integers in the interval [Lower,Upper]. Assumes Lower =< Upper and fails otherwise.

Compilation flags:

static

Template:

sequence(Lower,Upper,List)

Mode and number of proofs:

sequence(+integer,+integer,-list(integer)) - zero_or_one

sequence/4

Generates a list with the sequence of integers in the interval [Lower,Upper] by Step. Assumes Lower =< Upper, Step >= 1 and fails otherwise.

Compilation flags:

static

Template:

sequence(Lower,Upper,Step,List)

Mode and number of proofs:

sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.11 list

List predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 4:3:0

Date: 2024-05-24

Compilation flags:

static, context_switching_calls

Implements:

public `listp`

Extends:

public `compound`

Remarks:

- Portability notes: This object will use the backend Prolog system `msort/2` and `sort/4` built-in predicates when available.

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2` `append/2` `append/3` `check/1` `delete/3`
`delete_matches/3` `depth/2` `drop/3` `empty/1` `flatten/2` `ground/1` `hamming_distance/3` `keysort/2`
`last/2` `length/2` `max/2` `member/2` `memberchk/2` `min/2` `msort/2` `msort/3` `new/1` `nextto/3`
`nth0/3` `nth0/4` `nth1/3` `nth1/4` `numbervars/1` `numbervars/3` `occurrences/2` `occurrences/3`
`occurs/2` `partition/5` `permutation/2` `prefix/2` `prefix/3` `proper_prefix/2` `proper_prefix/3`

proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3
 select/3 select/4 selectchk/3 selectchk/4 sequential_occurrences/2 sequential_occurrences/3
 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4
 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 take/3 valid/1 variables/2 variant/2
 varnumbers/2 varnumbers/3

- Public predicates
 - as_difflist/2
- Protected predicates
- Private predicates
- Operators

Public predicates

as_difflist/2

Converts a list to a difference list.

Compilation flags:

static

Template:

as_difflist(List,Diffist)

Mode and number of proofs:

as_difflist(+list,-difference_list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`list(Type)`, `numberlist`, `varlist`, `difflist`

object

1.71.12 `list(Type)`

List predicates with elements constrained to a single type.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:22:0

Date: 2018-07-11

Compilation flags:

`static`, `context_switching_calls`

Extends:

public `list`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2` `append/2` `append/3` `as_difflist/2` `check/1`
`delete/3` `delete_matches/3` `depth/2` `drop/3` `empty/1` `flatten/2` `ground/1` `hamming_distance/3`
`keysort/2` `last/2` `length/2` `max/2` `member/2` `memberchk/2` `min/2` `msort/2` `msort/3` `new/1`
`nextto/3` `nth0/3` `nth0/4` `nth1/3` `nth1/4` `numbervars/1` `numbervars/3` `occurrences/2`
`occurrences/3` `occurs/2` `partition/5` `permutation/2` `prefix/2` `prefix/3` `proper_prefix/2`
`proper_prefix/3` `proper_suffix/2` `proper_suffix/3` `remove_duplicates/2` `reverse/2` `same_length/2`
`same_length/3` `select/3` `select/4` `selectchk/3` `selectchk/4` `sequential_occurrences/2`
`sequential_occurrences/3` `singletons/2` `sort/2` `sort/3` `sort/4` `split/4` `sublist/2` `subsequence/3`
`subsequence/4` `substitute/4` `subsumes/2` `subterm/2` `subtract/3` `suffix/2` `suffix/3` `take/3` `valid/1`
`variables/2` `variant/2` `varnumbers/2` `varnumbers/3`

- Public predicates
- Protected predicates

- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[list](#), [numberlist](#), [varlist](#), [difflist](#)

[protocol](#)

1.71.13 listp

List protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:18:0

Date: 2024-05-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - append/2
 - append/3
 - delete/3
 - delete_matches/3
 - empty/1
 - flatten/2
 - hamming_distance/3
 - keysort/2
 - last/2
 - length/2
 - max/2
 - member/2
 - memberchk/2
 - min/2
 - msort/2
 - msort/3
 - nextto/3
 - nth0/3
 - nth0/4
 - nth1/3
 - nth1/4
 - sequential_occurrences/2
 - sequential_occurrences/3
 - occurrences/2
 - occurrences/3
 - partition/5
 - permutation/2
 - prefix/2
 - prefix/3
 - proper_prefix/2
 - proper_prefix/3

- remove_duplicates/2
- reverse/2
- same_length/2
- same_length/3
- select/3
- selectchk/3
- select/4
- selectchk/4
- sort/2
- sort/3
- sort/4
- split/4
- sublist/2
- subsequence/3
- subsequence/4
- substitute/4
- subtract/3
- suffix/2
- suffix/3
- proper_suffix/2
- proper_suffix/3
- take/3
- drop/3
- Protected predicates
- Private predicates
- Operators

Public predicates

append/2

Appends all lists in a list of lists.

Compilation flags:

static

Template:

append(Lists,Concatenation)

Mode and number of proofs:

append(+list(list),?list) - zero_or_one

append/3

Appends two lists.

Compilation flags:

static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements. Uses ==/2 for element comparison.

Compilation flags:

static

Template:

delete(List,Element,Remaining)

Mode and number of proofs:

delete(@list,@term,?list) - one

`delete_matches/3`

Deletes all matching elements from a list, returning the list of remaining elements. Uses `=/2` for element comparison.

Compilation flags:

`static`

Template:

`delete_matches(List,Element,Remaining)`

Mode and number of proofs:

`delete_matches(@list,@term,?list) - one`

`empty/1`

True if the argument is an empty list.

Compilation flags:

`static`

Template:

`empty(List)`

Mode and number of proofs:

`empty(@list) - zero_or_one`

`flatten/2`

Flattens a list of lists into a list.

Compilation flags:

`static`

Template:

`flatten(List,Flatted)`

Mode and number of proofs:

`flatten(+list,-list) - one`

hamming_distance/3

Calculates the Hamming distance between two lists (using equality to compare list elements). Fails if the two lists are not of the same length.

Compilation flags:

static

Template:

hamming_distance(List1,List2,Distance)

Mode and number of proofs:

hamming_distance(+list,+list,-integer) - zero_or_one

keysort/2

Sorts a list of key-value pairs in ascending order.

Compilation flags:

static

Template:

keysort(List,Sorted)

Mode and number of proofs:

keysort(+list(pair),-list(pair)) - one

last/2

List last element (if it exists).

Compilation flags:

static

Template:

last(List,Last)

Mode and number of proofs:

`last(?list,?term) - zero_or_more`

`length/2`

List length.

Compilation flags:

`static`

Template:

`length(List,Length)`

Mode and number of proofs:

`length(?list,?integer) - zero_or_more`

`max/2`

Determines the list maximum value using standard order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`max(List,Maximum)`

Mode and number of proofs:

`max(+list,-term) - zero_or_one`

`member/2`

Element is a list member.

Compilation flags:

`static`

Template:

member(Element,List)

Mode and number of proofs:

member(?term,?list) - zero_or_more

memberchk/2

Checks if a term is a member of a list.

Compilation flags:

static

Template:

memberchk(Element,List)

Mode and number of proofs:

memberchk(?term,?list) - zero_or_one

min/2

Determines the minimum value in a list using standard order. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list,-term) - zero_or_one

`msort/2`

Sorts a list in ascending order (duplicated elements are not removed).

Compilation flags:

`static`

Template:

`msort(List,Sorted)`

Mode and number of proofs:

`msort(+list,-list) - one`

`msort/3`

Sorts a list using a user-specified comparison predicate modeled on the standard `compare/3` predicate (duplicated elements are not removed).

Compilation flags:

`static`

Template:

`msort(Closure,List,Sorted)`

Meta-predicate template:

`msort(3,*,*)`

Mode and number of proofs:

`msort(+callable,+list,-list) - one`

`nextto/3`

X and Y are consecutive elements in List.

Compilation flags:

`static`

Template:

`nextto(X,Y,List)`

Mode and number of proofs:

`nextto(?term,?term,?list) - zero_or_more`

`nth0/3`

Nth element of a list (counting from zero).

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element)`

Mode and number of proofs:

`nth0(?integer,?list,?term) - zero_or_more`

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,?list,?term,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,?list,?term) - zero_or_more`

`nth1/4`

Nth element of a list (counting from one). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,?list,?term,?list) - zero_or_more`

`sequential_occurrences/2`

Counts the number of sequential occurrences of each List element, unifying Occurrences with a list of Element-Count pairs. Uses term equality for element comparison.

Compilation flags:

`static`

Template:

`sequential_occurrences(List,Occurrences)`

Mode and number of proofs:

`sequential_occurrences(@list,-list(pair(term,positive_integer))) - one`

`sequential_occurrences/3`

Counts the number of sequential occurrences of each List element, unifying Occurrences with a list of Element-Count pairs. Uses Closure for element comparison.

Compilation flags:

`static`

Template:

`sequential_occurrences(List,Closure,Occurrences)`

Mode and number of proofs:

`sequential_occurrences(@list,@callable,-list(pair(term,positive_integer))) - one`

`occurrences/2`

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses term equality for element comparison.

Compilation flags:

`static`

Template:

`occurrences(List,Occurrences)`

Mode and number of proofs:

`occurrences(@list,-list(pair(term,positive_integer))) - one`

`occurrences/3`

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses Closure for element comparison.

Compilation flags:

`static`

Template:

`occurrences(List,Closure,Occurrences)`

Meta-predicate template:

```
occurrences(*,2,*)
```

Mode and number of proofs:

```
occurrences(@list,@callable,-list(pair(term,positive_integer))) - one
```

`partition/5`

Partitions a list in lists with values less, equal, and greater than a given value (using standard order).

Compilation flags:

```
static
```

Template:

```
partition(List,Value,Less,Equal,Greater)
```

Mode and number of proofs:

```
partition(+list,+number,-list,-list,-list) - one
```

`permutation/2`

The two lists are a permutation of the same list.

Compilation flags:

```
static
```

Template:

```
permutation(List,Permutation)
```

Mode and number of proofs:

```
permutation(?list,?list) - zero_or_more
```

`prefix/2`

Prefix is a prefix of List.

Compilation flags:

`static`

Template:

`prefix(Prefix,List)`

Mode and number of proofs:

`prefix(?list,+list) - zero_or_more`

`prefix/3`

Prefix is a prefix of length Length of List.

Compilation flags:

`static`

Template:

`prefix(Prefix,Length,List)`

Mode and number of proofs:

`prefix(?list,+integer,+list) - zero_or_one`

`prefix(?list,-integer,+list) - zero_or_more`

`proper_prefix/2`

Prefix is a proper prefix of List.

Compilation flags:

`static`

Template:

`proper_prefix(Prefix,List)`

Mode and number of proofs:

`proper_prefix(?list,+list) - zero_or_more`

`proper_prefix/3`

Prefix is a proper prefix of length Length of List.

Compilation flags:

static

Template:

`proper_prefix(Prefix,Length,List)`

Mode and number of proofs:

`proper_prefix(?list,+integer,+list) - zero_or_one`

`proper_prefix(?list,-integer,+list) - zero_or_more`

`remove_duplicates/2`

Removes duplicated list elements using equality (`==/2`) for comparison and keeping the left-most element when repeated.

Compilation flags:

static

Template:

`remove_duplicates(List,Set)`

Mode and number of proofs:

`remove_duplicates(+list,-list) - one`

`reverse/2`

Reverses a list.

Compilation flags:

static

Template:

```
reverse(List,Reversed)
```

Mode and number of proofs:

```
reverse(+list,?list) - zero_or_one
```

```
reverse(?list,+list) - zero_or_one
```

```
reverse(-list,-list) - one_or_more
```

same_length/2

The two lists have the same length.

Compilation flags:

```
static
```

Template:

```
same_length(List1,List2)
```

Mode and number of proofs:

```
same_length(+list,?list) - zero_or_one
```

```
same_length(?list,+list) - zero_or_one
```

```
same_length(-list,-list) - one_or_more
```

same_length/3

The two lists have the same length.

Compilation flags:

```
static
```

Template:

```
same_length(List1,List2,Length)
```

Mode and number of proofs:

```
same_length(+list,?list,?integer) - zero_or_one
```

```
same_length(?list,+list,?integer) - zero_or_one
```

```
same_length(-list,-list,-integer) - one_or_more
```

`select/3`

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`select(Element,List,Remaining)`

Mode and number of proofs:

`select(?term,?list,?list) - zero_or_more`

`selectchk/3`

Checks that an element can be selected from a list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`selectchk(Element,List,Remaining)`

Mode and number of proofs:

`selectchk(?term,?list,?list) - zero_or_one`

`select/4`

Selects an element from a list, replacing it by a new element and returning the resulting list.

Compilation flags:

`static`

Template:

`select(Old,OldList,New,NewList)`

Mode and number of proofs:

`select(?term,?list,?term,?list) - zero_or_more`

selectchk/4

Checks that an element from a list can be replaced by a new element, returning the resulting list.

Compilation flags:

static

Template:

selectchk(Old,OldList,New,NewList)

Mode and number of proofs:

selectchk(?term,?list,?term,?list) - zero_or_one

sort/2

Sorts a list in ascending order (duplicated elements are removed).

Compilation flags:

static

Template:

sort(List,Sorted)

Mode and number of proofs:

sort(+list,-list) - one

sort/3

Sorts a list using a user-specified comparison predicate modeled on the standard compare/3 predicate (duplicated elements are removed).

Compilation flags:

static

Template:

sort(Closure,List,Sorted)

Meta-predicate template:

sort(3,*,*)

Mode and number of proofs:

```
sort(+callable,+list,-list) - one
```

```
sort/4
```

Sorts a list using the given key and order. Uses the standard term comparison operators for the order. The key selects the argument in each element in the list to use for comparisons. A key value of zero uses the whole element for comparisons.

Compilation flags:

```
static
```

Template:

```
sort(Key,Order,List,Sorted)
```

Mode and number of proofs:

```
sort(+non_negative_integer,+atom,+list,-list) - one
```

Remarks:

- Removing duplicates: Use one of the @< or @> orders.
 - Keeping duplicates: Use one of the @=< or @>= orders.
 - Sorting in ascending order: Use one of the @< or @=< orders.
 - Sorting in descending order: Use one of the @> or @>= orders.
-

```
split/4
```

Splits a list into sublists of a given length. Also returns a list with the remaining elements. Fails if the length is zero or negative.

Compilation flags:

```
static
```

Template:

```
split(List,Length,Sublists,Remaining)
```

Mode and number of proofs:

```
split(+list,+integer,-list(list),-list) - zero_or_one
```

sublist/2

The first list is a sublist of the second.

Compilation flags:

static

Template:

sublist(Sublist,List)

Mode and number of proofs:

sublist(?list,+list) - zero_or_more

subsequence/3

List is an interleaving of Subsequence and Remaining. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Subsequence,Remaining)

Mode and number of proofs:

subsequence(?list,?list,?list) - zero_or_more

subsequence/4

Generates subsequences of a given length from a list. Also returns the remaining elements. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Length,Subsequence,Remaining)

Mode and number of proofs:

subsequence(+list,+integer,?list,?list) - zero_or_more

substitute/4

Substitutes all occurrences of Old in List by New, returning NewList. Uses term equality for element comparison.

Compilation flags:

static

Template:

substitute(Old,List,New,NewList)

Mode and number of proofs:

substitute(@term,@list,@term,-list) - one

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

static

Template:

subtract(List,Elements,Remaining)

Mode and number of proofs:

subtract(+list,+list,-list) - one

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,+list) - zero_or_more

suffix/3

Suffix is a suffix of length Length of List.

Compilation flags:

static

Template:

suffix(Suffix,Length,List)

Mode and number of proofs:

suffix(?list,+integer,+list) - zero_or_one

suffix(?list,-integer,+list) - zero_or_more

proper_suffix/2

Suffix is a proper suffix of List.

Compilation flags:

static

Template:

proper_suffix(Suffix,List)

Mode and number of proofs:

proper_suffix(?list,+list) - zero_or_more

`proper_suffix/3`

Suffix is a proper suffix of length Length of List.

Compilation flags:

`static`

Template:

`proper_suffix(Suffix,Length,List)`

Mode and number of proofs:

`proper_suffix(?list,+integer,+list) - zero_or_one`

`proper_suffix(?list,-integer,+list) - zero_or_more`

`take/3`

Takes the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

`static`

Template:

`take(N,List,Elements)`

Mode and number of proofs:

`take(+integer,+list,-list) - zero_or_one`

`drop/3`

Drops the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

`static`

Template:

`drop(N,List,Remaining)`

Mode and number of proofs:

`drop(+integer,+list,-list) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`list`, `list(Type)`, `numberlistp`, `varlistp`

`object`

1.71.14 `natural`

Natural numbers data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-03-06

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public integer`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(:=)/2` `(=<)/2` `(=\=)/2` `=~/2` `(>)/2` `(>=)/2` `approximately_equal/2`
`approximately_equal/3` `between/3` `check/1` `depth/2` `essentially_equal/3` `ground/1` `new/1`
`numbervars/1` `numbervars/3` `occurs/2` `plus/3` `sequence/3` `sequence/4` `singletons/2` `subsumes/2`
`subterm/2` `succ/2` `tolerance_equal/4` `valid/1` `variables/2` `variant/2` `varnumbers/2` `varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.15 number

Number data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:14:0

Date: 2023-12-07

Compilation flags:

`static, context_switching_calls`

Extends:

`public atomic`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - approximately_equal/2
 - approximately_equal/3
 - essentially_equal/3
 - tolerance_equal/4
 - ==~ / 2
- Protected predicates
- Private predicates
- Operators
 - op(700,xfx,==~)

Public predicates

approximately_equal/2

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. No type-checking.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2)

Mode and number of proofs:

approximately_equal(+number,+number) - zero_or_one

`approximately_equal/3`

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`approximately_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`approximately_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
- Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.

`essentially_equal/3`

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`essentially_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`essentially_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.

tolerance_equal/4

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. No type-checking.

Compilation flags:

static

Template:

tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)

Mode and number of proofs:

tolerance_equal(+number,+number,+number,+number) - zero_or_one

=~/2

Compares two floats (or lists of floats) for approximate equality using 100*epsilon for the absolute error and, if that fails, 99.999% accuracy for the relative error. Note that these precision values may not be adequate for all cases. No type-checking.

Compilation flags:

static

Template:

=~/(Float1,Float2)

Mode and number of proofs:

=~/(+number,+number) - zero_or_one

=~/(+list(number),+list(number)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

op(700,xfx,=~=)

Scope:

public

object

1.71.16 numberlist

List of numbers predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:15:1

Date: 2024-01-08

Compilation flags:

static, context_switching_calls

Implements:

public [numberlistp](#)

Extends:

public [list](#)

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 as_difflist/2 average/2
chebyshev_distance/3 chebyshev_norm/2 check/1 delete/3 delete_matches/3 depth/2 drop/3
empty/1 euclidean_distance/3 euclidean_norm/2 flatten/2 ground/1 hamming_distance/3
keysort/2 last/2 least_common_multiple/2 length/2 manhattan_distance/3 manhattan_norm/2
max/2 median/2 member/2 memberchk/2 min/2 min_max/3 modes/2 msort/2 msort/3

new/1 nextto/3 normalize_range/2 normalize_range/4 normalize_scalar/2 normalize_unit/2
nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
occurs/2 partition/5 permutation/2 prefix/2 prefix/3 product/2 proper_prefix/2
proper_prefix/3 proper_suffix/2 proper_suffix/3 remove_duplicates/2 rescale/3 reverse/2
same_length/2 same_length/3 scalar_product/3 select/3 select/4 selectchk/3 selectchk/4
sequential_occurrences/2 sequential_occurrences/3 singletons/2 sort/2 sort/3 sort/4 split/4
sublist/2 subsequence/3 subsequence/4 substitute/4 subsumes/2 subterm/2 subtract/3 suffix/2
suffix/3 sum/2 take/3 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

list, list(Type), varlist, difflist

protocol

1.71.17 numberlistp

List of numbers protocol.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:9:0

Date: 2023-12-10

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - min/2
 - max/2
 - min_max/3
 - product/2
 - sum/2
 - average/2
 - median/2
 - modes/2
 - euclidean_norm/2
 - chebyshev_norm/2
 - manhattan_norm/2
 - euclidean_distance/3
 - chebyshev_distance/3
 - manhattan_distance/3
 - scalar_product/3
 - normalize_range/2
 - normalize_range/4
 - normalize_unit/2
 - normalize_scalar/2
 - rescale/3
 - least_common_multiple/2

- Protected predicates
- Private predicates
- Operators

Public predicates

`min/2`

Determines the minimum value in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`min(List,Minimum)`

Mode and number of proofs:

`min(+list(number),-number) - zero_or_one`

`max/2`

Determines the list maximum value using arithmetic order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`max(List,Maximum)`

Mode and number of proofs:

`max(+list(number),-number) - zero_or_one`

`min_max/3`

Determines the minimum and maximum values in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`min_max(List,Minimum,Maximum)`

Mode and number of proofs:

`min_max(+list(number),-number,-number) - zero_or_one`

`product/2`

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`product(List,Product)`

Mode and number of proofs:

`product(+list(number),-number) - zero_or_one`

`sum/2`

Calculates the sum of all list numbers. Returns the integer zero if the list is empty.

Compilation flags:

`static`

Template:

`sum(List,Sum)`

Mode and number of proofs:

`sum(+list(number),-number) - one`

average/2

Calculates the average (i.e. arithmetic mean) of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

average(List,Average)

Mode and number of proofs:

average(+list(number),-float) - zero_or_one

median/2

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

median(List,Median)

Mode and number of proofs:

median(+list(number),-float) - zero_or_one

modes/2

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

static

Template:

modes(List,Modes)

Mode and number of proofs:

modes(+list(number),-list(number)) - zero_or_one

`euclidean_norm/2`

Calculates the Euclidean norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`euclidean_norm(List, Norm)`

Mode and number of proofs:

`euclidean_norm(+list(number), -float) - zero_or_one`

`chebyshev_norm/2`

Calculates the Chebyshev norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`chebyshev_norm(List, Norm)`

Mode and number of proofs:

`chebyshev_norm(+list(integer), -integer) - zero_or_one`

`chebyshev_norm(+list(float), -float) - zero_or_one`

`manhattan_norm/2`

Calculates the Manhattan norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`manhattan_norm(List, Norm)`

Mode and number of proofs:

`manhattan_norm(+list(integer), -integer) - zero_or_one`

`manhattan_norm(+list(float), -float) - zero_or_one`

`euclidean_distance/3`

Calculates the Euclidean distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`euclidean_distance(List1,List2,Distance)`

Mode and number of proofs:

`euclidean_distance(+list(number),+list(number),-float) - zero_or_one`

`chebyshev_distance/3`

Calculates the Chebyshev distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`chebyshev_distance(List1,List2,Distance)`

Mode and number of proofs:

`chebyshev_distance(+list(integer),+list(integer),-integer) - zero_or_one`

`chebyshev_distance(+list(float),+list(float),-float) - zero_or_one`

`manhattan_distance/3`

Calculates the Manhattan distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

```
manhattan_distance(List1,List2,Distance)
```

Mode and number of proofs:

```
manhattan_distance(+list(integer),+list(integer),-integer) - zero_or_one
```

```
manhattan_distance(+list(float),+list(float),-float) - zero_or_one
```

`scalar_product/3`

Calculates the scalar product of two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

```
static
```

Template:

```
scalar_product(List1,List2,Product)
```

Mode and number of proofs:

```
scalar_product(+list(integer),+list(integer),-integer) - zero_or_one
```

```
scalar_product(+list(float),+list(float),-float) - zero_or_one
```

`normalize_range/2`

Normalizes a list of numbers into the [0.0,1.0] range. Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

```
static
```

Template:

```
normalize_range(List,NormalizedList)
```

Mode and number of proofs:

```
normalize_range(+list(number),-list(float)) - one
```

`normalize_range/4`

Normalizes a list of numbers into the given range. Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

`static`

Template:

`normalize_range(List,Minimum,Maximum,NormalizedList)`

Mode and number of proofs:

`normalize_range(+list(number),+number,+number,-list(float)) - one`

`normalize_unit/2`

Normalizes a list of numbers returning its unit vector (i.e. a list with Euclidean norm equal to one). Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

`static`

Template:

`normalize_unit(List,NormalizedList)`

Mode and number of proofs:

`normalize_unit(+list(number),-list(float)) - one`

`normalize_scalar/2`

Normalizes a list of numbers such that the sum of all numbers is equal to one. Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

`static`

Template:

`normalize_scalar(List,NormalizedList)`

Mode and number of proofs:


```
normalize_scalar(+list(number),-list(float)) - one
```

rescale/3

Rescales all numbers in a list by the given factor.

Compilation flags:

```
static
```

Template:

```
rescale(List,Factor,RescaledList)
```

Mode and number of proofs:

```
rescale(+list(integer),+integer,-list(integer)) - one
```

```
rescale(+list(number),+float,-list(float)) - one
```

least_common_multiple/2

Computes the least common multiple of a list of two or more positive integers. Fails if the list is empty or contains a single element. Fails also if any of the elements is zero. May require backend support for unbound integer arithmetic.

Compilation flags:

```
static
```

Template:

```
least_common_multiple(Integers,LeastCommonMultiple)
```

Mode and number of proofs:

```
least_common_multiple(+list(positive_integer),-positive_integer) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`numberlist`, `listp`, `varlistp`

`object`

1.71.18 `pairs`

Useful predicates over lists of pairs (key-value terms).

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 2:1:1

Date: 2023-11-21

Compilation flags:

`static`, `context_switching_calls`

Dependencies:

(none)

Remarks:

- Usage: This object can be loaded independently of other entities in the `types` library by using the goal `logtalk_load(types(pairs))`.

Inherited public predicates:

(none)

- Public predicates
 - keys_values/3
 - keys/2
 - key/2
 - values/2
 - value/3
 - transpose/2
 - group_sorted_by_key/2
 - group_consecutive_by_key/2
 - group_by_key/2
 - map/3
- Protected predicates
- Private predicates
- Operators

Public predicates

keys_values/3

Converts between a list of pairs and lists of keys and values. When converting to pairs, this predicate fails if the list of keys and the list of values have different lengths.

Compilation flags:

static

Template:

keys_values(Pairs,Keys,Values)

Mode and number of proofs:

keys_values(+list(pair),-list,-list) - one

keys_values(-list(pair),+list,+list) - zero_or_one

keys/2

Returns a list of keys from a list of pairs.

Compilation flags:

static

Template:

keys(Pairs,Keys)

Mode and number of proofs:

keys(+list(pair),-list) - one

key/2

Enumerates by backtracking all keys from a list of pairs.

Compilation flags:

static

Template:

key(Pairs,Key)

Mode and number of proofs:

key(+list(pair),-term) - zero_or_more

values/2

Returns a list of values from a list of pairs.

Compilation flags:

static

Template:

values(Pairs,Values)

Mode and number of proofs:

values(+list(pair),-list) - one

value/3

Returns a value addressed by the given path (a key or a list of keys in the case of nested list of pairs). Fails if path does not exist.

Compilation flags:

static

Template:

value(Pairs,Path,Value)

Mode and number of proofs:

value(+list(pair),+term,-term) - zero_or_one

value(+list(pair),+list,-term) - zero_or_one

transpose/2

Transposes a list of pairs by swapping each pair key and value. The relative order of the list elements is kept.

Compilation flags:

static

Template:

transpose(Pairs,TransposedPairs)

Mode and number of proofs:

transpose(+list(pair),-list(pair)) - one

group_sorted_by_key/2

Groups pairs by key by sorting them and then constructing new pairs by grouping all values for a given key in a list. Keys are compared using equality. Relative order of values per key is kept. Resulting list of pairs is sorted by key.

Compilation flags:

static

Template:

```
group_sorted_by_key(Pairs,Groups)
```

Mode and number of proofs:

```
group_sorted_by_key(+list(pair),-list(pair)) - one
```

```
group_consecutive_by_key/2
```

Groups pairs by constructing new pairs by grouping all values for consecutive key in a list. Keys are compared using equality. The relative order of the values for the same key is kept.

Compilation flags:

```
static
```

Template:

```
group_consecutive_by_key(Pairs,Groups)
```

Mode and number of proofs:

```
group_consecutive_by_key(+list(pair),-list(pair)) - one
```

```
group_by_key/2
```

Same as the `group_sorted_by_key/2` predicate. Deprecated.

Compilation flags:

```
static
```

Template:

```
group_by_key(Pairs,Groups)
```

Mode and number of proofs:

```
group_by_key(+list(pair),-list(pair)) - one
```

map/3

Maps a list into pairs using a closure that applies to each list element to compute its key.

Compilation flags:

static

Template:

map(Closure,List,Pairs)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(@callable,+list,-list(pair)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.71.19 term

Term utility predicates.

Availability:

logtalk__load(types(loader))

Author: Paulo Moura

Version: 1:11:0

Date: 2022-05-13

Compilation flags:

static, context_switching_calls

Implements:

public `term`

Aliases:

`term` `variables/2` as `vars/2`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2` `check/1` `depth/2` `ground/1` `new/1`
`numbervars/1` `numbervars/3` `occurs/2` `singletons/2` `subsumes/2` `subterm/2` `valid/1` `variables/2`
`variant/2` `varnumbers/2` `varnumbers/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

`protocol`

1.71.20 `term`

Term utility predicates protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:35:0

Date: 2022-05-13

Compilation flags:

`static`

Extends:

`public comparingp`

Remarks:

`(none)`

Inherited public predicates:

`(<)/2` `(:=)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2`

- Public predicates
 - `depth/2`
 - `ground/1`
 - `new/1`
 - `occurs/2`
 - `subsumes/2`
 - `subterm/2`
 - `valid/1`
 - `check/1`
 - `variant/2`
 - `variables/2`
 - `singletons/2`
 - `numbervars/3`
 - `numbervars/1`

- varnumbers/3
- varnumbers/2
- Protected predicates
- Private predicates
- Operators

Public predicates

depth/2

True if the depth of Term is Depth. The depth of atomic terms is zero; the depth of a compound term is one plus the maximum depth of its sub-terms.

Compilation flags:

static

Template:

depth(Term,Depth)

Mode and number of proofs:

depth(@term,?integer) - zero_or_one

ground/1

True if the argument is ground. Deprecated. Use the ground/1 standard predicate instead.

Compilation flags:

static

Template:

ground(Term)

Mode and number of proofs:

ground(@term) - zero_or_one

`new/1`

Creates a new term instance (if meaningful).

Compilation flags:

`static`

Template:

`new(Term)`

Mode and number of proofs:

`new(-nonvar) - zero_or_one`

`occurs/2`

True if the variable occurs in the term.

Compilation flags:

`static`

Template:

`occurs(Variable,Term)`

Mode and number of proofs:

`occurs(@var,@term) - zero_or_one`

`subsumes/2`

The first term subsumes the second term. Deprecated. Use the `subsumes_term/2` standard predicate instead.

Compilation flags:

`static`

Template:

`subsumes(General,Specific)`

Mode and number of proofs:

`subsumes(@term,@term) - zero_or_one`

subterm/2

The first term is a subterm of the second term.

Compilation flags:

static

Template:

subterm(Subterm,Term)

Mode and number of proofs:

subterm(?term,+term) - zero_or_more

valid/1

Term is valid.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

check/1

Checks if a term is valid. Throws an exception if the term is not valid.

Compilation flags:

static

Template:

check(Term)

Mode and number of proofs:

check(@nonvar) - one

variant/2

Each term is a variant of the other (i.e. they are structurally equivalent).

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

variables/2

Returns a list of all term variables (ordered as found when doing a depth-first, left-to-right traversal of Term). Deprecated. Use the standard term_variables/2 predicate instead.

Compilation flags:

static

Template:

variables(Term,List)

Mode and number of proofs:

variables(@term,-list) - one

singletons/2

Returns a list of all term singleton variables (ordered as found when doing a depth-first, left-to-right traversal of Term).

Compilation flags:

static

Template:

singletons(Term,Singletons)

Mode and number of proofs:

singletons(@term,-list) - one

`numbervars/3`

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at From. The Next argument is unified with the next value for N after binding all variables.

Compilation flags:

`static`

Template:

`numbervars(Term,From,Next)`

Mode and number of proofs:

`numbervars(?term,+integer,?integer) - zero_or_one`

`numbervars/1`

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at 0.

Compilation flags:

`static`

Template:

`numbervars(Term)`

Mode and number of proofs:

`numbervars(?term) - zero_or_one`

`varnumbers/3`

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N greater or equal to From. Variables in Term are shared with Copy.

Compilation flags:

`static`

Template:

`varnumbers(Term,From,Copy)`

Mode and number of proofs:

`varnumbers(@term,+integer,?term) - zero_or_one`

`varnumbers/2`

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N greater or equal to 0. Variables in Term are shared with Copy.

Compilation flags:

`static`

Template:

`varnumbers(Term,Copy)`

Mode and number of proofs:

`varnumbers(@term,?term) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`term`

`object`

1.71.21 type

Type checking predicates. User extensible. New types can be defined by adding clauses for the type/1 and check/2 multifile predicates.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 2:5:0

Date: 2024-03-07

Compilation flags:

```
static, context_switching_calls, complements(restrict)
```

Uses:

[list](#)

Remarks:

- Logtalk specific types: entity, object, protocol, category, entity_identifier, object_identifier, protocol_identifier, category_identifier, event, predicate.
- Prolog module related types (when the backend compiler supports modules): module, module_identifier, qualified_callable.
- Prolog base types: term, var, nonvar, atomic, atom, number, integer, float, compound, callable, ground.
- Atom derived types: non_quoted_atom, non_empty_atom, boolean, character, in_character, char, operator_specifier, hex_char.
- Atom derived parametric types: atom(CharSet), atom(CharSet,Length), non_empty_atom(CharSet), character(CharSet), in_character(CharSet), char(CharSet).
- Number derived types: positive_number, negative_number, non_positive_number, non_negative_number.
- Float derived types: positive_float, negative_float, non_positive_float, non_negative_float, probability.
- Integer derived types: positive_integer, negative_integer, non_positive_integer, non_negative_integer, byte, in_byte, character_code, in_character_code, code, operator_priority, hex_code.
- Integer derived parametric types: character_code(CharSet), in_character_code(CharSet), code(CharSet).
- List types (compound derived types): list, non_empty_list, partial_list, list_or_partial_list, list(Type), list(Type,Length), list(Type,Min,Max), list(Type,Length,Min,Max), non_empty_list(Type), codes, chars.
- Difference list types (compound derived types): difference_list, difference_list(Type).

- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`, `cyclic`, `acyclic`.
- Stream types: `stream`, `stream_or_alias`, `stream(Property)`, `stream_or_alias(Property)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `constrain(Type,Closure)`, `type`.
- Type predicate notes: This type is used to check for an object public predicate specified as `Object::Functor/Arity`.
- Type boolean notes: The two value of this type are the atoms `true` and `false`.
- Stream types notes: In the case of the `stream(Property)` and `stream_or_alias(Property)` types, `Property` must be a valid stream property.
- Type order notes: The three possible values of this type are the single character atoms `<`, `=`, and `>`.
- Type `character_code` notes: This type takes into account Unicode support by the backend compiler. When Unicode is supported, it distinguishes between BMP and full support. When Unicode is not supported, it assumes a byte representation for characters.
- Type `Object::Closure` notes: Allows calling a public object predicate for type-checking. The predicate should provide valid/2 predicate semantics and assume called with a bound argument. The Closure closure is extended with a single argument, the value to be checked.
- Type `compound(Name,Types)` notes: This type verifies that a compound term have the given `Name` and its arguments conform to `Types`.
- Type `between(Type, Lower, Upper)` notes: The type argument allows distinguishing between numbers and other types. It also allows choosing between mixed integer/float comparisons and strict float or integer comparisons. The term is type-checked before testing for interval membership.
- Type `property(Type, Lambda)` notes: Verifies that `Term` satisfies a property described using a lambda expression of the form `[Parameter]>>Goal`. The lambda expression is applied in the context of `user`. The term is type-checked before calling the goal.
- Type `one_of(Type, Set)` notes: For checking if a given term is an element of a set. The set is represented using a list. The term is type-checked before testing for set membership.
- Type `var_or(Type)` notes: Allows checking if a term is either a variable or a valid value of the given type.
- Type `ground(Type)` notes: Allows checking if a term is ground and a valid value of the given type.
- Type `types(Types)` notes: Allows checking if a term is a valid value for one of the types in a list of types.
- Type `constrain(Type,Closure)` notes: Allows checking if a term is a valid value for the given type and satisfies the given closure.
- Type `type` notes: Allows checking if a term is a valid type.
- Type `qualified_callable` notes: Allows checking if a term is a possibly module-qualified callable term. When the term is qualified, it also checks that the qualification modules are type correct. When the term is not qualified, its semantics are the same as the callable type.
- Design choices: The main predicates are `valid/2` and `check/3`. These are defined using the predicate `check/2`. Defining clauses for `check/2` instead of `valid/2` gives the user full control of exception terms without requiring an additional predicate.
- Error context: The built-in execution-context method `context/1` can be used to provide the calling context for errors when using the predicate `check/3`.

- Registering new types: New types can be registered by defining clauses for the `type/1` and `check/2` multifile predicates. Clauses for both predicates must have a bound first argument to avoid introducing spurious choice-points when type-checking terms.
- Meta-types: Meta-types are types that have one or more sub-type arguments. E.g. `var_or(Type)`. The sub-types of a meta-type can be enumerated by defining a clause for the `meta_type/3` multifile predicate.
- Character sets: When testing character or character code based terms (e.g. `atom`), it is possible to choose a character set (`ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, or `unicode_full`) using the parameterizable types.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code type-checking is only ensured for LVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

```
arbitrary/1 arbitrary/2 edge_case/2 get_seed/1 max_size/1 mutation/3 set_seed/1 shrink/3
shrink_sequence/3 shrinker/1
```

- Public predicates
 - `type/1`
 - `meta_type/3`
 - `valid/2`
 - `check/3`
 - `check/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`type/1`

Table of defined types. A new type can be registered by defining a clause for this predicate and adding a clause for the `check/2` multifile predicate.

Compilation flags:

`static`, `multifile`

Template:

`type(Type)`

Mode and number of proofs:

`type(?callable) - zero_or_more`

`meta_type/3`

Table of defined meta-types. A registered type that is a meta-type can be described by defining a clause for this predicate to enumerate its sub-types and optional values in case of a single sub-type.

Compilation flags:
static, multifile

Template:
meta_type(MetaType,SubTypes,Values)
Mode and number of proofs:
meta_type(?callable,-list,-list) - zero_or_more

`valid/2`

True if the given term is of the specified type. Fails otherwise.

Compilation flags:
static

Template:
valid(Type,Term)
Mode and number of proofs:
valid(@callable,@term) - zero_or_one

`check/3`

True if the given term is of the specified type. Throws an error otherwise using the format error(Error, Context). For the possible values of Error see the check/2 predicate.

Compilation flags:
static

Template:

check(Type,Term,Context)

Mode and number of proofs:

check(@callable,@term,@term) - one_or_error

check/2

True if the given term is of the specified type. Throws an error otherwise. A new type can be added by defining a clause for this predicate and registering it by adding a clause for the type/1 multifile predicate.

Compilation flags:

static, multifile

Template:

check(Type,Term)

Meta-predicate template:

check(:,*)

Mode and number of proofs:

check(@callable,@term) - one_or_error

Exceptions:

Term is not bound as required:

instantiation_error

Term is bound but not of the specified type:

type_error(Type,Term)

Term is the of the correct type but not in the specified domain:

domain_error(Domain,Term)

Term is the of the correct type and domain but the resource it represents does not exist:

existence_error(Type,Term)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`arbitrary`, `os_types`, `either`, `maybe`

`object`

1.71.22 varlist

List of variables predicates.

Availability:

`logtalk__load(types(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public varlistp`

Remarks:

(none)

Inherited public predicates:

`append/3` `check/1` `delete/3` `empty/1` `flatten/2` `last/2` `length/2` `memberchk/2` `nextto/3` `nth0/3`
`nth0/4` `nth1/3` `nth1/4` `permutation/2` `prefix/2` `remove_duplicates/2` `reverse/2` `same_length/2`
`select/3` `sublist/2` `subtract/3` `suffix/2` `valid/1`

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`list`, `list(Type)`, `numberlist`, `difflist`
`protocol`

1.71.23 varlistp

List of variables protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2022-09-19

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - append/3
 - delete/3
 - empty/1
 - flatten/2
 - last/2
 - length/2
 - memberchk/2
 - nextto/3
 - nth0/3
 - nth0/4
 - nth1/3
 - nth1/4
 - permutation/2
 - prefix/2
 - remove_duplicates/2
 - reverse/2
 - same_length/2
 - select/3
 - sublist/2
 - subtract/3
 - suffix/2
 - valid/1
 - check/1
- Protected predicates
- Private predicates
- Operators

Public predicates

append/3

Appends two lists.

Compilation flags:
static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements.

Compilation flags:

static

Template:

delete(List,Element,Remaining)

Mode and number of proofs:

delete(@list,@term,?list) - one

empty/1

True if the argument is an empty list.

Compilation flags:

static

Template:

empty(List)

Mode and number of proofs:

empty(@list) - zero_or_one

`flatten/2`

Flattens a list of lists into a list.

Compilation flags:

`static`

Template:

`flatten(List,Flatted)`

Mode and number of proofs:

`flatten(@list,-list) - one`

`last/2`

List last element (if it exists).

Compilation flags:

`static`

Template:

`last(List,Last)`

Mode and number of proofs:

`last(@list,@var) - zero_or_one`

`length/2`

List length.

Compilation flags:

`static`

Template:

`length(List,Length)`

Mode and number of proofs:

`length(@list,?integer) - zero_or_one`

memberchk/2

Checks if a variable is a member of a list.

Compilation flags:

static

Template:

memberchk(Element,List)

Mode and number of proofs:

memberchk(@var,@list) - zero_or_one

nextto/3

X and Y are consecutive elements in List.

Compilation flags:

static

Template:

nextto(X,Y,List)

Mode and number of proofs:

nextto(@var,@var,?list) - zero_or_more

nth0/3

Nth element of a list (counting from zero).

Compilation flags:

static

Template:

nth0(Nth,List,Element)

Mode and number of proofs:

nth0(?integer,+list,@var) - zero_or_more

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,+list,@var,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,+list,@var) - zero_or_more`

`nth1/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,+list,@var,?list) - zero_or_more`

`permutation/2`

The two lists are a permutation of the same list.

Compilation flags:

`static`

Template:

`permutation(List,Permutation)`

Mode and number of proofs:

`permutation(@list,@list) - zero_or_one`

`prefix/2`

Prefix is a prefix of List.

Compilation flags:

`static`

Template:

`prefix(Prefix,List)`

Mode and number of proofs:

`prefix(?list,@list) - zero_or_more`

`remove_duplicates/2`

Removes duplicated variables and keeping the left-most variable when repeated.

Compilation flags:

`static`

Template:

`remove_duplicates(List,Set)`

Mode and number of proofs:

`remove_duplicates(+list,-list) - one`

`reverse/2`

Reverses a list.

Compilation flags:

`static`

Template:

`reverse(List,Reversed)`

Mode and number of proofs:

`reverse(@list,?list) - zero_or_one`

`reverse(?list,@list) - zero_or_one`

`reverse(-list,-list) - one_or_more`

`same_length/2`

The two lists have the same length.

Compilation flags:

`static`

Template:

`same_length(List1,List2)`

Mode and number of proofs:

`same_length(@list,?list) - zero_or_one`

`same_length(?list,@list) - zero_or_one`

`same_length(-list,-list) - one_or_more`

`select/3`

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`select(Element,List,Remaining)`

Mode and number of proofs:

`select(@var,?list,?list) - zero_or_more`

`sublist/2`

The first list is a sublist of the second.

Compilation flags:

`static`

Template:

`sublist(Sublist,List)`

Mode and number of proofs:

`sublist(?list,@list) - zero_or_more`

`subtract/3`

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`subtract(List,Elements,Remaining)`

Mode and number of proofs:

`subtract(@list,@list,-list) - one`

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,@list) - zero_or_more

valid/1

Term is a valid list of variables.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

check/1

Checks if a term is a valid list of variables. Throws an exception if the term is not valid.

Compilation flags:

static

Template:

check(Term)

Mode and number of proofs:

check(@nonvar) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`varlist`, `listp`, `numberlistp`

1.72 ulid

object

1.72.1 ulid

Universally Unique Lexicographically Sortable Identifier (ULID) generator using an atom representation.

Availability:

`logtalk__load(ulid(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public ulid(atom)`

Remarks:

(none)

Inherited public predicates:

`generate/1` `generate/2` `generate/8` `timestamp/2` `timestamp/8`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ulid(Representation)`, `ulid_types`, `uuid`, `uuid(Representation)`, `ids`, `ids(Representation,Bytes)`
object

1.72.2 `ulid(Representation)`

- Representation - Text representation for the ULID. Possible values are atom, chars, and codes.

Universally Unique Lexicographically Sortable Identifier (ULID) generator.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

```
static, context_switching_calls
```

Implements:

`public ulid_protocol`

Uses:

`fast_random`
`iso8601`
`list`
`os`

Remarks:

(none)

Inherited public predicates:

`generate/1` `generate/2` `generate/8` `timestamp/2` `timestamp/8`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ulid`, `ulid_types`, `uuid(Representation)`, `uuid`, `ids`, `ids(Representation,Bytes)`
`protocol`

1.72.3 ulid_protocol

Universally Unique Lexicographically Sortable Identifier (ULID) generator protocol.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-17

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - generate/1
 - generate/2
 - generate/8
 - timestamp/2
 - timestamp/8
- Protected predicates
- Private predicates
- Operators

Public predicates

generate/1

Generates a new ULID.

Compilation flags:
static

Template:
generate(ULID)
Mode and number of proofs:
generate(--ulid) - one

generate/2

Generates a new ULID from a timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:
static

Template:
generate(Milliseconds,ULID)
Mode and number of proofs:
generate(+integer,--ulid) - one

generate/8

Generates a new ULID from a timestamp discrete components.

Compilation flags:
static

Template:
generate(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds,ULID)
Mode and number of proofs:

generate(+integer,+integer,+integer,+integer,+integer,+integer,+integer,--ulid) - one

timestamp/2

Returns the given ULID timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:

static

Template:

timestamp(ULID,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer) - one

timestamp/8

Decodes a ULID into its timestamp discrete components.

Compilation flags:

static

Template:

timestamp(ULID,Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.72.4 ulid__types

ULID type definition.

Availability:

`logtalk__load(ulid(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

`static`

Provides:

`type::type/1`

`type::check/2`

Uses:

`list`

`type`

Remarks:

- **Provided types:** This category adds a `ulid(Representation)` type for type-checking when using the `ulid` library object. Valid representation values are `atom`, `chars`, and `codes`.

Inherited public predicates:

(none)

- [Public predicates](#)
 - [Protected predicates](#)

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ulid(Representation)`, `ulid`

1.73 union_find

object

1.73.1 union_find

Union find data structure implementation.

Availability:

`logtalk_load(union_find(loader))`

Author: José Antonio Ríaza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-18

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public union_find_protocol`

Extends:

public compound

Uses:

avltree

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 disjoint_sets/2 find/4
find/5 ground/1 make_set/3 new/1 new/2 numbervars/1 numbervars/3 occurs/2 singletons/2
subsumes/2 subterm/2 union/4 union_all/3 valid/1 variables/2 variant/2 varnumbers/2
varnumbers/3

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.73.2 union_find_protocol

Union-find data structure protocol.

Availability:

```
logtalk_load(union_find(loader))
```

Author: José Antonio Riaza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-17

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - new/2
 - make_set/3
 - union/4
 - union_all/3
 - find/4
 - find/5
 - disjoint_sets/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`new/2`

Creates a new union-find data structure with a list of elements as keys.

Compilation flags:

`static`

Template:

`new(Elements,UnionFind)`

Mode and number of proofs:

`new(+list(element),?union_find) - zero_or_one`

`make_set/3`

Makes a new set by creating a new element with a unique key `Element`, a rank of 0, and a parent pointer to itself. The parent pointer to itself indicates that the element is the representative member of its own set.

Compilation flags:

`static`

Template:

`make_set(UnionFind,Element,NewUnionFind)`

Mode and number of proofs:

`make_set(+union_find,+element,?union_find) - zero_or_one`

`union/4`

Merges the two trees, if distinct, that contain the given elements. The trees are joined by attaching the shorter tree (by rank) to the root of the taller tree. Fails if any of the elements is not found.

Compilation flags:

`static`

Template:

`union(UnionFind,Element1,Element2,NewUnionFind)`

Mode and number of proofs:

```
union(+union_find,+element,+element,?union_find) - zero_or_one
```

`union_all/3`

Merges the distinct trees for all the given elements returning the resulting union-find data structure. Fails if any of the elements is not found.

Compilation flags:

```
static
```

Template:

```
union_all(UnionFind,Elements,NewUnionFind)
```

Mode and number of proofs:

```
union_all(+union_find,+list(element),?union_find) - zero_or_one
```

`find/4`

Finds the root element of a set by following the chain of parent pointers from the given element. Root is the representative member of the set to which the element belongs, and may be element itself. Fails if the element is not found.

Compilation flags:

```
static
```

Template:

```
find(UnionFind,Element,Root,NewUnionFind)
```

Mode and number of proofs:

```
find(+union_find,+element,?element,?union_find) - zero_or_one
```

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.
-

find/5

Same as the find/4 predicate, but returning also the rank of the root. Fails if the element is not found.

Compilation flags:

static

Template:

find(UnionFind,Element,Root,Rank,UnionFindOut)

Mode and number of proofs:

find(+union_find,+element,?element,?rank,?union_find) - zero_or_one

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.
-

disjoint_sets/2

Returns the list of disjoint sets in the given union-find data structure.

Compilation flags:

static

Template:

disjoint_sets(UnionFind,Sets)

Mode and number of proofs:

disjoint_sets(+union_find,?sets) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[union_find](#)

1.74 uuid

object

1.74.1 uuid

Universally unique identifier (UUID) generator using an atom representation.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:2:0

Date: 2022-11-23

Compilation flags:

`static, context_switching_calls`

Extends:

`public uuid(atom)`

Remarks:

(none)

Inherited public predicates:

`random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1`

- [Public predicates](#)
- [Protected predicates](#)

- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[uuid\(Representation\)](#), [ulid](#), [ulid\(Representation\)](#), [ids](#), [ids\(Representation,Bytes\)](#)
object

1.74.2 [uuid\(Representation\)](#)

- Representation - Text representation for the UUID. Possible values are atom, chars, and codes.

Universally unique identifier (UUID) generator.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2022-11-23

Compilation flags:

`static, context_switching_calls`

Implements:

`public uuid_protocol`

Uses:

`fast_random`

iso8601
list
os

Remarks:

(none)

Inherited public predicates:

random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

uuid, ulid, ulid(Representation), ids, ids(Representation,Bytes)

protocol

1.74.3 uuid_protocol

Universally unique identifier (UUID) generator protocol.

Availability:

logtalk_load(uuid(loader))

Author: Paulo Moura

Version: 0:3:0

Date: 2021-03-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - uuid_v1/2
 - uuid_v4/1
 - uuid_null/1
 - random_node/1
- Protected predicates
- Private predicates
- Operators

Public predicates

`uuid_v1/2`

Returns a version 1 UUID for the given MAC address (a list of six bytes). The MAC address can be replaced by a random 6 bytes node identifier as per RFC 4122 when the MAC address is not available or should not be disclosed.

Compilation flags:

`static`

Template:

`uuid_v1(MAC,UUID)`

Mode and number of proofs:

`uuid_v1(+list(byte),--ground) - one`

`uuid_v4/1`

Returns a version 4 UUID.

Compilation flags:

`static`

Template:

`uuid_v4(UUID)`

Mode and number of proofs:

`uuid_v4(--ground) - one`

`uuid_null/1`

Returns the null UUID.

Compilation flags:

`static`

Template:

`uuid_null(UUID)`

Mode and number of proofs:

`uuid_null(--ground) - one`

`random_node/1`

Generates a list with six random bytes that can be used in alternative to a MAC address when generating version 1 UUIDs.

Compilation flags:

`static`

Template:

`random_node(Node)`

Mode and number of proofs:

`random_node(--list(byte)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.75 verdi_neruda

object

1.75.1 a_star_interpreter(W)

A* interpreter for general logic programs. The parameter W is used to fine tune the behavior. $W = 0$ gives us a breadth-first search and $W = 1$ gives us a greedy best-first search. The default value for W is 0.5.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public best_first
```

Remarks:

```
(none)
```

Inherited public predicates:

```
prove/2 prove/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.2 benchmark_generators

Generates random data structures for use in benchmarks.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

static, context_switching_calls

Uses:

random

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - random_tree/1
- Protected predicates
- Private predicates

- Operators
-

Public predicates

`random_tree/1`

Generates a random tree.

Compilation flags:

`static`

Template:

`random_tree(Tree)`

Mode and number of proofs:

`random_tree(-tree) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

`category`

1.75.3 `best_first`

Best-first framework for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:1:0

Date: 2019-03-08

Compilation flags:

static

Implements:

public [interpreterp](#)

Uses:

[counter](#)

[minheap](#)

Remarks:

(none)

Inherited public predicates:

[prove/2](#) [prove/3](#)

- [Public predicates](#)
- [Protected predicates](#)
 - [f/4](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

[f/4](#)

.

Compilation flags:

static

Template:

[f](#)([Length1](#),[Length2](#),[Depth](#),[Cost](#))

Mode and number of proofs:

[f](#)(+float,+float,+float,-float) - zero_or_more

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.4 `bfs_interpreter`

Breadth-first interpreter for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

`queue`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.5 bup_interpreter

Semi-naive bottom-up interpreter for general (stratified) logic programs. Magic transformation is realized through an expansion hook.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Ulf Nilsson. Ported to Logtalk and augmented with negation by Victor Lagerkvist.

Version: 1:1:3

Date: 2023-11-30

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public interpreterp
```

Uses:

```
counter
```

```
list
```

```
magic
```

```
term
```

Remarks:

```
(none)
```


Inherited public predicates:

`prove/2` `prove/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.6 counter

Counter implemented with `asserta/retract`.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:1

Date: 2022-10-08

Compilation flags:

`static`, `context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - increment/0
 - increase/1
 - set/1
 - value/1
 - reset/0
- Protected predicates
- Private predicates
 - c/1
- Operators

Public predicates

increment/0

Increment the counter by 1.

Compilation flags:

static

Mode and number of proofs:

increment - one

increase/1

Increments the counter by the specified amount.

Compilation flags:

static

Template:

increase(I)

Mode and number of proofs:

increase(+number) - one

set/1

Sets the counter to the specified amount.

Compilation flags:

static

Template:

set(N)

Mode and number of proofs:

set(+number) - one

value/1

Gets the current value of the counter.

Compilation flags:

static

Template:

value(N)

Mode and number of proofs:

value(?number) - one

reset/0

Resets the counter to zero.

Compilation flags:

static

Mode and number of proofs:

reset - one

Protected predicates

(none)

Private predicates

c/1

Stores the current value of the counter.

Compilation flags:

dynamic

Template:

c(N)

Mode and number of proofs:

c(?number) - zero__or__one

Operators

(none)

protocol

1.75.7 databasep

Database protocol.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - rule/4
 - rule/3
 - rule/2
 - bench_goal/1
- Protected predicates
- Private predicates
- Operators

Public predicates

rule/4

Clauses for this predicate are automatically generated using term-expansion. The third argument contains the length of Body.

Compilation flags:

static

Template:

rule(Head,Body,Length,Tail)

Mode and number of proofs:

rule(?callable,?callable,-,-) - zero_or_more

rule/3

Clauses for this predicate are automatically generated using term-expansion. The third argument denotes the tail of the Body.

Compilation flags:

static

Template:

rule(Head,Body,Tail)

Mode and number of proofs:

rule(?callable,?callable,-) - zero_or_more

rule/2

Clauses for this predicate are automatically generated using term-expansion.

Compilation flags:

static

Template:

rule(Head,Body)

Mode and number of proofs:

`rule(?callable,-list(callable)) - zero_or_more`

`bench_goal/1`

Table of benchmark goals. They are used from `shell.lgt` to make benchmarking easier.

Compilation flags:

`static`

Template:

`bench_goal(Goal)`

Mode and number of proofs:

`bench_goal(?callable) - zero_or_more`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.75.8 `debug_expansion`(Mode)

Expands `debug/1` calls. The parameter `Mode` can be either the atom “debug” or “production”.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2010-04-15

Compilation flags:

static, context_switching_calls

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.9 demodb

Availability:

`logtalk_load(verdi_neruda(loader))`

Compilation flags:

`static, context_switching_calls`

Implements:

public `databasep`

Remarks:

(none)

Inherited public predicates:

`bench_goal/1 rule/2 rule/3 rule/4`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.10 dfs_interpreter

Depth-first interpreter for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.75.11 flattening

Flattens conjunction of goals with the form `f and g` into a list `[f,g]`.

Availability:

`logtalk__load(verdi__neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static`

source: Based on source code from The Craft of Prolog, by Richard O’Keefe.

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
 - `flatten_goals//1`
- Private predicates
- Operators

Public predicates

(none)

Protected predicates

`flatten_goals//1`

Flattens a conjunction of goals.

Compilation flags:

`static`

Template:

`flatten_goals(Conjunction)`

Mode and number of proofs:

`flatten_goals(+callable) - one`

Private predicates

(none)

Operators

(none)

object

1.75.12 `heuristic_expansion`(Mode)

Expands rules of the form `p if f and g` to `rule(p, [f,g|Tail], Length, Tail)`.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Extends:

```
public rule_expansion(Mode)
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.13 iddfs_interpreter(Increment)

Iterative deepening depth-first interpreter for general logic programs. Based on source code from The Craft of Prolog, by Richard O’Keefe. The default value for the increment is 1.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

`dfs_interpreter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.75.14 interpreterp

Protocol for an interpreter.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - prove/2
 - prove/3
- Protected predicates
- Private predicates
- Operators

Public predicates

prove/2

True if goal is provable in the specified database.

Compilation flags:

static

Template:

prove(Goal,DB)

Mode and number of proofs:

prove(+goal,+database) - zero_or_more

prove/3

True if goal is provable within the given depth-limit in the specified database.

Compilation flags:

static

Template:

prove(Goal,Limit,DB)

Mode and number of proofs:

prove(+goal,+limit,+database) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.75.15 magic

Object encapsulating magic methods.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Ulf Nilsson. Ported to Logtalk and augmented with stratified negation by Victor Lagerkvist.

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

static, context_switching_calls

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [magicise/4](#)

- `magic/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`magicise/4`

Transform `(Head :- Body)` into a magic clause `(NewHead :- NewBody)`.

Compilation flags:

`static`

Template:

`magicise(Head,Body,NewHead,NewBody)`

Mode and number of proofs:

`magicise(+term,+list,-term,-list) - zero_or_one`

`magic/2`

Prefix the predicate symbol of `Old` with `magic`.

Compilation flags:

`static`

Template:

`magic(Old,New)`

Mode and number of proofs:

`magic(+callable,-callable) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.16 magic_expansion(Mode)

Expands rules of the form `p if f and g` to the more manageable rule `(p, [f,g])` and performs magic transformation of clauses.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Imports:

`public flatting`

Extends:

`public debug_expansion(Mode)`

Uses:

`list`

`magic`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.17 [rule_expansion](#)(Mode)

Expands rules of the form `p if f and g` to the more manageable rule(`p`, `[f,g]`).

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Imports:

```
public flattening
```

Extends:

```
public debug_expansion(Mode)
```

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.18 shell

User frontend to start the application.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2019-03-20

Compilation flags:

static, context_switching_calls

Uses:

shell(Interpreters)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - welcome/0
 - start/0
- Protected predicates
- Private predicates
- Operators

Public predicates

welcome/0

Compilation flags:

static

start/0

Compilation flags:

static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.19 shell(Interpreters)

Prolog shell for the interpreters.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist and Paulo Moura

Version: 1:1:3

Date: 2024-03-15

Compilation flags:

`static, context_switching_calls`

Uses:

`counter`

`list`

`meta`

`pairs`

Remarks:

(none)

Inherited public predicates:

(none)

- `Public predicates`

– `init/0`

- Protected predicates
- Private predicates
- Operators

Public predicates

init/0

Compilation flags:
static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
object

1.75.20 shell_expansion(Mode)

Expansion object for the shell.

Availability:
logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist
Version: 1:0:1
Date: 2022-10-08

Compilation flags:
static, context_switching_calls

Implements:

public expanding

Extends:

public rule_expansion(Mode)

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.76 wrapper

object

1.76.1 wrapper

Adviser tool for porting and wrapping plain Prolog applications.

Availability:

```
logtalk_load(wrapper(loader))
```

Author: Paulo Moura

Version: 0:12:2

Date: 2024-05-10

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_hook/4
```

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Uses:

```
logtalk
```

```
os
```

Remarks:

- `prolog_extensions(Extensions)` option: List of file name extensions used to recognize Prolog source files (default is `['.pl', '.pro', '.prolog']`).
- `logtalk_extension(Extension)` option: Logtalk file name extension to be used for the generated wrapper files (default is `'.lgt'`).
- `exclude_files(Files)` option: List of Prolog source files names to exclude (default is `[]`).
- `exclude_directories(Files)` option: List of sub-directory names to exclude (default is `[]`).
- `include_wrapped_files(Boolean)`: Generate `include/1` directives for the wrapped Prolog source files (default is `true`).

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - `rdirectory/2`

- rdirectory/1
- directory/2
- directory/1
- directories/2
- directories/1
- files/2
- files/1
- file/2
- file/1
- save/1
- save/0
- default_option/1
- default_options/1
- Protected predicates
- Private predicates
 - merge_options/2
 - predicate_called_but_not_defined_/2
 - object_predicate_called_/3
 - module_predicate_called_/3
 - unknown_predicate_called_/2
 - missing_predicate_directive_/3
 - non_standard_predicate_call_/2
 - dynamic_directive_/3
 - multifile_directive_/3
 - add_directive_before_entity_/2
 - add_directive_/2
 - add_directive_/3
 - remove_directive_/2
 - file_being_advised_/4
- Operators

Public predicates

`rdirectory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list(compound)) - one`

`rdirectory/1`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`directory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

directories/2

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list(compound)) - one

directories/1

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

files/2

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using the specified options.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list(compound)) - one

files/1

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using default options.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

file/2

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using the specified options.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - one

file/1

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using default options.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

save/1

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using the specified options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Template:

save(Options)

Mode and number of proofs:

save(+list(compound)) - one

save/0

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using default options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Mode and number of proofs:

save - one

default_option/1

Enumerates by backtracking the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_option(DefaultOption)

Mode and number of proofs:

default_option(?compound) - zero_or_more

default_options/1

Returns a list of the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_options(DefaultOptions)

Mode and number of proofs:

default_options(-list(compound)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

merge_options/2

Merges the user options with the default options, returning the list of options used when generating the wrapper objects.

Compilation flags:

static

Template:

merge_options(UserOptions,Options)

Mode and number of proofs:

merge_options(+list(compound),-list(compound)) - one

`predicate_called_but_not_defined_/2`

Table of called object predicates that are not locally defined.

Compilation flags:

dynamic

Template:

`predicate_called_but_not_defined_(Object,Predicate)`

Mode and number of proofs:

`predicate_called_but_not_defined_(?atom,?predicate_indicator) - zero_or_more`

`object_predicate_called_/3`

Table of called object predicates.

Compilation flags:

dynamic

Template:

`object_predicate_called_(Object,Other,Predicate)`

Mode and number of proofs:

`object_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more`

`module_predicate_called_/3`

Table of called module predicates.

Compilation flags:

dynamic

Template:

`module_predicate_called_(Object,Module,Predicate)`

Mode and number of proofs:

`module_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more`

`unknown_predicate_called_/2`

Table of predicates called but not defined.

Compilation flags:

dynamic

Template:

`unknown_predicate_called_(Object,Predicate)`

Mode and number of proofs:

`unknown_predicate_called_(?atom,?predicate_indicator) - zero_or_more`

`missing_predicate_directive_/3`

Table of missing predicate directives.

Compilation flags:

dynamic

Template:

`missing_predicate_directive_(Object,Directive,Predicate)`

Mode and number of proofs:

`missing_predicate_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more`

`non_standard_predicate_call_/2`

Table of called non-standard predicates.

Compilation flags:

dynamic

Template:

`non_standard_predicate_call_(Object,Predicate)`

Mode and number of proofs:

`non_standard_predicate_call_(?atom,?predicate_indicator) - zero_or_more`

`dynamic_directive_/3`

Table of declared dynamic predicates.

Compilation flags:

`dynamic`

Template:

`dynamic_directive_(Object,Line,Predicate)`

Mode and number of proofs:

`dynamic_directive_(?atom,?integer,?predicate_indicator) - zero_or_more`

`multifile_directive_/3`

Table of declared multifile predicates.

Compilation flags:

`dynamic`

Template:

`multifile_directive_(Object,Line,Predicate)`

Mode and number of proofs:

`multifile_directive_(?atom,?integer,?predicate_indicator) - zero_or_more`

`add_directive_before_entity_/2`

Table of directives to be added before the entity opening directive.

Compilation flags:

`dynamic`

Template:

`add_directive_before_entity_(Object,Directive)`

Mode and number of proofs:

`add_directive_before_entity_(?atom,?predicate_indicator) - zero_or_more`

`add_directive_/2`

Table of directives to be added.

Compilation flags:

`dynamic`

Template:

`add_directive_(Object,Directive)`

Mode and number of proofs:

`add_directive_(?atom,?predicate_indicator) - zero_or_more`

`add_directive_/3`

Table of directives to be added to complement existing directives.

Compilation flags:

`dynamic`

Template:

`add_directive_(Object,Directive,NewDirective)`

Mode and number of proofs:

`add_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more`

`remove_directive_/2`

Table of directives to be removed.

Compilation flags:

`dynamic`

Template:

`remove_directive_(Object,Directive)`

Mode and number of proofs:

`remove_directive_(?atom,?predicate_indicator) - zero_or_more`

`file_being_advised_/4`

Table of files being advised are respective directories and names (basename without extension).

Compilation flags:

`dynamic`

Template:

`file_being_advised__(File,Path,Directory,Name)`

Mode and number of proofs:

`file_being_advised__((?atom,?atom,?atom,?atom) - zero_or_more`

Operators

(none)

1.77 xml_parser

object

1.77.1 xml

Bi-directional XML parser.

Availability:

`logtalk_load(xml_parser(loader))`

Author: John Fletcher; adapted to Logtalk by Paulo Moura.

Version: 3:8:4

Date: 2024-03-14

Copyright: Copyright (C) 2001-2005 Binding Time Limited, Copyright (C) 2005-2013 John Fletcher

License: This program is offered free of charge, as unsupported source code. You may use it, copy it, distribute it, modify it or sell it without restriction, but entirely at your own risk.

Compilation flags:

`static, context_switching_calls`

Uses:

list
term

Remarks:

- On-line documentation: https://binding-time.co.uk/index.php/Parsing_XML_with_Prolog
- Compliance: This XML parser supports a subset of XML suitable for XML Data and Worldwide Web applications. It is neither as strict nor as comprehensive as the XML 1.0 Specification mandates.
- Compliance-strictness: It is not as strict, because, while the specification must eliminate ambiguities, not all errors need to be regarded as faults, and some reasonable examples of real XML usage would have to be rejected if they were.
- Compliance-comprehensive: It is not as comprehensive, because, where the XML specification makes provision for more or less complete DTDs to be provided as part of a document, xml.pl actions the local definition of ENTITIES only. Other DTD extensions are treated as commentary.
- Bi-directional conversions: Conversions are not fully symmetrical as weaker XML is accepted than can be generated. Notably, in-bound (Codes -> Document) parsing does not require strictly well-formed XML. If Codes does not represent well-formed XML, Document is instantiated to the term malformed(<attributes>,<content>).

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - parse/3
 - subterm/2
 - pp/1
- Protected predicates
- Private predicates
 - xml_to_document/3
 - empty_map/1
 - map_member/3
 - map_store/4
 - pp_string/1
 - fault/5
 - exception/4
 - document_generation//2
 - pcd_data_7bit//1
 - character_data_format/3

- `cdata_generation//1`
- Operators

Public predicates

`parse/2`

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)`.

Compilation flags:

`static`

Template:

`parse(Codes,Document)`

Mode and number of proofs:

`parse(+list(character_code),?nonvar) - zero_or_one`

`parse(?list(character_code),+nonvar) - zero_or_one`

`parse/3`

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)` using the given list of options.

Compilation flags:

`static`

Template:

`parse(Options,Codes,Document)`

Mode and number of proofs:

`parse(++list(compound),+list(character_code),?nonvar) - zero_or_one`

`parse(++list(compound),?list(character_code),+nonvar) - zero_or_one`

Remarks:

- `extended_characters(Boolean)` option: Use the extended character entities for XHTML (default true).
- `format(Boolean)` option: For parsing, strip layouts when no character data appears between elements (default true). For generating, indent the element content (default true).
- `remove_attribute_prefixes(Boolean)` option: Remove namespace prefixes from attributes when it's the same as the prefix of the parent element (default false).

- `allow_ampersand(Boolean)` option: Allow unescaped ampersand characters (&) to occur in PCDATA (default false).
-

`subterm/2`

Unifies Subterm with a sub-term of XMLTerm. Note that XMLTerm is a sub-term of itself.

Compilation flags:

`static`

Template:

`subterm(XMLTerm,Subterm)`

Mode and number of proofs:

`subterm(+nonvar,?nonvar) - zero_or_one`

`pp/1`

Pretty prints a XML document on the current output stream.

Compilation flags:

`static`

Template:

`pp(XMLDocument)`

Mode and number of proofs:

`pp(+nonvar) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`xml_to_document/3`

Translates the list of character codes XML into the Prolog term Document. Options is a list of terms controlling the treatment of layout characters and character entities.

Compilation flags:

static

Template:

`xml_to_document(Options,XML,Document)`

Mode and number of proofs:

`xml_to_document(+nonvar,+nonvar,?nonvar) - zero_or_one`

`empty_map/1`

True if Map is a null map.

Compilation flags:

static

Template:

`empty_map(Map)`

Mode and number of proofs:

`empty_map(?nonvar) - zero_or_one`

`map_member/3`

True if Map is a ordered map structure which records the pair Key-Data. Key must be ground.

Compilation flags:

static

Template:

`map_member(Key,Map,Data)`

Mode and number of proofs:

`map_member(+nonvar,+nonvar,?nonvar) - zero_or_one`

`map_store/4`

True if Map0 is an ordered map structure, Key must be ground, and Map1 is identical to Map0 except that the pair Key-Data is recorded by Map1.

Compilation flags:

`static`

Template:

`map_store(Map0,Key,Data,Map1)`

Mode and number of proofs:

`map_store(+nonvar,+nonvar,+nonvar,?nonvar) - zero_or_one`

`pp_string/1`

Prints String onto the current output stream. If String contains only 7-bit chars it is printed in shorthand quoted format, otherwise it is written as a list.

Compilation flags:

`static`

Template:

`pp_string(String)`

Mode and number of proofs:

`pp_string(+nonvar) - zero_or_one`

fault/5

Identifies SubTerm as a sub-term of Term which cannot be serialized after Indentation. Message is an atom naming the type of error; Path is a string encoding a list of SubTerm's ancestor elements in the form <tag>{(id)}* where <tag> is the element tag and <id> is the value of any attribute __named__ id.

Compilation flags:

static

Template:

fault(Term,Indentation,SubTerm,Path,Message)

Mode and number of proofs:

fault(+nonvar,+nonvar,?nonvar,?nonvar,?nonvar) - zero_or_one

exception/4

Hook to raise an exception to be raised in respect of a fault in the XML Term Document.

Compilation flags:

static

Template:

exception(Message,Document,Culprit,Path)

Mode and number of proofs:

exception(+atom,+nonvar,+nonvar,+nonvar) - one

document_generation//2

DCG generating Document as a list of character codes. Format is true|false defining whether layouts, to provide indentation, should be added between the element content of the resultant "string". Note that formatting is disabled for elements that are interspersed with pcddata/1 terms, such as XHTML's 'inline' elements. Also, Format is over-ridden, for an individual element, by an explicit 'xml:space'="preserve" attribute.

Compilation flags:

static

Template:

```
document_generation(Format,Document)
```

Mode and number of proofs:

```
document_generation(+nonvar,+nonvar) - zero_or_one
```

```
pcdata_7bit//1
```

Represents the ASCII character set in its simplest format, using the character entities &, ", <, and > which are common to both XML and HTML. The numeric entity ' is used in place of ' because browsers don't recognize it in HTML.

Compilation flags:

```
static
```

Template:

```
pcdata_7bit(Code)
```

Mode and number of proofs:

```
pcdata_7bit(?nonvar) - zero_or_one
```

```
character_data_format/3
```

Holds when Format0 and Format1 are the statuses of XML formatting before and after Codes - which may be null.

Compilation flags:

```
static
```

Template:

```
character_data_format(Codes,Format0,Format1)
```

Mode and number of proofs:

```
character_data_format(+nonvar,+nonvar,?nonvar) - zero_or_one
```

`cdata_generation//1`

Holds when Format0 and Format1 are the statuses of XML formatting before and after Codes - which may be null.

Compilation flags:

`static`

Template:

`cdata_generation(Codes)`

Mode and number of proofs:

`cdata_generation(+list) - zero_or_one`

Operators

(none)

1.78 zippers

protocol

1.78.1 zipperp

Zipper protocol.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-01-20

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - zip/2
 - zip/3
 - unzip/2
 - current/2
 - next/2
 - next/3
 - previous/2
 - previous/3
 - rewind/2
 - rewind/3
 - forward/2
 - forward/3
 - apply/2
 - insert_before/3
 - insert_after/3
 - replace/3
 - delete_and_previous/2
 - delete_and_next/2
 - delete_and_unzip/2
 - delete_all_before/2
 - delete_all_before_and_unzip/2
 - delete_all_after/2
 - delete_all_after_and_unzip/2
- Protected predicates
- Private predicates
- Operators

Public predicates

zip/2

Adds a zipper to a compound term holding a sequence of elements. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper)

Mode and number of proofs:

zip(+sequence,--zipper) - zero_or_one

zip/3

Adds a zipper to a compound term holding a sequence of elements. Also returns the first element. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper,First)

Mode and number of proofs:

zip(+sequence,--zipper,--term) - zero_or_one

unzip/2

Removes a zipper from a sequence.

Compilation flags:

static

Template:

unzip(Zipper,Sequence)

Mode and number of proofs:

`unzip(@zipper,--sequence) - one`

`current/2`

Current element.

Compilation flags:
static

Template:
current(Zipper,Current)
Mode and number of proofs:
current(+zipper,?term) - zero_or_one

`next/2`

Moves to the next element. Fails if already at the last elements.

Compilation flags:
static

Template:
next(Zipper,NewZipper)
Mode and number of proofs:
next(+zipper,--zipper) - zero_or_one

`next/3`

Moves to and returns the next element. Fails if already at the last elements.

Compilation flags:
static

Template:

```
next(Zipper,NewZipper,Next)
```

Mode and number of proofs:

```
next(+zipper,--zipper,-term) - zero_or_one
```

[previous/2](#)

Moves to the previous element. Fails if already at the first elements.

Compilation flags:

```
static
```

Template:

```
previous(Zipper,NewZipper)
```

Mode and number of proofs:

```
previous(+zipper,--zipper) - zero_or_one
```

[previous/3](#)

Moves to and returns the previous element. Fails if already at the first element.

Compilation flags:

```
static
```

Template:

```
previous(Zipper,NewZipper,Previous)
```

Mode and number of proofs:

```
previous(+zipper,--zipper,-term) - zero_or_one
```

rewind/2

Rewinds the zipper so that the first element becomes the current element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper)

Mode and number of proofs:

rewind(+zipper,--zipper) - one

rewind/3

Rewinds the zipper so that the first element becomes the current element. Also returns the first element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper,First)

Mode and number of proofs:

rewind(+zipper,--zipper,?term) - zero_or_one

forward/2

Forward the zipper so that the last element becomes the current element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper)

Mode and number of proofs:

forward(+zipper,--zipper) - one

forward/3

Forward the zipper so that the last element becomes the current element. Also returns the last element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper,Last)

Mode and number of proofs:

forward(+zipper,--zipper,?term) - zero_or_one

apply/2

Applies a closure to the current element.

Compilation flags:

static

Template:

apply(Closure,Zipper)

Meta-predicate template:

apply(1,*)

Mode and number of proofs:

apply(+callable,+zipper) - zero_or_more

insert_before/3

Inserts an element before the current one.

Compilation flags:

static

Template:

insert_before(Zipper,Element,NewZipper)

Mode and number of proofs:

insert_before(+zipper,?term,--zipper) - zero_or_one

`insert_after/3`

Inserts an element after the current one.

Compilation flags:

`static`

Template:

`insert_after(Zipper,Element,NewZipper)`

Mode and number of proofs:

`insert_after(+zipper,?term,--zipper) - zero_or_one`

`replace/3`

Replaces the current element with a new element.

Compilation flags:

`static`

Template:

`replace(Zipper,NewCurrent,NewZipper)`

Mode and number of proofs:

`replace(+zipper,?term,--zipper) - one`

`delete_and_previous/2`

Deletes the current element and moves to the previous element. Fails if no previous element exists.

Compilation flags:

`static`

Template:

`delete_and_previous(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_previous(+zipper,--zipper) - zero_or_one`

`delete_and_next/2`

Deletes the current element and moves to the next element. Fails if no next element exists.

Compilation flags:

`static`

Template:

`delete_and_next(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_next(+zipper,--zipper) - zero_or_one`

`delete_and_unzip/2`

Deletes the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_and_unzip(Zipper,Sequence)`

Mode and number of proofs:

`delete_and_unzip(+zipper,--sequence) - one`

`delete_all_before/2`

Deletes all elements before the current element.

Compilation flags:

`static`

Template:

```
delete_all_before(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before(+zipper,--zipper) - one
```

```
delete_all_before_and_unzip/2
```

Deletes all elements before the current element and removes the zipper returning the resulting sequence.

Compilation flags:

```
static
```

Template:

```
delete_all_before_and_unzip(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before_and_unzip(+zipper,--sequence) - one
```

```
delete_all_after/2
```

Deletes all elements after the current element.

Compilation flags:

```
static
```

Template:

```
delete_all_after(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_after(+zipper,--zipper) - one
```

`delete_all_after_and_unzip/2`

Deletes all elements after the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_all_after_and_unzip(Zipper,NewZipper)`

Mode and number of proofs:

`delete_all_after_and_unzip(+zipper,--sequence) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`zlist`

object

1.78.2 `zlist`

Zipper list predicates. Zippers should be regarded as opaque terms.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2019-03-12

Compilation flags:

static, context_switching_calls

Implements:

public zipperp

Remarks:

(none)

Inherited public predicates:

apply/2 current/2 delete_all_after/2 delete_all_after_and_unzip/2 delete_all_before/2
delete_all_before_and_unzip/2 delete_and_next/2 delete_and_previous/2 delete_and_unzip/2
forward/2 forward/3 insert_after/3 insert_before/3 next/2 next/3 previous/2 previous/3
replace/3 rewind/2 rewind/3 unzip/2 zip/2 zip/3

- Public predicates
 - zip_at_index/4
- Protected predicates
- Private predicates
- Operators

Public predicates

zip_at_index/4

Adds a zipper to a list opened at the given index and also returns the element at the index. Fails if the list is empty or the index (starting at 1) does not exist.

Compilation flags:

static

Template:

zip_at_index(Index,List,Zipper,Element)

Mode and number of proofs:

zip_at_index(+natural,+list,--zipper,--term) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

DIRECTORIES

To load an entity, always load the library that includes it using the goal `logtalk__load(library__name(loader))` instead of using its path. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

- 2.1** `contributions/flags/`
- 2.2** `contributions/iso8601/`
- 2.3** `contributions/pddl_parser/`
- 2.4** `contributions/verdi_neruda/`
- 2.5** `contributions/xml_parser/`
- 2.6** `core/`
- 2.7** `library/`
- 2.8** `library/arbitrary/`
- 2.9** `library/assignvars/`
- 2.10** `library/base64/`
- 2.11** `library/cbor/`
- 2.12** `library/coroutining/`
- 2.13** `library/csv/`
- 2.14** `library/dates/`
- 2.15** `library/dependents/`
- 2.16** `library/dictionaries/`
- 2.17** `library/dif/`
- 2.18** `library/edcg/`
- 2.19** `library/events/`
- 2.20** `library/expand_library_alias_paths/`
- 2.1.** `contributions/flags/`
- 2.21** `library/expecteds/`

ENTITIES

To load an entity, always load the library that includes it using the goal `logtalk__load(library__name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

3.1 Categories

3.2 Objects

3.3 Protocols

PREDICATES

This index lists all entities declaring a given predicate. To load an entity providing the predicate that you want to call, always load the library that includes it using the goal `logtalk_load(library_name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

4.1 `(/)/2`

- `help`

4.2 `(//)/2`

- `help`

4.3 `(<)/2`

- `comparingp`

4.4 `(<=)/2`

- `assignvarsp`
- `streamvars`

4.5 `(:=)/2`

- `comparingp`

4.6 $(= <)/2$

- `comparingp`

4.7 $(= >)/2$

- `assignvarsp`
- `streamvars`

4.8 $(= \backslash =)/2$

- `comparingp`

4.9 $= \sim = / 2$

- `lgtunit`
- `number`

4.10 $(>)/2$

- `comparingp`

4.11 $(> =)/2$

- `comparingp`

4.12 `absolute_file_name/2`

- `osp`

4.13 `activate_debug_handler/1`

- `logtalk`

4.14 activate_monitor/0

- monitorp

4.15 active_debug_handler/1

- logtalk

4.16 add/1

- registries

4.17 add/2

- registries

4.18 add/3

- difflist
- registries

4.19 addDependent/1

- subject

4.20 after/2

- intervalp

4.21 after/3

- monitoring

4.22 all/0

- `code__metric`
- `dead__code__scanner`
- `lgtdocp`

4.23 all/1

- `code__metric`
- `dead__code__scanner`
- `lgtdocp`

4.24 all_files/0

- `diagram(Format)`
- `diagrams(Format)`

4.25 all_files/1

- `diagram(Format)`
- `diagrams(Format)`

4.26 all_libraries/0

- `diagram(Format)`
- `diagrams(Format)`

4.27 all_libraries/1

- `diagram(Format)`
- `diagrams(Format)`

4.28 all_score/1

- code_metric

4.29 ancestor/1

- hierarchyp

4.30 ancestors/1

- hierarchyp

4.31 apis/0

- help_info_support

4.32 apis/1

- help_info_support

4.33 append/2

- listp

4.34 append/3

- listp
- queuep
- varlistp

4.35 apply/2

- zipperp

4.36 apply/4

- dictionaryp

4.37 approximately_equal/2

- lgtunit
- number

4.38 approximately_equal/3

- lgtunit
- number

4.39 arbitrary/1

- arbitrary

4.40 arbitrary/2

- arbitrary

4.41 archive/1

- registry_protocol

4.42 arithmetic_mean/2

- statisticsp

4.43 array_list/2

- java_utils_protocol

4.44 array__to__list/2

- java__utils__protocol

4.45 array__to__terms/2

- java__utils__protocol

4.46 array__to__terms/3

- java__utils__protocol

4.47 as__curly__bracketed/2

- dictionaryp
- nested_dictionary_protocol

4.48 as__dictionary/2

- dictionaryp

4.49 as__difflist/2

- list

4.50 as__heap/2

- heapp

4.51 as__list/2

- dictionaryp
- difflist
- heapp
- queuep
- setp

4.52 as__nested__dictionary/2

- nested_dictionary_protocol

4.53 as__set/2

- setp

4.54 ask__question/5

- logtalk

4.55 assertion/1

- assertions(Mode)
- lgtunit

4.56 assertion/2

- assertions(Mode)
- lgtunit

4.57 assignable/1

- assignvarsp

4.58 assignable/2

- assignvarsp

4.59 available/0

- packs

4.60 available/1

- packs

4.61 available/2

- packs

4.62 average/2

- numberlistp

4.63 average_deviation/3

- statisticsp

4.64 before/2

- intervalp

4.65 before/3

- monitoring

4.66 bench_goal/1

- databasep

4.67 benchmark/2

- lgtunit

4.68 benchmark/3

- lgtunit

4.69 benchmark/4

- lgtunit

4.70 benchmark_reified/3

- lgtunit

4.71 between/3

- integer
- random_protocol

4.72 bit//1

- number_grammars(Format)

4.73 bits//1

- number_grammars(Format)

4.74 blank//0

- blank_grammars(Format)

4.75 blanks//0

- blank_grammars(Format)

4.76 body_pred/1

- metagol

4.77 branch/2

- git_protocol

4.78 built_in_directive/4

- help

4.79 built_in_flag/2

- flags

4.80 built_in_method/4

- help

4.81 built_in_non_terminal/4

- help

4.82 built_in_predicate/4

- help

4.83 calendar_month/3

- iso8601

4.84 call_with_timeout/2

- timeout

4.85 call_with_timeout/3

- timeout

4.86 cat/2

- maybe

4.87 change_directory/1

- osp

4.88 changed/0

- subject

4.89 changed/1

- subject

4.90 chebyshev_distance/3

- numberlistp

4.91 chebyshev_norm/2

- numberlistp

4.92 check/1

- term
- varlist

4.93 check/2

- type

4.94 check/3

- type

4.95 check_option/1

- options_protocol

4.96 check_options/1

- options_protocol

4.97 chr_is/2

- toychrdb

4.98 chr_no_spy/1

- toychrdb

4.99 chr_nospy/0

- toychrdb

4.100 chr_notrace/0

- toychrdb

4.101 chr_option/2

- toychrdb

4.102 chr_spy/1

- toychrdb

4.103 chr_trace/0

- toychrdb

4.104 class/1

- class_hierarchyp

4.105 classes/1

- class_hierarchyp

4.106 clause/5

- ports_profiler

4.107 clause_location/6

- ports_profiler

4.108 clean/0

- packs
- registries

4.109 clean/1

- packs
- registries

4.110 clean/2

- packs

4.111 clone/1

- cloning
- registry__protocol

4.112 clone/3

- dictionaryp

4.113 clone/4

- dictionaryp

4.114 coefficient_of_variation/2

- statisticsp

4.115 `command_line_arguments/1`

- `osp`

4.116 `commit_author/2`

- `git_protocol`

4.117 `commit_date/2`

- `git_protocol`

4.118 `commit_hash/2`

- `git_protocol`

4.119 `commit_hash_abbreviated/2`

- `git_protocol`

4.120 `commit_log/3`

- `git_protocol`

4.121 `commit_message/2`

- `git_protocol`

4.122 `compile_aux_clauses/1`

- `logtalk`

4.123 compile_predicate_heads/4

- logtalk

4.124 compile_predicate_indicators/3

- logtalk

4.125 completion/2

- help

4.126 completions/2

- help

4.127 connect/1

- redis

4.128 connect/3

- redis

4.129 console/1

- redis

4.130 contains/2

- intervalp

4.131 control//0

- blank_grammars(Format)

4.132 control_construct/4

- help

4.133 controls//0

- blank_grammars(Format)

4.134 copy__file/2

- osp

4.135 counter/2

- counters
- mutations_store

4.136 cover/1

- lgtunit

4.137 cpu_time/1

- osp
- timep

4.138 current/2

- zipperp

4.139 data/0

- ports_profiler

4.140 data/1

- ports_profiler

4.141 data/2

- ports_profiler

4.142 date/4

- iso8601

4.143 date/5

- iso8601

4.144 date/6

- iso8601

4.145 date/7

- iso8601

4.146 date_string/3

- iso8601

4.147 date_time/7

- osp

4.148 days_in_month/3

- datep

4.149 deactivate_debug_handler/0

- logtalk

4.150 debug/0

- debuggerp

4.151 debug_handler/1

- logtalk

4.152 debug_handler/3

- logtalk

4.153 debugging/0

- debuggerp

4.154 debugging/1

- debuggerp

4.155 decide/1

- fcube

4.156 decide/2

- fcube

4.157 decode__exception/2

- java__utils__protocol

4.158 decode__exception/3

- java__utils__protocol

4.159 decompile__predicate__heads/4

- logtalk

4.160 decompile__predicate__indicators/4

- logtalk

4.161 decompose__file__name/3

- osp

4.162 decompose__file__name/4

- osp

4.163 decrement_counter/1

- counters

4.164 default_option/1

- options_protocol
- wrapper

4.165 default_options/1

- options_protocol
- wrapper

4.166 define_log_file/2

- loggingp

4.167 defined/4

- registries

4.168 defined_flag/6

- flags

4.169 del_monitors/0

- event_registryp

4.170 del_monitors/4

- event_registryp

4.171 del_spy_points/4

- monitorp

4.172 delete/0

- registries

4.173 delete/1

- registries

4.174 delete/2

- registries

4.175 delete/3

- listp
- setp
- varlistp

4.176 delete/4

- dictionaryp
- heapp

4.177 delete_all_after/2

- zipperp

4.178 delete_all_after_and_unzip/2

- zipperp

4.179 delete_all_before/2

- zipperp

4.180 delete_all_before_and_unzip/2

- zipperp

4.181 delete_and_next/2

- zipperp

4.182 delete_and_previous/2

- zipperp

4.183 delete_and_unzip/2

- zipperp

4.184 delete_directory/1

- osp

4.185 delete_file/1

- osp

4.186 delete_in/4

- nested_dictionary_protocol

4.187 delete_matches/3

- listp

4.188 delete_max/4

- dictionaryp

4.189 delete_min/4

- dictionaryp

4.190 dependents/1

- packs
- subject

4.191 dependents/2

- packs

4.192 dependents/3

- packs

4.193 depth/2

- term p

4.194 descendant/1

- hierarchyp

4.195 descendant_class/1

- class_hierarchyp

4.196 descendant_classes/1

- class_hierarchyp

4.197 descendant_instance/1

- class_hierarchyp

4.198 descendant_instances/1

- class_hierarchyp

4.199 descendants/1

- hierarchyp

4.200 describe/1

- packs
- registries

4.201 describe/2

- packs

4.202 description/1

- pack_protocol
- registry_protocol

4.203 deterministic/1

- lgtunit

4.204 deterministic/2

- lgtunit

4.205 diagram_description/1

- diagram(Format)

4.206 diagram_name_suffix/1

- diagram(Format)

4.207 dif/1

- coroutining
- dif

4.208 dif/2

- coroutining
- dif

4.209 digit//1

- number_grammars(Format)

4.210 digits//1

- number_grammars(Format)

4.211 directories/1

- lgtdocp
- wrapper

4.212 directories/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.213 directories/3

- diagram(Format)
- diagrams(Format)

4.214 directory/1

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs__common
- wrapper

4.215 directory/2

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs__common
- wrapper

4.216 directory/3

- `diagram(Format)`
- `diagrams(Format)`

4.217 directory_exists/1

- `osp`

4.218 directory_files/2

- `osp`

4.219 directory_files/3

- `osp`

4.220 directory_score/2

- `code_metric`

4.221 disable/1

- `debug_messages`

4.222 disable/2

- `debug_messages`

4.223 disable_logging/1

- `loggingp`

4.224 disconnect/1

- redis

4.225 disjoint/2

- setp

4.226 disjoint_sets/2

- union_find_protocol

4.227 doc_goal/1

- doclet

4.228 dot//1

- number_grammars(Format)

4.229 dowhile/2

- loopp

4.230 drop/3

- listp

4.231 during/2

- intervalp

4.232 easter__day/3

- iso8601

4.233 edge/6

- graph_language_protocol

4.234 edge__case/2

- arbitrary

4.235 either/3

- expected(Expected)

4.236 empty/1

- dictionaryp
- heapp
- listp
- nested_dictionary_protocol
- optional
- queuep
- setp
- varlistp

4.237 enable/1

- debug_messages

4.238 enable/2

- debug_messages

4.239 enable_logging/1

- loggingp

4.240 enabled/1

- debug_messages

4.241 enabled/2

- debug_messages

4.242 ensure_directory/1

- osp

4.243 ensure_file/1

- osp

4.244 entity/1

- code_metric
- dead_code_scanner
- help
- xref_diagram(Format)

4.245 entity/2

- xref_diagram(Format)

4.246 entity_info_pair_score_hook/3

- doc_metric

4.247 entity_info_score_hook/2

- doc_metric

4.248 entity_predicates_weights_hook/2

- doc_metric

4.249 entity_prefix/2

- logtalk

4.250 entity_score/2

- code_metric

4.251 enumerate/2

- random_protocol

4.252 environment_variable/2

- osp

4.253 epsilon/1

- lgtunit

4.254 equal/2

- intervalp
- setp

4.255 erase/1

- recorded_database_core

4.256 essentially_equal/3

- lgtunit
- number

4.257 euclidean_distance/3

- numberlistp

4.258 euclidean_norm/2

- numberlistp

4.259 exclude/3

- metap

4.260 execution_context/7

- logtalk

4.261 expand_library_path/2

- logtalk

4.262 expected/1

- expected(Expected)

4.263 expecteds/2

- either

4.264 explain//1

- tutor

4.265 extension/1

- proto_hierarchyp

4.266 extensions/1

- proto_hierarchyp

4.267 false/1

- java_utils_protocol

4.268 fcube/0

- fcube

4.269 file/1

- `code_metric`
- `dead_code_scanner`
- `entity_diagram(Format)`
- `lgtdocp`
- `wrapper`

4.270 file/2

- `code_metric`
- `dead_code_scanner`
- `entity_diagram(Format)`
- `lgtdocp`
- `wrapper`

4.271 file_exists/1

- `osp`

4.272 file_footer/3

- `graph_language_protocol`

4.273 file_header/3

- `graph_language_protocol`

4.274 file_modification_time/2

- `osp`

4.275 file__permission/2

- osp

4.276 file__score/2

- code__metric

4.277 file__size/2

- osp

4.278 file__to__bytes/2

- reader

4.279 file__to__bytes/3

- reader

4.280 file__to__chars/2

- reader

4.281 file__to__chars/3

- reader

4.282 file__to__codes/2

- reader

4.283 file_to_codes/3

- reader

4.284 file_to_terms/2

- reader

4.285 file_to_terms/3

- reader

4.286 file_type_extension/2

- logtalk

4.287 files/1

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.288 files/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.289 files/3

- diagram(Format)
- diagrams(Format)

4.290 filter/2

- optional(Optional)

4.291 find/4

- union_find_protocol

4.292 find/5

- union_find_protocol

4.293 findall_member/4

- metap

4.294 findall_member/5

- metap

4.295 finished_by/2

- intervalp

4.296 finishes/2

- intervalp

4.297 flag_group_chk/1

- flags

4.298 `flag_groups/1`

- `flags`

4.299 `flat_map/2`

- `expected(Expected)`
- `optional(Optional)`

4.300 `flatten/2`

- `listp`
- `varlistp`

4.301 `float//1`

- `number_grammars(Format)`

4.302 `fold_left/4`

- `metap`

4.303 `fold_left_1/3`

- `metap`

4.304 `fold_right/4`

- `metap`

4.305 `fold_right_1/3`

- `metap`

4.306 fordownto/3

- looppp

4.307 fordownto/4

- looppp

4.308 fordownto/5

- looppp

4.309 foreach/3

- looppp

4.310 foreach/4

- looppp

4.311 format/2

- format

4.312 format/3

- format

4.313 format_entity_score//2

- code_metric

4.314 `format__object/1`

- `diagram(Format)`

4.315 `format__to__atom/3`

- `term__io__protocol`

4.316 `format__to__chars/3`

- `term__io__protocol`

4.317 `format__to__chars/4`

- `term__io__protocol`

4.318 `format__to__codes/3`

- `term__io__protocol`

4.319 `format__to__codes/4`

- `term__io__protocol`

4.320 `forto/3`

- `loopp`

4.321 `forto/4`

- `loopp`

4.322 forto/5

- loopp

4.323 forward/1

- forwarding

4.324 forward/2

- zipperp

4.325 forward/3

- zipperp

4.326 fractile/3

- statisticsp

4.327 freeze/2

- coroutining

4.328 from_generator/2

- expected
- optional

4.329 from_generator/3

- expected
- optional

4.330 from_generator/4

- expected

4.331 from_goal/2

- expected
- optional

4.332 from_goal/3

- expected
- optional

4.333 from_goal/4

- expected

4.334 frozen/2

- coroutining

4.335 full_device_path/1

- osp

4.336 func_test/3

- metagol

4.337 functional/0

- metagol

4.338 generate/1

- `ids(Representation,Bytes)`
- `ulid__protocol`

4.339 generate/2

- `base64`
- `base64url`
- `cbor(StringRepresentation)`
- `html`
- `json__protocol`
- `ulid__protocol`

4.340 generate/8

- `ulid__protocol`

4.341 genint/2

- `genint__core`

4.342 gensym/2

- `gensym__core`

4.343 geometric_mean/2

- `statisticsp`

4.344 get/1

- `optional(Optional)`

4.345 get_field/2

- java_access_protocol

4.346 get_flag_value/2

- flags

4.347 get_seed/1

- arbitrary
- pseudo_random_protocol

4.348 gnu/0

- fcube

4.349 goal_expansion/2

- expanding

4.350 graph_footer/5

- graph_language_protocol

4.351 graph_header/5

- graph_language_protocol

4.352 ground/1

- temp

4.353 group_by_key/2

- pairs

4.354 group_consecutive_by_key/2

- pairs

4.355 group_sorted_by_key/2

- pairs

4.356 guess_arity/2

- csv_protocol

4.357 guess_separator/2

- csv_protocol

4.358 hamming_distance/3

- listp

4.359 handbook/0

- help_info_support

4.360 handbook/1

- help_info_support

4.361 harmonic_mean/2

- statisticsp

4.362 head/2

- queuep

4.363 head_pred/1

- metagol

4.364 help/0

- help
- packs_common

4.365 hex_digit//1

- number_grammars(Format)

4.366 hex_digits//1

- number_grammars(Format)

4.367 home/1

- pack_protocol
- registry_protocol

4.368 ibk/3

- metagol

4.369 if_empty/1

- optional(Optional)

4.370 if_expected/1

- expected(Expected)

4.371 if_expected_or_else/2

- expected(Expected)

4.372 if_present/1

- optional(Optional)

4.373 if_present_or_else/2

- optional(Optional)

4.374 if_unexpected/1

- expected(Expected)

4.375 include/3

- metap

4.376 increase/1

- counter

4.377 increment/0

- counter

4.378 increment_counter/1

- counters

4.379 init/0

- shell(Interpreters)

4.380 init_log_file/2

- loggingp

4.381 inorder/2

- bintree

4.382 insert/3

- setp

4.383 insert/4

- dictionaryp
- heapp

4.384 insert_after/3

- zipperp

4.385 insert_all/3

- heapp
- setp

4.386 insert_before/3

- zipperp

4.387 insert_in/4

- nested_dictionary_protocol

4.388 install/1

- packs

4.389 install/2

- packs

4.390 install/3

- packs

4.391 install/4

- packs

4.392 installed/0

- packs

4.393 installed/1

- packs

4.394 installed/3

- packs

4.395 installed/4

- packs

4.396 instance/1

- class_hierarchy

4.397 instance/2

- recorded_database_core

4.398 instances/1

- class_hierarchy

4.399 integer//1

- number_grammars(Format)

4.400 internal_os_path/2

- osp

4.401 intersect/2

- setp

4.402 intersection/2

- dictionaryp

4.403 intersection/3

- dictionaryp
- setp

4.404 intersection/4

- setp

4.405 invoke/1

- java__access__protocol

4.406 invoke/2

- java__access__protocol

4.407 ipv4//1

- ip_grammars(Format)

4.408 ipv6//1

- ip_grammars(Format)

4.409 `is__absolute__file__name/1`

- `osp`

4.410 `is__alpha/1`

- `characterp`

4.411 `is__alphanumeric/1`

- `characterp`

4.412 `is__ascii/1`

- `characterp`

4.413 `is__bin__digit/1`

- `characterp`

4.414 `is__control/1`

- `characterp`

4.415 `is__dec__digit/1`

- `characterp`

4.416 `is__empty/0`

- `optional(Optional)`

4.417 `is__end__of__line/1`

- `characterp`

4.418 `is__expected/0`

- `expected(Expected)`

4.419 `is__false/1`

- `java__utils__protocol`

4.420 `is__hex__digit/1`

- `characterp`

4.421 `is__layout/1`

- `characterp`

4.422 `is__letter/1`

- `characterp`

4.423 `is__lower__case/1`

- `characterp`

4.424 `is__newline/1`

- `characterp`

4.425 is__null/1

- java_utils_protocol

4.426 is__object/1

- java_utils_protocol

4.427 is__octal__digit/1

- characterp

4.428 is__period/1

- characterp

4.429 is__present/0

- optional(Optional)

4.430 is__punctuation/1

- characterp

4.431 is__quote/1

- characterp

4.432 is__true/1

- java_utils_protocol

4.433 is__unexpected/0

- expected(Expected)

4.434 is__upper__case/1

- characterp

4.435 is__void/1

- java_utils_protocol

4.436 is__vowel/1

- characterp

4.437 is__white__space/1

- characterp

4.438 iterator__element/2

- java_utils_protocol

4.439 join/3

- queuep

4.440 join__all/3

- queuep

4.441 jump/3

- queuep

4.442 jump_all/3

- queuep

4.443 jump_all_block/3

- queuep

4.444 key/2

- pairs

4.445 keys/2

- dictionaryp
- pairs

4.446 keys_values/3

- pairs

4.447 keysort/2

- listp

4.448 kurtosis/2

- statisticsp

4.449 language_object/2

- graph_language_registry

4.450 last/2

- listp
- varlistp

4.451 leaf/1

- hierarchyp

4.452 leaf_class/1

- class_hierarchyp

4.453 leaf_classes/1

- class_hierarchyp

4.454 leaf_instance/1

- class_hierarchyp

4.455 leaf_instances/1

- class_hierarchyp

4.456 leap_year/1

- datep
- iso8601

4.457 learn/0

- metagol_example_protocol

4.458 learn/1

- metagol_example_protocol

4.459 learn/2

- metagol

4.460 learn/3

- metagol

4.461 learn_seq/2

- metagol

4.462 learn_with_timeout/4

- metagol

4.463 leash/1

- debuggerp

4.464 leashing/1

- debuggerp

4.465 least_common_multiple/2

- numberlistp

4.466 leaves/1

- hierarchyp

4.467 length/2

- listp
- queuep
- varlistp

4.468 libraries/1

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.469 libraries/2

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.470 libraries/3

- diagram(Format)
- diagrams(Format)

4.471 library/0

- help

4.472 library/1

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- help
- lgtdocp

4.473 library/2

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.474 library__score/2

- code__metric

4.475 license/1

- pack__protocol

4.476 line__to__chars/2

- reader

4.477 line_to_chars/3

- reader

4.478 line_to_codes/2

- reader

4.479 line_to_codes/3

- reader

4.480 lint/0

- packs
- registries

4.481 lint/1

- packs
- registries

4.482 lint/2

- packs

4.483 list/0

- registries

4.484 list_to_array/2

- java_utils_protocol

4.485 listing/0

- listing

4.486 listing/1

- listing

4.487 loaded_file/1

- logtalk

4.488 loaded_file_property/2

- logtalk
- modules_diagram_support

4.489 log/3

- debuggerp

4.490 log_event/2

- loggingp

4.491 log_file/2

- loggingp

4.492 logging/1

- loggingp

4.493 logging/3

- debuggerp

4.494 logtalk_packs/0

- packs_common

4.495 logtalk_packs/1

- packs_common

4.496 lookup/2

- dictionaryp

4.497 lookup/3

- dictionaryp

4.498 lookup_in/3

- nested_dictionary_protocol

4.499 lower_upper/2

- characterp

4.500 magic/2

- magic

4.501 magicise/4

- magic

4.502 make_directory/1

- osp

4.503 make_directory_path/1

- osp

4.504 make_set/3

- union_find_protocol

4.505 man/1

- help_info_support

4.506 manhattan_distance/3

- numberlistp

4.507 manhattan_norm/2

- numberlistp

4.508 manuals/0

- help

4.509 map/2

- dictionaryp
- expected(Expected)
- metap
- optional(Optional)
- queuep

4.510 map/3

- dictionaryp
- metap
- pairs
- queuep

4.511 map/4

- metap

4.512 map/5

- metap

4.513 map/6

- metap

4.514 map/7

- metap

4.515 map/8

- metap

4.516 map_element/2

- java_utils_protocol

4.517 map_reduce/5

- metap

4.518 max/2

- listp
- numberlistp
- statisticsp

4.519 max/3

- dictionaryp

4.520 max_clauses/1

- metagol

4.521 max_inv_preds/1

- metagol

4.522 max_size/1

- arbitrary

4.523 maybe/0

- random_protocol

4.524 maybe/1

- random_protocol

4.525 maybe/2

- random_protocol

4.526 maybe_call/1

- random_protocol

4.527 maybe_call/2

- random_protocol

4.528 mean_deviation/2

- statisticsp

4.529 median/2

- numberlistp
- statisticsp

4.530 median_deviation/2

- statisticsp

4.531 meets/2

- intervalp

4.532 member/2

- listp
- random_protocol
- setp

4.533 memberchk/2

- listp
- setp
- varlistp

4.534 merge/3

- heapp

4.535 message_hook/4

- logtalk

4.536 message_prefix_stream/4

- logtalk

4.537 message_tokens//2

- logtalk

4.538 met_by/2

- intervalp

4.539 meta_type/3

- type

4.540 metarule/6

- metagol

4.541 metarule_next_id/1

- metagol

4.542 min/2

- listp
- numberlistp
- statisticsp

4.543 min/3

- dictionaryp

4.544 min_clauses/1

- metagol

4.545 min_max/3

- numberlistp
- statisticsp

4.546 modes/2

- numberlistp
- statisticsp

4.547 module_property/2

- modules_diagram_support

4.548 monitor/1

- event_registry

4.549 monitor/4

- event_registry

4.550 monitor_activated/0

- monitorp

4.551 monitored/1

- event_registry

4.552 monitors/1

- event_registry

4.553 msort/2

- listp

4.554 msort/3

- listp

4.555 mutation/3

- mutations
- mutations_store

4.556 name/1

- pack_protocol
- registry_protocol

4.557 name_of_day/3

- datep

4.558 name_of_month/3

- datep

4.559 natural//1

- number_grammars(Format)

4.560 new/1

- java_access_protocol
- nested_dictionary_protocol
- streamvars
- termp

4.561 new/2

- java__access__protocol
- streamvars
- union__find__protocol

4.562 new/3

- intervalp

4.563 new__line//0

- blank__grammars(Format)

4.564 new__lines//0

- blank__grammars(Format)

4.565 next/2

- zipperp

4.566 next/3

- zipperp

4.567 next/4

- dictionaryp

4.568 nextto/3

- listp
- varlistp

4.569 node/7

- graph_language_protocol

4.570 nodebug/0

- debuggerp

4.571 nolog/3

- debuggerp

4.572 nologall/0

- debuggerp

4.573 non_blank//1

- blank_grammars(Format)

4.574 non_blanks//1

- blank_grammars(Format)

4.575 normal_element/2

- html

4.576 normalize_range/2

- numberlistp

4.577 normalize_range/4

- numberlistp

4.578 normalize_scalar/2

- numberlistp

4.579 normalize_unit/2

- numberlistp

4.580 nospy/1

- debuggerp

4.581 nospy/4

- debuggerp

4.582 nospyall/0

- debuggerp

4.583 note/2

- registry_protocol

4.584 note/3

- pack_protocol

4.585 notrace/0

- debuggerp

4.586 now/3

- timep

4.587 nth0/3

- listp
- varlistp

4.588 nth0/4

- listp
- varlistp

4.589 nth1/3

- listp
- varlistp

4.590 nth1/4

- listp
- varlistp

4.591 null/1

- java_utils_protocol

4.592 null_device_path/1

- osp

4.593 number//1

- number_grammars(Format)

4.594 number_of_tests/1

- lgtunit

4.595 numbervars/1

- term_p

4.596 numbervars/3

- term_p

4.597 occurrences/2

- list_p

4.598 occurrences/3

- list_p

4.599 occurs/2

- term_p

4.600 of/2

- optional

4.601 of_expected/2

- expected

4.602 of_unexpected/2

- expected

4.603 one_or_more//0

- sequence_grammars

4.604 one_or_more//1

- sequence_grammars

4.605 one_or_more//2

- sequence_grammars

4.606 operating_system_machine/1

- osp

4.607 operating_system_name/1

- osp

4.608 `operating_system_release/1`

- `osp`

4.609 `operating_system_type/1`

- `osp`

4.610 `option/2`

- `options_protocol`

4.611 `option/3`

- `options_protocol`

4.612 `or/2`

- `optional(Optional)`

4.613 `or_else/2`

- `expected(Expected)`
- `optional(Optional)`

4.614 `or_else_call/2`

- `expected(Expected)`
- `optional(Optional)`

4.615 `or_else_fail/1`

- `expected(Expected)`
- `optional(Optional)`

4.616 or_else_get/2

- expected(Expected)
- optional(Optional)

4.617 or_else_throw/1

- expected(Expected)

4.618 or_else_throw/2

- optional(Optional)

4.619 orphaned/0

- packs

4.620 orphaned/2

- packs

4.621 outdated/0

- packs

4.622 outdated/1

- packs

4.623 outdated/4

- packs

4.624 output_file_name/2

- graph_language_protocol

4.625 overlapped_by/2

- intervalp

4.626 overlaps/2

- intervalp

4.627 parent/1

- proto_hierarchyp

4.628 parenthesis/2

- characterp

4.629 parents/1

- proto_hierarchyp

4.630 parse/2

- base64
- base64url
- cbor(StringRepresentation)
- json_protocol
- xml

4.631 parse/3

- xml

4.632 parse__domain/2

- pddl

4.633 parse__domain/3

- pddl

4.634 parse__problem/2

- pddl

4.635 parse__problem/3

- pddl

4.636 partial_map/4

- rbtrees

4.637 partition/3

- either

4.638 partition/4

- metap

4.639 partition/5

- listp

4.640 partition/6

- metap

4.641 path_concat/3

- osp

4.642 permutation/2

- listp
- random_protocol
- varlistp

4.643 pid/1

- osp

4.644 pin/0

- packs_common

4.645 pin/1

- packs_common

4.646 pinned/1

- packs_common

4.647 plus/3

- integer

4.648 port/5

- ports_profiler

4.649 portray_clause/1

- listing

4.650 postorder/2

- bintree

4.651 powerset/2

- setp

4.652 pp/1

- xml

4.653 pprint/1

- metagol

4.654 predicate/2

- dead_code_scanner

4.655 predicate_info_pair_score_hook/4

- doc_metric

4.656 predicate_info_score_hook/3

- doc_metric

4.657 predicate_mode_score_hook/3

- doc_metric

4.658 predicate_mode_score_hook/5

- doc_metric

4.659 predicates/2

- dead_code_scanner

4.660 prefix/0

- packs_common

4.661 prefix/1

- packs_common

4.662 prefix/2

- listp
- varlistp

4.663 prefix/3

- listp

4.664 preorder/2

- bintree

4.665 previous/2

- zipperp

4.666 previous/3

- zipperp

4.667 previous/4

- dictionaryp

4.668 print_flags/0

- flags
- flags_validator

4.669 print_flags/1

- flags

4.670 print_message/3

- logtalk

4.671 print_message_token/4

- logtalk

4.672 print_message_tokens/3

- logtalk

4.673 product/2

- numberlistp
- statisticsp

4.674 product/3

- setp

4.675 program_to_clauses/2

- metagol

4.676 proper_prefix/2

- listp

4.677 proper_prefix/3

- listp

4.678 proper_suffix/2

- listp

4.679 proper_suffix/3

- listp

4.680 prove/2

- interpreterp

4.681 prove/3

- interpreterp

4.682 provides/2

- registries

4.683 question_hook/6

- logtalk

4.684 question_prompt_stream/4

- logtalk

4.685 quick_check/1

- lgtunit

4.686 quick_check/2

- lgtunit

4.687 quick_check/3

- lgtunit

4.688 random/1

- random_protocol

4.689 random/3

- random_protocol

4.690 random_node/1

- uuid_protocol

4.691 random_tree/1

- benchmark_generators

4.692 randomize/1

- fast_random
- random

4.693 randseq/4

- random_protocol

4.694 randset/4

- random_protocol

4.695 range/2

- statisticsp

4.696 rdirectories/1

- lgtdocp

4.697 rdirectories/2

- lgtdocp

4.698 rdirectory/1

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.699 rdirectory/2

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.700 rdirectory/3

- diagram(Format)
- diagrams(Format)

4.701 rdirectory_score/2

- code_metric

4.702 read_file/2

- csv_protocol
- read_file
- tsv_protocol

4.703 read_file/3

- csv_protocol
- tsv_protocol

4.704 read_file_by_line/2

- csv_protocol
- tsv_protocol

4.705 read_file_by_line/3

- csv_protocol
- tsv_protocol

4.706 read_from_atom/2

- term_io_protocol

4.707 read_from_chars/2

- term_io_protocol

4.708 read_from_codes/2

- term_io_protocol

4.709 read_only_device_path/1

- osp

4.710 read_stream/2

- csv_protocol
- tsv_protocol

4.711 read_stream/3

- csv_protocol
- tsv_protocol

4.712 read_stream_by_line/2

- csv_protocol
- tsv_protocol

4.713 read_stream_by_line/3

- csv_protocol
- tsv_protocol

4.714 read_term_from_atom/3

- term_io_protocol

4.715 read_term_from_chars/3

- term_io_protocol

4.716 read_term_from_chars/4

- term_io_protocol

4.717 read_term_from_codes/3

- term_io_protocol

4.718 read_term_from_codes/4

- term_io_protocol

4.719 readme/1

- packs_common

4.720 readme/2

- packs_common

4.721 recorda/2

- recorded_database_core

4.722 recorda/3

- recorded_database_core

4.723 recorded/2

- recorded_database_core

4.724 recorded/3

- recorded_database_core

4.725 recordz/2

- recorded_database_core

4.726 recordz/3

- recorded_database_core

4.727 relative_standard_deviation/2

- statisticsp

4.728 removeDependent/1

- subject

4.729 remove_duplicates/2

- listp
- varlistp

4.730 rename_file/2

- osp

4.731 replace/3

- zipperp

4.732 replace_sub_atom/4

- atom

4.733 rescale/3

- numberlistp

4.734 reset/0

- counter
- debuggerp
- packs_common
- ports_profiler

4.735 reset/1

- ports_profiler

4.736 reset_counter/1

- counters

4.737 reset_counters/0

- counters

4.738 reset_flags/0

- flags

4.739 reset__flags/1

- flags

4.740 reset__genint/0

- genint_core

4.741 reset__genint/1

- genint_core

4.742 reset__gensym/0

- gensym_core

4.743 reset__gensym/1

- gensym_core

4.744 reset__monitor/0

- monitorp

4.745 reset__seed/0

- fast_random
- random

4.746 restore/1

- packs

4.747 restore/2

- packs

4.748 reverse/2

- listp
- varlistp

4.749 rewind/2

- zipperp

4.750 rewind/3

- zipperp

4.751 rlibraries/1

- lgtdocp

4.752 rlibraries/2

- lgtdocp

4.753 rlibrary/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.754 rlibrary/2

- `code_metric`
- `dead_code_scanner`
- `diagram(Format)`
- `diagrams(Format)`
- `lgtdocp`

4.755 rlibrary_score/2

- `code_metric`

4.756 rule/2

- `databasep`

4.757 rule/3

- `databasep`

4.758 rule/4

- `databasep`

4.759 run/0

- `lgtunit`

4.760 run/1

- `lgtunit`

4.761 run/2

- lgtunit

4.762 run_test_sets/1

- lgtunit

4.763 same_length/2

- listp
- varlistp

4.764 same_length/3

- listp

4.765 save/0

- wrapper

4.766 save/1

- packs
- wrapper

4.767 save/2

- packs

4.768 scalar_product/3

- numberlistp

4.769 scan_left/4

- metap

4.770 scan_left_1/3

- metap

4.771 scan_right/4

- metap

4.772 scan_right_1/3

- metap

4.773 search/1

- packs

4.774 select/3

- listp
- random_protocol
- setp
- varlistp

4.775 select/4

- listp
- random_protocol

4.776 selectchk/3

- listp
- setp

4.777 selectchk/4

- listp

4.778 send/3

- redis

4.779 sequence/3

- integer

4.780 sequence/4

- integer
- random_protocol

4.781 sequential_occurrences/2

- listp

4.782 sequential_occurrences/3

- listp

4.783 serve/3

- queuep

4.784 set/1

- counter

4.785 set/4

- random_protocol

4.786 set_element/2

- java_utils_protocol

4.787 set_field/2

- java_access_protocol

4.788 set_flag_value/2

- flags

4.789 set_flag_value/3

- flags

4.790 set_monitor/4

- event_registry

4.791 set_seed/1

- arbitrary
- pseudo_random_protocol

4.792 set_spy_point/4

- monitorp

4.793 setup/0

- packs_common

4.794 shell/1

- osp

4.795 shell/2

- osp

4.796 shell_command/1

- doclet

4.797 shrink/3

- arbitrary

4.798 shrink_sequence/3

- arbitrary

4.799 shrinker/1

- arbitrary

4.800 sign//1

- number__grammars(Format)

4.801 singletons/2

- term_p

4.802 size/2

- dictionary_p
- heap_p
- set_p

4.803 skewness/2

- statistics_p

4.804 sleep/1

- osp

4.805 sort/2

- list_p

4.806 sort/3

- list_p

4.807 sort/4

- list_p

4.808 `source_file_extension/1`

- `modules_diagram_support`

4.809 `space//0`

- `blank_grammars(Format)`

4.810 `spaces//0`

- `blank_grammars(Format)`

4.811 `split/3`

- `atom`

4.812 `split/4`

- `listp`

4.813 `spy/1`

- `debuggerp`

4.814 `spy/4`

- `debuggerp`

4.815 `spy_point/4`

- `monitorp`

4.816 spying/1

- debuggerp

4.817 spying/4

- debuggerp

4.818 standard_deviation/2

- statisticsp

4.819 start/0

- ports_profiler
- shell

4.820 start_redirect_to_file/2

- dump_trace

4.821 started_by/2

- intervalp

4.822 starts/2

- intervalp

4.823 stop/0

- ports_profiler

4.824 stop_redirect_to_file/0

- dump_trace

4.825 stream_to_bytes/2

- reader

4.826 stream_to_bytes/3

- reader

4.827 stream_to_chars/2

- reader

4.828 stream_to_chars/3

- reader

4.829 stream_to_codes/2

- reader

4.830 stream_to_codes/3

- reader

4.831 stream_to_terms/2

- reader

4.832 stream_to_terms/3

- reader

4.833 subclass/1

- class_hierarchyp

4.834 subclasses/1

- class_hierarchyp

4.835 sublist/2

- listp
- varlistp

4.836 subsequence/3

- listp

4.837 subsequence/4

- listp

4.838 subset/2

- setp

4.839 substitute/4

- listp

4.840 subsumes/2

- term_p

4.841 subterm/2

- term_p
- xml

4.842 subtract/3

- list_p
- set_p
- varlist_p

4.843 succ/2

- integer

4.844 suffix/2

- list_p
- varlist_p

4.845 suffix/3

- list_p

4.846 sum/2

- numberlist_p
- statistics_p

4.847 superclass/1

- class_hierarchy

4.848 superclasses/1

- class_hierarchy

4.849 suspend_monitor/0

- monitorp

4.850 swap/2

- random_protocol

4.851 swap_consecutive/2

- random_protocol

4.852 symdiff/3

- setp

4.853 tab//0

- blank_grammars(Format)

4.854 tabs//0

- blank_grammars(Format)

4.855 take/3

- listp

4.856 temporary_directory/1

- osp

4.857 term_expansion/2

- expanding

4.858 terms_to_array/2

- java_utils_protocol

4.859 test/1

- lgtunit

4.860 time_stamp/1

- osp

4.861 timeout/1

- metagol

4.862 timestamp/2

- ulid_protocol

4.863 timestamp/8

- ulid_protocol

4.864 today/3

- datep

4.865 tolerance_equal/4

- lgtunit
- number

4.866 top/3

- heapp

4.867 top_next/5

- heapp

4.868 trace/0

- debuggerp

4.869 trace_event/2

- logtalk

4.870 transpose/2

- pairs

4.871 true/1

- java_utils_protocol

4.872 type/1

- type

4.873 unexpected/1

- expected(Expected)

4.874 unexpecteds/2

- either

4.875 uninstall/0

- packs

4.876 uninstall/1

- packs

4.877 uninstall/2

- packs

4.878 union/3

- setp

4.879 union/4

- setp
- union_find_protocol

4.880 union_all/3

- union_find_protocol

4.881 unpin/0

- packs_common

4.882 unpin/1

- packs_common

4.883 unzip/2

- zipperp

4.884 update/0

- doclet
- packs
- registries

4.885 update/1

- observer
- packs
- registries

4.886 update/2

- packs
- registries

4.887 update/3

- dictionaryp
- packs

4.888 update/4

- dictionaryp

4.889 update/5

- dictionaryp

4.890 update_in/4

- nested_dictionary_protocol

4.891 update_in/5

- nested_dictionary_protocol

4.892 uuid_null/1

- uuid_protocol

4.893 uuid_v1/2

- uuid_protocol

4.894 uuid_v4/1

- uuid_protocol

4.895 valid/1

- intervalp
- statisticsp
- term_p
- varlistp

4.896 valid/2

- type

4.897 valid/3

- datep
- timep

4.898 valid_date/3

- iso8601

4.899 valid_option/1

- options_protocol

4.900 valid_options/1

- options_protocol

4.901 validate/1

- flags_validator

4.902 value/1

- counter

4.903 value/3

- pairs

4.904 value_reference/2

- java_utils_protocol

4.905 values/2

- dictionaryp
- pairs

4.906 variables/2

- temp

4.907 variance/2

- statisticsp

4.908 variant/2

- lgtunit
- temp

4.909 varnumbers/2

- temp

4.910 varnumbers/3

- temp

4.911 verify_commands_availability/0

- packs_common

4.912 version/6

- pack_protocol

4.913 versions/3

- packs

4.914 void/1

- java_utils_protocol

4.915 void_element/1

- html

4.916 wall_time/1

- osp

4.917 `weighted_mean/3`

- `statisticsp`

4.918 `welcome/0`

- `shell`

4.919 `when/2`

- `coroutining`

4.920 `whiledo/2`

- `loopp`

4.921 `white_space//0`

- `blank_grammars(Format)`

4.922 `white_spaces//0`

- `blank_grammars(Format)`

4.923 `with_output_to/2`

- `term_io_protocol`

4.924 `without//2`

- `sequence_grammars`

4.925 `working_directory/1`

- `osp`

4.926 `write_file/3`

- `csv_protocol`
- `tsv_protocol`

4.927 `write_stream/3`

- `csv_protocol`
- `tsv_protocol`

4.928 `write_term_to_atom/3`

- `term_io_protocol`

4.929 `write_term_to_chars/3`

- `term_io_protocol`

4.930 `write_term_to_chars/4`

- `term_io_protocol`

4.931 `write_term_to_codes/3`

- `term_io_protocol`

4.932 `write_term_to_codes/4`

- `term_io_protocol`

4.933 write_to_atom/2

- term_io_protocol

4.934 write_to_chars/2

- term_io_protocol

4.935 write_to_codes/2

- term_io_protocol

4.936 z_normalization/2

- statisticsp

4.937 zero_or_more//0

- sequence_grammars

4.938 zero_or_more//1

- sequence_grammars

4.939 zero_or_more//2

- sequence_grammars

4.940 zip/2

- zipperp

4.941 zip/3

- zipperp

4.942 zip_at_index/4

- zlist

INDICES AND TABLES

- `genindex`
- `search`

Generated on Tue Jun 4 11:28:57 WEST 2024

Symbols

(/)/2, 347
 (//)/2, 348
 (<)/2, 831
 (<=)/2, 15, 533
 (:=)/2, 833
 (=<)/2, 832
 (=>)/2, 15, 533
 (=\\=)/2, 833
 (>)/2, 832
 (>=)/2, 832
 =~= / 2, 479, 872

A

a_star_interpreter(W), 932
 absolute_file_name/2, 623
 acc_info/5, 260
 acc_info/7, 260
 activate_debug_handler/1, 74
 activate_monitor/0, 272
 active_debug_handler/1, 73
 active_debug_handler_/1, 80
 add/1, 685
 add/2, 685
 add/3, 683, 836
 add_directive_/2, 974
 add_directive_/3, 975
 add_directive_before_entity_/2, 974
 add_library_documentation_url/4, 221
 add_link_options/3, 167
 add_node_zoom_option/4, 168
 addDependent/1, 146
 after/2, 404
 after/3, 82
 after_event_registry, 262
 all/0, 31, 116, 460
 all/1, 31, 116, 460
 all_files/0, 158, 180
 all_files/1, 157, 180
 all_libraries/0, 151, 174
 all_libraries/1, 151, 174
 all_score/1, 34

ancestor/1, 365
 ancestor/4, 42
 ancestors/1, 365
 apis/0, 354
 apis/1, 354
 append/2, 847
 append/3, 713, 848, 905
 apply/2, 990
 apply/4, 251
 approximately_equal/2, 477, 870
 approximately_equal/3, 477, 870
 arbitrary, 1
 arbitrary/1, 4
 arbitrary/2, 4
 archive/1, 696
 arithmetic_mean/2, 775
 arithmetic_mean/5, 770
 array_list/2, 436
 array_to_list/2, 436
 array_to_terms/2, 435
 array_to_terms/3, 435
 as_curly_bracketed/2, 242, 591
 as_dictionary/2, 242
 as_difflist/2, 843
 as_heap/2, 342
 as_list/2, 242, 341, 714, 757, 836
 as_nested_dictionary/2, 591
 as_set/2, 757
 ask_question/5, 71
 assertion/1, 10, 471
 assertion/2, 10, 472
 assertions, 7
 assertions(Mode), 9
 assertions_messages, 11
 assignable/1, 14
 assignable/2, 14
 assignvars, 12
 assignvarsp, 13
 atom, 816
 atomic, 818
 automation_report, 461
 auxiliary_predicate_counter_/1, 510

available/0, 644
available/1, 643
available/2, 643
average/2, 877
average_deviation/3, 777
avltree, 236

B

backend_adapter_hook, 374
backend_random, 715
base64, 17
base64url, 19
base_/2, 313
before/2, 403
before/3, 82
before_event_registry, 263
bench_goal/1, 945
benchmark/2, 475
benchmark/3, 476
benchmark/4, 476
benchmark_generators, 934
benchmark_reified/3, 475
best_first, 935
between/3, 725, 840
bfs_interpreter, 937
binary_file_assertion/3, 506
binary_input_assertion/2, 490
binary_input_assertion/3, 490
binary_output_assertion/2, 501
binary_output_assertion/3, 500
binary_output_contents/1, 501
binary_output_contents/2, 501
bintree, 238
bit//1, 329
bits//1, 329
blank//0, 323
blank_grammars(Format), 319
blanks//0, 323
body_pred/1, 570
body_pred_call/2, 573
branch/2, 316
built_in_directive/4, 349
built_in_flag/2, 299
built_in_method/4, 349
built_in_non_terminal/4, 350
built_in_predicate/4, 349
bup_interpreter, 938

C

c/1, 942
calendar_month/3, 418
call_with_timeout/2, 795
call_with_timeout/3, 796
callable, 819

cat/2, 596
cbor, 21
cbor(StringRepresentation), 22
cc_metric, 24
cdata_generation//1, 983
change_directory/1, 626
changed/0, 145
changed/1, 145
character, 820
character_data_format/3, 983
characterp, 821
chebyshev_distance/3, 880
chebyshev_norm/2, 879
check/1, 894, 913
check/2, 902
check/3, 901
check_binary_file/2, 505
check_binary_input/1, 489
check_binary_input/2, 489
check_binary_output/1, 500
check_binary_output/2, 499
check_option/1, 611
check_options/1, 611
check_text_file/2, 504
check_text_file/3, 503
check_text_input/1, 486
check_text_input/2, 485
check_text_output/1, 494
check_text_output/2, 493
check_text_output/3, 493
chr_is/2, 798
chr_next_state/1, 801
chr_no_spy/1, 799
chr_nospy/0, 799
chr_notrace/0, 798
chr_option/2, 799
chr_option_allow_deep_guards/0, 801
chr_option_optimization_level/1, 800
chr_option_print_trace/0, 799
chr_option_show_history/0, 800
chr_option_show_id/0, 801
chr_option_show_stack/0, 800
chr_option_show_store/0, 800
chr_option_trace_interactive/0, 800
chr_rule_/1, 802
chr_spy/1, 798
chr_spy_point/1, 801
chr_trace/0, 798
class/1, 358
class_hierarchy, 355
class_hierarchyp, 357
classes/1, 358
clause/5, 705
clause_/5, 707

clause_location/6, 705
 clause_location_/6, 706
 clean/0, 659, 690
 clean/1, 659, 689
 clean/2, 658
 clean_binary_input/0, 491
 clean_binary_output/0, 502
 clean_directory/1, 507
 clean_file/1, 506
 clean_text_input/0, 487
 clean_text_output/0, 497
 cleanup/0, 481
 clone/1, 527, 695
 clone/3, 243
 clone/4, 243
 cloning, 526
 closed_input_stream/2, 507
 closed_output_stream/2, 508
 code_metric, 25
 code_metrics, 38
 code_metrics_messages, 40
 code_metrics_utilities, 41
 coefficient_of_variation/2, 778
 command/2, 676
 command_line_arguments/1, 636
 commit_author/2, 316
 commit_date/2, 317
 commit_hash/2, 317
 commit_hash_abbreviated/2, 318
 commit_log/3, 318
 commit_message/2, 318
 comparingp, 830
 compile_aux_clauses/1, 77
 compile_predicate_heads/4, 77
 compile_predicate_indicators/3, 78
 compiled_pred_call/2, 572
 completion/2, 348
 completions/2, 348
 compound, 834
 condition/0, 481
 connect/1, 750
 connect/3, 750
 console/1, 751
 contains/2, 406
 control/0, 324
 control_construct/4, 350
 controls/0, 325
 copy_file/2, 631
 core_messages, 62
 coroutining, 84
 counter, 939
 counter/2, 529, 584
 counter_/2, 310, 531, 585
 counters, 528

coupling_metric, 46
 cover/1, 468
 coverage_report, 462
 covered_/4, 512
 cpu_time/1, 109, 633
 create_binary_file/2, 503
 create_text_file/2, 503
 create_text_file/3, 502
 csv, 87
 csv(Header Separator IgnoreQuotes), 89
 csv_guess_questions, 90
 csv_protocol, 91
 current/2, 987
 current_entity/1, 42
 current_prog/1, 799

D

data/0, 703
 data/1, 703
 data/2, 704
 databasep, 942
 date, 102
 date/4, 410
 date/5, 411
 date/6, 412
 date/7, 413
 date_string/3, 414
 date_time/7, 633
 datep, 103
 days_in_month/3, 105
 deactivate_debug_handler/0, 74
 dead_code_scanner, 110
 dead_code_scanner_messages, 118
 debug/0, 133
 debug_expansion(Mode), 945
 debug_handler/1, 73
 debug_handler/3, 74
 debug_messages, 119
 debugger, 123
 debugger_messages, 130
 debuggerp, 131
 debugging/0, 134
 debugging/1, 134
 debugging_/0, 125
 decide/1, 293
 decide/2, 293
 declares_predicate/2, 43
 decode_exception/2, 438
 decode_exception/3, 438
 decode_url_spaces/2, 677
 decompile_predicate_heads/4, 78
 decompile_predicate_indicators/4, 79
 decompose_file_name/3, 623
 decompose_file_name/4, 623

- decrement_counter/1, 529
- default_atom_mutations, 575
- default_compound_mutations, 576
- default_float_mutations, 578
- default_integer_mutations, 579
- default_list_mutations, 580
- default_option/1, 613, 970
- default_options/1, 613, 970
- default_workflow_hook, 375
- define_flag/1, 300
- define_flag/2, 300
- define_log_file/2, 542
- defined/4, 683
- defined_flag/6, 299
- defined_flag_/6, 301
- defines_predicate/2, 43
- defines_predicate/3, 44
- del_monitors/0, 268
- del_monitors/4, 268
- del_spy_points/4, 273
- delete/0, 689
- delete/1, 689
- delete/2, 688
- delete/3, 758, 848, 906
- delete/4, 244, 340
- delete_all_after/2, 993
- delete_all_after_and_unzip/2, 993
- delete_all_before/2, 992
- delete_all_before_and_unzip/2, 993
- delete_and_next/2, 992
- delete_and_previous/2, 991
- delete_and_unzip/2, 992
- delete_directory/1, 625
- delete_file/1, 632
- delete_in/4, 593
- delete_matches/3, 848
- delete_max/4, 249
- delete_min/4, 249
- demodb, 946
- dependent_/1, 147
- dependents/1, 145, 664
- dependents/2, 663
- dependents/3, 663
- depth/2, 892
- descendant/1, 366
- descendant_class/1, 363
- descendant_classes/1, 363
- descendant_instance/1, 362
- descendant_instances/1, 362
- descendants/1, 366
- describe/1, 650, 682
- describe/2, 649
- description/1, 638, 694
- deterministic/1, 471

- deterministic/2, 471
- dfs_interpreter, 948
- diagram(Format), 147
- diagram_caption/3, 159
- diagram_description/1, 158
- diagram_name_suffix/1, 159
- diagrams, 169
- diagrams(Format), 171
- dictionaryp, 240
- dif, 254
- dif/1, 85, 255
- dif/2, 85, 255
- difflist, 835
- digit//1, 329
- digits//1, 330
- directories/1, 457, 967
- directories/2, 153, 176, 456, 967
- directories/3, 153, 176
- directory/1, 29, 113, 156, 178, 458, 672, 967
- directory/2, 28, 113, 155, 178, 457, 671, 966
- directory/3, 155, 178
- directory_dependency_diagram, 181
- directory_dependency_diagram(Format), 182
- directory_diagram(Format), 184
- directory_entity_/4, 446
- directory_exists/1, 629
- directory_files/2, 628
- directory_files/3, 628
- directory_load_diagram, 188
- directory_load_diagram(Format), 189
- directory_score/2, 33
- disable/1, 120
- disable/2, 121
- disable_logging/1, 544
- disconnect/1, 751
- disjoint/2, 758
- disjoint_sets/2, 926
- dit_metric, 48
- doc_goal/1, 257
- doc_metric, 49
- doclet, 256
- doctype/1, 394
- document_generation//2, 982
- dot//1, 332
- dot_graph_language, 191
- dowhile/2, 547
- drop/3, 867
- dump_trace, 140
- during/2, 406
- dynamic_directive_/3, 973

E

- easter_day/3, 418
- edcg, 258

edge/5, 163
 edge/6, 211
 edge_/5, 169
 edge_case/2, 5
 either, 276
 either/3, 288
 empty/1, 245, 341, 590, 598, 710, 759, 849, 906
 empty_map/1, 980
 enable/1, 120
 enable/2, 121
 enable_logging/1, 544
 enabled/1, 121
 enabled/2, 122
 enabled_/1, 122
 enabled_/2, 123
 ensure_directory/1, 629
 ensure_file/1, 632
 entity/1, 27, 112, 234, 351
 entity/2, 234
 entity_calls/3, 44
 entity_defines_/2, 707
 entity_diagram, 193
 entity_diagram(Format), 194
 entity_info_pair_score_hook/3, 51
 entity_info_score_hook/2, 51
 entity_kind/2, 44
 entity_predicates_weights_hook/2, 50
 entity_prefix/2, 77
 entity_property/2, 45
 entity_score/2, 32
 entity_updates/3, 45
 enumerate/2, 728
 environment_variable/2, 632
 epsilon/1, 479
 equal/2, 407, 758
 erase/1, 747
 essentially_equal/3, 478, 871
 euclidean_distance/3, 880
 euclidean_norm/2, 878
 event_registry, 264
 event_registry, 265
 exception/4, 982
 exclude/3, 555
 execution_context/7, 79
 expand_library_alias_paths, 274
 expand_library_path/2, 75
 expanding, 63
 expected, 278
 expected(Expected), 283
 expected/1, 286
 expecteds/2, 277
 explain//1, 815
 extension/1, 370
 extensions/1, 370

external_predicate_/1, 236

F

f/4, 936
 failed_/3, 511
 false/1, 432
 fast_random, 717
 fault/5, 981
 fcube, 291
 fcube/0, 293
 file/1, 28, 112, 195, 459, 969
 file/2, 28, 112, 195, 459, 969
 file_being_advised_/4, 975
 file_dependency_diagram, 198
 file_dependency_diagram(Format), 199
 file_diagram(Format), 201
 file_exists/1, 629
 file_footer/3, 209
 file_header/3, 209
 file_load_diagram, 204
 file_load_diagram(Format), 206
 file_modification_time/2, 630
 file_path/2, 482
 file_permission/2, 630
 file_score/2, 33
 file_size/2, 630
 file_to_bytes/2, 736
 file_to_bytes/3, 737
 file_to_chars/2, 735
 file_to_chars/3, 735
 file_to_codes/2, 734
 file_to_codes/3, 735
 file_to_terms/2, 736
 file_to_terms/3, 736
 file_type_extension/2, 76
 files/1, 157, 180, 458, 968
 files/2, 156, 179, 458, 968
 files/3, 156, 179
 filter/2, 604
 filter_external_file_extension/3, 167
 filter_file_extension/3, 166
 find/4, 925
 find/5, 925
 findall_member/4, 555
 findall_member/5, 556
 finished_by/2, 407
 finishes/2, 407
 fired_/3, 512
 fix_option/2, 615
 fix_options/2, 615
 flag_group_chk/1, 298
 flag_groups/1, 298
 flag_value_/2, 301
 flags, 295

flags_validator, 302
flaky_/1, 511
flat_map/2, 287, 605
flatten/2, 849, 906
flatten_goals//1, 950
flatting, 949
float, 837
float//1, 331
fold_left/4, 557
fold_left_1/3, 557
fold_right/4, 558
fold_right_1/3, 559
fordownto/3, 550
fordownto/4, 550
fordownto/5, 551
foreach/3, 548
foreach/4, 548
format, 304
format/2, 305
format/3, 305
format_entity_score//2, 34
format_object/1, 158
format_to_atom/3, 791
format_to_chars/3, 792
format_to_chars/4, 792
format_to_codes/3, 793
format_to_codes/4, 793
forto/3, 549
forto/4, 549
forto/5, 549
forward/1, 66
forward/2, 989
forward/3, 989
forwarding, 65
fractile/3, 780
freeze/2, 86
from_generator/2, 282, 600
from_generator/3, 282, 599
from_generator/4, 281
from_goal/2, 281, 599
from_goal/3, 280, 599
from_goal/4, 280
frozen/2, 86
full_device_path/1, 627
func_test/3, 571
functional/0, 571

G

generate/1, 399, 918
generate/2, 18, 20, 23, 393, 444, 918
generate/8, 918
generated_predicate_/1, 565
generating_/0, 516
genint, 306

genint/2, 309
genint_core, 307
gensym, 310
gensym/2, 313
gensym_core, 311
geometric_mean/2, 775
get/1, 605
get_field/2, 426
get_flag_value/2, 296
get_seed/1, 6, 720
git, 314
git_protocol, 315
gnu/0, 292
goal_expansion/2, 64
grammar_rules_hook, 376
graph_footer/5, 210
graph_header/5, 210
graph_language_protocol, 208
graph_language_registry, 212
ground/1, 892
ground_entity_identifier/3, 166
group_by_key/2, 888
group_consecutive_by_key/2, 888
group_sorted_by_key/2, 887
guess_arity/2, 101
guess_separator/2, 100

H

halstead_metric, 53
halstead_metric(Stroud), 54
hamming_distance/3, 850
handbook/0, 353
handbook/1, 353
harmonic_mean/2, 775
head/2, 710
head_pred/1, 570
heap(Order), 337
heapp, 338
help, 346
help/0, 347, 669
help_info_support, 352
heuristic_expansion(Mode), 950
hex_digit//1, 330
hex_digits//1, 330
hierarchyp, 364
home/1, 639, 695
hook_pipeline(Pipeline), 371
hook_set(Set), 372
html, 392
html5, 395

I

ibk/3, 570
iddfs_interpreter(Increment), 952

identity_hook, 377
 ids, 397
 ids(Representation Bytes), 398
 if_empty/1, 603
 if_expected/1, 285
 if_expected_or_else/2, 286
 if_present/1, 603
 if_present_or_else/2, 603
 if_unexpected/1, 285
 include/3, 555
 included_directory_/1, 187
 included_entity_/1, 196
 included_file_/1, 203
 included_library_/2, 222
 included_module_/1, 196
 included_predicate_/1, 235
 increase/1, 940
 increment/0, 940
 increment_counter/1, 529
 inheritance_diagram, 213
 inheritance_diagram(Format), 214
 init/0, 962
 init_log_file/2, 543
 inorder/2, 239
 insert/3, 759
 insert/4, 244, 339
 insert_after/3, 991
 insert_all/3, 340, 759
 insert_before/3, 990
 insert_in/4, 593
 install/1, 653
 install/2, 652
 install/3, 652
 install/4, 651
 installed/0, 646
 installed/1, 645
 installed/3, 645
 installed/4, 644
 instance/1, 359
 instance/2, 747
 instances/1, 359
 integer, 838
 integer//1, 331
 internal_os_path/2, 624
 interpreterp, 953
 intersect/2, 760
 intersection/2, 247
 intersection/3, 247, 760
 intersection/4, 760
 interval, 400
 intervalp, 401
 invocation_number_/1, 128
 invoke/1, 427
 invoke/2, 428

ip_grammars(Format), 325
 ipv4//1, 326
 ipv6//1, 327
 is_absolute_file_name/1, 622
 is_alpha/1, 823
 is_alphanumeric/1, 823
 is_ascii/1, 823
 is_bin_digit/1, 824
 is_control/1, 828
 is_dec_digit/1, 825
 is_empty/0, 602
 is_end_of_line/1, 829
 is_expected/0, 284
 is_false/1, 433
 is_hex_digit/1, 825
 is_layout/1, 827
 is_letter/1, 824
 is_lower_case/1, 825
 is_newline/1, 828
 is_null/1, 434
 is_object/1, 434
 is_octal_digit/1, 824
 is_period/1, 828
 is_present/0, 602
 is_punctuation/1, 827
 is_quote/1, 827
 is_true/1, 433
 is_unexpected/0, 284
 is_upper_case/1, 826
 is_validator/1, 302
 is_void/1, 433
 is_vowel/1, 826
 is_white_space/1, 826
 iso8601, 408
 issue_creator, 420
 iterator_element/2, 437

J

java, 421
 java(Reference), 422
 java(Reference ReturnValue), 423
 java_access_protocol, 425
 java_hook, 428
 java_utils_protocol, 430
 join/3, 711
 join_all/3, 711
 json, 439
 json(ObjectRepresentation PairRepresentation StringRepresentation)
 441
 json(StringRepresentation), 440
 json_protocol, 443
 jump/3, 712
 jump_all/3, 712
 jump_all_block/3, 712

jump_to_invocation_number_/1, 128

K

key/2, 886

keys/2, 250, 885

keys_values/3, 885

keysort/2, 850

kurtosis/2, 779

L

language_object/2, 213

last/2, 850, 907

leaf/1, 365

leaf_class/1, 361

leaf_classes/1, 362

leaf_instance/1, 361

leaf_instances/1, 361

leap_year/1, 104, 417

leaping_/1, 126

learn/0, 574

learn/1, 574

learn/2, 568

learn/3, 567

learn_seq/2, 568

learn_with_timeout/4, 568

leash/1, 138

leashing/1, 138

leashing_/1, 128

least_common_multiple/2, 883

leaves/1, 366

length/2, 713, 851, 907

lgtdoc, 445

lgtdoc_messages, 448

lgtdocp, 449

lgtunit, 464

lgtunit_messages, 513

libraries/1, 151, 173, 453

libraries/2, 150, 173, 453

libraries/3, 150, 173

library/0, 350

library/1, 30, 115, 153, 175, 351, 454

library/2, 30, 114, 152, 175, 454

library_dependency_diagram, 216

library_dependency_diagram(Format), 217

library_diagram(Format), 219

library_entity_/4, 446

library_load_diagram, 223

library_load_diagram(Format), 225

library_score/2, 32

license/1, 638

line_to_chars/2, 740

line_to_chars/3, 740

line_to_codes/2, 741

line_to_codes/3, 741

lint/0, 666, 691

lint/1, 665, 691

lint/2, 665

list, 842

list(Type), 844

list/0, 682

list_to_array/2, 436

listing, 534

listing/0, 535

listing/1, 535

listp, 845

load_registry/1, 676

loaded_file/1, 75

loaded_file_property/2, 75, 228

locate_directory/2, 165

locate_file/5, 166

locate_library/2, 165

log/3, 138

log_event/2, 543

log_file/2, 542

log_file_/2, 538, 540

logger, 537

logging, 539

logging/1, 543

logging/3, 139

logging_line_number_/3, 129

logging_to_file_/2, 539, 540

loggingp, 541

logtalk, 67

logtalk_packs/0, 674

logtalk_packs/1, 673

lookup/2, 246

lookup/3, 246

lookup_in/3, 591

loop, 545

loopp, 546

lower_upper/2, 830

M

magic, 955

magic/2, 956

magic_expansion(Mode), 957

magicise/4, 956

make/1, 482

make_directory/1, 624

make_directory_path/1, 625

make_set/3, 924

man/1, 355

manhattan_distance/3, 880

manhattan_norm/2, 879

manuals/0, 351

map/2, 250, 287, 560, 604, 714

map/3, 251, 560, 715, 888

map/4, 561

map/5, 561
 map/6, 562
 map/7, 562
 map/8, 562
 map_element/2, 437
 map_member/3, 980
 map_reduce/5, 563
 map_store/4, 981
 max/2, 774, 851, 876
 max/3, 248
 max_clauses/1, 571
 max_inv_preds/1, 571
 max_size/1, 7
 maxheap, 343
 maybe, 595
 maybe/0, 730
 maybe/1, 731
 maybe/2, 731
 maybe_call/1, 731
 maybe_call/2, 732
 mean_deviation/2, 777
 median/2, 776, 878
 median_deviation/2, 778
 meets/2, 404
 member/2, 726, 761, 851
 memberchk/2, 762, 852, 907
 merge/3, 340
 merge_options/2, 614, 971
 message_cache_/1, 521, 522, 524, 526
 message_diagram_description/1, 168
 message_hook/4, 71
 message_prefix_stream/4, 70
 message_tokens//2, 70
 met_by/2, 404
 meta, 552
 meta_compiler, 564
 meta_type/3, 901
 metagol, 566
 metagol_example_protocol, 573
 metap, 553
 metarule/6, 570
 metarule_next_id/1, 572
 min/2, 773, 852, 876
 min/3, 248
 min_clauses/1, 571
 min_max/3, 774, 876
 minheap, 344
 minimal_output, 514
 missing_predicate_directive_/3, 973
 modes/2, 776, 878
 module_predicate_called_/3, 972
 module_property/2, 228
 modules_diagram_support, 227
 monitor, 269

monitor/1, 267
 monitor/4, 267
 monitor_activated/0, 272
 monitored/1, 267
 monitoring, 81
 monitorp, 270
 monitors/1, 266
 msort/2, 852
 msort/3, 853
 multifile_directive_/3, 974
 mutation/3, 583, 584
 mutation/4, 585
 mutations, 582
 mutations_store, 583

N

name/1, 638, 694
 name_of_day/3, 105
 name_of_month/3, 105
 natural, 868
 natural//1, 331
 navltree, 586
 nbintree, 587
 nested_dictionary_protocol, 589
 new/1, 427, 532, 590, 892
 new/2, 427, 532, 924
 new/3, 403
 new_line//0, 322
 new_lines//0, 323
 next/2, 987
 next/3, 987
 next/4, 248
 nextto/3, 853, 908
 noc_metric, 56
 node/6, 162
 node/7, 210
 node_/6, 169
 nodebug/0, 133
 nolog/3, 139
 nologall/0, 140
 non_blank//1, 324
 non_blanks//1, 324
 non_standard_predicate_call_/2, 973
 nor_metric, 58
 normal_element/2, 394
 normalize_range/2, 881
 normalize_range/4, 881
 normalize_scalar/2, 882
 normalize_unit/2, 882
 nospy/1, 136
 nospy/4, 137
 nospyall/0, 137
 not_excluded_file/3, 45
 not_excluded_file/4, 164

- note/1, 482
- note/2, 696
- note/3, 640
- notrace/0, 135
- now/3, 109
- nrbtree, 594
- nth0/3, 854, 908
- nth0/4, 854, 908
- nth1/3, 854, 909
- nth1/4, 855, 909
- null/1, 432
- null_device_path/1, 627
- number, 869
- number//1, 332
- number_grammars(Format), 327
- number_of_tests/1, 470
- numberlist, 873
- numberlistp, 874
- numbervars/1, 896
- numbervars/3, 896

O

- object_file_/2, 463
- object_predicate_called_/3, 972
- object_wrapper_hook, 379
- object_wrapper_hook(Name Relations), 381
- object_wrapper_hook(Protocol), 380
- observer, 142
- occurrences/2, 856
- occurrences/3, 856
- occurs/2, 893
- of/2, 598
- of_expected/2, 280
- of_unexpected/2, 279
- omit_path_prefix/3, 167
- one_or_more//0, 336
- one_or_more//1, 335
- one_or_more//2, 334
- operating_system_machine/1, 635
- operating_system_name/1, 634
- operating_system_release/1, 635
- operating_system_type/1, 634
- option/2, 613
- option/3, 614
- optional, 597
- optional(Optional), 601
- options, 608
- options_protocol, 610
- or/2, 605
- or_else/2, 288, 606
- or_else_call/2, 289, 607
- or_else_fail/1, 290, 607
- or_else_get/2, 289, 606
- or_else_throw/1, 290

- or_else_throw/2, 608
- orphaned/0, 648
- orphaned/2, 648
- os, 616
- os_types, 617
- osp, 619
- outdated/0, 647
- outdated/1, 647
- outdated/4, 646
- output_edges/1, 163
- output externals/1, 160
- output_file/4, 161
- output_file_name/2, 209
- output_file_path/4, 165
- output_files/2, 161
- output_library/3, 160
- output_missing_externals/1, 164
- output_node/6, 162
- output_rdirectory/3, 160
- output_rlibrary/3, 159
- output_sub_diagrams/1, 161
- overlapped_by/2, 405
- overlaps/2, 405

P

- pack_protocol, 637
- packs, 641
- packs_common, 666
- packs_messages, 678
- packs_specs_hook, 679
- pairs, 884
- parent/1, 369
- parenthesis/2, 829
- parents/1, 369
- parse/2, 18, 20, 23, 444, 978
- parse/3, 978
- parse_domain/2, 698
- parse_domain/3, 698
- parse_problem/2, 698
- parse_problem/3, 699
- partial_/1, 516, 519
- partial_map/4, 253
- partition/3, 277
- partition/4, 556, 755
- partition/5, 857
- partition/6, 556
- pass_info/1, 261
- pass_info/2, 261
- passed_/3, 511
- path_concat/3, 624
- pcdata_7bit//1, 983
- pddl, 697
- permutation/2, 728, 857, 910
- pid/1, 621

pin/0, 670
 pin/1, 669
 pinned/1, 671
 plus/3, 840
 population, 766
 port/5, 705
 port_/5, 706
 portray_clause/1, 536
 ports_profiler, 701
 postorder/2, 239
 powerset/2, 762
 pp/1, 979
 pp_string/1, 981
 pprint/1, 569
 pprint_clause/1, 572
 pprint_clauses/1, 572
 pred_info/3, 260
 predicate/2, 117
 predicate_called_but_not_defined_/2, 971
 predicate_entity_/4, 447
 predicate_info_pair_score_hook/4, 53
 predicate_info_score_hook/3, 52
 predicate_mode_score_hook/3, 51
 predicate_mode_score_hook/5, 52
 predicates/2, 116
 prefix/0, 675
 prefix/1, 674
 prefix/2, 857, 910
 prefix/3, 858
 preorder/2, 239
 previous/2, 988
 previous/3, 988
 previous/4, 247
 print_flags/0, 298, 303
 print_flags/1, 299
 print_goal_hook, 383
 print_message/3, 69
 print_message_token/4, 70
 print_message_tokens/3, 69
 print_readme_file_path/1, 675
 process_all/1, 37
 process_directory/2, 36
 process_entity/2, 35
 process_file/2, 35
 process_library/2, 36
 process_rdirectory/2, 36
 process_rlibrary/2, 37
 product/2, 773, 877
 product/3, 762
 program_to_clauses/2, 569
 prolog_module_hook(Module), 384
 proper_prefix/2, 858
 proper_prefix/3, 859
 proper_suffix/2, 866

proper_suffix/3, 866
 proto_hierarchy, 367
 proto_hierarchyp, 368
 prove/2, 954
 prove/3, 954
 provides/2, 690
 pseudo_random_protocol, 719

Q

quasi_skipping_/0, 126
 question_hook/6, 72
 question_prompt_stream/4, 72
 queue, 708
 queuep, 709
 quick_check/1, 474
 quick_check/2, 473
 quick_check/3, 473

R

random, 721
 random/1, 725
 random/3, 729
 random_node/1, 932
 random_protocol, 724
 random_tree/1, 935
 randomize/1, 718, 723
 randseq/4, 729
 randset/4, 730
 range/2, 774
 rbtree, 252
 rdirectories/1, 455
 rdirectories/2, 455
 rdirectory/1, 29, 114, 154, 177, 456, 966
 rdirectory/2, 29, 114, 154, 177, 455, 966
 rdirectory/3, 154, 177
 rdirectory_score/2, 34
 read_file, 700
 read_file/2, 94, 701, 807
 read_file/3, 93, 806
 read_file_by_line/2, 97, 810
 read_file_by_line/3, 96, 809
 read_from_atom/2, 785
 read_from_chars/2, 787
 read_from_codes/2, 788
 read_only_device_path/1, 627
 read_stream/2, 95, 808
 read_stream/3, 93, 806
 read_stream_by_line/2, 98, 811
 read_stream_by_line/3, 97, 810
 read_term_from_atom/3, 785
 read_term_from_chars/3, 786
 read_term_from_chars/4, 786
 read_term_from_codes/3, 787
 read_term_from_codes/4, 787

reader, 733
readme/1, 673
readme/2, 672
readme_file_path/2, 675
record_/3, 748
recorda/2, 745
recorda/3, 744
recorded/2, 747
recorded/3, 746
recorded_database, 742
recorded_database_core, 743
recordz/2, 746
recordz/3, 745
redis, 749
reference_/1, 748
referenced_entity_/2, 197
referenced_logtalk_directory_/1, 187
referenced_logtalk_file_/1, 203
referenced_logtalk_library_/2, 222
referenced_module_/2, 197
referenced_predicate_/1, 235
referenced_prolog_directory_/1, 187
referenced_prolog_file_/1, 204
referenced_prolog_library_/2, 223
registries, 680
registry_loader_hook, 692
registry_protocol, 693
relative_standard_deviation/2, 779
remember_included_directory/1, 186
remember_included_file/1, 202
remember_included_library/2, 221
remember_referenced_logtalk_directory/1, 186
remember_referenced_logtalk_file/1, 202
remember_referenced_logtalk_library/2, 221
remember_referenced_prolog_directory/1, 186
remember_referenced_prolog_file/1, 203
remember_referenced_prolog_library/2, 222
remove_directive_/2, 975
remove_duplicates/2, 859, 910
removeDependent/1, 146
rename_file/2, 631
replace/3, 991
replace_sub_atom/4, 817
rescale/3, 883
reset/0, 133, 162, 668, 704, 941
reset/1, 704
reset_counter/1, 530
reset_counters/0, 530
reset_flags/0, 297
reset_flags/1, 297
reset_genint/0, 309
reset_genint/1, 309
reset_gensym/0, 312
reset_gensym/1, 312
reset_monitor/0, 272
reset_seed/0, 718, 722
restore/1, 662
restore/2, 661
reverse/2, 859, 911
rewind/2, 988
rewind/3, 989
rlibraries/1, 451
rlibraries/2, 451
rlibrary/1, 31, 115, 152, 175, 452
rlibrary/2, 30, 115, 152, 174, 452
rlibrary_score/2, 32
rule/2, 944
rule/3, 944
rule/4, 944
rule_expansion(Mode), 958
run/0, 468
run/1, 469
run/2, 469
run_quick_check_tests/5, 480
run_test_set/0, 480
run_test_sets/1, 470
run_tests/0, 480
run_tests/1, 480
running_test_sets_/0, 509

S

same_length/2, 860, 911
same_length/3, 860
sample, 767
save/0, 970
save/1, 661, 969
save/2, 660
save_edge/5, 163
scalar_product/3, 881
scan_left/4, 558
scan_left_1/3, 558
scan_right/4, 559
scan_right_1/3, 560
search/1, 650
seed_/3, 719, 723
select/3, 726, 763, 860, 911
select/4, 727, 861
selectchk/3, 763, 861
selectchk/4, 861
send/3, 751
sequence/3, 841
sequence/4, 728, 841
sequence_grammars, 333
sequential_occurrences/2, 855
sequential_occurrences/3, 855
serve/3, 713
set, 752
set(Type), 754

set/1, 941
 set/4, 729
 set_binary_input/1, 488
 set_binary_input/2, 488
 set_binary_input/3, 487
 set_binary_output/1, 499
 set_binary_output/2, 498
 set_binary_output/3, 498
 set_element/2, 437
 set_field/2, 426
 set_flag_value/2, 296
 set_flag_value/3, 297
 set_monitor/4, 268
 set_seed/1, 6, 721
 set_spy_point/4, 273
 set_text_input/1, 485
 set_text_input/2, 484
 set_text_input/3, 484
 set_text_output/1, 492
 set_text_output/2, 492
 set_text_output/3, 491
 setp, 756
 setup/0, 481, 668
 shell, 959
 shell(Interpreters), 961
 shell/1, 622
 shell/2, 621
 shell_command/1, 257
 shell_expansion(Mode), 962
 shrink/3, 5
 shrink_sequence/3, 5
 shrinker/1, 4
 sign//1, 332
 singletons/2, 895
 size/2, 251, 341, 761
 size_metric, 59
 skewness/2, 779
 skipped_/1, 510
 skipping_/0, 125
 skipping_unleashed_/1, 126
 sleep/1, 636
 sort/2, 755, 862
 sort/3, 862
 sort/4, 863
 source_file_extension/1, 228
 space//0, 321
 spaces//0, 321
 split/3, 817
 split/4, 863
 spy/1, 135
 spy/4, 136
 spy_point/4, 273
 spy_point_/4, 270
 spying/1, 135
 spying/4, 136
 spying_context_/4, 127
 spying_line_number_/2, 127
 spying_predicate_/3, 127
 squares_and_cubes/6, 770
 squares_and_hypers/6, 770
 standard_deviation/2, 778
 start/0, 703, 960
 start_redirect_to_file/2, 141
 started_by/2, 406
 starts/2, 405
 statistics, 768
 statisticsp, 771
 stop/0, 703
 stop_redirect_to_file/0, 141
 stream_position/1, 508
 stream_to_bytes/2, 739
 stream_to_bytes/3, 740
 stream_to_chars/2, 738
 stream_to_chars/3, 738
 stream_to_codes/2, 737
 stream_to_codes/3, 737
 stream_to_terms/2, 739
 stream_to_terms/3, 739
 streamvars, 531
 sub_diagram_/1, 200, 207, 219, 226
 sub_diagram_/2, 184, 191
 sub_directory/2, 37
 sub_library/2, 38
 subclass/1, 359
 subclasses/1, 360
 subject, 144
 sublist/2, 863, 912
 subsequence/3, 864
 subsequence/4, 864
 subset/2, 763
 substitute/4, 865
 subsumes/2, 893
 subterm/2, 893, 979
 subtract/3, 764, 865, 912
 succ/2, 840
 suffix/2, 865, 912
 suffix/3, 866
 sum/2, 773, 877
 superclass/1, 360
 superclasses/1, 360
 supported_archive/1, 677
 supported_url_archive/1, 677
 suppress_binary_output/0, 483
 suppress_goal_hook, 385
 suppress_text_output/0, 483
 suspend_monitor/0, 272
 swap/2, 727
 swap_consecutive/2, 727

syndiff/3, 764

T

tab//0, 322
tabs//0, 322
take/3, 867
tap_output, 515
tap_report, 517
tar_command/1, 676
temporary_directory/1, 626
temporary_file_/1, 783
term, 889
term_expansion/2, 64
term_io, 782
term_io_protocol, 783
termp, 890
terms_to_array/2, 434
test/1, 470
test/2, 509
test/3, 509
test_/2, 510
test_count_/1, 517, 519
text_file_assertion/3, 505
text_file_assertion/4, 504
text_input_assertion/2, 487
text_input_assertion/3, 486
text_output_assertion/2, 495
text_output_assertion/3, 495
text_output_assertion/4, 494
text_output_contents/1, 497
text_output_contents/2, 496
text_output_contents/3, 496
time, 107
time_stamp/1, 633
timeout, 794
timeout/1, 572
timep, 108
timestamp/2, 919
timestamp/8, 919
timestamp_/6, 463
today/3, 104
tolerance_equal/4, 478, 871
top/3, 342
top_next/5, 342
toychrdb, 796
trace/0, 134
trace_event/2, 72
tracing_/0, 125
transpose/2, 887
true/1, 431
tsv, 802
tsv(Header), 803
tsv_protocol, 804
tutor, 814

type, 897
type/1, 900
type/3, 573
type_entity_/4, 447

U

ulid, 914
ulid(Representation), 915
ulid_protocol, 916
ulid_types, 920
unexpected/1, 286
unexpecteds/2, 277
uninstall/0, 658
uninstall/1, 657
uninstall/2, 657
union/3, 764
union/4, 765, 924
union_all/3, 925
union_find, 921
union_find_protocol, 922
unknown_predicate_called_/2, 972
unpin/0, 670
unpin/1, 670
unsafe_set_flag_value/2, 300
unzip/2, 986
update/0, 257, 656, 687
update/1, 143, 656, 687
update/2, 655, 686
update/3, 245, 654
update/4, 244
update/5, 245
update_in/4, 592
update_in/5, 592
upn_metric, 61
user, 83
uses_diagram, 229
uses_diagram(Format), 230
uuid, 927
uuid(Representation), 928
uuid_null/1, 931
uuid_protocol, 929
uuid_v1/2, 931
uuid_v4/1, 931

V

valid/1, 403, 781, 894, 913
valid/2, 901
valid/3, 106, 109
valid_date/3, 416
valid_option/1, 612
valid_options/1, 612
validate/1, 303
validate/3, 302
validate_type/1, 302

[value/1](#), 941
[value/3](#), 886
[value_reference/2](#), 431
[values/2](#), 250, 886
[variables/2](#), 895
[variance/2](#), 780
[variance/6](#), 771
[variant/2](#), 476, 894
[varlist](#), 903
[varlistp](#), 904
[varnumbers/2](#), 897
[varnumbers/3](#), 896
[verify_commands_availability/0](#), 669
[version/6](#), 639
[versions/3](#), 648
[void/1](#), 432
[void_element/1](#), 393

W

[wall_time/1](#), 634
[weighted_mean/3](#), 776
[welcome/0](#), 960
[when/2](#), 87
[whiledo/2](#), 547
[white_space/0](#), 321
[white_spaces/0](#), 321
[with_output_to/2](#), 793
[without/2](#), 336
[working_directory/1](#), 626
[wrapper](#), 963
[write_file/3](#), 99, 812
[write_max_depth_/1](#), 129
[write_stream/3](#), 99, 812
[write_term_to_atom/3](#), 788
[write_term_to_chars/3](#), 789
[write_term_to_chars/4](#), 789
[write_term_to_codes/3](#), 790
[write_term_to_codes/4](#), 791
[write_to_atom/2](#), 789
[write_to_chars/2](#), 790
[write_to_codes/2](#), 791
[write_to_file_hook\(File\)](#), 387
[write_to_file_hook\(File Options\)](#), 388
[write_to_stream_hook\(Stream\)](#), 389
[write_to_stream_hook\(Stream Options\)](#), 391

X

[xhtml11](#), 396
[xml](#), 976
[xml_to_document/3](#), 980
[xref_diagram](#), 232
[xref_diagram\(Format\)](#), 233
[xunit_net_v2_output](#), 519
[xunit_net_v2_report](#), 521

[xunit_output](#), 523
[xunit_report](#), 524

Z

[z_normalization/2](#), 780
[zap_to_port_/1](#), 129
[zero_or_more//0](#), 336
[zero_or_more//1](#), 335
[zero_or_more//2](#), 334
[zip/2](#), 986
[zip/3](#), 986
[zip_at_index/4](#), 995
[zipperp](#), 984
[zlist](#), 994